



# GroupWise® Software Developer Kit Administration REST API Guide

January 2023

## **Legal Notices**

© Copyright 1993 - 2020 Micro Focus or one of its affiliates.

The only warranties for products and services of Micro Focus and its affiliates and licensors ("Micro Focus") are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Micro Focus shall not be liable for technical or editorial errors or omissions contained herein. The information contained herein is subject to change without notice.

---

# Contents

<b>About This Guide</b>	<b>7</b>
<b>1 Overview</b>	<b>9</b>
Information Resources .....	9
GroupWise Administration Architecture .....	10
GroupWise Admin Console .....	10
GroupWise Admin API .....	10
Directory Independence for Your GroupWise System .....	11
Sample Code for the Admin API .....	11
Supported and Recommended GroupWise APIs .....	12
<b>2 Working with the GroupWise Administration Service</b>	<b>13</b>
<b>3 Admin API Resources</b>	<b>15</b>
<b>A Sample Requests and Responses</b>	<b>17</b>
Requesting a List of Domains in the GroupWise System .....	20
Requesting a List of Post Offices in a Domain .....	25
Requesting a List of Users in the GroupWise System .....	27
Requesting a List of Users in the GroupWise System Using a Wildcard Character .....	33
Requesting a List of Users in a Domain .....	34
Requesting a List of Users in a Post Office .....	38
Requesting a List of User Attributes .....	42
Requesting a List of Groups in the GroupWise System .....	45
Requesting a List of Groups in a Domain .....	46
Requesting a List of Groups in a Post Office .....	48
Requesting a List of Group Memberships for a User .....	49
Requesting a List of Members in a Group .....	50
Requesting a List of Resources in the GroupWise System .....	51
Requesting a List of Resources in a Domain .....	52
Requesting a List of Resources in a Post Office .....	54
Requesting a List of Resources That a User Owns .....	55
Requesting a List of Nicknames in the GroupWise System .....	57
Requesting a List of Nicknames in a Domain .....	59
Requesting a List of Nicknames in a Post Office .....	62
Requesting a List of Nicknames for a User .....	65
Requesting Statistical Information about the GroupWise System .....	67
Requesting Configuration Information about the GroupWise System .....	69
Requesting Configuration Information about a Domain .....	74
Requesting Configuration Information about an MTA .....	78
Requesting Configuration Information about a POA .....	81
Creating a GroupWise User .....	85

Creating an External User . . . . .	86
Creating a GroupWise User with Chinese Characters in the Last Name . . . . .	87
Updating a User's First Name That Has Chinese Characters . . . . .	88
Renaming a User . . . . .	88
Creating a GroupWise Group . . . . .	89
Adding a Member to a Group . . . . .	89
Updating the Participation of a Member of a Group . . . . .	90
Requesting an Access Control List for a Group . . . . .	90
Creating a GroupWise Resource . . . . .	92
Creating a GroupWise Nickname . . . . .	93
Finding a Domain by Name . . . . .	93
Finding a Domain by Type . . . . .	98
Finding a Post Office . . . . .	100
Finding a User in the GroupWise System . . . . .	105
Finding a User in a Domain . . . . .	107
Finding a User in a Post Office . . . . .	110
Finding a User in a Group . . . . .	115
Finding a User's Last Name That Has Chinese Characters . . . . .	116
Finding a Group in the GroupWise System . . . . .	118
Finding a Group in a Post Office . . . . .	119
Finding a Resource in the GroupWise System . . . . .	122
Finding a Resource in a Post Office . . . . .	124
Finding a Nickname in the GroupWise System . . . . .	127
Finding a Nickname in a Post Office . . . . .	130
Moving Users to a Different Post Office . . . . .	133
Moving a Group to a Different Post Office . . . . .	134
Moving a Resource to a Different Post Office . . . . .	135
Deleting a User from the GroupWise System . . . . .	136
Deleting a User That Owns Resources from the GroupWise System . . . . .	137
Deleting a User That Has Been Moved from the GroupWise System . . . . .	138
Deleting a Group from the GroupWise System . . . . .	138
Deleting a Member from a Group . . . . .	138
Deleting a Resource from the GroupWise System . . . . .	139
Deleting a Nickname from the GroupWise System . . . . .	139
Requesting the Client Options for a User . . . . .	139
Updating the Client Options of a User . . . . .	197
Setting the GroupWise Password of a User . . . . .	232
Clearing the GroupWise Password of a User . . . . .	233
Restoring the Compose Views of a User . . . . .	233
Modifying the Send Priority Settings of a User . . . . .	234
Modifying the Calendar Settings of a User . . . . .	234
Modifying the Alarm Settings of a User . . . . .	235
Disabling and Locking the Publish Free Busy Setting of a User . . . . .	236
Enabling the Vibe Access and Configuring the Vibe URL of a User . . . . .	237
Performing a Batch Operation to Add Members to a Group . . . . .	237
Performing a Batch Operation to Modify Members of a Group . . . . .	238
Performing a Batch Operation to Add ACL Members to a Group . . . . .	239
Performing a Batch Operation to Modify ACL Members of a Group . . . . .	240
Creating a Trusted Application Record . . . . .	241

Updating a Trusted Application Record.....	242
Deleting a Trusted Application Record .....	243

**B Invalid Characters 245**

Invalid Characters in GroupWise Object Names.....	245
Invalid Characters in Internet Email Addresses .....	245



# About This Guide

GroupWise Administration API provides GroupWise developers with access to events and actions that occur at the GroupWise Administration console.

This guide contains the following sections:

- ♦ [Chapter 1, “Overview,” on page 9](#)
- ♦ [Chapter 2, “Working with the GroupWise Administration Service,” on page 13](#)
- ♦ [Chapter 3, “Admin API Resources,” on page 15](#)
- ♦ [Appendix A, “Sample Requests and Responses,” on page 17](#)
- ♦ [Appendix B, “Invalid Characters,” on page 245](#)

## Audience

This guide is intended for GroupWise developers.

## Feedback

We want to hear your comments and suggestions about this manual and the other documentation included with this product. Please use the **comment on this topic** feature at the bottom of each page of the online documentation.

## Documentation Updates

For the most recent version of this guide, see the [GroupWise 18 \(https://www.novell.com/documentation/groupwise18/\)](https://www.novell.com/documentation/groupwise18/) Documentation website.

## Additional Information

For the developer support postings for GroupWise, see the related [Developer Support Forums \(http://developer.novell.com/ndk/devforums.htm\)](http://developer.novell.com/ndk/devforums.htm)

## Documentation Conventions

In Micro Focus documentation, a greater-than symbol (>) is used to separate actions within a step and items in a cross-reference path.





# 1 Overview

In order for the GroupWise Administration console to be available, the GroupWise Administration service must be running. The GroupWise Administration API provides GroupWise developers with access to events and actions that occur at the GroupWise Administration console. The GroupWise Administration API uses Representational State Transfer (REST) architectural principals.

- ♦ “Information Resources” on page 9
- ♦ “GroupWise Administration Architecture” on page 10
- ♦ “GroupWise Admin Console” on page 10
- ♦ “GroupWise Admin API” on page 10
- ♦ “Directory Independence for Your GroupWise System” on page 11
- ♦ “Sample Code for the Admin API” on page 11
- ♦ “Supported and Recommended GroupWise APIs” on page 12

## Information Resources

Before working with the GroupWise Admin API, you should be familiar with the following sources of information:

- ♦ Novell Developer Forum (<http://forums.novell.com/forum.php>)
- ♦ GroupWise 18 Documentation website (<https://www.novell.com/documentation/groupwise18/>)
- ♦ REST (<http://en.wikipedia.org/wiki/REST>)
- ♦ JSON (<http://www.json.org>)
- ♦ jQuery (<http://jquery.com>)
- ♦ AJAX (<http://api.jquery.com/jquery.ajax>)
- ♦ Jersey (<http://jersey.java.net>)
- ♦ Maven (<http://maven.apache.org>)
- ♦ Open API Interface ([http://en.wikipedia.org/wiki/Open\\_API](http://en.wikipedia.org/wiki/Open_API))
- ♦ CRUD Operations ([http://en.wikipedia.org/wiki/Create,\\_read,\\_update\\_and\\_delete](http://en.wikipedia.org/wiki/Create,_read,_update_and_delete))
- ♦ Token-based Authentication ([http://en.wikipedia.org/wiki/Security\\_token](http://en.wikipedia.org/wiki/Security_token))

# GroupWise Administration Architecture

Starting in GroupWise 2014, the GroupWise Admin service provides the GroupWise Admin console for managing your GroupWise system. The GroupWise Admin console replaces ConsoleOne, which was the GroupWise administration tool for earlier versions of GroupWise.

The GroupWise Admin service is automatically installed on each server where you create domains and post offices and install the GroupWise agents:

- ◆ Message Transfer Agent (MTA)
- ◆ Post Office Agent (POA)
- ◆ Document Viewer Agent (DVA)
- ◆ Internet Agent (GWIA)
- ◆ Monitor Agent

Because GroupWise administration is handled by a web service, you can access it from your web browser. You do not need to be on a specific machine where specific administration software has been installed. You do not need drive mappings to servers throughout your GroupWise system.

## GroupWise Admin Console

The GroupWise agents have long had web consoles. The web-based GroupWise 18 Admin console now provides all required administration functionality that was provided by ConsoleOne in earlier versions of GroupWise.

The GroupWise Admin console is available at the following URL:

`https://ip_address:9710/gwadmin-console`

The *GroupWise 18 Administration Guide* ([https://www.novell.com/documentation/groupwise18/gw18\\_guide\\_admin/data/admin\\_front.html](https://www.novell.com/documentation/groupwise18/gw18_guide_admin/data/admin_front.html)) details how to use the GroupWise Admin console to manage your GroupWise system.

## GroupWise Admin API

The GroupWise 18 Admin API provides you with access to events and actions that occur at the GroupWise Admin console.

The Admin API is available at the following URL:

`https://server_address:9710/gwadmin-service/static/apidocs/index.html`

The main Admin API page appears:



This guide details how to use the Admin API to customize GroupWise administration. In addition, online documentation located on each GroupWise server provides a complete list of Admin API resources through the **Detailed Documentation** links on the Admin API page.

## Directory Independence for Your GroupWise System

Versions of GroupWise before GroupWise 2014 were dependent on Micro Focus eDirectory for the storage of object data. GroupWise 18 can store all its object data internally (using no external directory service), or it can be configured to integrate with Micro Focus eDirectory, Microsoft Active Directory, or any other LDAP directory service.

When you initially install GroupWise 18, it is not configured to integrate with any directory service. When you update from an earlier version of GroupWise, you can configure GroupWise 18 to continue to integrate with eDirectory, or you can configure it differently as needed.

Although GroupWise can be configured to not use a directory service, directory services have advantages:

- ♦ User information such as login credentials can be accessed by GroupWise as well as by other user applications across your network.
- ♦ Administrative roles can be defined so that GroupWise administrators can be authorized to perform various subsets of administrative tasks.

If you choose to use a directory service with GroupWise, object data can be synchronized from the directory service to GroupWise as needed. Synchronization from GroupWise to the directory service is not yet available in GroupWise 18.

## Sample Code for the Admin API

Two Readmes help you use the sample code that is available for the Admin API:

- ♦ GroupWise Admin SDK Readme (gwsdk\_gwadminweb\_readme.txt)

The SDK Readme covers the documentation and sample code that is included in the SDK.

- ◆ GroupWise Admin API Sample Code Readme (`readme.txt`)

The API Sample Code Readme is located in the `docs` subdirectory of the SDK download. It covers system requirements and instructions for working with the sample code.

[Appendix A, “Sample Requests and Responses,” on page 17](#) provides detailed examples of JSON and XML requests and responses:

- ◆ [“Samples by GroupWise Object” on page 17](#)
- ◆ [“Samples by Task” on page 19](#)

## Supported and Recommended GroupWise APIs

- ◆ The GroupWise 18 Administration (REST) API is fully supported for use with GroupWise 18 and beyond.
- ◆ The [GroupWise Web Service \(SOAP\) API](#) is fully supported for use with GroupWise 18 and beyond.

It is also supported with GroupWise 2012 and GroupWise 8.

- ◆ The [GroupWise Administration Object API](#) is no longer supported and has limited application in GroupWise 18.

As long as existing eDirectory objects are still present, the Admin Object API will continue to work with GroupWise 18. We recommend moving to the new GroupWise 18 Administration (REST) API. The capabilities provided by the legacy Admin Object API are provided much more effectively by the Administration (REST) API and the Web Service (SOAP) API.

## 2 Working with the GroupWise Administration Service

The GroupWise Administration service is installed and configured wherever you install the GroupWise agents. For system requirements and installation instructions, see the *GroupWise 18 Installation Guide* ([https://www.novell.com/documentation/groupwise18/gw18\\_guide\\_install/data/inst\\_front.html](https://www.novell.com/documentation/groupwise18/gw18_guide_install/data/inst_front.html)).



# 3 Admin API Resources

Documentation for the GroupWise Admin API is available on the server where the Admin service is installed:

`https://server_address:9710/gwadmin-service/static/apidocs/index.html`

The **Detailed Documentation** link provides a complete resources listing of the APIs available.

---

**IMPORTANT:** Refer to the listing displayed on your GroupWise server for the most current information. The information in this guide might not be as current as the information available on your GroupWise server.

---

A copy of the GroupWise Admin REST API resource documentation can be found at the following link:

- ◆ [gwadmin-service](#)





# A

## Sample Requests and Responses

### Samples by GroupWise Object

GroupWise Objects	Tasks
◆ GroupWise system	<a href="#">Requesting Statistical Information about the GroupWise System</a> <a href="#">Requesting Configuration Information about the GroupWise System</a>
◆ Domains	<a href="#">Requesting a List of Domains in the GroupWise System</a> <a href="#">Requesting Configuration Information about a Domain</a> <a href="#">Finding a Domain by Name</a> <a href="#">Finding a Domain by Type</a>
◆ Post offices	<a href="#">Requesting a List of Post Offices in a Domain</a> <a href="#">Finding a Post Office</a>
◆ Users	<a href="#">Requesting a List of Users in the GroupWise System</a> <a href="#">Requesting a List of Users in the GroupWise System Using a Wildcard Character</a> <a href="#">Requesting a List of Users in a Domain</a> <a href="#">Requesting a List of Users in a Post Office</a> <a href="#">Requesting a List of User Attributes</a> <a href="#">Creating a GroupWise User</a> <a href="#">Creating an External User</a> <a href="#">Adding a Member to a Group</a> <a href="#">Renaming a User</a> <a href="#">Moving Users to a Different Post Office</a> <a href="#">Finding a User in the GroupWise System</a> <a href="#">Finding a User in a Domain</a> <a href="#">Finding a User in a Post Office</a> <a href="#">Requesting a List of Group Memberships for a User</a> <a href="#">Requesting a List of Nicknames for a User</a> <a href="#">Requesting a List of Resources That a User Owns</a> <a href="#">Requesting the Client Options for a User</a>

## GroupWise Objects

## Tasks

- ◆ Groups
  - Requesting a List of Groups in the GroupWise System
  - Requesting a List of Groups in a Domain
  - Requesting a List of Groups in a Post Office
  - Requesting a List of Group Memberships for a User
  - Requesting an Access Control List for a Group
  - Creating a GroupWise Group
  - Adding a Member to a Group
  - Updating the Participation of a Member of a Group
  - Moving a Group to a Different Post Office
  - Performing a Batch Operation to Add Members to a Group
  - Performing a Batch Operation to Modify Members of a Group
  - Performing a Batch Operation to Add ACL Members to a Group
  - Performing a Batch Operation to Modify ACL Members of a Group
- ◆ Resources
  - Requesting a List of Resources in the GroupWise System
  - Requesting a List of Resources in a Domain
  - Requesting a List of Resources in a Post Office
  - Requesting a List of Resources That a User Owns
  - Creating a GroupWise Resource
  - Moving a Resource to a Different Post Office
- ◆ Nicknames
  - Requesting a List of Nicknames in the GroupWise System
  - Requesting a List of Nicknames in a Domain
  - Requesting a List of Nicknames in a Post Office
  - Requesting a List of Nicknames for a User
  - Creating a GroupWise Nickname
- ◆ Agents
  - Requesting Configuration Information about an MTA
  - Requesting Configuration Information about a POA
- ◆ Trusted applications
  - Creating a Trusted Application Record
  - Updating a Trusted Application Record
  - Deleting a Trusted Application Record

## Samples by Task

Tasks	Related GroupWise Objects
◆ Requesting a list	<ul style="list-style-type: none"><li>Requesting a List of Domains in the GroupWise System</li><li>Requesting a List of Post Offices in a Domain</li><li>Requesting a List of Users in the GroupWise System</li><li>Requesting a List of Users in the GroupWise System Using a Wildcard Character</li><li>Requesting a List of Users in a Domain</li><li>Requesting a List of Users in a Post Office</li><li>Requesting a List of User Attributes</li><li>Requesting a List of Groups in the GroupWise System</li><li>Requesting a List of Groups in a Domain</li><li>Requesting a List of Groups in a Post Office</li><li>Requesting a List of Group Memberships for a User</li><li>Requesting an Access Control List for a Group</li><li>Requesting a List of Resources in the GroupWise System</li><li>Requesting a List of Resources in a Domain</li><li>Requesting a List of Resources in a Post Office</li><li>Requesting a List of Resources That a User Owns</li><li>Requesting a List of Nicknames in the GroupWise System</li><li>Requesting a List of Nicknames in a Domain</li><li>Requesting a List of Nicknames in a Post Office</li><li>Requesting a List of Nicknames for a User</li><li>Requesting Configuration Information about a POA</li></ul>
◆ Requesting information	<ul style="list-style-type: none"><li>Requesting Statistical Information about the GroupWise System</li><li>Requesting Configuration Information about the GroupWise System</li><li>Requesting Configuration Information about a Domain</li><li>Requesting Configuration Information about an MTA</li><li>Requesting the Client Options for a User</li></ul>
◆ Creating	<ul style="list-style-type: none"><li>Creating a GroupWise User</li><li>Creating an External User</li><li>Creating a GroupWise Group</li><li>Creating a GroupWise Resource</li><li>Creating a GroupWise Nickname</li><li>Creating a Trusted Application Record</li></ul>
◆ Renaming	<ul style="list-style-type: none"><li>Renaming a User</li></ul>
◆ Finding	<ul style="list-style-type: none"><li>Finding a Domain by Name</li><li>Finding a Domain by Type</li><li>Finding a Post Office</li><li>Finding a User in the GroupWise System</li><li>Finding a User in a Domain</li><li>Finding a User in a Post Office</li></ul>

<b>Tasks</b>	<b>Related GroupWise Objects</b>
<ul style="list-style-type: none"> <li>◆ Moving</li> </ul>	<ul style="list-style-type: none"> <li>Moving Users to a Different Post Office</li> <li>Moving a Group to a Different Post Office</li> <li>Moving a Resource to a Different Post Office</li> </ul>
<ul style="list-style-type: none"> <li>◆ Deleting</li> </ul>	<ul style="list-style-type: none"> <li>Deleting a User from the GroupWise System</li> <li>Deleting a User That Owns Resources from the GroupWise System</li> <li>Deleting a User That Has Been Moved from the GroupWise System</li> <li>Deleting a Group from the GroupWise System</li> <li>Deleting a Member from a Group</li> <li>Deleting a Resource from the GroupWise System</li> <li>Deleting a Nickname from the GroupWise System</li> </ul>
<ul style="list-style-type: none"> <li>◆ Modifying Client Options</li> </ul>	<ul style="list-style-type: none"> <li>Requesting the Client Options for a User</li> <li>Updating the Client Options of a User</li> <li>Setting the GroupWise Password of a User</li> <li>Clearing the GroupWise Password of a User</li> <li>Restoring the Compose Views of a User</li> <li>Modifying the Send Priority Settings of a User</li> <li>Modifying the Calendar Settings of a User</li> <li>Modifying the Alarm Settings of a User</li> <li>Disabling and Locking the Publish Free Busy Setting of a User</li> <li>Enabling the Vibe Access and Configuring the Vibe URL of a User</li> </ul>
<ul style="list-style-type: none"> <li>◆ Working with double-byte characters</li> </ul>	<ul style="list-style-type: none"> <li>Creating a GroupWise User with Chinese Characters in the Last Name</li> <li>Updating a User's First Name That Has Chinese Characters</li> <li>Finding a User's Last Name That Has Chinese Characters</li> </ul>
<ul style="list-style-type: none"> <li>◆ Performing batch operations</li> </ul>	<ul style="list-style-type: none"> <li>Performing a Batch Operation to Add Members to a Group</li> <li>Performing a Batch Operation to Modify Members of a Group</li> <li>Performing a Batch Operation to Add ACL Members to a Group</li> <li>Performing a Batch Operation to Modify ACL Members of a Group</li> </ul>

## Requesting a List of Domains in the GroupWise System

Request:  
GET https://localhost:9710/gwadmin-service/domains

Response Status:  
200 - OK

JSON Response:

```
[ {
  "id" : "DOMAIN.testDom1",
  "guid" : "BC755C40-086F-0000-AE24-CEFE66AF19D4",
  "name" : "testDom1",
  "links" : null,
  "timeCreated" : null,
  "timeLastMod" : 1370885999000,
  "legacyDn" : null,
```

```

"lastModifiedBy" : "Unknown admin",
"lastModifiedOp" : "ADD",
"pendingOp" : null,
"allowedAddressFormats" : null,
"addressBookView" : null,
"alternateInternetAgentName" : null,
"enableICalBrowse" : null,
"databaseVersion" : null,
"defaultInternetAgentName" : null,
"defaultWebAccess" : null,
"description" : null,
"directoryName" : null,
"directorySyncDomainName" : "testDom1",
"domainRebuildCount" : 0,
"domainType" : "PRIMARY",
"domainVersion" : 1212,
"externalSync" : null,
"fileId" : "tesf6f",
"gwId" : null,
"hideUserComments" : null,
"internetDomainName" : null,
"language" : "English - US",
"languageId" : "0",
"linkedDomainName" : null,
"lockoutOldAdmin" : null,
"minimumAdminReleaseDate" : null,
"minimumAdminVersion" : null,
"platform" : null,
"preferredAddressFormat" : null,
"timezone" : "(GMT-07:00) Mountain Time (US & Canada)",
"timezoneId" : "MST",
"path" : "C:\\Novell\\GroupWise\\testDomain1\\",
"adminChanges" : null,
"mtaAddress" : null,
"mtaMtpPort" : null,
"mtaHttpPort" : null,
"mtaAdminPort" : null,
"remoteCreation" : null,
"notifyUser" : null,
"clearNotifyUser" : false,
"connected" : true,
"@type" : "domain",
"@url" : "/gwadmin-service/domains/testDom1"
}, {
  "id" : "DOMAIN.testDom2",
  "guid" : "5FC6CEE0-08FE-0000-8A08-5BB4E7C4BAB9",
  "name" : "testDom2",
  "links" : null,
  "timeCreated" : 1370968862000,
  "timeLastMod" : 1370968863000,
  "legacyDn" : null,
  "lastModifiedBy" : "Unknown admin",
  "lastModifiedOp" : "MODIFY",
  "pendingOp" : "MODIFY",
  "allowedAddressFormats" : null,

```

```

"addressBookView" : null,
"alternateInternetAgentName" : null,
"enableICalBrowse" : null,
"databaseVersion" : null,
"defaultInternetAgentName" : null,
"defaultWebAccess" : null,
"description" : null,
"directoryName" : null,
"directorySyncDomainName" : "testDom2",
"domainRebuildCount" : 1,
"domainType" : "SECONDARY",
"domainVersion" : 1212,
"externalSync" : null,
"fileId" : "tesfebe",
"gwId" : null,
"hideUserComments" : null,
"internetDomainName" : null,
"language" : "English - US",
"languageId" : "0",
"linkedDomainName" : null,
"lockoutOldAdmin" : null,
"minimumAdminReleaseDate" : null,
"minimumAdminVersion" : null,
"platform" : null,
"preferredAddressFormat" : null,
"timezone" : "(GMT-07:00) Mountain Time (US & Canada)",
"timezoneId" : "MST",
"path" : "C:\\Novell\\GroupWise\\testDomain2",
"adminChanges" : null,
"mtaAddress" : null,
"mtaMtpPort" : null,
"mtaHttpPort" : null,
"mtaAdminPort" : null,
"remoteCreation" : null,
"notifyUser" : null,
"clearNotifyUser" : false,
"connected" : false,
"@type" : "domain",
"@url" : "/gwadmin-service/domains/testDom2"
}, {
  "id" : "DOMAIN.testExtDom1",
  "guid" : "7F95C180-0904-0000-8A08-C421ECE16D93",
  "name" : "testExtDom1",
  "links" : null,
  "timeCreated" : 1370971492000,
  "timeLastMod" : 1370971492000,
  "legacyDn" : null,
  "lastModifiedBy" : "admin.testSystem1",
  "lastModifiedOp" : "ADD",
  "pendingOp" : null,
  "allowedAddressFormats" : null,
  "addressBookView" : null,
  "alternateInternetAgentName" : null,
  "enableICalBrowse" : null,
  "databaseVersion" : null,

```

```

"defaultInternetAgentName" : null,
"defaultWebAccess" : null,
"description" : null,
"directoryName" : null,
"directorySyncDomainName" : "testExtDom1",
"domainRebuildCount" : 0,
"domainType" : "EXTERNAL_GROUPWISE",
"domainVersion" : 1212,
"externalSync" : null,
"fileId" : "tes904",
"gwId" : null,
"hideUserComments" : null,
"internetDomainName" : null,
"language" : "English - US",
"languageId" : "0",
"linkedDomainName" : null,
"lockoutOldAdmin" : null,
"minimumAdminReleaseDate" : null,
"minimumAdminVersion" : null,
"platform" : null,
"preferredAddressFormat" : null,
"timezone" : "(GMT-07:00) Mountain Time (US & Canada)",
"timezoneId" : "MST",
"path" : null,
"adminChanges" : null,
"mtaAddress" : null,
"mtaMtpPort" : null,
"mtaHttpPort" : null,
"mtaAdminPort" : null,
"remoteCreation" : null,
"notifyUser" : null,
"clearNotifyUser" : false,
"connected" : false,
"@type" : "domain",
"@url" : "/gwadmin-service/domains/testExtDom1"
} ]

```

XML Response:

```

<list>
  <domain>
    <id>DOMAIN.testDom1</id>
    <guid>BC755C40-086F-0000-AE24-CEFE66AF19D4</guid>
    <name>testDom1</name>
    <objType>domain</objType>
    <url>/gwadmin-service/domains/testDom1</url>
    <timeLastMod>1370885999000</timeLastMod>
    <lastModifiedBy>Unknown admin</lastModifiedBy>
    <lastModifiedOp>ADD</lastModifiedOp>
    <forceNullOnAttrs/>
    <directorySyncDomainName>testDom1</directorySyncDomainName>
    <domainRebuildCount>0</domainRebuildCount>
    <domainType>PRIMARY</domainType>
    <domainVersion>1212</domainVersion>
    <fileId>tesf6f</fileId>
    <language>English - US</language>
  </domain>
</list>

```

```

<languageId>0</languageId>
<timezone>(GMT-07:00) Mountain Time (US & Canada)</timezone>
<timezoneId>MST</timezoneId>
<path>C:\Novell\GroupWise\testDomain1\</path>
<clearNotifyUser>>false</clearNotifyUser>
<connected>>true</connected>
</domain>
<domain>
  <id>DOMAIN.testDom2</id>
  <guid>5FC6CEE0-08FE-0000-8A08-5BB4E7C4BAB9</guid>
  <name>testDom2</name>
  <objType>domain</objType>
  <url>/gwadmin-service/domains/testDom2</url>
  <timeCreated>1370968862000</timeCreated>
  <timeLastMod>1370968863000</timeLastMod>
  <lastModifiedBy>Unknown admin</lastModifiedBy>
  <lastModifiedOp>MODIFY</lastModifiedOp>
  <pendingOp>MODIFY</pendingOp>
  <forceNullOnAttrs/>
  <directorySyncDomainName>testDom2</directorySyncDomainName>
  <domainRebuildCount>1</domainRebuildCount>
  <domainType>SECONDARY</domainType>
  <domainVersion>1212</domainVersion>
  <fileId>tesfebe</fileId>
  <language>English - US</language>
  <languageId>0</languageId>
  <timezone>(GMT-07:00) Mountain Time (US & Canada)</timezone>
  <timezoneId>MST</timezoneId>
  <path>C:\Novell\GroupWise\testDomain2</path>
  <clearNotifyUser>>false</clearNotifyUser>
  <connected>>false</connected>
</domain>
<domain>
  <id>DOMAIN.testExtDom1</id>
  <guid>7F95C180-0904-0000-8A08-C421ECE16D93</guid>
  <name>testExtDom1</name>
  <objType>domain</objType>
  <url>/gwadmin-service/domains/testExtDom1</url>
  <timeCreated>1370971492000</timeCreated>
  <timeLastMod>1370971492000</timeLastMod>
  <lastModifiedBy>admin.testSystem1</lastModifiedBy>
  <lastModifiedOp>ADD</lastModifiedOp>

```



```

    <forceNullOnAttrs/>
    <directorySyncDomainName>testExtDom1</directorySyncDomainName>
    <domainRebuildCount>0</domainRebuildCount>
    <domainType>EXTERNAL_GROUPWISE</domainType>
    <domainVersion>1212</domainVersion>
    <fileId>tes904</fileId>
    <language>English - US</language>
    <languageId>0</languageId>
    <timezone>(GMT-07:00) Mountain Time (US & Canada)</timezone>
    <timezoneId>MST</timezoneId>
    <clearNotifyUser>false</clearNotifyUser>
    <connected>false</connected>
  </domain>
</list>

```

## Requesting a List of Post Offices in a Domain

Request:

```
GET https://localhost:9710/gwadmin-service/domains/testDom1/postoffices
```

Response Status:

200 - OK

JSON Response:

```

[ {
  "id" : "POST_OFFICE.testDom1.testPO1",
  "guid" : "56A986B0-0870-0000-8A08-FB644894ACE1",
  "name" : "testPO1",
  "links" : null,
  "timeCreated" : 1370907858000,
  "timeLastMod" : 1370907860000,
  "legacyDn" : null,
  "lastModifiedBy" : "Unknown admin",
  "lastModifiedOp" : "MODIFY",
  "pendingOp" : null,
  "adminChanges" : null,
  "accessMode" : "CLIENT_SERVER",
  "allowedAddressFormats" : null,
  "archiveServiceTrustedAppName" : null,
  "clientLockout" : null,
  "clientLockoutDate" : null,
  "clientLockoutVersion" : null,
  "defaultInternetAgentName" : null,
  "description" : null,
  "domainName" : "testDom1",
  "deliveryMode" : "APP_THRESHOLD",
  "disableDeltaRecords" : null,
  "disableLdapPasswordChange" : null,
  "disableLiveMove" : null,
  "disableLogins" : false,
  "deltaRecordsMaxAge" : null,
  "enableICalBrowse" : null,
  "externalRecord" : false,
  "externalSync" : null,

```

```

"fileId" : "tes1072",
"gwId" : null,
"internetDomainName" : null,
"intruderDetection" : true,
"intruderLockoutAttempts" : 5,
"intruderLockoutAttemptsInterval" : 30,
"intruderLockoutResetInterval" : 30,
"language" : "English - US",
"languageId" : "0",
"ldapDefaultDirectory" : null,
"ldapUser" : null,
"ldapPassword" : null,
"ldapInactiveConnectionTimeout" : null,
"ldapPoolServerResetTimeout" : null,
"ldapQuarantineThreshold" : null,
"linkAddress" : "C:\\Novell\\GroupWise\\testPostOffice1",
"linkAddressType" : "TCP_IP",
"mtpAppName" : "POA",
"mtpMaxSendSize" : null,
"platform" : null,
"postOfficeVersion" : 1212,
"preferredAddressFormat" : null,
"remoteUser" : null,
"remotePassword" : null,
"restoreAreaName" : null,
"securitySettings" : [ "HIGH" ],
"softwareAreaGuid" : null,
"softwareVersion" : null,
"syncContext" : null,
"timezone" : "(GMT-07:00) Mountain Time (US & Canada)",
"timezoneId" : "MST",
"path" : "C:\\Novell\\GroupWise\\testPostOffice1",
"associationsUpdate" : null,
"poaAddress" : null,
"poaCsPort" : null,
"poaMtpPort" : null,
"poaHttpPort" : null,
"timeStamp" : null,
"clientUpdateBumpNumber" : 0,
"poaAdminPort" : null,
"remoteCreation" : null,
"displayName" : "testPO1",
"draggable" : true,
"@type" : "postOffice",
"@url" : "/gwadmin-service/domains/testDom1/postoffices/testPO1"
} ]

```

XML Response:

```

<list>
  <postOffice>
    <id>POST_OFFICE.testDom1.testPO1</id>
    <guid>56A986B0-0870-0000-8A08-FB644894ACE1</guid>
    <name>testPO1</name>
    <objType>postOffice</objType>
    <url>/gwadmin-service/domains/testDom1/postoffices/testPO1</url>
  </postOffice>
</list>

```

```

<timeCreated>1370907858000</timeCreated>
<timeLastMod>1370907860000</timeLastMod>
<lastModifiedBy>Unknown admin</lastModifiedBy>
<lastModifiedOp>MODIFY</lastModifiedOp>
<forceNullOnAttrs/>
<accessMode>CLIENT_SERVER</accessMode>
<domainName>testDom1</domainName>
<deliveryMode>APP_THRESHOLD</deliveryMode>
<disableLogins>>false</disableLogins>
<externalEntity>>false</externalEntity>
<externalRecord>>false</externalRecord>
<fileId>tes1072</fileId>
<intruderDetection>>true</intruderDetection>
<intruderLockoutAttempts>5</intruderLockoutAttempts>
<intruderLockoutAttemptsInterval>30</intruderLockoutAttemptsInterval>
<intruderLockoutResetInterval>30</intruderLockoutResetInterval>
<language>English - US</language>
<languageId>0</languageId>
<linkAddress>C:\Novell\GroupWise\testPostOffice1</linkAddress>
<linkAddressType>TCP_IP</linkAddressType>
<mtpAppName>POA</mtpAppName>
<postOfficeVersion>1212</postOfficeVersion>
<securitySettings class="AttrNoUsed">HIGH</securitySettings>
<timezone>(GMT-07:00) Mountain Time (US & Canada)</timezone>
<timezoneId>MST</timezoneId>
<path>C:\Novell\GroupWise\testPostOffice1</path>
<clientUpdateBumpNumber>0</clientUpdateBumpNumber>
</postOffice>
</list>

```

## Requesting a List of Users in the GroupWise System

JSON Request:  
GET/XML https://localhost:9710/gwadmin-service/list/USER

Response Status:  
200 - OK

JSON Response:

```

[ {
  "id" : "USER.testDom1.testPO1.testChineseUser1",
  "guid" : "3D438970-09EF-0000-8A08-20888CC82C5A",
  "name" : "testChineseUser1",
  "links" : null,
  "timeCreated" : 1371072312000,
  "timeLastMod" : 1371072312000,
  "legacyDn" : null,
  "lastModifiedBy" : "admin.testSystem1",
  "lastModifiedOp" : "ADD",
  "pendingOp" : null,
  "domainName" : "testDom1",
  "postOfficeName" : "testPO1",
  "description" : null,
  "emailAddresses" : null,

```

```
"visibility" : "SYSTEM",
"defaultInternetAgentName" : null,
"allowedAddressFormats" : null,
"internetDomainName" : null,
"preferredAddressFormat" : null,
"preferredEmailId" : null,
"moveStatus" : null,
"ldapDn" : null,
"ldapId" : null,
"directoryId" : null,
"enableICalBrowse" : null,
"restoreArea" : null,
"expirationDate" : 0,
"externalRecord" : null,
"externalSync" : null,
"fileId" : "77i",
"accountId" : null,
"city" : null,
"company" : null,
"country" : null,
"department" : null,
"externalEntity" : null,
"externalSyncOverride" : null,
"faxNumber" : null,
"gatewayAccess" : null,
"givenName" : null,
"gwId" : null,
"homePhoneNumber" : null,
"ldapAuthentication" : null,
"location" : null,
"lastClientLoginTime" : null,
"lastClientType" : null,
"loginDisabled" : null,
"mailboxId" : null,
"middleInitial" : null,
"mobilePhoneNumber" : null,
"networkId" : null,
"otherPhoneNumber" : null,
"pagerNumber" : null,
"postalZipCode" : null,
"postOfficeBox" : null,
"stateProvince" : null,
"streetAddress" : null,
"suffix" : null,
"surname" : "????",
"telephoneNumber" : null,
"title" : null,
"groupAccessControlUpdateList" : null,
"groupMembersUpdateList" : null,
"adminDefined1" : null,
"adminDefined2" : null,
"adminDefined3" : null,
"adminDefined4" : null,
"adminDefined5" : null,
"adminDefined6" : null,
```

```

"adminDefined7" : null,
"adminDefined8" : null,
"adminDefined9" : null,
"adminDefined10" : null,
"adminDefined11" : null,
"adminDefined12" : null,
"adminDefined13" : null,
"adminDefined14" : null,
"adminDefined15" : null,
"adminDefined16" : null,
"adminDefined17" : null,
"adminDefined18" : null,
"adminDefined19" : null,
"adminDefined20" : null,
"mailboxSizeMb" : null,
"mailboxLicenseType" : null,
"moveComplete" : null,
"directoryUser" : false,
"@type" : "user",
"@url" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/users/
testChineseUser1"
}, {
  "id" : "USER.testExtDom1.testExtPO1.testExtUser1",
  "guid" : null,
  "name" : "testExtUser1",
  "links" : null,
  "timeCreated" : 1371072312000,
  "timeLastMod" : 1371072312000,
  "legacyDn" : null,
  "lastModifiedBy" : "admin.testSystem1",
  "lastModifiedOp" : "ADD",
  "pendingOp" : null,
  "domainName" : "testExtDom1",
  "postOfficeName" : "testExtPO1",
  "description" : null,
  "emailAddresses" : null,
  "visibility" : "SYSTEM",
  "defaultInternetAgentName" : null,
  "allowedAddressFormats" : null,
  "internetDomainName" : null,
  "preferredAddressFormat" : null,
  "preferredEmailId" : null,
  "moveStatus" : null,
  "ldapDn" : null,
  "ldapId" : null,
  "directoryId" : null,
  "enableICalBrowse" : null,
  "restoreArea" : null,
  "expirationDate" : 0,
  "externalRecord" : true,
  "externalSync" : null,
  "fileId" : null,
  "accountId" : null,
  "city" : null,
  "company" : null,

```

```
"country" : null,
"department" : null,
"externalEntity" : null,
"externalSyncOverride" : null,
"faxNumber" : null,
"gatewayAccess" : null,
"givenName" : null,
"gwId" : null,
"homePhoneNumber" : null,
"ldapAuthentication" : null,
"location" : null,
"lastClientLoginTime" : null,
"lastClientType" : null,
"loginDisabled" : null,
"mailboxId" : null,
"middleInitial" : null,
"mobilePhoneNumber" : null,
"networkId" : null,
"otherPhoneNumber" : null,
"pagerNumber" : null,
"postalZipCode" : null,
"postOfficeBox" : null,
"stateProvince" : null,
"streetAddress" : null,
"suffix" : null,
"surname" : null,
"telephoneNumber" : null,
"title" : null,
"groupAccessControlUpdateList" : null,
"groupMembersUpdateList" : null,
"adminDefined1" : null,
"adminDefined2" : null,
"adminDefined3" : null,
"adminDefined4" : null,
"adminDefined5" : null,
"adminDefined6" : null,
"adminDefined7" : null,
"adminDefined8" : null,
"adminDefined9" : null,
"adminDefined10" : null,
"adminDefined11" : null,
"adminDefined12" : null,
"adminDefined13" : null,
"adminDefined14" : null,
"adminDefined15" : null,
"adminDefined16" : null,
"adminDefined17" : null,
"adminDefined18" : null,
"adminDefined19" : null,
"adminDefined20" : null,
"mailboxSizeMb" : null,
"mailboxLicenseType" : null,
"moveComplete" : null,
"directoryUser" : false,
"@type" : "user",
```

```

    "@url" : "/gwadmin-service/domains/testExtDom1/postoffices/testExtPO1/
users/testExtUser1"
  }, {
    "id" : "USER.testDom1.testPO1.testUser1",
    "guid" : "3C0BF3D0-09EF-0000-8A08-20888CC82C5A",
    "name" : "testUser1",
    "links" : null,
    "timeCreated" : 1371072310000,
    "timeLastMod" : 1371072310000,
    "legacyDn" : null,
    "lastModifiedBy" : "admin.testSystem1",
    "lastModifiedOp" : "ADD",
    "pendingOp" : null,
    "domainName" : "testDom1",
    "postOfficeName" : "testPO1",
    "description" : null,
    "emailAddresses" : null,
    "visibility" : "SYSTEM",
    "defaultInternetAgentName" : null,
    "allowedAddressFormats" : null,
    "internetDomainName" : null,
    "preferredAddressFormat" : null,
    "preferredEmailId" : null,
    "moveStatus" : null,
    "ldapDn" : null,
    "ldapId" : null,
    "directoryId" : null,
    "enableICalBrowse" : null,
    "restoreArea" : null,
    "expirationDate" : 0,
    "externalRecord" : null,
    "externalSync" : null,
    "fileId" : "fri",
    "accountId" : null,
    "city" : null,
    "company" : null,
    "country" : null,
    "department" : null,
    "externalEntity" : null,
    "externalSyncOverride" : null,
    "faxNumber" : null,
    "gatewayAccess" : null,
    "givenName" : null,
    "gwId" : null,
    "homePhoneNumber" : null,
    "ldapAuthentication" : null,
    "location" : null,
    "lastClientLoginTime" : null,
    "lastClientType" : null,
    "loginDisabled" : null,
    "mailboxId" : null,
    "middleInitial" : null,
    "mobilePhoneNumber" : null,
    "networkId" : null,
    "otherPhoneNumber" : null,
  }

```

```

"pagerNumber" : null,
"postalZipCode" : null,
"postOfficeBox" : null,
"stateProvince" : null,
"streetAddress" : null,
"suffix" : null,
"surname" : "testSurname1",
"telephoneNumber" : null,
"title" : null,
"groupAccessControlUpdateList" : null,
"groupMembersUpdateList" : null,
"adminDefined1" : null,
"adminDefined2" : null,
"adminDefined3" : null,
"adminDefined4" : null,
"adminDefined5" : null,
"adminDefined6" : null,
"adminDefined7" : null,
"adminDefined8" : null,
"adminDefined9" : null,
"adminDefined10" : null,
"adminDefined11" : null,
"adminDefined12" : null,
"adminDefined13" : null,
"adminDefined14" : null,
"adminDefined15" : null,
"adminDefined16" : null,
"adminDefined17" : null,
"adminDefined18" : null,
"adminDefined19" : null,
"adminDefined20" : null,
"mailboxSizeMb" : null,
"mailboxLicenseType" : null,
"moveComplete" : null,
"directoryUser" : false,
"@type" : "user",
"@url" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/users/
testUser1"
} ]

```

XML Response:

```

<list>
  <user>
    <id>USER.testDom1.testPO1.testChineseUser1</id>
    <guid>D9ACBC50-09EF-0000-8A08-20888CC82C5A</guid>
    <name>testChineseUser1</name>
    <objType>user</objType>
    <url>/gwadmin-service/domains/testDom1/postoffices/testPO1/users/
testChineseUser1</url>
    <timeCreated>1371072575000</timeCreated>
    <timeLastMod>1371072575000</timeLastMod>
    <lastModifiedBy>admin.testSystem1</lastModifiedBy>
    <lastModifiedOp>ADD</lastModifiedOp>
    <forceNullOnAttrs/>
    <domainName>testDom1</domainName>
  
```



```

    <postOfficeName>testPO1</postOfficeName>
    <visibility>SYSTEM</visibility>
    <fileId>iit</fileId>
    <surname>????</surname>
  </user>
  <user>
    <id>USER.testExtDom1.testExtPO1.testExtUser1</id>
    <name>testExtUser1</name>
    <objType>user</objType>
    <url>/gwadmin-service/domains/testExtDom1/postoffices/testExtPO1/
users/testExtUser1</url>
    <timeCreated>1371072575000</timeCreated>
    <timeLastMod>1371072575000</timeLastMod>
    <lastModifiedBy>admin.testSystem1</lastModifiedBy>
    <lastModifiedOp>ADD</lastModifiedOp>
    <forceNullOnAttrs/>
    <domainName>testExtDom1</domainName>
    <postOfficeName>testExtPO1</postOfficeName>
    <visibility>SYSTEM</visibility>
    <externalRecord>true</externalRecord>
  </user>
  <user>
    <id>USER.testDom1.testPO1.testUser1</id>
    <guid>D8C01260-09EF-0000-8A08-20888CC82C5A</guid>
    <name>testUser1</name>
    <objType>user</objType>
    <url>/gwadmin-service/domains/testDom1/postoffices/testPO1/users/
testUser1</url>
    <timeCreated>1371072573000</timeCreated>
    <timeLastMod>1371072573000</timeLastMod>
    <lastModifiedBy>admin.testSystem1</lastModifiedBy>
    <lastModifiedOp>ADD</lastModifiedOp>
    <forceNullOnAttrs/>
    <domainName>testDom1</domainName>
    <postOfficeName>testPO1</postOfficeName>
    <visibility>SYSTEM</visibility>
    <fileId>q2t</fileId>
    <surname>testSurname1</surname>
  </user>
</list>

```

## Requesting a List of Users in the GroupWise System Using a Wildcard Character

Request :

GET https://localhost:9710/gwadmin-service/list/USER?name=testGroupMember\*

Response Status:

200 - OK

---

**NOTE:** The ?name query automatically does end of name wildcard searching.

---

# Requesting a List of Users in a Domain

Request:

```
GET https://localhost:9710/gwadmin-service/list/USER/DOMAIN.testDom1
```

Response Status:

200 - OK

JSON Response:

```
[ {
  "id" : "USER.testDom1.testPO1.testChineseUser1",
  "guid" : "3D438970-09EF-0000-8A08-20888CC82C5A",
  "name" : "testChineseUser1",
  "links" : null,
  "timeCreated" : 1371072312000,
  "timeLastMod" : 1371072312000,
  "legacyDn" : null,
  "lastModifiedBy" : "admin.testSystem1",
  "lastModifiedOp" : "ADD",
  "pendingOp" : null,
  "domainName" : "testDom1",
  "postOfficeName" : "testPO1",
  "description" : null,
  "emailAddresses" : null,
  "visibility" : "SYSTEM",
  "defaultInternetAgentName" : null,
  "allowedAddressFormats" : null,
  "internetDomainName" : null,
  "preferredAddressFormat" : null,
  "preferredEmailId" : null,
  "moveStatus" : null,
  "ldapDn" : null,
  "ldapId" : null,
  "directoryId" : null,
  "enableICalBrowse" : null,
  "restoreArea" : null,
  "expirationDate" : 0,
  "externalRecord" : null,
  "externalSync" : null,
  "fileId" : "77i",
  "accountId" : null,
  "city" : null,
  "company" : null,
  "country" : null,
  "department" : null,
  "externalEntity" : null,
  "externalSyncOverride" : null,
  "faxNumber" : null,
  "gatewayAccess" : null,
  "givenName" : null,
  "gwId" : null,
  "homePhoneNumber" : null,
  "ldapAuthentication" : null,
  "location" : null,
```

```

"lastClientLoginTime" : null,
"lastClientType" : null,
"loginDisabled" : null,
"mailboxId" : null,
"middleInitial" : null,
"mobilePhoneNumber" : null,
"networkId" : null,
"otherPhoneNumber" : null,
"pagerNumber" : null,
"postalZipCode" : null,
"postOfficeBox" : null,
"stateProvince" : null,
"streetAddress" : null,
"suffix" : null,
"surname" : "????",
"telephoneNumber" : null,
"title" : null,
"groupAccessControlUpdateList" : null,
"groupMembersUpdateList" : null,
"adminDefined1" : null,
"adminDefined2" : null,
"adminDefined3" : null,
"adminDefined4" : null,
"adminDefined5" : null,
"adminDefined6" : null,
"adminDefined7" : null,
"adminDefined8" : null,
"adminDefined9" : null,
"adminDefined10" : null,
"adminDefined11" : null,
"adminDefined12" : null,
"adminDefined13" : null,
"adminDefined14" : null,
"adminDefined15" : null,
"adminDefined16" : null,
"adminDefined17" : null,
"adminDefined18" : null,
"adminDefined19" : null,
"adminDefined20" : null,
"mailboxSizeMb" : null,
"mailboxLicenseType" : null,
"moveComplete" : null,
"directoryUser" : false,
"@type" : "user",
"@url" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/users/
testChineseUser1"
}, {
  "id" : "USER.testDom1.testPO1.testUser1",
  "guid" : "3C0BF3D0-09EF-0000-8A08-20888CC82C5A",
  "name" : "testUser1",
  "links" : null,
  "timeCreated" : 1371072310000,
  "timeLastMod" : 1371072310000,
  "legacyDn" : null,
  "lastModifiedBy" : "admin.testSystem1",

```

```
"lastModifiedOp" : "ADD",
"pendingOp" : null,
"domainName" : "testDom1",
"postOfficeName" : "testPO1",
"description" : null,
"emailAddresses" : null,
"visibility" : "SYSTEM",
"defaultInternetAgentName" : null,
"allowedAddressFormats" : null,
"internetDomainName" : null,
"preferredAddressFormat" : null,
"preferredEmailId" : null,
"moveStatus" : null,
"ldapDn" : null,
"ldapId" : null,
"directoryId" : null,
"enableICalBrowse" : null,
"restoreArea" : null,
"expirationDate" : 0,
"externalRecord" : null,
"externalSync" : null,
"fileId" : "fri",
"accountId" : null,
"city" : null,
"company" : null,
"country" : null,
"department" : null,
"externalEntity" : null,
"externalSyncOverride" : null,
"faxNumber" : null,
"gatewayAccess" : null,
"givenName" : null,
"gwId" : null,
"homePhoneNumber" : null,
"ldapAuthentication" : null,
"location" : null,
"lastClientLoginTime" : null,
"lastClientType" : null,
"loginDisabled" : null,
"mailboxId" : null,
"middleInitial" : null,
"mobilePhoneNumber" : null,
"networkId" : null,
"otherPhoneNumber" : null,
"pagerNumber" : null,
"postalZipCode" : null,
"postOfficeBox" : null,
"stateProvince" : null,
"streetAddress" : null,
"suffix" : null,
"surname" : "testSurname1",
"telephoneNumber" : null,
"title" : null,
"groupAccessControlUpdateList" : null,
"groupMembersUpdateList" : null,
```

```

"adminDefined1" : null,
"adminDefined2" : null,
"adminDefined3" : null,
"adminDefined4" : null,
"adminDefined5" : null,
"adminDefined6" : null,
"adminDefined7" : null,
"adminDefined8" : null,
"adminDefined9" : null,
"adminDefined10" : null,
"adminDefined11" : null,
"adminDefined12" : null,
"adminDefined13" : null,
"adminDefined14" : null,
"adminDefined15" : null,
"adminDefined16" : null,
"adminDefined17" : null,
"adminDefined18" : null,
"adminDefined19" : null,
"adminDefined20" : null,
"mailboxSizeMb" : null,
"mailboxLicenseType" : null,
"moveComplete" : null,
"directoryUser" : false,
"@type" : "user",
"@url" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/users/
testUser1"
} ]

```

XML Response:

```

<list>
  <user>
    <id>USER.testDom1.testPO1.testChineseUser1</id>
    <guid>D9ACBC50-09EF-0000-8A08-20888CC82C5A</guid>
    <name>testChineseUser1</name>
    <objType>user</objType>
    <url>/gwadmin-service/domains/testDom1/postoffices/testPO1/users/
testChineseUser1</url>
    <timeCreated>1371072575000</timeCreated>
    <timeLastMod>1371072575000</timeLastMod>
    <lastModifiedBy>admin.testSystem1</lastModifiedBy>
    <lastModifiedOp>ADD</lastModifiedOp>
    <forceNullOnAttrs/>
    <domainName>testDom1</domainName>
    <postOfficeName>testPO1</postOfficeName>
    <visibility>SYSTEM</visibility>
    <fileId>iit</fileId>
    <surname>????</surname>
  </user>
  <user>
    <id>USER.testDom1.testPO1.testUser1</id>
    <guid>D8C01260-09EF-0000-8A08-20888CC82C5A</guid>
    <name>testUser1</name>
    <objType>user</objType>

```

```

    <url>/gadmin-service/domains/testDom1/postoffices/testPO1/users/
testUser1</url>
    <timeCreated>1371072573000</timeCreated>
    <timeLastMod>1371072573000</timeLastMod>
    <lastModifiedBy>admin.testSystem1</lastModifiedBy>
    <lastModifiedOp>ADD</lastModifiedOp>
    <forceNullOnAttrs/>
    <domainName>testDom1</domainName>
    <postOfficeName>testPO1</postOfficeName>
    <visibility>SYSTEM</visibility>
    <fileId>q2t</fileId>
    <surname>testSurname1</surname>
  </user>
</list>

```

## Requesting a List of Users in a Post Office

Request:

```

GET https://localhost:9710/gadmin-service/list/USER/
POST_OFFICE.testDom1.testPO1

```

Response Status:

200 - OK

JSON Response:

```

[ {
  "id" : "USER.testDom1.testPO1.testChineseUser1",
  "guid" : "3D438970-09EF-0000-8A08-20888CC82C5A",
  "name" : "testChineseUser1",
  "links" : null,
  "timeCreated" : 1371072312000,
  "timeLastMod" : 1371072312000,
  "legacyDn" : null,
  "lastModifiedBy" : "admin.testSystem1",
  "lastModifiedOp" : "ADD",
  "pendingOp" : null,
  "domainName" : "testDom1",
  "postOfficeName" : "testPO1",
  "description" : null,
  "emailAddresses" : null,
  "visibility" : "SYSTEM",
  "defaultInternetAgentName" : null,
  "allowedAddressFormats" : null,
  "internetDomainName" : null,
  "preferredAddressFormat" : null,
  "preferredEmailId" : null,
  "moveStatus" : null,
  "ldapDn" : null,
  "ldapId" : null,
  "directoryId" : null,
  "enableICalBrowse" : null,
  "restoreArea" : null,
  "expirationDate" : 0,
  "externalRecord" : null,

```

```
"externalSync" : null,
"fileId" : "77i",
"accountId" : null,
"city" : null,
"company" : null,
"country" : null,
"department" : null,
"externalEntity" : null,
"externalSyncOverride" : null,
"faxNumber" : null,
"gatewayAccess" : null,
"givenName" : null,
"gwId" : null,
"homePhoneNumber" : null,
"ldapAuthentication" : null,
"location" : null,
"lastClientLoginTime" : null,
"lastClientType" : null,
"loginDisabled" : null,
"mailboxId" : null,
"middleInitial" : null,
"mobilePhoneNumber" : null,
"networkId" : null,
"otherPhoneNumber" : null,
"pagerNumber" : null,
"postalZipCode" : null,
"postOfficeBox" : null,
"stateProvince" : null,
"streetAddress" : null,
"suffix" : null,
"surname" : "????",
"telephoneNumber" : null,
"title" : null,
"groupAccessControlUpdateList" : null,
"groupMembersUpdateList" : null,
"adminDefined1" : null,
"adminDefined2" : null,
"adminDefined3" : null,
"adminDefined4" : null,
"adminDefined5" : null,
"adminDefined6" : null,
"adminDefined7" : null,
"adminDefined8" : null,
"adminDefined9" : null,
"adminDefined10" : null,
"adminDefined11" : null,
"adminDefined12" : null,
"adminDefined13" : null,
"adminDefined14" : null,
"adminDefined15" : null,
"adminDefined16" : null,
"adminDefined17" : null,
"adminDefined18" : null,
"adminDefined19" : null,
"adminDefined20" : null,
```

```

    "mailboxSizeMb" : null,
    "mailboxLicenseType" : null,
    "moveComplete" : null,
    "directoryUser" : false,
    "@type" : "user",
    "@url" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/users/
testChineseUser1"
  }, {
    "id" : "USER.testDom1.testPO1.testUser1",
    "guid" : "3C0BF3D0-09EF-0000-8A08-20888CC82C5A",
    "name" : "testUser1",
    "links" : null,
    "timeCreated" : 1371072310000,
    "timeLastMod" : 1371072310000,
    "legacyDn" : null,
    "lastModifiedBy" : "admin.testSystem1",
    "lastModifiedOp" : "ADD",
    "pendingOp" : null,
    "domainName" : "testDom1",
    "postOfficeName" : "testPO1",
    "description" : null,
    "emailAddresses" : null,
    "visibility" : "SYSTEM",
    "defaultInternetAgentName" : null,
    "allowedAddressFormats" : null,
    "internetDomainName" : null,
    "preferredAddressFormat" : null,
    "preferredEmailId" : null,
    "moveStatus" : null,
    "ldapDn" : null,
    "ldapId" : null,
    "directoryId" : null,
    "enableICalBrowse" : null,
    "restoreArea" : null,
    "expirationDate" : 0,
    "externalRecord" : null,
    "externalSync" : null,
    "fileId" : "fri",
    "accountId" : null,
    "city" : null,
    "company" : null,
    "country" : null,
    "department" : null,
    "externalEntity" : null,
    "externalSyncOverride" : null,
    "faxNumber" : null,
    "gatewayAccess" : null,
    "givenName" : null,
    "gwId" : null,
    "homePhoneNumber" : null,
    "ldapAuthentication" : null,
    "location" : null,
    "lastClientLoginTime" : null,
    "lastClientType" : null,
    "loginDisabled" : null,

```



```

"mailboxId" : null,
"middleInitial" : null,
"mobilePhoneNumber" : null,
"networkId" : null,
"otherPhoneNumber" : null,
"pagerNumber" : null,
"postalZipCode" : null,
"postOfficeBox" : null,
"stateProvince" : null,
"streetAddress" : null,
"suffix" : null,
"surname" : "testSurname1",
"telephoneNumber" : null,
"title" : null,
"groupAccessControlUpdateList" : null,
"groupMembersUpdateList" : null,
"adminDefined1" : null,
"adminDefined2" : null,
"adminDefined3" : null,
"adminDefined4" : null,
"adminDefined5" : null,
"adminDefined6" : null,
"adminDefined7" : null,
"adminDefined8" : null,
"adminDefined9" : null,
"adminDefined10" : null,
"adminDefined11" : null,
"adminDefined12" : null,
"adminDefined13" : null,
"adminDefined14" : null,
"adminDefined15" : null,
"adminDefined16" : null,
"adminDefined17" : null,
"adminDefined18" : null,
"adminDefined19" : null,
"adminDefined20" : null,
"mailboxSizeMb" : null,
"mailboxLicenseType" : null,
"moveComplete" : null,
"directoryUser" : false,
"@type" : "user",
"@url" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/users/
testUser1"
} ]

```

XML Response:

```

<list>
  <user>
    <id>USER.testDom1.testPO1.testChineseUser1</id>
    <guid>D9ACBC50-09EF-0000-8A08-20888CC82C5A</guid>
    <name>testChineseUser1</name>
    <objType>user</objType>
    <url>/gwadmin-service/domains/testDom1/postoffices/testPO1/users/
testChineseUser1</url>
    <timeCreated>1371072575000</timeCreated>
  </user>
</list>

```

```

    <timeLastMod>1371072575000</timeLastMod>
    <lastModifiedBy>admin.testSystem1</lastModifiedBy>
    <lastModifiedOp>ADD</lastModifiedOp>
    <forceNullOnAttrs/>
    <domainName>testDom1</domainName>
    <postOfficeName>testPO1</postOfficeName>
    <visibility>SYSTEM</visibility>
    <fileId>iit</fileId>
    <surname>????</surname>
  </user>
  <user>
    <id>USER.testDom1.testPO1.testUser1</id>
    <guid>D8C01260-09EF-0000-8A08-20888CC82C5A</guid>
    <name>testUser1</name>
    <objType>user</objType>
    <url>/gadmin-service/domains/testDom1/postoffices/testPO1/users/
testUser1</url>
    <timeCreated>1371072573000</timeCreated>
    <timeLastMod>1371072573000</timeLastMod>
    <lastModifiedBy>admin.testSystem1</lastModifiedBy>
    <lastModifiedOp>ADD</lastModifiedOp>
    <forceNullOnAttrs/>
    <domainName>testDom1</domainName>
    <postOfficeName>testPO1</postOfficeName>
    <visibility>SYSTEM</visibility>
    <fileId>q2t</fileId>
    <surname>testSurname1</surname>
  </user>
</list>

```

## Requesting a List of User Attributes

Request:

```
GET https://localhost:9710/gadmin-service/diagnostics/object/
USER.testDom1.testPO1.testUser1
```

Response Status:

200 - OK

JSON Response:

```

{
  "attr" : [ {
    "@id" : "50073",
    "$" : "testUser1"
  }, {
    "@id" : "50072",
    "$" : "4"
  }, {
    "@id" : "58014",
    "$" : "testDom1"
  }, {
    "@id" : "59019",
    "$" : "admin.testSystem1"
  }, {

```

```

    "@id" : "50101",
    "$" : "0"
  }, {
    "@id" : "50087",
    "$" : "1"
  }, {
    "@id" : "50080",
    "$" : "3C0BF3D0-09EF-0000-8A08-20888CC82C5A"
  }, {
    "@id" : "50144",
    "$" : "1"
  }, {
    "@id" : "50038",
    "$" : "fri"
  }, {
    "@id" : "50035",
    "$" : "testDom1"
  }, {
    "@id" : "50064",
    "$" : "1371072310"
  }, {
    "@id" : "50001",
    "$" : "2"
  }, {
    "@id" : "50062",
    "$" : "testPO1"
  }, {
    "@id" : "50093",
    "$" : "testSurname1"
  }, {
    "@id" : "63096",
    "$" : "1"
  }, {
    "@id" : "61109",
    "$" : "1371072310"
  }, {
    "@id" : "50076",
    "$" : "2"
  }, {
    "@id" : "50075",
    "$" : "6"
  } ],
  "@id" : "USER.testDom1.testPO1.testUser1"
}

```

XML Response:

```

<objectAttributes>
  <id>USER.testDom1.testPO1.testUser1</id>
  <attr>
    <objectAttributes>
      <id>50073</id>
      <value>testUser1</value>
    </objectAttributes>
    <objectAttributes>
      <id>50072</id>

```

```
<value>4</value>
</objectAttributes>
<objectAttributes>
  <id>58014</id>
  <value>testDom1</value>
</objectAttributes>
<objectAttributes>
  <id>59019</id>
  <value>admin.testSystem1</value>
</objectAttributes>
<objectAttributes>
  <id>50101</id>
  <value>0</value>
</objectAttributes>
<objectAttributes>
  <id>50087</id>
  <value>1</value>
</objectAttributes>
<objectAttributes>
  <id>50080</id>
  <value>D8C01260-09EF-0000-8A08-20888CC82C5A</value>
</objectAttributes>
<objectAttributes>
  <id>50144</id>
  <value>1</value>
</objectAttributes>
<objectAttributes>
  <id>50038</id>
  <value>q2t</value>
</objectAttributes>
<objectAttributes>
  <id>50035</id>
  <value>testDom1</value>
</objectAttributes>
<objectAttributes>
  <id>50064</id>
  <value>1371072573</value>
</objectAttributes>
<objectAttributes>
  <id>50001</id>
  <value>2</value>
</objectAttributes>
<objectAttributes>
  <id>50062</id>
  <value>testPO1</value>
</objectAttributes>
<objectAttributes>
  <id>50093</id>
  <value>testSurname1</value>
</objectAttributes>
<objectAttributes>
  <id>63096</id>
  <value>1</value>
</objectAttributes>
```

```

    <objectAttributes>
      <id>61109</id>
      <value>1371072573</value>
    </objectAttributes>
    <objectAttributes>
      <id>50076</id>
      <value>2</value>
    </objectAttributes>
    <objectAttributes>
      <id>50075</id>
      <value>6</value>
    </objectAttributes>
  </attr>
</objectAttributes>

```

## Requesting a List of Groups in the GroupWise System

Request:

```
GET https://localhost:9710/gwadmin-service/list/GROUP
```

Response Status:

200 - OK

JSON Response:

```

[ {
  "id" : "GROUP.testDom1.testPO1.testGroup1",
  "guid" : "3D593450-09EF-0000-8A08-20888CC82C5A",
  "name" : "testGroup1",
  "links" : null,
  "timeCreated" : 1371072313000,
  "timeLastMod" : 1371072313000,
  "legacyDn" : null,
  "lastModifiedBy" : "admin.testSystem1",
  "lastModifiedOp" : "ADD",
  "pendingOp" : null,
  "domainName" : "testDom1",
  "postOfficeName" : "testPO1",
  "description" : null,
  "emailAddresses" : null,
  "visibility" : "POST_OFFICE",
  "defaultInternetAgentName" : null,
  "allowedAddressFormats" : null,
  "internetDomainName" : null,
  "preferredAddressFormat" : null,
  "preferredEmailId" : null,
  "moveStatus" : null,
  "ldapDn" : null,
  "ldapId" : null,
  "directoryId" : null,
  "postOffice" : null,
  "groupType" : "DISTRIBUTION_LIST",
  "replicationOverride" : null,
  "exclusiveInternetDomain" : false,
  "groupAccessControlUpdateList" : null,

```

```

"groupMembershipUpdateList" : null,
"externalSync" : null,
"moveComplete" : null,
"directoryUser" : false,
"@type" : "group",
"@url" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/groups/
testGroup1"
} ]

```

XML Response:

```

<list>
  <group>
    <id>GROUP.testDom1.testPO1.testGroup1</id>
    <guid>D9C2B550-09EF-0000-8A08-20888CC82C5A</guid>
    <name>testGroup1</name>
    <objType>group</objType>
    <url>/gwadmin-service/domains/testDom1/postoffices/testPO1/groups/
testGroup1</url>
    <timeCreated>1371072575000</timeCreated>
    <timeLastMod>1371072575000</timeLastMod>
    <lastModifiedBy>admin.testSystem1</lastModifiedBy>
    <lastModifiedOp>ADD</lastModifiedOp>
    <forceNullOnAttrs/>
    <domainName>testDom1</domainName>
    <postOfficeName>testPO1</postOfficeName>
    <visibility>POST_OFFICE</visibility>
    <groupType>DISTRIBUTION_LIST</groupType>
    <exclusiveInternetDomain>>false</exclusiveInternetDomain>
  </group>
</list>

```

## Requesting a List of Groups in a Domain

Request:

```
GET https://localhost:9710/gwadmin-service/list/GROUP/DOMAIN.testDom1
```

Response Status:

200 - OK

JSON Response:

```

[ {
  "id" : "GROUP.testDom1.testPO1.testGroup1",
  "guid" : "3D593450-09EF-0000-8A08-20888CC82C5A",
  "name" : "testGroup1",
  "links" : null,
  "timeCreated" : 1371072313000,
  "timeLastMod" : 1371072313000,
  "legacyDn" : null,
  "lastModifiedBy" : "admin.testSystem1",
  "lastModifiedOp" : "ADD",
  "pendingOp" : null,
  "domainName" : "testDom1",
  "postOfficeName" : "testPO1",
  "description" : null,

```

```

"emailAddresses" : null,
"visibility" : "POST_OFFICE",
"defaultInternetAgentName" : null,
"allowedAddressFormats" : null,
"internetDomainName" : null,
"preferredAddressFormat" : null,
"preferredEmailId" : null,
"moveStatus" : null,
"ldapDn" : null,
"ldapId" : null,
"directoryId" : null,
"postOffice" : null,
"groupType" : "DISTRIBUTION_LIST",
"replicationOverride" : null,
"exclusiveInternetDomain" : false,
"groupAccessControlUpdateList" : null,
"groupMembershipUpdateList" : null,
"externalSync" : null,
"moveComplete" : null,
"directoryUser" : false,
"@type" : "group",
"@url" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/groups/
testGroup1"
} ]

```

XML Response:

```

<list>
  <group>
    <id>GROUP.testDom1.testPO1.testGroup1</id>
    <guid>D9C2B550-09EF-0000-8A08-20888CC82C5A</guid>
    <name>testGroup1</name>
    <objType>group</objType>
    <url>/gwadmin-service/domains/testDom1/postoffices/testPO1/groups/
testGroup1</url>
    <timeCreated>1371072575000</timeCreated>
    <timeLastMod>1371072575000</timeLastMod>
    <lastModifiedBy>admin.testSystem1</lastModifiedBy>
    <lastModifiedOp>ADD</lastModifiedOp>
    <forceNullOnAttrs/>
    <domainName>testDom1</domainName>
    <postOfficeName>testPO1</postOfficeName>
    <visibility>POST_OFFICE</visibility>
    <groupType>DISTRIBUTION_LIST</groupType>
    <exclusiveInternetDomain>false</exclusiveInternetDomain>
  </group>
</list>

```

## Requesting a List of Groups in a Post Office

Request:

```
GET https://localhost:9710/gwadmin-service/list/GROUP/  
POST_OFFICE.testDom1.testPO1
```

Response Status:

200 - OK

JSON Response:

```
[ {  
  "id" : "GROUP.testDom1.testPO1.testGroup1",  
  "guid" : "3D593450-09EF-0000-8A08-20888CC82C5A",  
  "name" : "testGroup1",  
  "links" : null,  
  "timeCreated" : 1371072313000,  
  "timeLastMod" : 1371072313000,  
  "legacyDn" : null,  
  "lastModifiedBy" : "admin.testSystem1",  
  "lastModifiedOp" : "ADD",  
  "pendingOp" : null,  
  "domainName" : "testDom1",  
  "postOfficeName" : "testPO1",  
  "description" : null,  
  "emailAddresses" : null,  
  "visibility" : "POST_OFFICE",  
  "defaultInternetAgentName" : null,  
  "allowedAddressFormats" : null,  
  "internetDomainName" : null,  
  "preferredAddressFormat" : null,  
  "preferredEmailId" : null,  
  "moveStatus" : null,  
  "ldapDn" : null,  
  "ldapId" : null,  
  "directoryId" : null,  
  "postOffice" : null,  
  "groupType" : "DISTRIBUTION_LIST",  
  "replicationOverride" : null,  
  "exclusiveInternetDomain" : false,  
  "groupAccessControlUpdateList" : null,  
  "groupMembershipUpdateList" : null,  
  "externalSync" : null,  
  "moveComplete" : null,  
  "directoryUser" : false,  
  "@type" : "group",  
  "@url" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/groups/  
testGroup1"  
} ]
```

XML Response:

```
<list>  
  <group>  
    <id>GROUP.testDom1.testPO1.testGroup1</id>  
    <guid>D9C2B550-09EF-0000-8A08-20888CC82C5A</guid>
```



```

    <name>testGroup1</name>
    <objType>group</objType>
    <url>/gwadmin-service/domains/testDom1/postoffices/testPO1/groups/
testGroup1</url>
    <timeCreated>1371072575000</timeCreated>
    <timeLastMod>1371072575000</timeLastMod>
    <lastModifiedBy>admin.testSystem1</lastModifiedBy>
    <lastModifiedOp>ADD</lastModifiedOp>
    <forceNullOnAttrs/>
    <domainName>testDom1</domainName>
    <postOfficeName>testPO1</postOfficeName>
    <visibility>POST_OFFICE</visibility>
    <groupType>DISTRIBUTION_LIST</groupType>
    <exclusiveInternetDomain>false</exclusiveInternetDomain>
  </group>
</list>

```

## Requesting a List of Group Memberships for a User

Request:

```
GET https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/
testPO1/users/testUser1/groupmemberships
```

Response Status:

200 - OK

JSON Response:

```
[ {
  "id" : "GROUP.testDom1.testPO1.testGroup1",
  "guid" : null,
  "name" : "testGroup1",
  "links" : null,
  "timeCreated" : null,
  "timeLastMod" : null,
  "legacyDn" : null,
  "lastModifiedBy" : null,
  "lastModifiedOp" : null,
  "pendingOp" : null,
  "postOfficeName" : "testPO1",
  "domainName" : "testDom1",
  "givenName" : null,
  "participation" : "PRIMARY",
  "type" : null,
  "surname" : null,
  "@type" : "membership",
  "@url" : null
}
```

```
} ]
```

XML Response:

```
<list>
  <member>
    <id>GROUP.testDom1.testPO1.testGroup1</id>
    <name>testGroup1</name>
    <objType>membership</objType>
    <forceNullOnAttrs/>
    <postOfficeName>testPO1</postOfficeName>
    <domainName>testDom1</domainName>
    <participation>PRIMARY</participation>
  </member>
</list>
```

## Requesting a List of Members in a Group

Request:

```
GET https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/
testPO1/groups/testGroup1/members
```

Response Status:

200 - OK

JSON Response:

```
[ {
  "id" : "USER.testDom1.testPO1.testUser1",
  "guid" : null,
  "name" : "testUser1",
  "links" : null,
  "timeCreated" : null,
  "timeLastMod" : null,
  "legacyDn" : null,
  "lastModifiedBy" : null,
  "lastModifiedOp" : null,
  "pendingOp" : null,
  "postOfficeName" : "testPO1",
  "domainName" : "testDom1",
  "givenName" : null,
  "participation" : "PRIMARY",
  "type" : "USER",
  "surname" : "testSurname1",
  "@type" : "member",
  "@url" : null
} ]
```

XML Response:

```
<list>
  <member>
    <id>USER.testDom1.testPO1.testUser1</id>
    <name>testUser1</name>
    <objType>member</objType>
    <forceNullOnAttrs/>
    <postOfficeName>testPO1</postOfficeName>
    <domainName>testDom1</domainName>
    <participation>PRIMARY</participation>
    <type>USER</type>
    <surname>testSurname1</surname>
  </member>
</list>
```

## Requesting a List of Resources in the GroupWise System

Request:

```
GET https://localhost:9710/gwadmin-service/list/RESOURCE
```

Response Status:

200 - OK

JSON Response:

```
[ {
  "id" : "RESOURCE.testDom1.testPO1.testResource1",
  "guid" : "3E3CB680-09EF-0000-8A08-20888CC82C5A",
  "name" : "testResource1",
  "links" : null,
  "timeCreated" : 1371072314000,
  "timeLastMod" : 1371072314000,
  "legacyDn" : null,
  "lastModifiedBy" : "admin.testSystem1",
  "lastModifiedOp" : "ADD",
  "pendingOp" : null,
  "domainName" : "testDom1",
  "postOfficeName" : "testPO1",
  "description" : null,
  "emailAddresses" : null,
  "visibility" : "SYSTEM",
  "defaultInternetAgentName" : null,
  "allowedAddressFormats" : null,
  "internetDomainName" : null,
  "preferredAddressFormat" : null,
  "preferredEmailId" : null,
  "moveStatus" : null,
  "ldapDn" : null,
  "ldapId" : null,
  "directoryId" : null,
  "enableICalBrowse" : null,
  "restoreArea" : null,
  "expirationDate" : 0,
  "externalRecord" : null,
  "externalSync" : null,
```

```

    "fileId" : "66e",
    "owner" : "testUser1",
    "postOffice" : null,
    "resourceType" : "RESOURCE",
    "telephoneNumber" : null,
    "groupMembershipUpdateList" : null,
    "nicknamesUrl" : null,
    "moveComplete" : null,
    "directoryUser" : false,
    "@type" : "resource",
    "@url" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/
resources/testResource1"
  } ]

```

XML Response:

```

<list>
  <resource>
    <id>RESOURCE.testDom1.testPO1.testResource1</id>
    <guid>DAD49A80-09EF-0000-8A08-20888CC82C5A</guid>
    <name>testResource1</name>
    <objType>resource</objType>
    <url>/gwadmin-service/domains/testDom1/postoffices/testPO1/resources/
testResource1</url>
    <timeCreated>1371072577000</timeCreated>
    <timeLastMod>1371072577000</timeLastMod>
    <lastModifiedBy>admin.testSystem1</lastModifiedBy>
    <lastModifiedOp>ADD</lastModifiedOp>
    <forceNullOnAttrs/>
    <domainName>testDom1</domainName>
    <postOfficeName>testPO1</postOfficeName>
    <visibility>SYSTEM</visibility>
    <fileId>hhp</fileId>
    <owner>testUser1</owner>
    <resourceType>RESOURCE</resourceType>
  </resource>
</list>

```

## Requesting a List of Resources in a Domain

Request:

```
GET https://localhost:9710/gwadmin-service/list/RESOURCE/DOMAIN.testDom1
```

Response Status:

200 - OK

JSON Response:

```

[ {
  "id" : "RESOURCE.testDom1.testPO1.testResource1",
  "guid" : "3E3CB680-09EF-0000-8A08-20888CC82C5A",
  "name" : "testResource1",
  "links" : null,
  "timeCreated" : 1371072314000,
  "timeLastMod" : 1371072314000,
  "legacyDn" : null,

```

```

"lastModifiedBy" : "admin.testSystem1",
"lastModifiedOp" : "ADD",
"pendingOp" : null,
"domainName" : "testDom1",
"postOfficeName" : "testPO1",
"description" : null,
"emailAddresses" : null,
"visibility" : "SYSTEM",
"defaultInternetAgentName" : null,
"allowedAddressFormats" : null,
"internetDomainName" : null,
"preferredAddressFormat" : null,
"preferredEmailId" : null,
"moveStatus" : null,
"ldapDn" : null,
"ldapId" : null,
"directoryId" : null,
"enableICalBrowse" : null,
"restoreArea" : null,
"expirationDate" : 0,
"externalRecord" : null,
"externalSync" : null,
"fileId" : "66e",
"owner" : "testUser1",
"postOffice" : null,
"resourceType" : "RESOURCE",
"telephoneNumber" : null,
"groupMembershipUpdateList" : null,
"nicknamesUrl" : null,
"moveComplete" : null,
"directoryUser" : false,
"@type" : "resource",
"@url" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/
resources/testResource1"
} ]

```

XML Response:

```

<list>
  <resource>
    <id>RESOURCE.testDom1.testPO1.testResource1</id>
    <guid>DAD49A80-09EF-0000-8A08-20888CC82C5A</guid>
    <name>testResource1</name>
    <objType>resource</objType>
    <url>/gwadmin-service/domains/testDom1/postoffices/testPO1/resources/

```

```

testResource1</url>
  <timeCreated>1371072577000</timeCreated>
  <timeLastMod>1371072577000</timeLastMod>
  <lastModifiedBy>admin.testSystem1</lastModifiedBy>
  <lastModifiedOp>ADD</lastModifiedOp>
  <forceNullOnAttrs/>
  <domainName>testDom1</domainName>
  <postOfficeName>testPO1</postOfficeName>
  <visibility>SYSTEM</visibility>
  <fileId>hhp</fileId>
  <owner>testUser1</owner>
  <resourceType>RESOURCE</resourceType>
</resource>
</list>

```

## Requesting a List of Resources in a Post Office

Request:

```
GET https://localhost:9710/gwadmin-service/list/RESOURCE/
POST_OFFICE.testDom1.testPO1
```

Response Status:

200 - OK

JSON Response:

```

[ {
  "id" : "RESOURCE.testDom1.testPO1.testResource1",
  "guid" : "3E3CB680-09EF-0000-8A08-20888CC82C5A",
  "name" : "testResource1",
  "links" : null,
  "timeCreated" : 1371072314000,
  "timeLastMod" : 1371072314000,
  "legacyDn" : null,
  "lastModifiedBy" : "admin.testSystem1",
  "lastModifiedOp" : "ADD",
  "pendingOp" : null,
  "domainName" : "testDom1",
  "postOfficeName" : "testPO1",
  "description" : null,
  "emailAddresses" : null,
  "visibility" : "SYSTEM",
  "defaultInternetAgentName" : null,
  "allowedAddressFormats" : null,
  "internetDomainName" : null,
  "preferredAddressFormat" : null,
  "preferredEmailId" : null,
  "moveStatus" : null,
  "ldapDn" : null,
  "ldapId" : null,
  "directoryId" : null,
  "enableICalBrowse" : null,
  "restoreArea" : null,
  "expirationDate" : 0,
  "externalRecord" : null,

```

```

"externalSync" : null,
"fileId" : "66e",
"owner" : "testUser1",
"postOffice" : null,
"resourceType" : "RESOURCE",
"telephoneNumber" : null,
"groupMembershipUpdateList" : null,
"nicknamesUrl" : null,
"moveComplete" : null,
"directoryUser" : false,
"@type" : "resource",
"@url" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/
resources/testResource1"
} ]

```

XML Response:

```

<list>
  <resource>
    <id>RESOURCE.testDom1.testPO1.testResource1</id>
    <guid>DAD49A80-09EF-0000-8A08-20888CC82C5A</guid>
    <name>testResource1</name>
    <objType>resource</objType>
    <url>/gwadmin-service/domains/testDom1/postoffices/testPO1/resources/
testResource1</url>
    <timeCreated>1371072577000</timeCreated>
    <timeLastMod>1371072577000</timeLastMod>
    <lastModifiedBy>admin.testSystem1</lastModifiedBy>
    <lastModifiedOp>ADD</lastModifiedOp>
    <forceNullOnAttrs/>
    <domainName>testDom1</domainName>
    <postOfficeName>testPO1</postOfficeName>
    <visibility>SYSTEM</visibility>
    <fileId>hhp</fileId>
    <owner>testUser1</owner>
    <resourceType>RESOURCE</resourceType>
  </resource>
</list>

```

## Requesting a List of Resources That a User Owns

Request:

```

GET https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/
testPO1/users/testUser1/resources

```

Response Status:

200 - OK

JSON Response:

```

[ {
  "id" : "RESOURCE.testDom1.testPO1.testResource1",
  "guid" : "3E3CB680-09EF-0000-8A08-20888CC82C5A",
  "name" : "testResource1",
  "links" : null,
  "timeCreated" : 1371072314000,

```

```

"timeLastMod" : 1371072314000,
"legacyDn" : null,
"lastModifiedBy" : "admin.testSystem1",
"lastModifiedOp" : "ADD",
"pendingOp" : null,
"domainName" : "testDom1",
"postOfficeName" : "testPO1",
"description" : null,
"emailAddresses" : null,
"visibility" : "SYSTEM",
"defaultInternetAgentName" : null,
"allowedAddressFormats" : null,
"internetDomainName" : null,
"preferredAddressFormat" : null,
"preferredEmailId" : null,
"moveStatus" : null,
"ldapDn" : null,
"ldapId" : null,
"directoryId" : null,
"enableICalBrowse" : null,
"restoreArea" : null,
"expirationDate" : 0,
"externalRecord" : null,
"externalSync" : null,
"fileId" : "66e",
"owner" : "testUser1",
"postOffice" : null,
"resourceType" : "RESOURCE",
"telephoneNumber" : null,
"groupMembershipUpdateList" : null,
"nicknamesUrl" : null,
"moveComplete" : null,
"directoryUser" : false,
"@type" : "resource",
"@url" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/
resources/testResource1"
} ]

```

XML Response:

```

<list>
  <resource>
    <id>RESOURCE.testDom1.testPO1.testResource1</id>
    <guid>DAD49A80-09EF-0000-8A08-20888CC82C5A</guid>
    <name>testResource1</name>
    <objType>resource</objType>
    <url>/gwadmin-service/domains/testDom1/postoffices/testPO1/resources/

```



```

testResource1</url>
  <timeCreated>1371072577000</timeCreated>
  <timeLastMod>1371072577000</timeLastMod>
  <lastModifiedBy>admin.testSystem1</lastModifiedBy>
  <lastModifiedOp>ADD</lastModifiedOp>
  <forceNullOnAttrs/>
  <domainName>testDom1</domainName>
  <postOfficeName>testPO1</postOfficeName>
  <visibility>SYSTEM</visibility>
  <fileId>hhp</fileId>
  <owner>testUser1</owner>
  <resourceType>RESOURCE</resourceType>
</resource>
</list>

```

## Requesting a List of Nicknames in the GroupWise System

Request:

```
GET https://localhost:9710/gwadmin-service/list/NICKNAME
```

Response Status:

200 - OK

JSON Response:

```

[ {
  "id" : "NICKNAME.testDom1.testPO1.testNicknameName1",
  "guid" : "3E2536E0-09EF-0000-8A08-20888CC82C5A",
  "name" : "testNicknameName1",
  "links" : null,
  "timeCreated" : 1371072314000,
  "timeLastMod" : 1371072314000,
  "legacyDn" : null,
  "lastModifiedBy" : "admin.testSystem1",
  "lastModifiedOp" : "ADD",
  "pendingOp" : null,
  "domainName" : "testDom1",
  "postOfficeName" : "testPO1",
  "description" : null,
  "emailAddresses" : null,
  "visibility" : "SYSTEM",
  "defaultInternetAgentName" : null,
  "allowedAddressFormats" : null,
  "internetDomainName" : null,
  "preferredAddressFormat" : null,
  "preferredEmailId" : null,
  "moveStatus" : null,
  "ldapDn" : null,
  "ldapId" : null,
  "directoryId" : null,
  "enableICalBrowse" : null,
  "restoreArea" : null,
  "expirationDate" : 0,
  "externalRecord" : null,
  "externalSync" : null,

```

```
"fileId" : null,
"accountId" : null,
"city" : null,
"company" : null,
"country" : null,
"department" : null,
"externalEntity" : null,
"externalSyncOverride" : null,
"faxNumber" : null,
"gatewayAccess" : null,
"givenName" : null,
"gwId" : null,
"homePhoneNumber" : null,
"ldapAuthentication" : null,
"location" : null,
"lastClientLoginTime" : null,
"lastClientType" : null,
"loginDisabled" : null,
"mailboxId" : null,
"middleInitial" : null,
"mobilePhoneNumber" : null,
"networkId" : null,
"otherPhoneNumber" : null,
"pagerNumber" : null,
"postalZipCode" : null,
"postOfficeBox" : null,
"stateProvince" : null,
"streetAddress" : null,
"suffix" : null,
"surname" : "testNicknameSurname1",
"telephoneNumber" : null,
"title" : null,
"groupAccessControlUpdateList" : null,
"groupMembersUpdateList" : null,
"adminDefined1" : null,
"adminDefined2" : null,
"adminDefined3" : null,
"adminDefined4" : null,
"adminDefined5" : null,
"adminDefined6" : null,
"adminDefined7" : null,
"adminDefined8" : null,
"adminDefined9" : null,
"adminDefined10" : null,
"adminDefined11" : null,
"adminDefined12" : null,
"adminDefined13" : null,
"adminDefined14" : null,
"adminDefined15" : null,
"adminDefined16" : null,
"adminDefined17" : null,
"adminDefined18" : null,
"adminDefined19" : null,
"adminDefined20" : null,
"mailboxSizeMb" : null,
```

```

"mailboxLicenseType" : null,
"referredUserName" : null,
"userName" : "testUser1",
"userPostOfficeName" : "testPO1",
"userDomainName" : "testDom1",
"realMemberType" : "USER",
"moveComplete" : null,
"directoryUser" : false,
"@type" : "nickname",
"@url" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/nicknames/testNicknameName1"
} ]

```

XML Response:

```

<list>
  <nickname>
    <id>NICKNAME.testDom1.testPO1.testNicknameName1</id>
    <guid>DAB356E0-09EF-0000-8A08-20888CC82C5A</guid>
    <name>testNicknameName1</name>
    <objType>nickname</objType>
    <url>/gwadmin-service/domains/testDom1/postoffices/testPO1/nicknames/testNicknameName1</url>
    <timeCreated>1371072577000</timeCreated>
    <timeLastMod>1371072577000</timeLastMod>
    <lastModifiedBy>admin.testSystem1</lastModifiedBy>
    <lastModifiedOp>ADD</lastModifiedOp>
    <forceNullOnAttrs/>
    <domainName>testDom1</domainName>
    <postOfficeName>testPO1</postOfficeName>
    <visibility>SYSTEM</visibility>
    <surname>testNicknameSurname1</surname>
    <userName>testUser1</userName>
    <userPostOfficeName>testPO1</userPostOfficeName>
    <userDomainName>testDom1</userDomainName>
    <realMemberType>USER</realMemberType>
  </nickname>
</list>

```

## Requesting a List of Nicknames in a Domain

Request:

```
GET https://localhost:9710/gwadmin-service/list/NICKNAME/DOMAIN.testDom1
```

Response Status:

200 - OK

JSON Response:

```

[ {
  "id" : "NICKNAME.testDom1.testPO1.testNicknameName1",
  "guid" : "3E2536E0-09EF-0000-8A08-20888CC82C5A",
  "name" : "testNicknameName1",
  "links" : null,
  "timeCreated" : 1371072314000,
  "timeLastMod" : 1371072314000,

```

```
"legacyDn" : null,
"lastModifiedBy" : "admin.testSystem1",
"lastModifiedOp" : "ADD",
"pendingOp" : null,
"domainName" : "testDom1",
"postOfficeName" : "testPO1",
"description" : null,
"emailAddresses" : null,
"visibility" : "SYSTEM",
"defaultInternetAgentName" : null,
"allowedAddressFormats" : null,
"internetDomainName" : null,
"preferredAddressFormat" : null,
"preferredEmailId" : null,
"moveStatus" : null,
"ldapDn" : null,
"ldapId" : null,
"directoryId" : null,
"enableICalBrowse" : null,
"restoreArea" : null,
"expirationDate" : 0,
"externalRecord" : null,
"externalSync" : null,
"fileId" : null,
"accountId" : null,
"city" : null,
"company" : null,
"country" : null,
"department" : null,
"externalEntity" : null,
"externalSyncOverride" : null,
"faxNumber" : null,
"gatewayAccess" : null,
"givenName" : null,
"gwId" : null,
"homePhoneNumber" : null,
"ldapAuthentication" : null,
"location" : null,
"lastClientLoginTime" : null,
"lastClientType" : null,
"loginDisabled" : null,
"mailboxId" : null,
"middleInitial" : null,
"mobilePhoneNumber" : null,
"networkId" : null,
"otherPhoneNumber" : null,
"pagerNumber" : null,
"postalZipCode" : null,
"postOfficeBox" : null,
"stateProvince" : null,
"streetAddress" : null,
"suffix" : null,
"surname" : "testNicknameSurname1",
"telephoneNumber" : null,
"title" : null,
```

```

"groupAccessControlUpdateList" : null,
"groupMembersUpdateList" : null,
"adminDefined1" : null,
"adminDefined2" : null,
"adminDefined3" : null,
"adminDefined4" : null,
"adminDefined5" : null,
"adminDefined6" : null,
"adminDefined7" : null,
"adminDefined8" : null,
"adminDefined9" : null,
"adminDefined10" : null,
"adminDefined11" : null,
"adminDefined12" : null,
"adminDefined13" : null,
"adminDefined14" : null,
"adminDefined15" : null,
"adminDefined16" : null,
"adminDefined17" : null,
"adminDefined18" : null,
"adminDefined19" : null,
"adminDefined20" : null,
"mailboxSizeMb" : null,
"mailboxLicenseType" : null,
"referredUserName" : null,
"userName" : "testUser1",
"userPostOfficeName" : "testPO1",
"userDomainName" : "testDom1",
"realMemberType" : "USER",
"moveComplete" : null,
"directoryUser" : false,
"@type" : "nickname",
"@url" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/
nicknames/testNicknameName1"
} ]

```

XML Response:

```

<list>
  <nickname>
    <id>NICKNAME.testDom1.testPO1.testNicknameName1</id>
    <guid>DAB356E0-09EF-0000-8A08-20888CC82C5A</guid>
    <name>testNicknameName1</name>
    <objType>nickname</objType>
    <url>/gwadmin-service/domains/testDom1/postoffices/testPO1/nicknames/
testNicknameName1</url>
    <timeCreated>1371072577000</timeCreated>
  </nickname>
</list>

```

```

<timeLastMod>1371072577000</timeLastMod>
<lastModifiedBy>admin.testSystem1</lastModifiedBy>
<lastModifiedOp>ADD</lastModifiedOp>
<forceNullOnAttrs/>
<domainName>testDom1</domainName>
<postOfficeName>testPO1</postOfficeName>
<visibility>SYSTEM</visibility>
<surname>testNicknameSurname1</surname>
<userName>testUser1</userName>
<userPostOfficeName>testPO1</userPostOfficeName>
<userDomainName>testDom1</userDomainName>
<realMemberType>USER</realMemberType>
</nickname>
</list>

```

## Requesting a List of Nicknames in a Post Office

Request:

```
GET https://localhost:9710/gwadmin-service/list/NICKNAME/
POST_OFFICE.testDom1.testPO1
```

Response Status:

200 - OK

JSON Response:

```

[ {
  "id" : "NICKNAME.testDom1.testPO1.testNicknameName1",
  "guid" : "3E2536E0-09EF-0000-8A08-20888CC82C5A",
  "name" : "testNicknameName1",
  "links" : null,
  "timeCreated" : 1371072314000,
  "timeLastMod" : 1371072314000,
  "legacyDn" : null,
  "lastModifiedBy" : "admin.testSystem1",
  "lastModifiedOp" : "ADD",
  "pendingOp" : null,
  "domainName" : "testDom1",
  "postOfficeName" : "testPO1",
  "description" : null,
  "emailAddresses" : null,
  "visibility" : "SYSTEM",
  "defaultInternetAgentName" : null,
  "allowedAddressFormats" : null,
  "internetDomainName" : null,
  "preferredAddressFormat" : null,
  "preferredEmailId" : null,
  "moveStatus" : null,
  "ldapDn" : null,
  "ldapId" : null,
  "directoryId" : null,
  "enableICalBrowse" : null,
  "restoreArea" : null,
  "expirationDate" : 0,
  "externalRecord" : null,

```

```
"externalSync" : null,
"fileId" : null,
"accountId" : null,
"city" : null,
"company" : null,
"country" : null,
"department" : null,
"externalEntity" : null,
"externalSyncOverride" : null,
"faxNumber" : null,
"gatewayAccess" : null,
"givenName" : null,
"gwId" : null,
"homePhoneNumber" : null,
"ldapAuthentication" : null,
"location" : null,
"lastClientLoginTime" : null,
"lastClientType" : null,
"loginDisabled" : null,
"mailboxId" : null,
"middleInitial" : null,
"mobilePhoneNumber" : null,
"networkId" : null,
"otherPhoneNumber" : null,
"pagerNumber" : null,
"postalZipCode" : null,
"postOfficeBox" : null,
"stateProvince" : null,
"streetAddress" : null,
"suffix" : null,
"surname" : "testNicknameSurname1",
"telephoneNumber" : null,
"title" : null,
"groupAccessControlUpdateList" : null,
"groupMembersUpdateList" : null,
"adminDefined1" : null,
"adminDefined2" : null,
"adminDefined3" : null,
"adminDefined4" : null,
"adminDefined5" : null,
"adminDefined6" : null,
"adminDefined7" : null,
"adminDefined8" : null,
"adminDefined9" : null,
"adminDefined10" : null,
"adminDefined11" : null,
"adminDefined12" : null,
"adminDefined13" : null,
"adminDefined14" : null,
"adminDefined15" : null,
"adminDefined16" : null,
"adminDefined17" : null,
"adminDefined18" : null,
"adminDefined19" : null,
"adminDefined20" : null,
```

```

"mailboxSizeMb" : null,
"mailboxLicenseType" : null,
"referredUserName" : null,
"userName" : "testUser1",
"userPostOfficeName" : "testPO1",
"userDomainName" : "testDom1",
"realMemberType" : "USER",
"moveComplete" : null,
"directoryUser" : false,
"@type" : "nickname",
"@url" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/
nicknames/testNicknameName1"
} ]

```

XML Response:

```

<list>
  <nickname>
    <id>NICKNAME.testDom1.testPO1.testNicknameName1</id>
    <guid>DAB356E0-09EF-0000-8A08-20888CC82C5A</guid>
    <name>testNicknameName1</name>
    <objType>nickname</objType>
    <url>/gwadmin-service/domains/testDom1/postoffices/testPO1/nicknames/
testNicknameName1</url>
    <timeCreated>1371072577000</timeCreated>
    <timeLastMod>1371072577000</timeLastMod>
    <lastModifiedBy>admin.testSystem1</lastModifiedBy>
    <lastModifiedOp>ADD</lastModifiedOp>
    <forceNullOnAttrs/>
    <domainName>testDom1</domainName>
    <postOfficeName>testPO1</postOfficeName>
    <visibility>SYSTEM</visibility>
    <surname>testNicknameSurname1</surname>
    <userName>testUser1</userName>
    <userPostOfficeName>testPO1</userPostOfficeName>
    <userDomainName>testDom1</userDomainName>
    <realMemberType>USER</realMemberType>
  </nickname>
</list>

```



## Requesting a List of Nicknames for a User

Request:

```
GET https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/testPO1/users/testUser1/nicknames
```

Response Status:

200 - OK

JSON Response:

```
[ {  
  "id" : "NICKNAME.testDom1.testPO1.testNicknameName1",  
  "guid" : "3E2536E0-09EF-0000-8A08-20888CC82C5A",  
  "name" : "testNicknameName1",  
  "links" : null,  
  "timeCreated" : 1371072314000,  
  "timeLastMod" : 1371072314000,  
  "legacyDn" : null,  
  "lastModifiedBy" : "admin.testSystem1",  
  "lastModifiedOp" : "ADD",  
  "pendingOp" : null,  
  "domainName" : "testDom1",  
  "postOfficeName" : "testPO1",  
  "description" : null,  
  "emailAddresses" : null,  
  "visibility" : "SYSTEM",  
  "defaultInternetAgentName" : null,  
  "allowedAddressFormats" : null,  
  "internetDomainName" : null,  
  "preferredAddressFormat" : null,  
  "preferredEmailId" : null,  
  "moveStatus" : null,  
  "ldapDn" : null,  
  "ldapId" : null,  
  "directoryId" : null,  
  "enableICalBrowse" : null,  
  "restoreArea" : null,  
  "expirationDate" : 0,  
  "externalRecord" : null,  
  "externalSync" : null,  
  "fileId" : null,  
  "accountId" : null,  
  "city" : null,  
  "company" : null,  
  "country" : null,  
  "department" : null,  
  "externalEntity" : null,  
  "externalSyncOverride" : null,  
  "faxNumber" : null,  
  "gatewayAccess" : null,  
  "givenName" : null,  
  "gwId" : null,  
  "homePhoneNumber" : null,  
  "ldapAuthentication" : null,  
}
```

```

"location" : null,
"lastClientLoginTime" : null,
"lastClientType" : null,
"loginDisabled" : null,
"mailboxId" : null,
"middleInitial" : null,
"mobilePhoneNumber" : null,
"networkId" : null,
"otherPhoneNumber" : null,
"pagerNumber" : null,
"postalZipCode" : null,
"postOfficeBox" : null,
"stateProvince" : null,
"streetAddress" : null,
"suffix" : null,
"surname" : "testNicknameSurname1",
"telephoneNumber" : null,
"title" : null,
"groupAccessControlUpdateList" : null,
"groupMembersUpdateList" : null,
"adminDefined1" : null,
"adminDefined2" : null,
"adminDefined3" : null,
"adminDefined4" : null,
"adminDefined5" : null,
"adminDefined6" : null,
"adminDefined7" : null,
"adminDefined8" : null,
"adminDefined9" : null,
"adminDefined10" : null,
"adminDefined11" : null,
"adminDefined12" : null,
"adminDefined13" : null,
"adminDefined14" : null,
"adminDefined15" : null,
"adminDefined16" : null,
"adminDefined17" : null,
"adminDefined18" : null,
"adminDefined19" : null,
"adminDefined20" : null,
"mailboxSizeMb" : null,
"mailboxLicenseType" : null,
"referredUserName" : null,
"userName" : "testUser1",
"userPostOfficeName" : "testPO1",
"userDomainName" : "testDom1",
"realMemberType" : "USER",
"moveComplete" : null,
"directoryUser" : false,
"@type" : "nickname",
"@url" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/
nicknames/testNicknameName1"
} ]

```

XML Response:

```

<list>
  <nickname>
    <id>NICKNAME.testDom1.testPO1.testNicknameName1</id>
    <guid>DAB356E0-09EF-0000-8A08-20888CC82C5A</guid>
    <name>testNicknameName1</name>
    <objType>nickname</objType>
    <url>/gwadmin-service/domains/testDom1/postoffices/testPO1/nicknames/
testNicknameName1</url>
    <timeCreated>1371072577000</timeCreated>
    <timeLastMod>1371072577000</timeLastMod>
    <lastModifiedBy>admin.testSystem1</lastModifiedBy>
    <lastModifiedOp>ADD</lastModifiedOp>
    <forceNullOnAttrs/>
    <domainName>testDom1</domainName>
    <postOfficeName>testPO1</postOfficeName>
    <visibility>SYSTEM</visibility>
    <surname>testNicknameSurname1</surname>
    <userName>testUser1</userName>
    <userPostOfficeName>testPO1</userPostOfficeName>
    <userDomainName>testDom1</userDomainName>
    <realMemberType>USER</realMemberType>
  </nickname>
</list>

```

## Requesting Statistical Information about the GroupWise System

Request:

```
GET https://localhost:9710/gwadmin-service/system/info
```

Response Status:

200 - OK

JSON Response:

```

{
  "id" : null,
  "guid" : null,
  "name" : null,
  "links" : null,
  "timeCreated" : null,
  "timeLastMod" : null,
  "legacyDn" : null,
  "lastModifiedBy" : null,
  "lastModifiedOp" : null,
  "pendingOp" : null,
  "externalDomainCount" : 1,
  "externalGatewayCount" : 0,
  "externalPostOfficeCount" : 1,
  "domainCount" : 2,
  "gatewayCount" : 1,
  "postOfficeCount" : 2,
  "lastAuditDate" : null,
  "ownedResourceCount" : null,

```

```

"gatewayAliasCount" : null,
"nicknameCount" : null,
"groupMembershipCount" : null,
"libraryAccessCount" : null,
"accessAccountsCount" : null,
"mailboxSize" : null,
"lastLoginDate" : null,
"lastModTime" : null,
"lastClientType" : null,
"lastClientVersion" : null,
"lastClientLanguage" : null,
"memberCount" : null,
"externalGroupCount" : 0,
"externalLibraryCount" : 0,
"externalResourceCount" : 0,
"externalUserCount" : 1,
"fullLicenseMailboxCount" : 0,
"groupCount" : 1,
"inactiveMailboxCount" : 0,
"libraryCount" : 2,
"limitedLicenseMailboxCount" : 0,
"linuxMailboxCount" : null,
"linux65XMailboxCount" : null,
"linux70XMailboxCount" : null,
"linux80XMailboxCount" : null,
"mac5XMailboxCount" : null,
"mac6XMailboxCount" : null,
"mac70XMailboxCount" : null,
"mac80XMailboxCount" : null,
"macMailboxCount" : null,
"outlookConnector65XMailboxCount" : null,
"outlookConnector70XMailboxCount" : null,
"outlookConnector80XMailboxCount" : null,
"outlookConnectorMailboxCount" : null,
"resourceCount" : 1,
"totalMailboxCount" : 0,
"winX65XMailboxCount" : null,
"winX70XMailboxCount" : null,
"winX80XMailboxCount" : null,
"winXMailboxCount" : null,
"uncategorizedMailboxCount" : null,
"windows65XMailboxCount" : null,
"windows70XMailboxCount" : null,
"windows80XMailboxCount" : null,
"windowsMailboxCount" : null,
"windows2012XMailboxCount" : null,
"userCount" : 8,
"coexistenceExportedUserCount" : null,
"coexistenceImportedUserCount" : null,
"x400Count" : null,
"@type" : null,
"@url" : null
}

```

XML Response:

```

<systemInfo>
  <forceNullOnAttrs/>
  <externalDomainCount>1</externalDomainCount>
  <externalGatewayCount>0</externalGatewayCount>
  <externalPostOfficeCount>1</externalPostOfficeCount>
  <domainCount>2</domainCount>
  <gatewayCount>1</gatewayCount>
  <postOfficeCount>2</postOfficeCount>
  <externalGroupCount>0</externalGroupCount>
  <externalLibraryCount>0</externalLibraryCount>
  <externalResourceCount>0</externalResourceCount>
  <externalUserCount>1</externalUserCount>
  <fullLicenseMailboxCount>0</fullLicenseMailboxCount>
  <groupCount>1</groupCount>
  <inactiveMailboxCount>0</inactiveMailboxCount>
  <libraryCount>2</libraryCount>
  <limitedLicenseMailboxCount>0</limitedLicenseMailboxCount>
  <resourceCount>1</resourceCount>
  <totalMailboxCount>0</totalMailboxCount>
  <userCount>8</userCount>
</systemInfo>

```

## Requesting Configuration Information about the GroupWise System

Request:

```
GET https://localhost:9710/gwadmin-service/system
```

Response Status:

200 - OK

JSON Response:

```

{
  "id" : "SYSTEM_RECORD.testSystem1",
  "guid" : "B5F73870-086F-0000-AE24-CEFE66AF19D4",
  "name" : "testSystem1",
  "links" : [ {
    "@title" : "adminservices",
    "@href" : "/gwadmin-service/system/adminservices"
  }, {
    "@title" : "calpubhosts",
    "@href" : "/gwadmin-service/system/calpubhosts"
  }, {
    "@title" : "customaddresses",
    "@href" : "/gwadmin-service/system/customaddresses"
  }, {
    "@title" : "customaddressestest",
    "@href" : "/gwadmin-service/system/customaddresses/test"
  }, {
    "@title" : "defaulttimezones",
    "@href" : "/gwadmin-service/system/defaulttimezones"
  }, {
    "@title" : "directories",

```

```

    "@href" : "/gwadmin-service/system/directories"
  }, {
    "@title" : "expired",
    "@href" : "/gwadmin-service/system/expired"
  }, {
    "@title" : "externalsystems",
    "@href" : "/gwadmin-service/system/externalsystems"
  }, {
    "@title" : "globalsignatures",
    "@href" : "/gwadmin-service/system/globalsignatures"
  }, {
    "@title" : "info",
    "@href" : "/gwadmin-service/system/info"
  }, {
    "@title" : "internetdomains",
    "@href" : "/gwadmin-service/system/internetdomains"
  }, {
    "@title" : "ldapservers",
    "@href" : "/gwadmin-service/system/ldapservers"
  }, {
    "@title" : "maintenance",
    "@href" : "/gwadmin-service/system/maintenance"
  }, {
    "@title" : "moverequests",
    "@href" : "/gwadmin-service/system/moverequests"
  }, {
    "@title" : "pending",
    "@href" : "/gwadmin-service/system/pending"
  }, {
    "@title" : "recoverconnection",
    "@href" : "/gwadmin-service/system/recoverconnection"
  }, {
    "@title" : "acl",
    "@href" : "/gwadmin-service/system/acl"
  }, {
    "@title" : "restoreareas",
    "@href" : "/gwadmin-service/system/restoreareas"
  }, {
    "@title" : "scheduleevents",
    "@href" : "/gwadmin-service/system/scheduleevents"
  }, {
    "@title" : "scheduleeventactions",
    "@href" : "/gwadmin-service/system/scheduleeventactions"
  }, {
    "@title" : "softwareareas",
    "@href" : "/gwadmin-service/system/softwareareas"
  }, {
    "@title" : "timezones",
    "@href" : "/gwadmin-service/system/timezones"
  }, {
    "@title" : "trustedapps",
    "@href" : "/gwadmin-service/system/trustedapps"
  }, {
    "@title" : "userbyemail",
    "@href" : "/gwadmin-service/system/userbyemail"
  }

```

```

}, {
  "@title" : "domains",
  "@href" : "/gwadmin-service/domains"
}, {
  "@title" : "gateways",
  "@href" : "/gwadmin-service/list/GATEWAY"
}, {
  "@title" : "gwias",
  "@href" : "/gwadmin-service/list/GWIA"
}, {
  "@title" : "groups",
  "@href" : "/gwadmin-service/list/GROUP"
}, {
  "@title" : "libraries",
  "@href" : "/gwadmin-service/list/LIBRARY"
}, {
  "@title" : "mtas",
  "@href" : "/gwadmin-service/list/MTA"
}, {
  "@title" : "nicknames",
  "@href" : "/gwadmin-service/list/NICKNAME"
}, {
  "@title" : "poas",
  "@href" : "/gwadmin-service/list/POA"
}, {
  "@title" : "postoffices",
  "@href" : "/gwadmin-service/list/POST_OFFICE"
}, {
  "@title" : "resources",
  "@href" : "/gwadmin-service/list/RESOURCE"
}, {
  "@title" : "users",
  "@href" : "/gwadmin-service/list/USER"
} ],
"timeCreated" : null,
"timeLastMod" : 1370908693000,
"legacyDn" : null,
"lastModifiedBy" : "admin.testSystem1",
"lastModifiedOp" : "MODIFY",
"pendingOp" : null,
"description" : null,
"externalDomain" : null,
"receiveExternalDomains" : null,
"receiveExternalGroups" : null,
"receiveExternalPostOffices" : null,
"receiveExternalResources" : null,
"receiveExternalUsers" : null,
"sendExternalDomains" : null,
"sendExternalGroups" : null,
"sendExternalPostOffices" : null,
"sendExternalResources" : null,
"sendExternalUsers" : null,
"showDirXMLWarnings" : false,
"allowedAddressFormats" : [ "HOST", "USER", "LAST_FIRST", "FIRST_LAST",
"FLAST" ],

```

```

"allowExternalBusySearch" : false,
"allowExternalStatusTracking" : false,
"archiveServiceApp" : null,
"allowSendDirect" : false,
"autoCreateNickname" : "PROMPT",
"autoSetUserRights" : false,
"defaultGlobalSignatureName" : null,
"defaultInternetAgentName" : "testDom1.GWIA",
"defaultNewUserPassword" : null,
"defaultRoutingDomain" : null,
"domainType" : null,
"emailPublish" : [ "PREFERRED_ADDRESS" ],
"emailPublishFormats" : [ "PREFERRED" ],
"enableICalBrowse" : true,
"firstInitialLastNameMatch" : false,
"forceMessages" : false,
"preferredAddressFormat" : "FULL",
"internetDomainName" : "testdomain.com",
"lockoutOldVersions" : null,
"minSnapinDate" : null,
"minSnapinVersion" : null,
"mtaProfileName" : null,
"nicknameExpireDays" : 30,
"primaryConnectionRequired" : null,
"restrictOpsToPrimaryDom" : true,
"systemType" : "LOCAL",
"systemAdminName" : "admin",
"useFullDN" : true,
"@type" : null,
"@url" : "/gwadmin-service/system"
}

```

XML Response:

```

<system>
  <id>SYSTEM_RECORD.testSystem1</id>
  <guid>B5F73870-086F-0000-AE24-CEFE66AF19D4</guid>
  <name>testSystem1</name>
  <url>/gwadmin-service/system</url>
  <links key="adminservices" href="/gwadmin-service/system/adminservices"/>
  <links key="calpubhosts" href="/gwadmin-service/system/calpubhosts"/>
  <links key="customaddresses" href="/gwadmin-service/system/customaddresses"/>
  <links key="customaddressestest" href="/gwadmin-service/system/customaddresses/test"/>
  <links key="defaulttimezones" href="/gwadmin-service/system/defaulttimezones"/>
  <links key="directories" href="/gwadmin-service/system/directories"/>
  <links key="expired" href="/gwadmin-service/system/expired"/>
  <links key="externalsystemsynchron" href="/gwadmin-service/system/externalsystemsynchron"/>
  <links key="globalsignatures" href="/gwadmin-service/system/globalsignatures"/>
  <links key="info" href="/gwadmin-service/system/info"/>
  <links key="internetdomains" href="/gwadmin-service/system/

```



```

internetdomains"/>
  <links key="ldapservers" href="/gwadmin-service/system/ldapservers"/>
  <links key="maintenance" href="/gwadmin-service/system/maintenance"/>
  <links key="moverequests" href="/gwadmin-service/system/moverequests"/>
  <links key="pending" href="/gwadmin-service/system/pending"/>
  <links key="recoverconnection" href="/gwadmin-service/system/
recoverconnection"/>
  <links key="acl" href="/gwadmin-service/system/acl"/>
  <links key="restoreareas" href="/gwadmin-service/system/restoreareas"/>
  <links key="schedulesvents" href="/gwadmin-service/system/
schedulesvents"/>
  <links key="schedulesventactions" href="/gwadmin-service/system/
schedulesventactions"/>
  <links key="softwareareas" href="/gwadmin-service/system/softwareareas"/
>
  <links key="timezones" href="/gwadmin-service/system/timezones"/>
  <links key="trustedapps" href="/gwadmin-service/system/trustedapps"/>
  <links key="userbyemail" href="/gwadmin-service/system/userbyemail"/>
  <links key="domains" href="/gwadmin-service/domains"/>
  <links key="gateways" href="/gwadmin-service/list/GATEWAY"/>
  <links key="gwias" href="/gwadmin-service/list/GWIA"/>
  <links key="groups" href="/gwadmin-service/list/GROUP"/>
  <links key="libraries" href="/gwadmin-service/list/LIBRARY"/>
  <links key="mtas" href="/gwadmin-service/list/MTA"/>
  <links key="nicknames" href="/gwadmin-service/list/NICKNAME"/>
  <links key="poas" href="/gwadmin-service/list/POA"/>
  <links key="postoffices" href="/gwadmin-service/list/POST_OFFICE"/>
  <links key="resources" href="/gwadmin-service/list/RESOURCE"/>
  <links key="users" href="/gwadmin-service/list/USER"/>
  <timeLastMod>1370908693000</timeLastMod>
  <lastModifiedBy>admin.testSystem1</lastModifiedBy>
  <lastModifiedOp>MODIFY</lastModifiedOp>
  <forceNullOnAttrs/>
  <allowedAddressFormats class="AttrNoUsed">HOST</allowedAddressFormats>
  <allowedAddressFormats class="AttrNoUsed">USER</allowedAddressFormats>
  <allowedAddressFormats class="AttrNoUsed">LAST_FIRST</
allowedAddressFormats>
  <allowedAddressFormats class="AttrNoUsed">FIRST_LAST</
allowedAddressFormats>
  <allowedAddressFormats class="AttrNoUsed">FLAST</allowedAddressFormats>
  <allowExternalBusySearch>>false</allowExternalBusySearch>
  <allowExternalStatusTracking>>false</allowExternalStatusTracking>
  <allowSendDirect>>false</allowSendDirect>
  <autoCreateNickname>PROMPT</autoCreateNickname>
  <autoSetUserRights>>false</autoSetUserRights>
  <defaultInternetAgentName>testDom1.GWIA</defaultInternetAgentName>

```

```

<emailPublish>PREFERRED_ADDRESS</emailPublish>
<emailPublishFormats>PREFERRED</emailPublishFormats>
<enableICalBrowse>true</enableICalBrowse>
<firstInitialLastNameMatch>>false</firstInitialLastNameMatch>
<forceMessages>>false</forceMessages>
<preferredAddressFormat>FULL</preferredAddressFormat>
<internetDomainName>testdomain.com</internetDomainName>
<nicknameExpireDays>30</nicknameExpireDays>
<restrictOpsToPrimaryDom>>true</restrictOpsToPrimaryDom>
<showDirXMLWarnings>>false</showDirXMLWarnings>
<systemType>LOCAL</systemType>
<systemAdminName>admin</systemAdminName>
<useFullDN>>true</useFullDN>
</system>

```

## Requesting Configuration Information about a Domain

Request:

```
GET https://localhost:9710/gwadmin-service/system/connecteddomain
```

Response Status:

200 - OK

JSON Response:

```

{
  "id" : "DOMAIN.testDom1",
  "guid" : "BC755C40-086F-0000-AE24-CEFE66AF19D4",
  "name" : "testDom1",
  "links" : [ {
    "@title" : "administrator",
    "@href" : "/gwadmin-service/domains/testDom1/administrator"
  }, {
    "@title" : "clientoptions",
    "@href" : "/gwadmin-service/domains/testDom1/clientoptions"
  }, {
    "@title" : "customaddresses",
    "@href" : "/gwadmin-service/domains/testDom1/customaddresses"
  }, {
    "@title" : "customaddressestest",
    "@href" : "/gwadmin-service/domains/testDom1/customaddresses/test"
  }, {
    "@title" : "gatewaysubdirs",
    "@href" : "/gwadmin-service/domains/testDom1/gatewaysubdirs"
  }, {
    "@title" : "info",
    "@href" : "/gwadmin-service/domains/testDom1/info"
  }, {
    "@title" : "maintenance",
    "@href" : "/gwadmin-service/domains/testDom1/maintenance"
  }, {
    "@title" : "moverequests",
    "@href" : "/gwadmin-service/domains/testDom1/moverequests"
  }, {
    "@title" : "mta",

```

```

    "@href" : "/gwadmin-service/domains/testDom1/mta"
  }, {
    "@title" : "postoffices",
    "@href" : "/gwadmin-service/domains/testDom1/postoffices"
  }, {
    "@title" : "acl",
    "@href" : "/gwadmin-service/domains/testDom1/acl"
  }, {
    "@title" : "synchronize",
    "@href" : "/gwadmin-service/domains/testDom1/synchronize"
  }, {
    "@title" : "users",
    "@href" : "/gwadmin-service/list/USER/DOMAIN.testDom1"
  }, {
    "@title" : "mtas",
    "@href" : "/gwadmin-service/list/MTA/DOMAIN.testDom1"
  }, {
    "@title" : "libraries",
    "@href" : "/gwadmin-service/list/LIBRARY/DOMAIN.testDom1"
  }, {
    "@title" : "poas",
    "@href" : "/gwadmin-service/list/POA/DOMAIN.testDom1"
  }, {
    "@title" : "resources",
    "@href" : "/gwadmin-service/list/RESOURCE/DOMAIN.testDom1"
  }, {
    "@title" : "gwias",
    "@href" : "/gwadmin-service/list/GWIA/DOMAIN.testDom1"
  }, {
    "@title" : "groups",
    "@href" : "/gwadmin-service/list/GROUP/DOMAIN.testDom1"
  } ],
  "timeCreated" : null,
  "timeLastMod" : 1370885999000,
  "legacyDn" : null,
  "lastModifiedBy" : "Unknown admin",
  "lastModifiedOp" : "ADD",
  "pendingOp" : null,
  "allowedAddressFormats" : {
    "inherited" : true,
    "inheritedFrom" : "testSystem1",
    "inheritedValue" : [ "FLAST", "USER", "FIRST_LAST", "HOST",
"LAST_FIRST" ],
    "value" : [ "FLAST", "USER", "FIRST_LAST", "HOST", "LAST_FIRST" ]
  },
  "addressBookView" : null,
  "alternateInternetAgentName" : null,
  "enableICalBrowse" : {
    "value" : true,
    "inheritedValue" : true,
    "inheritedFrom" : "testSystem1",
    "inherited" : true
  },
  "databaseVersion" : null,
  "defaultInternetAgentName" : {

```

```

    "value" : "testDom1.GWIA",
    "inheritedValue" : "testDom1.GWIA",
    "inheritedFrom" : "testSystem1",
    "inherited" : true
  },
  "defaultWebAccess" : null,
  "description" : null,
  "directoryName" : null,
  "directorySyncDomainName" : "testDom1",
  "domainRebuildCount" : 0,
  "domainType" : "PRIMARY",
  "domainVersion" : 1212,
  "externalSync" : null,
  "fileId" : "tesf6f",
  "gwId" : null,
  "hideUserComments" : null,
  "internetDomainName" : {
    "inherited" : true,
    "inheritedFrom" : "testSystem1",
    "inheritedValue" : "testdomain.com",
    "value" : "testdomain.com",
    "exclusive" : null
  },
  "language" : "English - US",
  "languageId" : "0",
  "linkedDomainName" : null,
  "lockoutOldAdmin" : null,
  "minimumAdminReleaseDate" : null,
  "minimumAdminVersion" : null,
  "platform" : null,
  "preferredAddressFormat" : {
    "inherited" : true,
    "inheritedFrom" : "testSystem1",
    "inheritedValue" : "FULL",
    "value" : "FULL"
  },
  "timezone" : "(GMT-07:00) Mountain Time (US & Canada)",
  "timezoneId" : "MST",
  "path" : "C:\\Novell\\GroupWise\\testDomain1\\",
  "adminChanges" : null,
  "mtaAddress" : null,
  "mtaMtpPort" : null,
  "mtaHttpPort" : null,
  "mtaAdminPort" : null,
  "remoteCreation" : null,
  "notifyUser" : null,
  "clearNotifyUser" : false,
  "connected" : true,
  "@type" : null,
  "@url" : "/gwadmin-service/domains/testDom1"
}

```

XML Response:

```

<domain>
  <id>DOMAIN.testDom1</id>

```

```

<guid>BC755C40-086F-0000-AE24-CEFE66AF19D4</guid>
<name>testDom1</name>
<url>/gwadmin-service/domains/testDom1</url>
<links key="administrator" href="/gwadmin-service/domains/testDom1/
administrator"/>
<links key="clientoptions" href="/gwadmin-service/domains/testDom1/
clientoptions"/>
<links key="customaddresses" href="/gwadmin-service/domains/testDom1/
customaddresses"/>
<links key="customaddressestest" href="/gwadmin-service/domains/
testDom1/customaddresses/test"/>
<links key="gatewaysubdirs" href="/gwadmin-service/domains/testDom1/
gatewaysubdirs"/>
<links key="info" href="/gwadmin-service/domains/testDom1/info"/>
<links key="maintenance" href="/gwadmin-service/domains/testDom1/
maintenance"/>
<links key="moverequests" href="/gwadmin-service/domains/testDom1/
moverequests"/>
<links key="mta" href="/gwadmin-service/domains/testDom1/mta"/>
<links key="postoffices" href="/gwadmin-service/domains/testDom1/
postoffices"/>
<links key="acl" href="/gwadmin-service/domains/testDom1/acl"/>
<links key="synchronize" href="/gwadmin-service/domains/testDom1/
synchronize"/>
<links key="users" href="/gwadmin-service/list/USER/DOMAIN.testDom1"/>
<links key="mtas" href="/gwadmin-service/list/MTA/DOMAIN.testDom1"/>
<links key="libraries" href="/gwadmin-service/list/LIBRARY/
DOMAIN.testDom1"/>
<links key="poas" href="/gwadmin-service/list/POA/DOMAIN.testDom1"/>
<links key="resources" href="/gwadmin-service/list/RESOURCE/
DOMAIN.testDom1"/>
<links key="gwias" href="/gwadmin-service/list/GWIA/DOMAIN.testDom1"/>
<links key="groups" href="/gwadmin-service/list/GROUP/DOMAIN.testDom1"/>
<timeLastMod>1370885999000</timeLastMod>
<lastModifiedBy>Unknown admin</lastModifiedBy>
<lastModifiedOp>ADD</lastModifiedOp>
<forceNullOnAttrs/>
<allowedAddressFormats>
<inherited>true</inherited>
<inheritedFrom>testSystem1</inheritedFrom>
<inheritedValue>
<AttrNoUsed>FLAST</AttrNoUsed>
<AttrNoUsed>FIRST_LAST</AttrNoUsed>
<AttrNoUsed>LAST_FIRST</AttrNoUsed>
<AttrNoUsed>HOST</AttrNoUsed>
<AttrNoUsed>USER</AttrNoUsed>
</inheritedValue>
<value>
<AttrNoUsed>FLAST</AttrNoUsed>
<AttrNoUsed>FIRST_LAST</AttrNoUsed>
<AttrNoUsed>LAST_FIRST</AttrNoUsed>
<AttrNoUsed>HOST</AttrNoUsed>
<AttrNoUsed>USER</AttrNoUsed>
</value>
</allowedAddressFormats>

```

```

<enableICalBrowse>
  <value class="boolean">true</value>
  <inheritedValue class="boolean">true</inheritedValue>
  <inheritedFrom>testSystem1</inheritedFrom>
  <inherited>true</inherited>
</enableICalBrowse>
<defaultInternetAgentName>
  <value class="string">testDom1.GWIA</value>
  <inheritedValue class="string">testDom1.GWIA</inheritedValue>
  <inheritedFrom>testSystem1</inheritedFrom>
  <inherited>true</inherited>
</defaultInternetAgentName>
<directorySyncDomainName>testDom1</directorySyncDomainName>
<domainRebuildCount>0</domainRebuildCount>
<domainType>PRIMARY</domainType>
<domainVersion>1212</domainVersion>
<fileId>tesf6f</fileId>
<internetDomainName>
  <inherited>true</inherited>
  <inheritedFrom>testSystem1</inheritedFrom>
  <inheritedValue>testdomain.com</inheritedValue>
  <value>testdomain.com</value>
</internetDomainName>
<language>English - US</language>
<languageId>0</languageId>
<preferredAddressFormat>
  <inherited>true</inherited>
  <inheritedFrom>testSystem1</inheritedFrom>
  <inheritedValue>FULL</inheritedValue>
  <value>FULL</value>
</preferredAddressFormat>
<timezone>(GMT-07:00) Mountain Time (US & Canada)</timezone>
<timezoneId>MST</timezoneId>
<path>C:\Novell\GroupWise\testDomain1\</path>
<clearNotifyUser>>false</clearNotifyUser>
<connected>true</connected>
</domain>

```

## Requesting Configuration Information about an MTA

Request:

```
GET https://localhost:9710/gwadmin-service/domains/testDom1/mta
```

Response Status:

200 - OK

JSON Response:

```

{
  "id" : "MTA.testDom1",
  "guid" : "BC7694C0-086F-0000-AE24-CEFE66AF19D4",
  "name" : "MTA",
  "links" : [ {
    "@title" : "manage",
    "@href" : "/gwadmin-service/domains/testDom1/mta/manage"
  }
]

```

```

}, {
  "@title" : "refevents",
  "@href" : "/gwadmin-service/domains/testDom1/mta/refevents"
}, {
  "@title" : "domain",
  "@href" : "/gwadmin-service/domains/testDom1"
} ],
"timeCreated" : null,
"timeLastMod" : 1370970807000,
"legacyDn" : null,
"lastModifiedBy" : "admin.testSystem1",
"lastModifiedOp" : "MODIFY",
"pendingOp" : null,
"adminName" : null,
"agentType" : "MTA",
"bindExclusive" : null,
"description" : "GroupWise Message Transfer Agent",
"httpPort" : 7180,
"httpUser" : "admin",
"logFilePath" : null,
"logLevel" : "NORMAL",
"logMaxAge" : 30,
"logMaxSize" : 102400,
"platform" : "WINDOWS",
"snmpCommunityGetString" : null,
"sslCertfile" : null,
"sslKeyFile" : null,
"sslKeyPassword" : null,
"ipAddress" : "127.0.0.1",
"ipPort" : null,
"sslEnabled" : null,
"domainName" : "testDom1",
"postOfficeName" : null,
"timezoneId" : null,
"languageId" : null,
"timezone" : null,
"language" : null,
"externalSync" : null,
"httpPortUsesSsl" : "DISABLED",
"attachRetry" : 60,
"autoDBRecovery" : true,
"collectDeliveryStatusReports" : null,
"collectOtherStatusReports" : null,
"correlateDeliveryStatusReports" : null,
"defaultRoutingDomain" : null,
"messageLogFilePath" : null,
"messageLogging" : "OFF",
"mtpPortUsesSsl" : "DISABLED",
"mtaRouteDelivery" : 0,
"mtaSendDirect" : 0,
"mtpPort" : 7100,
"reportsCleanupDays" : null,
"scanCycle" : 15,
"scanHigh" : 5,
"trackAdminMessages" : null,

```

```

"use2ndHighScanner" : true,
"use2ndMailScanner" : true,
"serverFlags" : 1,
"adminPort" : 9710,
"syncIdapServerName" : null,
"httpEnabled" : null,
"httpPassword" : null,
"exchangeCoexistenceProfiles" : null,
"coexistenceSyncInterval" : 0,
"coexistenceSyncStartOffset" : 0,
"@type" : null,
"@url" : "/gwadmin-service/domains/testDom1/mta",
"FID" : null
}

```

XML Response:

```

<mta>
  <id>MTA.testDom1</id>
  <guid>BC7694C0-086F-0000-AE24-CEFE66AF19D4</guid>
  <name>MTA</name>
  <url>/gwadmin-service/domains/testDom1/mta</url>
  <links key="manage" href="/gwadmin-service/domains/testDom1/mta/manage"/
>
  <links key="refevents" href="/gwadmin-service/domains/testDom1/mta/
refevents"/>
  <links key="domain" href="/gwadmin-service/domains/testDom1"/>
  <timeLastMod>1370970807000</timeLastMod>
  <lastModifiedBy>admin.testSystem1</lastModifiedBy>
  <lastModifiedOp>MODIFY</lastModifiedOp>
  <forceNullOnAttrs/>
  <agentType>MTA</agentType>
  <description>GroupWise Message Transfer Agent</description>
  <httpPort>7180</httpPort>
  <logLevel>NORMAL</logLevel>
  <logMaxAge>30</logMaxAge>
  <logMaxSize>102400</logMaxSize>
  <platform>WINDOWS</platform>
  <ipAddress>127.0.0.1</ipAddress>
  <domainName>testDom1</domainName>
  <httpPortUsesSsl>DISABLED</httpPortUsesSsl>
  <attachRetry>60</attachRetry>
  <autoDBRecovery>true</autoDBRecovery>
  <messageLogging>OFF</messageLogging>

```



```
<mtpPortUsesSsl>DISABLED</mtpPortUsesSsl>
<mtaRouteDelivery>0</mtaRouteDelivery>
<mtaSendDirect>0</mtaSendDirect>
<mtpPort>7100</mtpPort>
<scanCycle>15</scanCycle>
<scanHigh>5</scanHigh>
<use2ndHighScanner>true</use2ndHighScanner>
<use2ndMailScanner>true</use2ndMailScanner>
<serverFlags>1</serverFlags>
<adminPort>9710</adminPort>
<httpUser>admin</httpUser>
<coexistenceSyncInterval>0</coexistenceSyncInterval>
<coexistenceSyncStartOffset>0</coexistenceSyncStartOffset>
</mta>
```

## Requesting Configuration Information about a POA

Request:

```
GET https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/
testPO1/poas
```

Response Status:

200 - OK

JSON Response:

```
[ {
  "id" : "POA.testDom1.testPO1.POA",
  "guid" : "56A986B1-0870-0000-8A08-FB644894ACE1",
  "name" : "POA",
  "links" : null,
  "timeCreated" : null,
  "timeLastMod" : 1370970807000,
  "legacyDn" : null,
  "lastModifiedBy" : "admin.testSystem1",
  "lastModifiedOp" : "MODIFY",
  "pendingOp" : null,
  "adminName" : null,
  "agentType" : "POA",
  "bindExclusive" : false,
  "description" : "GroupWise Post Office Agent",
  "httpPort" : 7181,
  "httpUser" : "admin",
  "logFilePath" : null,
  "logLevel" : "NORMAL",
  "logMaxAge" : 30,
  "logMaxSize" : 102400,
  "platform" : "WINDOWS",
  "snmpCommunityGetString" : null,
  "sslCertfile" : null,
  "sslKeyFile" : null,
  "sslKeyPassword" : null,
  "ipAddress" : "127.0.0.1",
  "ipPort" : null,
  "sslEnabled" : null,
```

```
"domainName" : "testDom1",
"postOfficeName" : "testPO1",
"timezoneId" : null,
"languageId" : null,
"timezone" : null,
"language" : null,
"externalSync" : null,
"httpPortUsesSsl" : "DISABLED",
"address" : null,
"adminAgentFlag" : 0,
"administrationTaskProcessingDisabled" : false,
"appConnections" : 2048,
"cacheEnabled" : true,
"calendarPublishingEnabled" : true,
"calendarPublishingPort" : 7171,
"calendarPublishingThreads" : 4,
"clientServerEnabled" : true,
"clientServerThreads" : 10,
"cpuUtilization" : 85,
"delayTime" : 100,
"externalIpAddress" : null,
"externalClientServerPort" : 0,
"fileId" : null,
"httpEnabled" : true,
"httpPassword" : null,
"imapEnabled" : false,
"imapPort" : 143,
"imapSslPort" : 993,
"imapThreads" : 40,
"internalClientServerPort" : 1677,
"ipxAddress" : null,
"messageFileProcessing" : "ALL_MESSAGES",
"messageHandlerThreads" : 6,
"mtaport" : null,
"mtpPort" : 7101,
"physicalConnections" : 2048,
"primeMoveThreadUsage" : 30,
"snmpEnabled" : false,
"soapPort" : 7191,
"soapExternalPort" : 7191,
"soapEnabled" : true,
"soapThreads" : 40,
"quickFinderEnabled" : true,
"quickFinderIndexBase" : 20,
"quickFinderIndexBaseMinute" : 59,
"quickFinderInterval" : 23,
"quickFinderIntervalMinute" : 59,
"quickFinderQuarantineFiles" : false,
"autoDBRecovery" : true,
"maintenanceHandlerThreads" : 4,
"performUserUpkeep" : true,
"userUpkeepOffset" : 1,
"generateRemoteAddressBook" : true,
"generateRemoteAddressBookOffset" : 0,
"diskCheckInterval" : 5,
```

```

"diskCheckDelay" : 2,
"clientServerExtUsesSsl" : "ENABLED",
"clientServerUsesSsl" : "ENABLED",
"imapUsesSsl" : "DISABLED",
"soapUsesSsl" : "DISABLED",
"mtpPortUsesSsl" : "DISABLED",
"adminPort" : 9710,
"@type" : "poa",
"@url" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/poas/
POA",
"FID" : null
} ]

```

XML Response:

```

<list>
  <poa>
    <id>POA.testDom1.testPO1.POA</id>
    <guid>56A986B1-0870-0000-8A08-FB644894ACE1</guid>
    <name>POA</name>
    <objType>poa</objType>
    <url>/gwadmin-service/domains/testDom1/postoffices/testPO1/poas/POA</
url>
    <timeLastMod>1370970807000</timeLastMod>
    <lastModifiedBy>admin.testSystem1</lastModifiedBy>
    <lastModifiedOp>MODIFY</lastModifiedOp>
    <forceNullOnAttrs/>
    <agentType>POA</agentType>
    <bindExclusive>>false</bindExclusive>
    <description>GroupWise Post Office Agent</description>
    <httpPort>7181</httpPort>
    <logLevel>NORMAL</logLevel>
    <logMaxAge>30</logMaxAge>
    <logMaxSize>102400</logMaxSize>
    <platform>WINDOWS</platform>
    <ipAddress>127.0.0.1</ipAddress>
    <domainName>testDom1</domainName>
    <postOfficeName>testPO1</postOfficeName>
    <adminAgentFlag>0</adminAgentFlag>
    <administrationTaskProcessingDisabled>>false</
administrationTaskProcessingDisabled>
    <appConnections>2048</appConnections>
    <cacheEnabled>>true</cacheEnabled>
    <calendarPublishingEnabled>>true</calendarPublishingEnabled>
    <calendarPublishingPort>7171</calendarPublishingPort>
    <calendarPublishingThreads>4</calendarPublishingThreads>
    <clientServerEnabled>>true</clientServerEnabled>
    <clientServerThreads>10</clientServerThreads>
    <cpuUtilization>85</cpuUtilization>
    <delayTime>100</delayTime>
    <externalClientServerPort>0</externalClientServerPort>
    <httpEnabled>>true</httpEnabled>
    <httpUser>admin</httpUser>
    <imapEnabled>>false</imapEnabled>
    <imapPort>143</imapPort>
    <imapSslPort>993</imapSslPort>

```

```

<imapThreads>40</imapThreads>
<internalClientServerPort>1677</internalClientServerPort>
<messageFileProcessing>ALL_MESSAGES</messageFileProcessing>
<messageHandlerThreads>6</messageHandlerThreads>
<mtpPort>7101</mtpPort>
<physicalConnections>2048</physicalConnections>
<primeMoveThreadUsage>30</primeMoveThreadUsage>
<snmpEnabled>>false</snmpEnabled>
<soapPort>7191</soapPort>
<soapExternalPort>7191</soapExternalPort>
<soapEnabled>>true</soapEnabled>
<soapThreads>40</soapThreads>
<quickFinderEnabled>>true</quickFinderEnabled>
<quickFinderIndexBase>20</quickFinderIndexBase>
<quickFinderIndexBaseMinute>59</quickFinderIndexBaseMinute>
<quickFinderInterval>23</quickFinderInterval>
<quickFinderIntervalMinute>59</quickFinderIntervalMinute>
<quickFinderQuarantineFiles>>false</quickFinderQuarantineFiles>
<autoDBRecovery>>true</autoDBRecovery>
<maintenanceHandlerThreads>4</maintenanceHandlerThreads>
<performUserUpkeep>>true</performUserUpkeep>
<userUpkeepOffset>1</userUpkeepOffset>
<generateRemoteAddressBook>>true</generateRemoteAddressBook>
<generateRemoteAddressBookOffset>0</generateRemoteAddressBookOffset>
<diskCheckInterval>5</diskCheckInterval>
<diskCheckDelay>2</diskCheckDelay>
<clientServerExtUsesSsl>ENABLED</clientServerExtUsesSsl>
<clientServerUsesSsl>ENABLED</clientServerUsesSsl>
<imapUsesSsl>DISABLED</imapUsesSsl>
<soapUsesSsl>DISABLED</soapUsesSsl>
<httpPortUsesSsl>DISABLED</httpPortUsesSsl>
<mtpPortUsesSsl>DISABLED</mtpPortUsesSsl>
<adminPort>9710</adminPort>
</poa>
</list>

```

## Creating a GroupWise User

JSON Request:

```
POST https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/
testP01/users
  expirationDate=0
  postOfficeName=testP01
  name=testUser1
  surname=testSurname1
  directoryUser=false
  domainName=testDom1
```

XML Request:

```
POST https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/
testP01/users
<user>
  <name>testUser1</name>
  <forceNullOnAttrs/>
  <domainName>testDom1</domainName>
  <postOfficeName>testP01</postOfficeName>
  <surname>testSurname1</surname>
</user>
```

Response Status:

201 - Created

URL location of the User = <https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/testP01/users/testUser1>

## Creating an External User

JSON Request:

```
POST https://localhost:9710/gwadmin-service/domains/testExtDom1/
postoffices/testExtPO1/users
  expirationDate=0
  postOfficeName=testExtPO1
  name=testExtUser1
  directoryUser=false
  domainName=testExtDom1
```

XML Request:

```
POST https://localhost:9710/gwadmin-service/domains/testExtDom1/
postoffices/testExtPO1/users
<user>
  <name>testExtUser1</name>
  <forceNullOnAttrs/>
  <domainName>testExtDom1</domainName>
  <postOfficeName>testExtPO1</postOfficeName>
</user>
```

Response Status:

201 - Created

URL location of the external User = <https://localhost:9710/gwadmin-service/domains/testExtDom1/postoffices/testExtPO1/users/testExtUser1>

# Creating a GroupWise User with Chinese Characters in the Last Name

JSON Request:

```
POST https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/
testP01/users
  expirationDate=0
  postOfficeName=testP01
  name=testChineseUser1
  surname=????
  directoryUser=false
  domainName=testDom1
```

XML Request:

```
POST https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/
testP01/users
<user>
  <name>testChineseUser1</name>
  <forceNullOnAttrs/>
  <domainName>testDom1</domainName>
  <postOfficeName>testP01</postOfficeName>
  <surname>????</surname>
</user>
```

Response Status:

201 - Created

URL location of the User = <https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/testP01/users/testChineseUser1>

## Updating a User's First Name That Has Chinese Characters

JSON Request:

```
PUT https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/
testP01/users/testChineseUser1
  streetAddress=?
  expirationDate=0
  directoryUser=false
  givenName=?
  country=China
```

XML Request:

```
PUT https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/
testP01/users/testChineseUser1
<user>
  <forceNullOnAttrs/>
  <country>China</country>
  <givenName>?</givenName>
  <streetAddress>?</streetAddress>
</user>
```

Response Status:

200 - OK

## Renaming a User

JSON Request:

```
POST https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/
testP01/rename
  objectId=USER.testDom1.testP01.testChineseUser1
  newObjectId=testRenamedUser1
```

XML Request:

```
POST https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/
testP01/rename
<renameRequest>
  <objectId>USER.testDom1.testP01.testChineseUser1</objectId>
  <newObjectId>testRenamedUser1</newObjectId>
</renameRequest>
```

Response Status:

200 - OK



## Creating a GroupWise Group

JSON Request:  
POST https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/  
testP01/groups  
    exclusiveInternetDomain=false  
    postOfficeName=testP01  
    name=testGroup1  
    directoryUser=false  
    domainName=testDom1

XML Request:  
POST https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/  
testP01/groups  
<group>  
    <name>testGroup1</name>  
    <forceNullOnAttrs/>  
    <domainName>testDom1</domainName>  
    <postOfficeName>testP01</postOfficeName>  
    <exclusiveInternetDomain>false</exclusiveInternetDomain>  
</group>

Response Status:  
201 - Created

URL location of the Group = https://localhost:9710/gwadmin-service/domains/  
testDom1/postoffices/testP01/groups/testGroup1

## Adding a Member to a Group

JSON Request:  
POST https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/  
testP01/groups/testGroup1/members  
    id=GROUP.testDom1.testP01.testUser1  
    participation=PRIMARY

XML Request:  
POST https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/  
testP01/groups/testGroup1/members  
<member>  
    <id>GROUP.testDom1.testP01.testUser1</id>  
    <forceNullOnAttrs/>  
    <participation>PRIMARY</participation>  
</member>

Response Status:  
201 - Created

## Updating the Participation of a Member of a Group

JSON Request:

```
PUT https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/
testPO1/groups/testGroup1/members/USER.testDom1.testPO1.testUser1
  participation=CARBON_COPY
```

XML Request:

```
PUT https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/
testPO1/groups/testGroup1/members/USER.testDom1.testPO1.testUser1
<member>
  <forceNullOnAttrs/>
  <participation>CARBON_COPY</participation>
</member>
```

Response Status:

200 - OK

## Requesting an Access Control List for a Group

Request:

```
GET https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/
testPO1/groups/testGroup1/acl
```

Response Status:

200 - OK

JSON Response:

```
[ {
  "id" : "USER.testDom1.testPO1.testGroupMember3",
  "guid" : null,
  "name" : "testGroupMember3",
  "links" : null,
  "timeCreated" : null,
  "timeLastMod" : null,
  "legacyDn" : null,
  "lastModifiedBy" : null,
  "lastModifiedOp" : null,
  "pendingOp" : null,
  "postOfficeName" : "testPO1",
  "domainName" : "testDom1",
  "rights" : "READ",
  "@type" : "accessControl",
  "@url" : null
}, {
  "id" : "USER.testDom1.testPO1.testGroupMember4",
  "guid" : null,
  "name" : "testGroupMember4",
  "links" : null,
  "timeCreated" : null,
  "timeLastMod" : null,
  "legacyDn" : null,
  "lastModifiedBy" : null,
```

```

    "lastModifiedOp" : null,
    "pendingOp" : null,
    "postOfficeName" : "testPO1",
    "domainName" : "testDom1",
    "rights" : "READ",
    "@type" : "accessControl",
    "@url" : null
  }, {
    "id" : "USER.testDom1.testPO1.testGroupMember5",
    "guid" : null,
    "name" : "testGroupMember5",
    "links" : null,
    "timeCreated" : null,
    "timeLastMod" : null,
    "legacyDn" : null,
    "lastModifiedBy" : null,
    "lastModifiedOp" : null,
    "pendingOp" : null,
    "postOfficeName" : "testPO1",
    "domainName" : "testDom1",
    "rights" : "READ",
    "@type" : "accessControl",
    "@url" : null
  }, {
    "id" : "USER.testDom1.testPO1.testGroupMember6",
    "guid" : null,
    "name" : "testGroupMember6",
    "links" : null,
    "timeCreated" : null,
    "timeLastMod" : null,
    "legacyDn" : null,
    "lastModifiedBy" : null,
    "lastModifiedOp" : null,
    "pendingOp" : null,
    "postOfficeName" : "testPO1",
    "domainName" : "testDom1",
    "rights" : "READ",
    "@type" : "accessControl",
    "@url" : null
  } ]

```

XML Response:

```

<list>
  <accessControl>
    <objType>accessControl</objType>
    <forceNullOnAttrs/>
    <postOfficeName>testPO1</postOfficeName>
    <domainName>testDom1</domainName>
    <name>testGroupMember3</name>
    <id>USER.testDom1.testPO1.testGroupMember3</id>
    <rights>READ</rights>
  </accessControl>
  <accessControl>
    <objType>accessControl</objType>
    <forceNullOnAttrs/>

```

```

    <postOfficeName>testP01</postOfficeName>
    <domainName>testDom1</domainName>
    <name>testGroupMember4</name>
    <id>USER.testDom1.testP01.testGroupMember4</id>
    <rights>READ</rights>
  </accessControl>
  <accessControl>
    <objType>accessControl</objType>
    <forceNullOnAttrs/>
    <postOfficeName>testP01</postOfficeName>
    <domainName>testDom1</domainName>
    <name>testGroupMember5</name>
    <id>USER.testDom1.testP01.testGroupMember5</id>
    <rights>READ</rights>
  </accessControl>
  <accessControl>
    <objType>accessControl</objType>
    <forceNullOnAttrs/>
    <postOfficeName>testP01</postOfficeName>
    <domainName>testDom1</domainName>
    <name>testGroupMember6</name>
    <id>USER.testDom1.testP01.testGroupMember6</id>
    <rights>READ</rights>
  </accessControl>
</list>

```

## Creating a GroupWise Resource

JSON Request:

```

POST https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/
testP01/resources
  expirationDate=0
  postOfficeName=testP01
  name=testResource1
  owner=testUser1
  directoryUser=false
  domainName=testDom1

```

XML Request:

```

POST https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/
testP01/resources
<resource>
  <name>testResource1</name>
  <forceNullOnAttrs/>
  <domainName>testDom1</domainName>
  <postOfficeName>testP01</postOfficeName>
  <owner>testUser1</owner>
</resource>

```

Response Status:

201 - Created

URL location of the Resource = <https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/testP01/resources/testResource1>

## Creating a GroupWise Nickname

```
JSON Request:
POST https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/
testPO1/nicknames
  userPostOfficeName=testPO1
  expirationDate=0
  postOfficeName=testPO1
  name=testNicknameName1
  userName=testUser1
  surname=testNicknameSurname1
  directoryUser=false
  domainName=testDom1
  userDomainName=testDom1
```

```
XML Request:
POST https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/
testPO1/nicknames
<nickname>
  <name>testNicknameName1</name>
  <forceNullOnAttrs/>
  <domainName>testDom1</domainName>
  <postOfficeName>testPO1</postOfficeName>
  <surname>testNicknameSurname1</surname>
  <userName>testUser1</userName>
  <userPostOfficeName>testPO1</userPostOfficeName>
  <userDomainName>testDom1</userDomainName>
</nickname>
```

```
Response Status:
201 - Created
```

URL location of the Nickname = <https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/testPO1/nicknames/testNicknameName1>

## Finding a Domain by Name

```
Request:
GET https://localhost:9710/gwadmin-service/domains/testDom1
```

```
Response Status:
200 - OK
```

```
JSON Response:
{
  "id" : "DOMAIN.testDom1",
  "guid" : "BC755C40-086F-0000-AE24-CEFE66AF19D4",
  "name" : "testDom1",
  "links" : [ {
    "@title" : "administrator",
    "@href" : "/gwadmin-service/domains/testDom1/administrator"
  }, {
    "@title" : "clientoptions",
```

```

    "@href" : "/gwadmin-service/domains/testDom1/clientoptions"
  }, {
    "@title" : "customaddresses",
    "@href" : "/gwadmin-service/domains/testDom1/customaddresses"
  }, {
    "@title" : "customaddressestest",
    "@href" : "/gwadmin-service/domains/testDom1/customaddresses/test"
  }, {
    "@title" : "gatewaysubdirs",
    "@href" : "/gwadmin-service/domains/testDom1/gatewaysubdirs"
  }, {
    "@title" : "info",
    "@href" : "/gwadmin-service/domains/testDom1/info"
  }, {
    "@title" : "maintenance",
    "@href" : "/gwadmin-service/domains/testDom1/maintenance"
  }, {
    "@title" : "moverequests",
    "@href" : "/gwadmin-service/domains/testDom1/moverequests"
  }, {
    "@title" : "mta",
    "@href" : "/gwadmin-service/domains/testDom1/mta"
  }, {
    "@title" : "postoffices",
    "@href" : "/gwadmin-service/domains/testDom1/postoffices"
  }, {
    "@title" : "acl",
    "@href" : "/gwadmin-service/domains/testDom1/acl"
  }, {
    "@title" : "synchronize",
    "@href" : "/gwadmin-service/domains/testDom1/synchronize"
  }, {
    "@title" : "users",
    "@href" : "/gwadmin-service/list/USER/DOMAIN.testDom1"
  }, {
    "@title" : "mtas",
    "@href" : "/gwadmin-service/list/MTA/DOMAIN.testDom1"
  }, {
    "@title" : "libraries",
    "@href" : "/gwadmin-service/list/LIBRARY/DOMAIN.testDom1"
  }, {
    "@title" : "poas",
    "@href" : "/gwadmin-service/list/POA/DOMAIN.testDom1"
  }, {
    "@title" : "resources",
    "@href" : "/gwadmin-service/list/RESOURCE/DOMAIN.testDom1"
  }, {
    "@title" : "gwas",
    "@href" : "/gwadmin-service/list/GWIA/DOMAIN.testDom1"
  }, {
    "@title" : "groups",
    "@href" : "/gwadmin-service/list/GROUP/DOMAIN.testDom1"
  } ],
  "timeCreated" : null,
  "timeLastMod" : 1370885999000,

```

```

"legacyDn" : null,
"lastModifiedBy" : "Unknown admin",
"lastModifiedOp" : "ADD",
"pendingOp" : null,
"allowedAddressFormats" : {
  "inherited" : true,
  "inheritedFrom" : "testSystem1",
  "inheritedValue" : [ "FLAST", "USER", "FIRST_LAST", "HOST",
"LAST_FIRST" ],
  "value" : [ "FLAST", "USER", "FIRST_LAST", "HOST", "LAST_FIRST" ]
},
"addressBookView" : null,
"alternateInternetAgentName" : null,
"enableICalBrowse" : {
  "value" : true,
  "inheritedValue" : true,
  "inheritedFrom" : "testSystem1",
  "inherited" : true
},
"databaseVersion" : null,
"defaultInternetAgentName" : {
  "value" : "testDom1.GWIA",
  "inheritedValue" : "testDom1.GWIA",
  "inheritedFrom" : "testSystem1",
  "inherited" : true
},
"defaultWebAccess" : null,
"description" : null,
"directoryName" : null,
"directorySyncDomainName" : "testDom1",
"domainRebuildCount" : 0,
"domainType" : "PRIMARY",
"domainVersion" : 1212,
"externalSync" : null,
"fileId" : "tesf6f",
"gwId" : null,
"hideUserComments" : null,
"internetDomainName" : {
  "inherited" : true,
  "inheritedFrom" : "testSystem1",
  "inheritedValue" : "testdomain.com",
  "value" : "testdomain.com",
  "exclusive" : null
},
"language" : "English - US",
"languageId" : "0",
"linkedDomainName" : null,
"lockoutOldAdmin" : null,
"minimumAdminReleaseDate" : null,
"minimumAdminVersion" : null,
"platform" : null,
"preferredAddressFormat" : {
  "inherited" : true,
  "inheritedFrom" : "testSystem1",
  "inheritedValue" : "FULL",

```

```

    "value" : "FULL"
  },
  "timezone" : "(GMT-07:00) Mountain Time (US & Canada)",
  "timezoneId" : "MST",
  "path" : "C:\\Novell\\GroupWise\\testDomain1\\",
  "adminChanges" : null,
  "mtaAddress" : null,
  "mtaMtpPort" : null,
  "mtaHttpPort" : null,
  "mtaAdminPort" : null,
  "remoteCreation" : null,
  "notifyUser" : null,
  "clearNotifyUser" : false,
  "connected" : true,
  "@type" : null,
  "@url" : "/gwadmin-service/domains/testDom1"
}

```

XML Response:

```

<domain>
  <id>DOMAIN.testDom1</id>
  <guid>BC755C40-086F-0000-AE24-CEFE66AF19D4</guid>
  <name>testDom1</name>
  <url>/gwadmin-service/domains/testDom1</url>
  <links key="administrator" href="/gwadmin-service/domains/testDom1/
administrator"/>
  <links key="clientoptions" href="/gwadmin-service/domains/testDom1/
clientoptions"/>
  <links key="customaddresses" href="/gwadmin-service/domains/testDom1/
customaddresses"/>
  <links key="customaddressestest" href="/gwadmin-service/domains/
testDom1/customaddresses/test"/>
  <links key="gatewaysubdirs" href="/gwadmin-service/domains/testDom1/
gatewaysubdirs"/>
  <links key="info" href="/gwadmin-service/domains/testDom1/info"/>
  <links key="maintenance" href="/gwadmin-service/domains/testDom1/
maintenance"/>
  <links key="moverequests" href="/gwadmin-service/domains/testDom1/
moverequests"/>
  <links key="mta" href="/gwadmin-service/domains/testDom1/mta"/>
  <links key="postoffices" href="/gwadmin-service/domains/testDom1/
postoffices"/>
  <links key="acl" href="/gwadmin-service/domains/testDom1/acl"/>
  <links key="synchronize" href="/gwadmin-service/domains/testDom1/
synchronize"/>
  <links key="users" href="/gwadmin-service/list/USER/DOMAIN.testDom1"/>
  <links key="mtas" href="/gwadmin-service/list/MTA/DOMAIN.testDom1"/>
  <links key="libraries" href="/gwadmin-service/list/LIBRARY/
DOMAIN.testDom1"/>
  <links key="poas" href="/gwadmin-service/list/POA/DOMAIN.testDom1"/>
  <links key="resources" href="/gwadmin-service/list/RESOURCE/
DOMAIN.testDom1"/>
  <links key="gwas" href="/gwadmin-service/list/GWIA/DOMAIN.testDom1"/>
  <links key="groups" href="/gwadmin-service/list/GROUP/DOMAIN.testDom1"/>
  <timeLastMod>1370885999000</timeLastMod>

```



```

<lastModifiedBy>Unknown admin</lastModifiedBy>
<lastModifiedOp>ADD</lastModifiedOp>
<forceNullOnAttrs/>
<allowedAddressFormats>
  <inherited>true</inherited>
  <inheritedFrom>testSystem1</inheritedFrom>
  <inheritedValue>
    <AttrNoUsed>FLAST</AttrNoUsed>
    <AttrNoUsed>FIRST_LAST</AttrNoUsed>
    <AttrNoUsed>LAST_FIRST</AttrNoUsed>
    <AttrNoUsed>HOST</AttrNoUsed>
    <AttrNoUsed>USER</AttrNoUsed>
  </inheritedValue>
  <value>
    <AttrNoUsed>FLAST</AttrNoUsed>
    <AttrNoUsed>FIRST_LAST</AttrNoUsed>
    <AttrNoUsed>LAST_FIRST</AttrNoUsed>
    <AttrNoUsed>HOST</AttrNoUsed>
    <AttrNoUsed>USER</AttrNoUsed>
  </value>
</allowedAddressFormats>
<enableICalBrowse>
  <value class="boolean">true</value>
  <inheritedValue class="boolean">true</inheritedValue>
  <inheritedFrom>testSystem1</inheritedFrom>
  <inherited>true</inherited>
</enableICalBrowse>
<defaultInternetAgentName>
  <value class="string">testDom1.GWIA</value>
  <inheritedValue class="string">testDom1.GWIA</inheritedValue>
  <inheritedFrom>testSystem1</inheritedFrom>
  <inherited>true</inherited>
</defaultInternetAgentName>
<directorySyncDomainName>testDom1</directorySyncDomainName>
<domainRebuildCount>0</domainRebuildCount>
<domainType>PRIMARY</domainType>
<domainVersion>1212</domainVersion>
<fileId>tesf6f</fileId>
<internetDomainName>
  <inherited>true</inherited>
  <inheritedFrom>testSystem1</inheritedFrom>
  <inheritedValue>testdomain.com</inheritedValue>
  <value>testdomain.com</value>
</internetDomainName>

```

```

<language>English - US</language>
<languageId>0</languageId>
<preferredAddressFormat>
  <inherited>true</inherited>
  <inheritedFrom>testSystem1</inheritedFrom>
  <inheritedValue>FULL</inheritedValue>
  <value>FULL</value>
</preferredAddressFormat>
<timezone>(GMT-07:00) Mountain Time (US & Canada)</timezone>
<timezoneId>MST</timezoneId>
<path>C:\Novell\GroupWise\testDomain1\</path>
<clearNotifyUser>false</clearNotifyUser>
<connected>true</connected>
</domain>

```

## Finding a Domain by Type

Request:

```

GET https://localhost:9710/gwadmin-service/list/
DOMAIN?domainType=SECONDARY

```

Response Status:

200 - OK

JSON Response:

```

[ {
  "id" : "DOMAIN.testDom2",
  "guid" : "5FC6CEE0-08FE-0000-8A08-5BB4E7C4BAB9",
  "name" : "testDom2",
  "links" : null,
  "timeCreated" : 1370968862000,
  "timeLastMod" : 1370968863000,
  "legacyDn" : null,
  "lastModifiedBy" : "Unknown admin",
  "lastModifiedOp" : "MODIFY",
  "pendingOp" : "MODIFY",
  "allowedAddressFormats" : null,
  "addressBookView" : null,
  "alternateInternetAgentName" : null,
  "enableICalBrowse" : null,
  "databaseVersion" : null,
  "defaultInternetAgentName" : null,
  "defaultWebAccess" : null,
  "description" : null,
  "directoryName" : null,
  "directorySyncDomainName" : "testDom2",
  "domainRebuildCount" : 1,
  "domainType" : "SECONDARY",
  "domainVersion" : 1212,
  "externalSync" : null,
  "fileId" : "tesfebe",
  "gwId" : null,
  "hideUserComments" : null,
  "internetDomainName" : null,

```

```

"language" : "English - US",
"languageId" : "0",
"linkedDomainName" : null,
"lockoutOldAdmin" : null,
"minimumAdminReleaseDate" : null,
"minimumAdminVersion" : null,
"platform" : null,
"preferredAddressFormat" : null,
"timezone" : "(GMT-07:00) Mountain Time (US & Canada)",
"timezoneId" : "MST",
"path" : "C:\\Novell\\GroupWise\\testDomain2",
"adminChanges" : null,
"mtaAddress" : null,
"mtaMtpPort" : null,
"mtaHttpPort" : null,
"mtaAdminPort" : null,
"remoteCreation" : null,
"notifyUser" : null,
"clearNotifyUser" : false,
"connected" : false,
"@type" : "domain",
"@url" : "/gwadmin-service/domains/testDom2"
} ]

```

XML Response:

```

<list>
  <domain>
    <id>DOMAIN.testDom2</id>
    <guid>5FC6CEE0-08FE-0000-8A08-5BB4E7C4BAB9</guid>
    <name>testDom2</name>
    <objType>domain</objType>
    <url>/gwadmin-service/domains/testDom2</url>
    <timeCreated>1370968862000</timeCreated>
    <timeLastMod>1370968863000</timeLastMod>
    <lastModifiedBy>Unknown admin</lastModifiedBy>
    <lastModifiedOp>MODIFY</lastModifiedOp>
    <pendingOp>MODIFY</pendingOp>
    <forceNullOnAttrs/>
    <directorySyncDomainName>testDom2</directorySyncDomainName>
    <domainRebuildCount>1</domainRebuildCount>
    <domainType>SECONDARY</domainType>
    <domainVersion>1212</domainVersion>
    <fileId>tesfebe</fileId>
    <language>English - US</language>
    <languageId>0</languageId>
    <timezone>(GMT-07:00) Mountain Time (US & Canada)</timezone>
    <timezoneId>MST</timezoneId>
    <path>C:\\Novell\\GroupWise\\testDomain2</path>
    <clearNotifyUser>false</clearNotifyUser>
    <connected>false</connected>
  </domain>
</list>

```

## Finding a Post Office

Request:

```
GET https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/testPO1
```

Response Status:

200 - OK

JSON Response:

```
{
  "id" : "POST_OFFICE.testDom1.testPO1",
  "guid" : "56A986B0-0870-0000-8A08-FB644894ACE1",
  "name" : "testPO1",
  "links" : [ {
    "@title" : "aliases",
    "@href" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/aliases"
  }, {
    "@title" : "bumpclientupdate",
    "@href" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/bumpclientupdate"
  }, {
    "@title" : "certificatefiles",
    "@href" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/certificatefiles"
  }, {
    "@title" : "clientoptions",
    "@href" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/clientoptions"
  }, {
    "@title" : "info",
    "@href" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/info"
  }, {
    "@title" : "groups",
    "@href" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/groups"
  }, {
    "@title" : "gwcheck",
    "@href" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/gwcheck"
  }, {
    "@title" : "libraries",
    "@href" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/libraries"
  }, {
    "@title" : "maintenance",
    "@href" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/maintenance"
  }, {
    "@title" : "moverequests",
    "@href" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/moverequests"
  }, {
```

```

    "@title" : "nicknames",
    "@href" : "/gwadmin-service/domains/testDom1/postoffices/testP01/
nicknames"
  }, {
    "@title" : "poas",
    "@href" : "/gwadmin-service/domains/testDom1/postoffices/testP01/poas"
  }, {
    "@title" : "acl",
    "@href" : "/gwadmin-service/domains/testDom1/postoffices/testP01/acl"
  }, {
    "@title" : "refldapservers",
    "@href" : "/gwadmin-service/domains/testDom1/postoffices/testP01/
refldapservers"
  }, {
    "@title" : "resources",
    "@href" : "/gwadmin-service/domains/testDom1/postoffices/testP01/
resources"
  }, {
    "@title" : "synchronize",
    "@href" : "/gwadmin-service/domains/testDom1/postoffices/testP01/
synchronize"
  }, {
    "@title" : "timestamp",
    "@href" : "/gwadmin-service/domains/testDom1/postoffices/testP01/
timestamp"
  }, {
    "@title" : "users",
    "@href" : "/gwadmin-service/domains/testDom1/postoffices/testP01/users"
  }, {
    "@title" : "rename",
    "@href" : "/gwadmin-service/domains/testDom1/postoffices/testP01/
rename"
  }, {
    "@title" : "domain",
    "@href" : "/gwadmin-service/domains/testDom1"
  } ],
  "timeCreated" : 1370907858000,
  "timeLastMod" : 1370907860000,
  "legacyDn" : null,
  "lastModifiedBy" : "Unknown admin",
  "lastModifiedOp" : "MODIFY",
  "pendingOp" : null,
  "adminChanges" : null,
  "accessMode" : "CLIENT_SERVER",
  "allowedAddressFormats" : {
    "inherited" : true,
    "inheritedFrom" : "testSystem1",
    "inheritedValue" : [ "FLAST", "USER", "FIRST_LAST", "HOST",
"LAST_FIRST" ],
    "value" : [ "FLAST", "USER", "FIRST_LAST", "HOST", "LAST_FIRST" ]
  },
  "archiveServiceTrustedAppName" : null,
  "clientLockout" : null,
  "clientLockoutDate" : null,
  "clientLockoutVersion" : null,

```

```

"defaultInternetAgentName" : null,
"description" : null,
"domainName" : "testDom1",
"deliveryMode" : "APP_THRESHOLD",
"disableDeltaRecords" : null,
"disableIdapPasswordChange" : null,
"disableLiveMove" : null,
"disableLogins" : false,
"deltaRecordsMaxAge" : null,
"enableICalBrowse" : {
  "value" : true,
  "inheritedValue" : true,
  "inheritedFrom" : "testSystem1",
  "inherited" : true
},
"externalRecord" : false,
"externalSync" : null,
"fileId" : "tes1072",
"gwId" : null,
"internetDomainName" : {
  "inherited" : true,
  "inheritedFrom" : "testSystem1",
  "inheritedValue" : "testdomain.com",
  "value" : "testdomain.com",
  "exclusive" : null
},
"intruderDetection" : true,
"intruderLockoutAttempts" : 5,
"intruderLockoutAttemptsInterval" : 30,
"intruderLockoutResetInterval" : 30,
"language" : "English - US",
"languageId" : "0",
"ldapDefaultDirectory" : null,
"ldapUser" : null,
"ldapPassword" : null,
"ldapInactiveConnectionTimeout" : null,
"ldapPoolServerResetTimeout" : null,
"ldapQuarantineThreshold" : null,
"linkAddress" : "C:\\Novell\\GroupWise\\testPostOffice1",
"linkAddressType" : "TCP_IP",
"mtpAppName" : "POA",
"mtpMaxSendSize" : null,
"platform" : null,
"postOfficeVersion" : 1212,
"preferredAddressFormat" : {
  "inherited" : true,
  "inheritedFrom" : "testSystem1",
  "inheritedValue" : "FULL",
  "value" : "FULL"
},
"remoteUser" : null,
"remotePassword" : null,
"restoreAreaName" : null,
"securitySettings" : [ "HIGH" ],
"softwareAreaGuid" : null,

```

```

"softwareVersion" : null,
"syncContext" : null,
"timezone" : "(GMT-07:00) Mountain Time (US & Canada)",
"timezoneId" : "MST",
"path" : "C:\\Novell\\GroupWise\\testPostOffice1",
"associationsUpdate" : null,
"poaAddress" : null,
"poaCsPort" : null,
"poaMtpPort" : null,
"poaHttpPort" : null,
"timeStamp" : null,
"clientUpdateBumpNumber" : 0,
"poaAdminPort" : null,
"remoteCreation" : null,
"displayName" : "testPO1",
"draggable" : true,
"@type" : null,
"@url" : "/gwadmin-service/domains/testDom1/postoffices/testPO1"
}

```

XML Response:

```

<postOffice>
  <id>POST_OFFICE.testDom1.testPO1</id>
  <guid>56A986B0-0870-0000-8A08-FB644894ACE1</guid>
  <name>testPO1</name>
  <url>/gwadmin-service/domains/testDom1/postoffices/testPO1</url>
  <links key="aliases" href="/gwadmin-service/domains/testDom1/
postoffices/testPO1/aliases"/>
  <links key="bumpclientupdate" href="/gwadmin-service/domains/testDom1/
postoffices/testPO1/bumpclientupdate"/>
  <links key="certificatefiles" href="/gwadmin-service/domains/testDom1/
postoffices/testPO1/certificatefiles"/>
  <links key="clientoptions" href="/gwadmin-service/domains/testDom1/
postoffices/testPO1/clientoptions"/>
  <links key="info" href="/gwadmin-service/domains/testDom1/postoffices/
testPO1/info"/>
  <links key="groups" href="/gwadmin-service/domains/testDom1/postoffices/
testPO1/groups"/>
  <links key="gwcheck" href="/gwadmin-service/domains/testDom1/
postoffices/testPO1/gwcheck"/>
  <links key="libraries" href="/gwadmin-service/domains/testDom1/
postoffices/testPO1/libraries"/>
  <links key="maintenance" href="/gwadmin-service/domains/testDom1/
postoffices/testPO1/maintenance"/>
  <links key="moverequests" href="/gwadmin-service/domains/testDom1/
postoffices/testPO1/moverequests"/>
  <links key="nicknames" href="/gwadmin-service/domains/testDom1/
postoffices/testPO1/nicknames"/>
  <links key="poas" href="/gwadmin-service/domains/testDom1/postoffices/
testPO1/poas"/>
  <links key="acl" href="/gwadmin-service/domains/testDom1/postoffices/
testPO1/acl"/>
  <links key="refldapservers" href="/gwadmin-service/domains/testDom1/
postoffices/testPO1/refldapservers"/>
  <links key="resources" href="/gwadmin-service/domains/testDom1/

```

```

postoffices/testPO1/resources"/>
  <links key="synchronize" href="/gwadmin-service/domains/testDom1/
postoffices/testPO1/synchronize"/>
  <links key="timestamp" href="/gwadmin-service/domains/testDom1/
postoffices/testPO1/timestamp"/>
  <links key="users" href="/gwadmin-service/domains/testDom1/postoffices/
testPO1/users"/>
  <links key="rename" href="/gwadmin-service/domains/testDom1/postoffices/
testPO1/rename"/>
  <links key="domain" href="/gwadmin-service/domains/testDom1"/>
<timeCreated>1370907858000</timeCreated>
<timeLastMod>1370907860000</timeLastMod>
<lastModifiedBy>Unknown admin</lastModifiedBy>
<lastModifiedOp>MODIFY</lastModifiedOp>
<forceNullOnAttrs/>
<accessMode>CLIENT_SERVER</accessMode>
<allowedAddressFormats>
  <inherited>true</inherited>
  <inheritedFrom>testSystem1</inheritedFrom>
  <inheritedValue>
    <AttrNoUsed>FLAST</AttrNoUsed>
    <AttrNoUsed>FIRST_LAST</AttrNoUsed>
    <AttrNoUsed>LAST_FIRST</AttrNoUsed>
    <AttrNoUsed>HOST</AttrNoUsed>
    <AttrNoUsed>USER</AttrNoUsed>
  </inheritedValue>
  <value>
    <AttrNoUsed>FLAST</AttrNoUsed>
    <AttrNoUsed>FIRST_LAST</AttrNoUsed>
    <AttrNoUsed>LAST_FIRST</AttrNoUsed>
    <AttrNoUsed>HOST</AttrNoUsed>
    <AttrNoUsed>USER</AttrNoUsed>
  </value>
</allowedAddressFormats>
<domainName>testDom1</domainName>
<deliveryMode>APP_THRESHOLD</deliveryMode>
<disableLogins>>false</disableLogins>
<enableICalBrowse>
  <value class="boolean">true</value>
  <inheritedValue class="boolean">true</inheritedValue>
  <inheritedFrom>testSystem1</inheritedFrom>
  <inherited>true</inherited>
</enableICalBrowse>
<externalEntity>>false</externalEntity>
<externalRecord>>false</externalRecord>
<fileId>tes1072</fileId>
<internetDomainName>
  <inherited>true</inherited>
  <inheritedFrom>testSystem1</inheritedFrom>
  <inheritedValue>testdomain.com</inheritedValue>
  <value>testdomain.com</value>
</internetDomainName>
<intruderDetection>true</intruderDetection>
<intruderLockoutAttempts>5</intruderLockoutAttempts>
<intruderLockoutAttemptsInterval>30</intruderLockoutAttemptsInterval>

```



```

<intruderLockoutResetInterval>30</intruderLockoutResetInterval>
<language>English - US</language>
<languageId>0</languageId>
<linkAddress>C:\Novell\GroupWise\testPostOffice1</linkAddress>
<linkAddressType>TCP_IP</linkAddressType>
<mtpAppName>POA</mtpAppName>
<postOfficeVersion>1212</postOfficeVersion>
<preferredAddressFormat>
  <inherited>true</inherited>
  <inheritedFrom>testSystem1</inheritedFrom>
  <inheritedValue>FULL</inheritedValue>
  <value>FULL</value>
</preferredAddressFormat>
<securitySettings class="AttrNoUsed">HIGH</securitySettings>
<timezone>(GMT-07:00) Mountain Time (US & Canada)</timezone>
<timezoneId>MST</timezoneId>
<path>C:\Novell\GroupWise\testPostOffice1</path>
<clientUpdateBumpNumber>0</clientUpdateBumpNumber>
</postOffice>

```

## Finding a User in the GroupWise System

Request:

```
GET https://localhost:9710/gwadmin-service/list/USER?filter=name match
'testUser1'
```

Response Status:

200 - OK

JSON Response:

```

{
  "id" : "USER.testDom1.testPO1.testUser1",
  "guid" : "3C0BF3D0-09EF-0000-8A08-20888CC82C5A",
  "name" : "testUser1",
  "links" : null,
  "timeCreated" : 1371072310000,
  "timeLastMod" : 1371072310000,
  "legacyDn" : null,
  "lastModifiedBy" : "admin.testSystem1",
  "lastModifiedOp" : "ADD",
  "pendingOp" : null,
  "domainName" : "testDom1",
  "postOfficeName" : "testPO1",
  "description" : null,
  "emailAddresses" : null,
  "visibility" : "SYSTEM",
  "defaultInternetAgentName" : null,
  "allowedAddressFormats" : null,
  "internetDomainName" : null,
  "preferredAddressFormat" : null,
  "preferredEmailId" : null,
  "moveStatus" : null,
  "ldapDn" : null,
  "ldapId" : null,

```

```
"directoryId" : null,
"enableICalBrowse" : null,
"restoreArea" : null,
"expirationDate" : 0,
"externalRecord" : null,
"externalSync" : null,
"fileId" : "fri",
"accountId" : null,
"city" : null,
"company" : null,
"country" : null,
"department" : null,
"externalEntity" : null,
"externalSyncOverride" : null,
"faxNumber" : null,
"gatewayAccess" : null,
"givenName" : null,
"gwId" : null,
"homePhoneNumber" : null,
"ldapAuthentication" : null,
"location" : null,
"lastClientLoginTime" : null,
"lastClientType" : null,
"loginDisabled" : null,
"mailboxId" : null,
"middleInitial" : null,
"mobilePhoneNumber" : null,
"networkId" : null,
"otherPhoneNumber" : null,
"pagerNumber" : null,
"postalZipCode" : null,
"postOfficeBox" : null,
"stateProvince" : null,
"streetAddress" : null,
"suffix" : null,
"surname" : "testSurname1",
"telephoneNumber" : null,
"title" : null,
"groupAccessControlUpdateList" : null,
"groupMembersUpdateList" : null,
"adminDefined1" : null,
"adminDefined2" : null,
"adminDefined3" : null,
"adminDefined4" : null,
"adminDefined5" : null,
"adminDefined6" : null,
"adminDefined7" : null,
"adminDefined8" : null,
"adminDefined9" : null,
"adminDefined10" : null,
"adminDefined11" : null,
"adminDefined12" : null,
"adminDefined13" : null,
"adminDefined14" : null,
"adminDefined15" : null,
```

```

"adminDefined16" : null,
"adminDefined17" : null,
"adminDefined18" : null,
"adminDefined19" : null,
"adminDefined20" : null,
"mailboxSizeMb" : null,
"mailboxLicenseType" : null,
"moveComplete" : null,
"directoryUser" : false,
"@type" : "user",
"@url" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/users/
testUser1"
}

```

XML Response:

```

<user>
  <id>USER.testDom1.testPO1.testUser1</id>
  <guid>D8C01260-09EF-0000-8A08-20888CC82C5A</guid>
  <name>testUser1</name>
  <objType>user</objType>
  <url>/gwadmin-service/domains/testDom1/postoffices/testPO1/users/
testUser1</url>
  <timeCreated>1371072573000</timeCreated>
  <timeLastMod>1371072573000</timeLastMod>
  <lastModifiedBy>admin.testSystem1</lastModifiedBy>
  <lastModifiedOp>ADD</lastModifiedOp>
  <forceNullOnAttrs/>
  <domainName>testDom1</domainName>
  <postOfficeName>testPO1</postOfficeName>
  <visibility>SYSTEM</visibility>
  <fileId>q2t</fileId>
  <surname>testSurname1</surname>
</user>

```

## Finding a User in a Domain

Request:

```

GET https://localhost:9710/gwadmin-service/list/USER/
DOMAIN.testDom1?name=testUser1

```

Response Status:

200 - OK

JSON Response:

```

{
  "id" : "USER.testDom1.testPO1.testUser1",
  "guid" : "3C0BF3D0-09EF-0000-8A08-20888CC82C5A",
  "name" : "testUser1",
  "links" : null,
  "timeCreated" : 1371072310000,
  "timeLastMod" : 1371072310000,
  "legacyDn" : null,
  "lastModifiedBy" : "admin.testSystem1",
  "lastModifiedOp" : "ADD",

```

```
"pendingOp" : null,
"domainName" : "testDom1",
"postOfficeName" : "testPO1",
"description" : null,
"emailAddresses" : null,
"visibility" : "SYSTEM",
"defaultInternetAgentName" : null,
"allowedAddressFormats" : null,
"internetDomainName" : null,
"preferredAddressFormat" : null,
"preferredEmailId" : null,
"moveStatus" : null,
"ldapDn" : null,
"ldapId" : null,
"directoryId" : null,
"enableICalBrowse" : null,
"restoreArea" : null,
"expirationDate" : 0,
"externalRecord" : null,
"externalSync" : null,
"fileId" : "fri",
"accountId" : null,
"city" : null,
"company" : null,
"country" : null,
"department" : null,
"externalEntity" : null,
"externalSyncOverride" : null,
"faxNumber" : null,
"gatewayAccess" : null,
"givenName" : null,
"gwId" : null,
"homePhoneNumber" : null,
"ldapAuthentication" : null,
"location" : null,
"lastClientLoginTime" : null,
"lastClientType" : null,
"loginDisabled" : null,
"mailboxId" : null,
"middleInitial" : null,
"mobilePhoneNumber" : null,
"networkId" : null,
"otherPhoneNumber" : null,
"pagerNumber" : null,
"postalZipCode" : null,
"postOfficeBox" : null,
"stateProvince" : null,
"streetAddress" : null,
"suffix" : null,
"surname" : "testSurname1",
"telephoneNumber" : null,
"title" : null,
"groupAccessControlUpdateList" : null,
"groupMembersUpdateList" : null,
"adminDefined1" : null,
```

```

"adminDefined2" : null,
"adminDefined3" : null,
"adminDefined4" : null,
"adminDefined5" : null,
"adminDefined6" : null,
"adminDefined7" : null,
"adminDefined8" : null,
"adminDefined9" : null,
"adminDefined10" : null,
"adminDefined11" : null,
"adminDefined12" : null,
"adminDefined13" : null,
"adminDefined14" : null,
"adminDefined15" : null,
"adminDefined16" : null,
"adminDefined17" : null,
"adminDefined18" : null,
"adminDefined19" : null,
"adminDefined20" : null,
"mailboxSizeMb" : null,
"mailboxLicenseType" : null,
"moveComplete" : null,
"directoryUser" : false,
"@type" : "user",
"@url" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/users/
testUser1"
}

```

XML Response:

```

<user>
  <id>USER.testDom1.testPO1.testUser1</id>
  <guid>D8C01260-09EF-0000-8A08-20888CC82C5A</guid>
  <name>testUser1</name>
  <objType>user</objType>
  <url>/gwadmin-service/domains/testDom1/postoffices/testPO1/users/
testUser1</url>
  <timeCreated>1371072573000</timeCreated>
  <timeLastMod>1371072573000</timeLastMod>
  <lastModifiedBy>admin.testSystem1</lastModifiedBy>
  <lastModifiedOp>ADD</lastModifiedOp>
  <forceNullOnAttrs/>
  <domainName>testDom1</domainName>
  <postOfficeName>testPO1</postOfficeName>
  <visibility>SYSTEM</visibility>
  <fileId>q2t</fileId>
  <surname>testSurname1</surname>
</user>

```

---

**NOTE:** The ?name query automatically does end of name wildcard searching.

---

## Finding a User in a Post Office

Request:

```
GET https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/testPO1/users/testUser1
```

Response Status:

200 - OK

JSON Response:

```
{
  "id" : "USER.testDom1.testPO1.testUser1",
  "guid" : "3C0BF3D0-09EF-0000-8A08-20888CC82C5A",
  "name" : "testUser1",
  "links" : [ {
    "@title" : "administeredgroups",
    "@href" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/users/testUser1/administeredgroups"
  }, {
    "@title" : "aliases",
    "@href" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/users/testUser1/aliases"
  }, {
    "@title" : "clientoptions",
    "@href" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/users/testUser1/clientoptions"
  }, {
    "@title" : "info",
    "@href" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/users/testUser1/info"
  }, {
    "@title" : "emailaddresses",
    "@href" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/users/testUser1/emailaddresses"
  }, {
    "@title" : "groupmemberships",
    "@href" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/users/testUser1/groupmemberships"
  }, {
    "@title" : "gwcheck",
    "@href" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/users/testUser1/gwcheck"
  }, {
    "@title" : "resources",
    "@href" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/users/testUser1/resources"
  }, {
    "@title" : "nicknames",
    "@href" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/users/testUser1/nicknames"
  }, {
    "@title" : "synchronize",
    "@href" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/users/testUser1/synchronize"
  }
]
```

```

    }, {
      "@title" : "restorearea",
      "@href" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/users/
testUser1/restorearea"
    }, {
      "@title" : "restoremailbox",
      "@href" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/users/
testUser1/restoremailbox"
    }, {
      "@title" : "domain",
      "@href" : "/gwadmin-service/domains/testDom1"
    }, {
      "@title" : "postoffice",
      "@href" : "/gwadmin-service/domains/testDom1/postoffices/testPO1"
    } ],
    "timeCreated" : 1371072310000,
    "timeLastMod" : 1371072310000,
    "legacyDn" : null,
    "lastModifiedBy" : "admin.testSystem1",
    "lastModifiedOp" : "ADD",
    "pendingOp" : null,
    "domainName" : "testDom1",
    "postOfficeName" : "testPO1",
    "description" : null,
    "emailAddresses" : [ "testUser1.testPO1.testDom1@testdomain.com" ],
    "visibility" : "SYSTEM",
    "defaultInternetAgentName" : null,
    "allowedAddressFormats" : {
      "inherited" : true,
      "inheritedFrom" : "testSystem1",
      "inheritedValue" : [ "FLAST", "USER", "FIRST_LAST", "HOST",
"LAST_FIRST" ],
      "value" : [ "FLAST", "USER", "FIRST_LAST", "HOST", "LAST_FIRST" ]
    },
    "internetDomainName" : {
      "inherited" : true,
      "inheritedFrom" : "testSystem1",
      "inheritedValue" : "testdomain.com",
      "value" : "testdomain.com",
      "exclusive" : null
    },
    "preferredAddressFormat" : {
      "inherited" : true,
      "inheritedFrom" : "testSystem1",
      "inheritedValue" : "FULL",
      "value" : "FULL"
    },
    "preferredEmailId" : null,
    "moveStatus" : null,
    "ldapDn" : null,
    "ldapId" : null,
    "directoryId" : null,
    "enableICalBrowse" : {
      "value" : true,
      "inheritedValue" : true,

```

```

    "inheritedFrom" : "testSystem1",
    "inherited" : true
  },
  "restoreArea" : null,
  "expirationDate" : 0,
  "externalRecord" : null,
  "externalSync" : null,
  "fileId" : "fri",
  "accountId" : null,
  "city" : null,
  "company" : null,
  "country" : null,
  "department" : null,
  "externalEntity" : null,
  "externalSyncOverride" : null,
  "faxNumber" : null,
  "gatewayAccess" : null,
  "givenName" : null,
  "gwId" : null,
  "homePhoneNumber" : null,
  "ldapAuthentication" : null,
  "location" : null,
  "lastClientLoginTime" : null,
  "lastClientType" : null,
  "loginDisabled" : null,
  "mailboxId" : null,
  "middleInitial" : null,
  "mobilePhoneNumber" : null,
  "networkId" : null,
  "otherPhoneNumber" : null,
  "pagerNumber" : null,
  "postalZipCode" : null,
  "postOfficeBox" : null,
  "stateProvince" : null,
  "streetAddress" : null,
  "suffix" : null,
  "surname" : "testSurname1",
  "telephoneNumber" : null,
  "title" : null,
  "groupAccessControlUpdateList" : null,
  "groupMembersUpdateList" : null,
  "adminDefined1" : null,
  "adminDefined2" : null,
  "adminDefined3" : null,
  "adminDefined4" : null,
  "adminDefined5" : null,
  "adminDefined6" : null,
  "adminDefined7" : null,
  "adminDefined8" : null,
  "adminDefined9" : null,
  "adminDefined10" : null,
  "adminDefined11" : null,
  "adminDefined12" : null,
  "adminDefined13" : null,
  "adminDefined14" : null,

```



```

"adminDefined15" : null,
"adminDefined16" : null,
"adminDefined17" : null,
"adminDefined18" : null,
"adminDefined19" : null,
"adminDefined20" : null,
"mailboxSizeMb" : null,
"mailboxLicenseType" : null,
"moveComplete" : null,
"directoryUser" : false,
"@type" : null,
"@url" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/users/
testUser1"
}

```

XML Response:

```

<user>
  <id>USER.testDom1.testPO1.testUser1</id>
  <guid>D8C01260-09EF-0000-8A08-20888CC82C5A</guid>
  <name>testUser1</name>
  <url>/gwadmin-service/domains/testDom1/postoffices/testPO1/users/
testUser1</url>
  <links key="administeredgroups" href="/gwadmin-service/domains/testDom1/
postoffices/testPO1/users/testUser1/administeredgroups"/>
  <links key="aliases" href="/gwadmin-service/domains/testDom1/
postoffices/testPO1/users/testUser1/aliases"/>
  <links key="clientoptions" href="/gwadmin-service/domains/testDom1/
postoffices/testPO1/users/testUser1/clientoptions"/>
  <links key="info" href="/gwadmin-service/domains/testDom1/postoffices/
testPO1/users/testUser1/info"/>
  <links key="emailaddresses" href="/gwadmin-service/domains/testDom1/
postoffices/testPO1/users/testUser1/emailaddresses"/>
  <links key="groupmemberships" href="/gwadmin-service/domains/testDom1/
postoffices/testPO1/users/testUser1/groupmemberships"/>
  <links key="gwcheck" href="/gwadmin-service/domains/testDom1/
postoffices/testPO1/users/testUser1/gwcheck"/>
  <links key="resources" href="/gwadmin-service/domains/testDom1/
postoffices/testPO1/users/testUser1/resources"/>
  <links key="nicknames" href="/gwadmin-service/domains/testDom1/
postoffices/testPO1/users/testUser1/nicknames"/>
  <links key="synchronize" href="/gwadmin-service/domains/testDom1/
postoffices/testPO1/users/testUser1/synchronize"/>
  <links key="restorearea" href="/gwadmin-service/domains/testDom1/
postoffices/testPO1/users/testUser1/restorearea"/>
  <links key="restoremailbox" href="/gwadmin-service/domains/testDom1/
postoffices/testPO1/users/testUser1/restoremailbox"/>
  <links key="domain" href="/gwadmin-service/domains/testDom1"/>
  <links key="postoffice" href="/gwadmin-service/domains/testDom1/
postoffices/testPO1"/>
  <timeCreated>1371072573000</timeCreated>
  <timeLastMod>1371072573000</timeLastMod>
  <lastModifiedBy>admin.testSystem1</lastModifiedBy>
  <lastModifiedOp>ADD</lastModifiedOp>
  <forceNullOnAttrs/>
  <domainName>testDom1</domainName>

```

```

<postOfficeName>testPO1</postOfficeName>
<emailAddresses>
  <string>testUser1.testPO1.testDom1@testdomain.com</string>
</emailAddresses>
<visibility>SYSTEM</visibility>
<allowedAddressFormats>
  <inherited>true</inherited>
  <inheritedFrom>testSystem1</inheritedFrom>
  <inheritedValue>
    <AttrNoUsed>FLAST</AttrNoUsed>
    <AttrNoUsed>FIRST_LAST</AttrNoUsed>
    <AttrNoUsed>LAST_FIRST</AttrNoUsed>
    <AttrNoUsed>HOST</AttrNoUsed>
    <AttrNoUsed>USER</AttrNoUsed>
  </inheritedValue>
  <value>
    <AttrNoUsed>FLAST</AttrNoUsed>
    <AttrNoUsed>FIRST_LAST</AttrNoUsed>
    <AttrNoUsed>LAST_FIRST</AttrNoUsed>
    <AttrNoUsed>HOST</AttrNoUsed>
    <AttrNoUsed>USER</AttrNoUsed>
  </value>
</allowedAddressFormats>
<internetDomainName>
  <inherited>true</inherited>
  <inheritedFrom>testSystem1</inheritedFrom>
  <inheritedValue>testdomain.com</inheritedValue>
  <value>testdomain.com</value>
</internetDomainName>
<preferredAddressFormat>
  <inherited>true</inherited>
  <inheritedFrom>testSystem1</inheritedFrom>
  <inheritedValue>FULL</inheritedValue>
  <value>FULL</value>
</preferredAddressFormat>
<enableICalBrowse>
  <value class="boolean">true</value>
  <inheritedValue class="boolean">true</inheritedValue>
  <inheritedFrom>testSystem1</inheritedFrom>
  <inherited>true</inherited>
</enableICalBrowse>
<fileId>q2t</fileId>
<surname>testSurname1</surname>
</user>

```

## Finding a User in a Group

Request:

```
GET https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/testPO1/groups/testGroup1/members/GROUP.testDom1.testPO1.testUser1
```

Response Status:

200 - OK

JSON Response:

```
{
  "id" : "USER.testDom1.testPO1.testUser1",
  "guid" : null,
  "name" : "testUser1",
  "links" : null,
  "timeCreated" : null,
  "timeLastMod" : null,
  "legacyDn" : null,
  "lastModifiedBy" : null,
  "lastModifiedOp" : null,
  "pendingOp" : null,
  "postOfficeName" : "testPO1",
  "domainName" : "testDom1",
  "givenName" : null,
  "participation" : "PRIMARY",
  "type" : "USER",
  "surname" : "testSurname1",
  "@type" : null,
  "@url" : null
}
```

XML Response:

```
<member>
  <id>USER.testDom1.testPO1.testUser1</id>
  <name>testUser1</name>
  <forceNullOnAttrs/>
  <postOfficeName>testPO1</postOfficeName>
  <domainName>testDom1</domainName>
  <participation>PRIMARY</participation>
  <type>USER</type>
  <surname>testSurname1</surname>
</member>
```

## Finding a User's Last Name That Has Chinese Characters

Request:

```
GET https://localhost:9710/gwadmin-service/list/USER?surname=????
```

Response Status:

200 - OK

JSON Response:

```
{
  "id" : "USER.testDom1.testPO1.testChineseUser1",
  "guid" : "3D438970-09EF-0000-8A08-20888CC82C5A",
  "name" : "testChineseUser1",
  "links" : null,
  "timeCreated" : 1371072312000,
  "timeLastMod" : 1371072312000,
  "legacyDn" : null,
  "lastModifiedBy" : "admin.testSystem1",
  "lastModifiedOp" : "ADD",
  "pendingOp" : null,
  "domainName" : "testDom1",
  "postOfficeName" : "testPO1",
  "description" : null,
  "emailAddresses" : null,
  "visibility" : "SYSTEM",
  "defaultInternetAgentName" : null,
  "allowedAddressFormats" : null,
  "internetDomainName" : null,
  "preferredAddressFormat" : null,
  "preferredEmailId" : null,
  "moveStatus" : null,
  "ldapDn" : null,
  "ldapId" : null,
  "directoryId" : null,
  "enableICalBrowse" : null,
  "restoreArea" : null,
  "expirationDate" : 0,
  "externalRecord" : null,
  "externalSync" : null,
  "fileId" : "77i",
  "accountId" : null,
  "city" : null,
  "company" : null,
  "country" : null,
  "department" : null,
  "externalEntity" : null,
  "externalSyncOverride" : null,
  "faxNumber" : null,
  "gatewayAccess" : null,
  "givenName" : null,
  "gwId" : null,
  "homePhoneNumber" : null,
  "ldapAuthentication" : null,
  "location" : null,
```

```

"lastClientLoginTime" : null,
"lastClientType" : null,
"loginDisabled" : null,
"mailboxId" : null,
"middleInitial" : null,
"mobilePhoneNumber" : null,
"networkId" : null,
"otherPhoneNumber" : null,
"pagerNumber" : null,
"postalZipCode" : null,
"postOfficeBox" : null,
"stateProvince" : null,
"streetAddress" : null,
"suffix" : null,
"surname" : "????",
"telephoneNumber" : null,
"title" : null,
"groupAccessControlUpdateList" : null,
"groupMembersUpdateList" : null,
"adminDefined1" : null,
"adminDefined2" : null,
"adminDefined3" : null,
"adminDefined4" : null,
"adminDefined5" : null,
"adminDefined6" : null,
"adminDefined7" : null,
"adminDefined8" : null,
"adminDefined9" : null,
"adminDefined10" : null,
"adminDefined11" : null,
"adminDefined12" : null,
"adminDefined13" : null,
"adminDefined14" : null,
"adminDefined15" : null,
"adminDefined16" : null,
"adminDefined17" : null,
"adminDefined18" : null,
"adminDefined19" : null,
"adminDefined20" : null,
"mailboxSizeMb" : null,
"mailboxLicenseType" : null,
"moveComplete" : null,
"directoryUser" : false,
"@type" : "user",
"@url" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/users/
testChineseUser1"
}

```

XML Response:

```

<user>
  <id>USER.testDom1.testPO1.testChineseUser1</id>
  <guid>D9ACBC50-09EF-0000-8A08-20888CC82C5A</guid>
  <name>testChineseUser1</name>

```

```
<objType>user</objType>
<url>/gwadmin-service/domains/testDom1/postoffices/testPO1/users/
testChineseUser1</url>
<timeCreated>1371072575000</timeCreated>
<timeLastMod>1371072575000</timeLastMod>
<lastModifiedBy>admin.testSystem1</lastModifiedBy>
<lastModifiedOp>ADD</lastModifiedOp>
<forceNullOnAttrs/>
<domainName>testDom1</domainName>
<postOfficeName>testPO1</postOfficeName>
<visibility>SYSTEM</visibility>
<fileId>iit</fileId>
<surname>????</surname>
</user>
```

## Finding a Group in the GroupWise System

Request:

```
GET https://localhost:9710/gwadmin-service/list/GROUP?name=testGroup1
```

Response Status:

200 - OK

JSON Response:

```
{
  "id" : "GROUP.testDom1.testPO1.testGroup1",
  "guid" : "3D593450-09EF-0000-8A08-20888CC82C5A",
  "name" : "testGroup1",
  "links" : null,
  "timeCreated" : 1371072313000,
  "timeLastMod" : 1371072313000,
  "legacyDn" : null,
  "lastModifiedBy" : "admin.testSystem1",
  "lastModifiedOp" : "ADD",
  "pendingOp" : null,
  "domainName" : "testDom1",
  "postOfficeName" : "testPO1",
  "description" : null,
  "emailAddresses" : null,
  "visibility" : "POST_OFFICE",
  "defaultInternetAgentName" : null,
  "allowedAddressFormats" : null,
  "internetDomainName" : null,
  "preferredAddressFormat" : null,
  "preferredEmailId" : null,
  "moveStatus" : null,
  "ldapDn" : null,
  "ldapId" : null,
  "directoryId" : null,
  "postOffice" : null,
  "groupType" : "DISTRIBUTION_LIST",
  "replicationOverride" : null,
  "exclusiveInternetDomain" : false,
  "groupAccessControlUpdateList" : null,
```

```
"groupMembershipUpdateList" : null,
"externalSync" : null,
"moveComplete" : null,
"directoryUser" : false,
"@type" : "group",
"@url" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/groups/
testGroup1"
}
```

XML Response:

```
<group>
  <id>GROUP.testDom1.testPO1.testGroup1</id>
  <guid>D9C2B550-09EF-0000-8A08-20888CC82C5A</guid>
  <name>testGroup1</name>
  <objType>group</objType>
  <url>/gwadmin-service/domains/testDom1/postoffices/testPO1/groups/
testGroup1</url>
  <timeCreated>1371072575000</timeCreated>
  <timeLastMod>1371072575000</timeLastMod>
  <lastModifiedBy>admin.testSystem1</lastModifiedBy>
  <lastModifiedOp>ADD</lastModifiedOp>
  <forceNullOnAttrs/>
  <domainName>testDom1</domainName>
  <postOfficeName>testPO1</postOfficeName>
  <visibility>POST_OFFICE</visibility>
  <groupType>DISTRIBUTION_LIST</groupType>
  <exclusiveInternetDomain>>false</exclusiveInternetDomain>
</group>
```

---

**NOTE:** The ?name query automatically does end of name wildcard searching.

---

## Finding a Group in a Post Office

Request:

```
GET https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/
testPO1/groups/testGroup1
```

Response Status:

200 - OK

JSON Response:

```
{
  "id" : "GROUP.testDom1.testPO1.testGroup1",
  "guid" : "3D593450-09EF-0000-8A08-20888CC82C5A",
  "name" : "testGroup1",
  "links" : [ {
    "@title" : "groupmemberships",
    "@href" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/
groups/testGroup1/groupmemberships"
  }, {
    "@title" : "nicknames",
    "@href" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/
groups/testGroup1/nicknames"
```

```

    }, {
      "@title" : "members",
      "@href" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/
groups/testGroup1/members"
    }, {
      "@title" : "acl",
      "@href" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/
groups/testGroup1/acl"
    }, {
      "@title" : "domain",
      "@href" : "/gwadmin-service/domains/testDom1"
    }, {
      "@title" : "postoffice",
      "@href" : "/gwadmin-service/domains/testDom1/postoffices/testPO1"
    } ],
    "timeCreated" : 1371072313000,
    "timeLastMod" : 1371072313000,
    "legacyDn" : null,
    "lastModifiedBy" : "admin.testSystem1",
    "lastModifiedOp" : "ADD",
    "pendingOp" : null,
    "domainName" : "testDom1",
    "postOfficeName" : "testPO1",
    "description" : null,
    "emailAddresses" : [ "testGroup1.testPO1.testDom1@testdomain.com" ],
    "visibility" : "POST_OFFICE",
    "defaultInternetAgentName" : null,
    "allowedAddressFormats" : {
      "inherited" : true,
      "inheritedFrom" : "testSystem1",
      "inheritedValue" : [ "FLAST", "USER", "FIRST_LAST", "HOST",
"LAST_FIRST" ],
      "value" : [ "FLAST", "USER", "FIRST_LAST", "HOST", "LAST_FIRST" ]
    },
    "internetDomainName" : {
      "inherited" : true,
      "inheritedFrom" : "testSystem1",
      "inheritedValue" : "testdomain.com",
      "value" : "testdomain.com",
      "exclusive" : null
    },
    "preferredAddressFormat" : {
      "inherited" : true,
      "inheritedFrom" : "testSystem1",
      "inheritedValue" : "FULL",
      "value" : "FULL"
    },
    "preferredEmailId" : null,
    "moveStatus" : null,
    "ldapDn" : null,
    "ldapId" : null,
    "directoryId" : null,
    "postOffice" : null,
    "groupType" : "DISTRIBUTION_LIST",
    "replicationOverride" : null,

```



```

    "exclusiveInternetDomain" : false,
    "groupAccessControlUpdateList" : null,
    "groupMembershipUpdateList" : null,
    "externalSync" : null,
    "moveComplete" : null,
    "directoryUser" : false,
    "@type" : null,
    "@url" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/groups/
testGroup1"
}

```

XML Response:

```

<group>
  <id>GROUP.testDom1.testPO1.testGroup1</id>
  <guid>D9C2B550-09EF-0000-8A08-20888CC82C5A</guid>
  <name>testGroup1</name>
  <url>/gwadmin-service/domains/testDom1/postoffices/testPO1/groups/
testGroup1</url>
  <links key="groupmemberships" href="/gwadmin-service/domains/testDom1/
postoffices/testPO1/groups/testGroup1/groupmemberships"/>
  <links key="nicknames" href="/gwadmin-service/domains/testDom1/
postoffices/testPO1/groups/testGroup1/nicknames"/>
  <links key="members" href="/gwadmin-service/domains/testDom1/
postoffices/testPO1/groups/testGroup1/members"/>
  <links key="acl" href="/gwadmin-service/domains/testDom1/postoffices/
testPO1/groups/testGroup1/acl"/>
  <links key="domain" href="/gwadmin-service/domains/testDom1"/>
  <links key="postoffice" href="/gwadmin-service/domains/testDom1/
postoffices/testPO1"/>
  <timeCreated>1371072575000</timeCreated>
  <timeLastMod>1371072575000</timeLastMod>
  <lastModifiedBy>admin.testSystem1</lastModifiedBy>
  <lastModifiedOp>ADD</lastModifiedOp>
  <forceNullOnAttrs/>
  <domainName>testDom1</domainName>
  <postOfficeName>testPO1</postOfficeName>
  <emailAddresses>
    <string>testGroup1.testPO1.testDom1@testdomain.com</string>
  </emailAddresses>
  <visibility>POST_OFFICE</visibility>
  <allowedAddressFormats>
    <inherited>true</inherited>
    <inheritedFrom>testSystem1</inheritedFrom>
    <inheritedValue>
      <AttrNoUsed>FLAST</AttrNoUsed>
      <AttrNoUsed>FIRST_LAST</AttrNoUsed>
      <AttrNoUsed>LAST_FIRST</AttrNoUsed>
      <AttrNoUsed>HOST</AttrNoUsed>
      <AttrNoUsed>USER</AttrNoUsed>
    </inheritedValue>
    <value>
      <AttrNoUsed>FLAST</AttrNoUsed>
      <AttrNoUsed>FIRST_LAST</AttrNoUsed>
      <AttrNoUsed>LAST_FIRST</AttrNoUsed>
      <AttrNoUsed>HOST</AttrNoUsed>
    </value>
  </allowedAddressFormats>

```

```

        <AttrNoUsed>USER</AttrNoUsed>
    </value>
</allowedAddressFormats>
<internetDomainName>
    <inherited>true</inherited>
    <inheritedFrom>testSystem1</inheritedFrom>
    <inheritedValue>testdomain.com</inheritedValue>
    <value>testdomain.com</value>
</internetDomainName>
<preferredAddressFormat>
    <inherited>true</inherited>
    <inheritedFrom>testSystem1</inheritedFrom>
    <inheritedValue>FULL</inheritedValue>
    <value>FULL</value>
</preferredAddressFormat>
<groupType>DISTRIBUTION_LIST</groupType>
<exclusiveInternetDomain>>false</exclusiveInternetDomain>
</group>

```

## Finding a Resource in the GroupWise System

Request:

```

GET https://localhost:9710/gwadmin-service/list/
RESOURCE?name=testResource1

```

Response Status:

200 - OK

JSON Response:

```

{
  "id" : "RESOURCE.testDom1.testPO1.testResource1",
  "guid" : "3E3CB680-09EF-0000-8A08-20888CC82C5A",
  "name" : "testResource1",
  "links" : null,
  "timeCreated" : 1371072314000,
  "timeLastMod" : 1371072314000,
  "legacyDn" : null,
  "lastModifiedBy" : "admin.testSystem1",
  "lastModifiedOp" : "ADD",
  "pendingOp" : null,
  "domainName" : "testDom1",
  "postOfficeName" : "testPO1",
  "description" : null,
  "emailAddresses" : null,
  "visibility" : "SYSTEM",
  "defaultInternetAgentName" : null,
  "allowedAddressFormats" : null,
  "internetDomainName" : null,
  "preferredAddressFormat" : null,
  "preferredEmailId" : null,
  "moveStatus" : null,
  "ldapDn" : null,
  "ldapId" : null,
  "directoryId" : null,

```

```

"enableICalBrowse" : null,
"restoreArea" : null,
"expirationDate" : 0,
"externalRecord" : null,
"externalSync" : null,
"fileId" : "66e",
"owner" : "testUser1",
"postOffice" : null,
"resourceType" : "RESOURCE",
"telephoneNumber" : null,
"groupMembershipUpdateList" : null,
"nicknamesUrl" : null,
"moveComplete" : null,
"directoryUser" : false,
"@type" : "resource",
"@url" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/
resources/testResource1"
}

```

XML Response:

```

<resource>
  <id>RESOURCE.testDom1.testPO1.testResource1</id>
  <guid>DAD49A80-09EF-0000-8A08-20888CC82C5A</guid>
  <name>testResource1</name>
  <objType>resource</objType>
  <url>/gwadmin-service/domains/testDom1/postoffices/testPO1/resources/
testResource1</url>
  <timeCreated>1371072577000</timeCreated>
  <timeLastMod>1371072577000</timeLastMod>
  <lastModifiedBy>admin.testSystem1</lastModifiedBy>
  <lastModifiedOp>ADD</lastModifiedOp>
  <forceNullOnAttrs/>
  <domainName>testDom1</domainName>
  <postOfficeName>testPO1</postOfficeName>
  <visibility>SYSTEM</visibility>
  <fileId>hhp</fileId>
  <owner>testUser1</owner>
  <resourceType>RESOURCE</resourceType>
</resource>

```

---

**NOTE:** The ?name query automatically does end of name wildcard searching.

---

## Finding a Resource in a Post Office

Request:

```
GET https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/testPO1/resources/testResource1
```

Response Status:

200 - OK

JSON Response:

```
{
  "id" : "RESOURCE.testDom1.testPO1.testResource1",
  "guid" : "3E3CB680-09EF-0000-8A08-20888CC82C5A",
  "name" : "testResource1",
  "links" : [ {
    "@title" : "clientoptions",
    "@href" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/resources/testResource1/clientoptions"
  }, {
    "@title" : "emailaddresses",
    "@href" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/resources/testResource1/emailaddresses"
  }, {
    "@title" : "groupmemberships",
    "@href" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/resources/testResource1/groupmemberships"
  }, {
    "@title" : "gwcheck",
    "@href" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/resources/testResource1/gwcheck"
  }, {
    "@title" : "nicknames",
    "@href" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/resources/testResource1/nicknames"
  }, {
    "@title" : "restorearea",
    "@href" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/resources/testResource1/restorearea"
  }, {
    "@title" : "restoremailbox",
    "@href" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/resources/testResource1/restoremailbox"
  }, {
    "@title" : "domain",
    "@href" : "/gwadmin-service/domains/testDom1"
  }, {
    "@title" : "postoffice",
    "@href" : "/gwadmin-service/domains/testDom1/postoffices/testPO1"
  } ],
  "timeCreated" : 1371072314000,
  "timeLastMod" : 1371072314000,
  "legacyDn" : null,
  "lastModifiedBy" : "admin.testSystem1",
  "lastModifiedOp" : "ADD",
```

```

"pendingOp" : null,
"domainName" : "testDom1",
"postOfficeName" : "testPO1",
"description" : null,
"emailAddresses" : [ "testResource1.testPO1.testDom1@testdomain.com" ],
"visibility" : "SYSTEM",
"defaultInternetAgentName" : null,
"allowedAddressFormats" : {
  "inherited" : true,
  "inheritedFrom" : "testSystem1",
  "inheritedValue" : [ "FLAST", "USER", "FIRST_LAST", "HOST",
"LAST_FIRST" ],
  "value" : [ "FLAST", "USER", "FIRST_LAST", "HOST", "LAST_FIRST" ]
},
"internetDomainName" : {
  "inherited" : true,
  "inheritedFrom" : "testSystem1",
  "inheritedValue" : "testdomain.com",
  "value" : "testdomain.com",
  "exclusive" : null
},
"preferredAddressFormat" : {
  "inherited" : true,
  "inheritedFrom" : "testSystem1",
  "inheritedValue" : "FULL",
  "value" : "FULL"
},
"preferredEmailId" : null,
"moveStatus" : null,
"ldapDn" : null,
"ldapId" : null,
"directoryId" : null,
"enableICalBrowse" : {
  "value" : true,
  "inheritedValue" : true,
  "inheritedFrom" : "testSystem1",
  "inherited" : true
},
"restoreArea" : null,
"expirationDate" : 0,
"externalRecord" : null,
"externalSync" : null,
"fileId" : "66e",
"owner" : "testUser1",
"postOffice" : null,
"resourceType" : "RESOURCE",
"telephoneNumber" : null,
"groupMembershipUpdateList" : null,
"nicknamesUrl" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/
resources/testResource1/nicknames",
"moveComplete" : null,
"directoryUser" : false,
"@type" : null,
"@url" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/
resources/testResource1"

```

```
}
```

XML Response:

```
<resource>
  <id>RESOURCE.testDom1.testPO1.testResource1</id>
  <guid>DAD49A80-09EF-0000-8A08-20888CC82C5A</guid>
  <name>testResource1</name>
  <url>/gwadmin-service/domains/testDom1/postoffices/testPO1/resources/
testResource1</url>
  <links key="clientoptions" href="/gwadmin-service/domains/testDom1/
postoffices/testPO1/resources/testResource1/clientoptions"/>
  <links key="emailaddresses" href="/gwadmin-service/domains/testDom1/
postoffices/testPO1/resources/testResource1/emailaddresses"/>
  <links key="groupmemberships" href="/gwadmin-service/domains/testDom1/
postoffices/testPO1/resources/testResource1/groupmemberships"/>
  <links key="gwcheck" href="/gwadmin-service/domains/testDom1/
postoffices/testPO1/resources/testResource1/gwcheck"/>
  <links key="nicknames" href="/gwadmin-service/domains/testDom1/
postoffices/testPO1/resources/testResource1/nicknames"/>
  <links key="restorearea" href="/gwadmin-service/domains/testDom1/
postoffices/testPO1/resources/testResource1/restorearea"/>
  <links key="restoremailbox" href="/gwadmin-service/domains/testDom1/
postoffices/testPO1/resources/testResource1/restoremailbox"/>
  <links key="domain" href="/gwadmin-service/domains/testDom1"/>
  <links key="postoffice" href="/gwadmin-service/domains/testDom1/
postoffices/testPO1"/>
  <timeCreated>1371072577000</timeCreated>
  <timeLastMod>1371072577000</timeLastMod>
  <lastModifiedBy>admin.testSystem1</lastModifiedBy>
  <lastModifiedOp>ADD</lastModifiedOp>
  <forceNullOnAttrs/>
  <domainName>testDom1</domainName>
  <postOfficeName>testPO1</postOfficeName>
  <emailAddresses>
    <string>testResource1.testPO1.testDom1@testdomain.com</string>
  </emailAddresses>
  <visibility>SYSTEM</visibility>
  <allowedAddressFormats>
    <inherited>true</inherited>
    <inheritedFrom>testSystem1</inheritedFrom>
    <inheritedValue>
      <AttrNoUsed>FLAST</AttrNoUsed>
      <AttrNoUsed>FIRST_LAST</AttrNoUsed>
      <AttrNoUsed>LAST_FIRST</AttrNoUsed>
      <AttrNoUsed>HOST</AttrNoUsed>
      <AttrNoUsed>USER</AttrNoUsed>
    </inheritedValue>
    <value>
      <AttrNoUsed>FLAST</AttrNoUsed>
      <AttrNoUsed>FIRST_LAST</AttrNoUsed>
      <AttrNoUsed>LAST_FIRST</AttrNoUsed>
      <AttrNoUsed>HOST</AttrNoUsed>
      <AttrNoUsed>USER</AttrNoUsed>
    </value>
  </allowedAddressFormats>

```

```

<internetDomainName>
  <inherited>true</inherited>
  <inheritedFrom>testSystem1</inheritedFrom>
  <inheritedValue>testdomain.com</inheritedValue>
  <value>testdomain.com</value>
</internetDomainName>
<preferredAddressFormat>
  <inherited>true</inherited>
  <inheritedFrom>testSystem1</inheritedFrom>
  <inheritedValue>FULL</inheritedValue>
  <value>FULL</value>
</preferredAddressFormat>
<enableICalBrowse>
  <value class="boolean">true</value>
  <inheritedValue class="boolean">true</inheritedValue>
  <inheritedFrom>testSystem1</inheritedFrom>
  <inherited>true</inherited>
</enableICalBrowse>
<fileId>hhp</fileId>
<owner>testUser1</owner>
<resourceType>RESOURCE</resourceType>
</resource>

```

## Finding a Nickname in the GroupWise System

Request:

```

GET https://localhost:9710/gwadmin-service/list/
NICKNAME?name=testNicknameName1

```

Response Status:

200 - OK

JSON Response:

```

{
  "id" : "NICKNAME.testDom1.testPO1.testNicknameName1",
  "guid" : "3E2536E0-09EF-0000-8A08-20888CC82C5A",
  "name" : "testNicknameName1",
  "links" : null,
  "timeCreated" : 1371072314000,
  "timeLastMod" : 1371072314000,
  "legacyDn" : null,
  "lastModifiedBy" : "admin.testSystem1",
  "lastModifiedOp" : "ADD",
  "pendingOp" : null,
  "domainName" : "testDom1",
  "postOfficeName" : "testPO1",
  "description" : null,
  "emailAddresses" : null,
  "visibility" : "SYSTEM",
  "defaultInternetAgentName" : null,
  "allowedAddressFormats" : null,
  "internetDomainName" : null,
  "preferredAddressFormat" : null,
  "preferredEmailId" : null,

```

```
"moveStatus" : null,
"ldapDn" : null,
"ldapId" : null,
"directoryId" : null,
"enableICalBrowse" : null,
"restoreArea" : null,
"expirationDate" : 0,
"externalRecord" : null,
"externalSync" : null,
"fileId" : null,
"accountId" : null,
"city" : null,
"company" : null,
"country" : null,
"department" : null,
"externalEntity" : null,
"externalSyncOverride" : null,
"faxNumber" : null,
"gatewayAccess" : null,
"givenName" : null,
"gwId" : null,
"homePhoneNumber" : null,
"ldapAuthentication" : null,
"location" : null,
"lastClientLoginTime" : null,
"lastClientType" : null,
"loginDisabled" : null,
"mailboxId" : null,
"middleInitial" : null,
"mobilePhoneNumber" : null,
"networkId" : null,
"otherPhoneNumber" : null,
"pagerNumber" : null,
"postalZipCode" : null,
"postOfficeBox" : null,
"stateProvince" : null,
"streetAddress" : null,
"suffix" : null,
"surname" : "testNicknameSurname1",
"telephoneNumber" : null,
"title" : null,
"groupAccessControlUpdateList" : null,
"groupMembersUpdateList" : null,
"adminDefined1" : null,
"adminDefined2" : null,
"adminDefined3" : null,
"adminDefined4" : null,
"adminDefined5" : null,
"adminDefined6" : null,
"adminDefined7" : null,
"adminDefined8" : null,
"adminDefined9" : null,
"adminDefined10" : null,
"adminDefined11" : null,
"adminDefined12" : null,
```



```

"adminDefined13" : null,
"adminDefined14" : null,
"adminDefined15" : null,
"adminDefined16" : null,
"adminDefined17" : null,
"adminDefined18" : null,
"adminDefined19" : null,
"adminDefined20" : null,
"mailboxSizeMb" : null,
"mailboxLicenseType" : null,
"referredUserName" : null,
"userName" : "testUser1",
"userPostOfficeName" : "testPO1",
"userDomainName" : "testDom1",
"realMemberType" : "USER",
"moveComplete" : null,
"directoryUser" : false,
"@type" : "nickname",
"@url" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/
nicknames/testNicknameName1"
}

```

XML Response:

```

<nickname>
  <id>NICKNAME.testDom1.testPO1.testNicknameName1</id>
  <guid>DAB356E0-09EF-0000-8A08-20888CC82C5A</guid>
  <name>testNicknameName1</name>
  <objType>nickname</objType>
  <url>/gwadmin-service/domains/testDom1/postoffices/testPO1/nicknames/
testNicknameName1</url>
  <timeCreated>1371072577000</timeCreated>
  <timeLastMod>1371072577000</timeLastMod>
  <lastModifiedBy>admin.testSystem1</lastModifiedBy>
  <lastModifiedOp>ADD</lastModifiedOp>
  <forceNullOnAttrs/>
  <domainName>testDom1</domainName>
  <postOfficeName>testPO1</postOfficeName>
  <visibility>SYSTEM</visibility>
  <surname>testNicknameSurname1</surname>
  <userName>testUser1</userName>
  <userPostOfficeName>testPO1</userPostOfficeName>
  <userDomainName>testDom1</userDomainName>
  <realMemberType>USER</realMemberType>
</nickname>

```

---

**NOTE:** The ?name query automatically does end of name wildcard searching.

---

## Finding a Nickname in a Post Office

Request:

```
GET https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/testPO1/nicknames/testNicknameName1
```

Response Status:

200 - OK

JSON Response:

```
{
  "id" : "NICKNAME.testDom1.testPO1.testNicknameName1",
  "guid" : "3E2536E0-09EF-0000-8A08-20888CC82C5A",
  "name" : "testNicknameName1",
  "links" : [ {
    "@title" : "domain",
    "@href" : "/gwadmin-service/domains/testDom1"
  }, {
    "@title" : "postoffice",
    "@href" : "/gwadmin-service/domains/testDom1/postoffices/testPO1"
  }, {
    "@title" : "emailaddresses",
    "@href" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/nicknames/testNicknameName1/emailaddresses"
  } ],
  "timeCreated" : 1371072314000,
  "timeLastMod" : 1371072314000,
  "legacyDn" : null,
  "lastModifiedBy" : "admin.testSystem1",
  "lastModifiedOp" : "ADD",
  "pendingOp" : null,
  "domainName" : "testDom1",
  "postOfficeName" : "testPO1",
  "description" : null,
  "emailAddresses" : [ "testNicknameName1.testPO1.testDom1@testdomain.com" ],
  "visibility" : "SYSTEM",
  "defaultInternetAgentName" : null,
  "allowedAddressFormats" : {
    "inherited" : true,
    "inheritedFrom" : "testSystem1",
    "inheritedValue" : [ "FLAST", "USER", "FIRST_LAST", "HOST", "LAST_FIRST" ],
    "value" : [ "FLAST", "USER", "FIRST_LAST", "HOST", "LAST_FIRST" ]
  },
  "internetDomainName" : {
    "inherited" : true,
    "inheritedFrom" : "testSystem1",
    "inheritedValue" : "testdomain.com",
    "value" : "testdomain.com",
    "exclusive" : null
  },
  "preferredAddressFormat" : {
    "inherited" : true,
```

```

    "inheritedFrom" : "testSystem1",
    "inheritedValue" : "FULL",
    "value" : "FULL"
  },
  "preferredEmailId" : null,
  "moveStatus" : null,
  "ldapDn" : null,
  "ldapId" : null,
  "directoryId" : null,
  "enableICalBrowse" : null,
  "restoreArea" : null,
  "expirationDate" : 0,
  "externalRecord" : null,
  "externalSync" : null,
  "fileId" : null,
  "accountId" : null,
  "city" : null,
  "company" : null,
  "country" : null,
  "department" : null,
  "externalEntity" : null,
  "externalSyncOverride" : null,
  "faxNumber" : null,
  "gatewayAccess" : null,
  "givenName" : null,
  "gwId" : null,
  "homePhoneNumber" : null,
  "ldapAuthentication" : null,
  "location" : null,
  "lastClientLoginTime" : null,
  "lastClientType" : null,
  "loginDisabled" : null,
  "mailboxId" : null,
  "middleInitial" : null,
  "mobilePhoneNumber" : null,
  "networkId" : null,
  "otherPhoneNumber" : null,
  "pagerNumber" : null,
  "postalZipCode" : null,
  "postOfficeBox" : null,
  "stateProvince" : null,
  "streetAddress" : null,
  "suffix" : null,
  "surname" : "testNicknameSurname1",
  "telephoneNumber" : null,
  "title" : null,
  "groupAccessControlUpdateList" : null,
  "groupMembersUpdateList" : null,
  "adminDefined1" : null,
  "adminDefined2" : null,
  "adminDefined3" : null,
  "adminDefined4" : null,
  "adminDefined5" : null,
  "adminDefined6" : null,
  "adminDefined7" : null,

```

```

"adminDefined8" : null,
"adminDefined9" : null,
"adminDefined10" : null,
"adminDefined11" : null,
"adminDefined12" : null,
"adminDefined13" : null,
"adminDefined14" : null,
"adminDefined15" : null,
"adminDefined16" : null,
"adminDefined17" : null,
"adminDefined18" : null,
"adminDefined19" : null,
"adminDefined20" : null,
"mailboxSizeMb" : null,
"mailboxLicenseType" : null,
"referredUserName" : null,
"userName" : "testUser1",
"userPostOfficeName" : "testPO1",
"userDomainName" : "testDom1",
"realMemberType" : "USER",
"moveComplete" : null,
"directoryUser" : false,
"@type" : null,
"@url" : "/gwadmin-service/domains/testDom1/postoffices/testPO1/
nicknames/testNicknameName1"
}

```

XML Response:

```

<nickname>
  <id>NICKNAME.testDom1.testPO1.testNicknameName1</id>
  <guid>DAB356E0-09EF-0000-8A08-20888CC82C5A</guid>
  <name>testNicknameName1</name>
  <url>/gwadmin-service/domains/testDom1/postoffices/testPO1/nicknames/
testNicknameName1</url>
  <links key="domain" href="/gwadmin-service/domains/testDom1"/>
  <links key="postoffice" href="/gwadmin-service/domains/testDom1/
postoffices/testPO1"/>
  <links key="emailaddresses" href="/gwadmin-service/domains/testDom1/
postoffices/testPO1/nicknames/testNicknameName1/emailaddresses"/>
  <timeCreated>1371072577000</timeCreated>
  <timeLastMod>1371072577000</timeLastMod>
  <lastModifiedBy>admin.testSystem1</lastModifiedBy>
  <lastModifiedOp>ADD</lastModifiedOp>
  <forceNullOnAttrs/>
  <domainName>testDom1</domainName>
  <postOfficeName>testPO1</postOfficeName>
  <emailAddresses>
    <string>testNicknameName1.testPO1.testDom1@testdomain.com</string>
  </emailAddresses>
  <visibility>SYSTEM</visibility>
  <allowedAddressFormats>
    <inherited>true</inherited>
    <inheritedFrom>testSystem1</inheritedFrom>
    <inheritedValue>
      <AttrNoUsed>FLAST</AttrNoUsed>

```

```

    <AttrNoUsed>FIRST_LAST</AttrNoUsed>
    <AttrNoUsed>LAST_FIRST</AttrNoUsed>
    <AttrNoUsed>HOST</AttrNoUsed>
    <AttrNoUsed>USER</AttrNoUsed>
  </inheritedValue>
  <value>
    <AttrNoUsed>FLAST</AttrNoUsed>
    <AttrNoUsed>FIRST_LAST</AttrNoUsed>
    <AttrNoUsed>LAST_FIRST</AttrNoUsed>
    <AttrNoUsed>HOST</AttrNoUsed>
    <AttrNoUsed>USER</AttrNoUsed>
  </value>
</allowedAddressFormats>
<internetDomainName>
  <inherited>true</inherited>
  <inheritedFrom>testSystem1</inheritedFrom>
  <inheritedValue>testdomain.com</inheritedValue>
  <value>testdomain.com</value>
</internetDomainName>
<preferredAddressFormat>
  <inherited>true</inherited>
  <inheritedFrom>testSystem1</inheritedFrom>
  <inheritedValue>FULL</inheritedValue>
  <value>FULL</value>
</preferredAddressFormat>
<surname>testNicknameSurname1</surname>
<userName>testUser1</userName>
<userPostOfficeName>testPO1</userPostOfficeName>
<userDomainName>testDom1</userDomainName>
<realMemberType>USER</realMemberType>
</nickname>

```

## Moving Users to a Different Post Office

JSON Request:

```

POST https://localhost:9710/gwadmin-service/system/moverequests
  sources=[{id=USER.testDom1.testPO1.testMoveUser1},
  {id=USER.testDom1.testPO1.testMoveUser2},
  {id=USER.testDom1.testPO1.testMoveUser3}]
  postOfficeId=POST_OFFICE.testDom2.testPO2

```

JSON Response:

```

{
  "succeeded" : 2,
  "failed" : [ {
    "id" : "USER.testDom1.testPO1.testMoveUser2",
    "status" : {
      "error" : true,
      "httpStatusCode" : 403,
      "statusCode" : 56073,
      "statusMsg" : "User owns resources that must be transferred before it
can be deleted",
      "locationHeader" : null
    }
  }
}

```

```
} ]  
}
```

XML Request:

```
POST https://localhost:9710/gwadmin-service/system/moverequests  
<moveRequest><sources><id>USER.testDom1.testPO1.testMoveUser1</id></  
sources><sources><id>USER.testDom1.testPO1.testMoveUser2</id></  
sources><sources><id>USER.testDom1.testPO1.testMoveUser3</id></  
sources><postOfficeId>POST_OFFICE.testDom2.testPO2</postOfficeId></  
moveRequest>
```

XML Response:

```
<batchResult>  
  <succeeded>2</succeeded>  
  <failed>  
    <id>USER.testDom1.testPO1.testMoveUser2</id>  
    <status>  
      <error>true</error>  
      <statusCode>403</statusCode>  
      <statusCode>56073</statusCode>  
      <statusMsg>User owns resources that must be transferred before it  
can be deleted</statusMsg>  
    </status>  
  </failed>  
</batchResult>
```

Response Status:

200 - OK

## Moving a Group to a Different Post Office

JSON Request:

```
POST https://localhost:9710/gwadmin-service/system/moverequests  
  sources=[{id=GROUP.testDom1.testPO1.testMoveGroup1}]  
  postOfficeId=POST_OFFICE.testDom2.testPO2
```

JSON Response:

```
{  
  "succeeded" : 0,  
  "failed" : [ {  
    "id" : "GROUP.testDom1.testPO1.testMoveGroup1",  
    "status" : {  
      "error" : true,  
      "statusCode" : 404,  
      "statusCode" : 56074,  
      "statusMsg" : "The object is invalid.  
testDom1.testPO1.testMoveGroup1.",  
      "locationHeader" : null  
    }  
  } ]  
}
```

XML Request:

```
POST https://localhost:9710/gwadmin-service/system/moverequests
```

```
<moveRequest><sources><id>GROUP.testDom1.testPO1.testMoveGroup1</id></sources><postOfficeId>POST_OFFICE.testDom2.testPO2</postOfficeId></moveRequest>
```

XML Response:

```
<batchResult>
  <succeeded>0</succeeded>
  <failed>
    <id>GROUP.testDom1.testPO1.testMoveGroup1</id>
    <status>
      <error>true</error>
      <statusCode>404</statusCode>
      <statusCode>56074</statusCode>
      <statusMsg>The object is invalid.
testDom1.testPO1.testMoveGroup1.</statusMsg>
    </status>
  </failed>
</batchResult>
```

Response Status:

200 - OK

## Moving a Resource to a Different Post Office

JSON Request:

```
POST https://localhost:9710/gwadmin-service/system/moverequests
  "sources": [{"id": "RESOURCE.testDom1.testPO1.testMoveResource1",
"resourceOwnerId": "testMoveUser1"}]
  "postOfficeId": "POST_OFFICE.testDom2.testPO2"
```

JSON Response:

```
{
  "succeeded" : 0,
  "failed" : [ {
    "id" : "RESOURCE.testDom1.testPO1.testMoveResource1",
    "status" : {
      "error" : true,
      "statusCode" : 404,
      "statusCode" : 56074,
      "statusMsg" : "The object is invalid.
testDom1.testPO1.testMoveResource1.",
      "locationHeader" : null
    }
  } ]
}
```

XML Request:

```
POST https://localhost:9710/gwadmin-service/system/moverequests
<moveRequest><sources><id>RESOURCE.testDom1.testPO1.testMoveResource1</id><resourceOwnerId>testMoveUser1</resourceOwnerId></sources><postOfficeId>POST_OFFICE.testDom2.testPO2</postOfficeId></moveRequest>
```

XML Response:

```
<batchResult>
  <succeeded>0</succeeded>
  <failed>
    <id>RESOURCE.testDom1.testPO1.testMoveResource1</id>
    <status>
      <error>true</error>
      <statusCode>404</statusCode>
      <statusCode>56074</statusCode>
      <statusMsg>The object is invalid.
testDom1.testPO1.testMoveResource1.</statusMsg>
    </status>
  </failed>
</batchResult>
```

Response Status:  
200 - OK

## Deleting a User from the GroupWise System

Request:  
DELETE https://localhost:9710/gwadmin-service/domains/testDom1/  
postoffices/testPO1/users/testUser1

Response Status:  
200 - OK



# Deleting a User That Owns Resources from the GroupWise System

Request:

```
DELETE https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/testPO1/users/testMoveUser2
```

JSON Response:

```
{
  "error" : true,
  "httpStatusCode" : 403,
  "statusCode" : 56073,
  "statusMsg" : "User owns resources that must be transferred before it can be deleted",
  "locationHeader" : null
}
```

XML Response:

```
<apiStatus>
  <error>true</error>
  <httpStatusCode>403</httpStatusCode>
  <statusCode>56073</statusCode>
  <statusMsg>User owns resources that must be transferred before it can be deleted</statusMsg>
</apiStatus>
```

Response Status:

403 - Forbidden

56073: User owns resources that must be transferred before it can be deleted

## Deleting a User That Has Been Moved from the GroupWise System

Request:

```
DELETE https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/testP01/users/testMoveUser3
```

JSON Response:

```
{
  "error" : true,
  "httpStatusCode" : 500,
  "statusCode" : 56064,
  "statusMsg" : "Pending move or delete operation",
  "locationHeader" : null
}
```

XML Response:

```
<apiStatus>
  <error>true</error>
  <httpStatusCode>500</httpStatusCode>
  <statusCode>56064</statusCode>
  <statusMsg>Pending move or delete operation</statusMsg>
</apiStatus>
```

Response Status:

```
500 - Internal Server Error
56064: Pending move or delete operation
```

## Deleting a Group from the GroupWise System

Request:

```
DELETE https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/testP01/groups/testGroup1
```

Response Status:

```
200 - OK
```

## Deleting a Member from a Group

Request:

```
DELETE https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/testP01/groups/testGroup1/members/GROUP.testDom1.testP01.testUser1
```

Response Status:

```
200 - OK
```

## Deleting a Resource from the GroupWise System

Request:  
DELETE https://localhost:9710/gwadmin-service/domains/testDom1/  
postoffices/testPO1/resources/testResource1

Response Status:  
200 - OK

## Deleting a Nickname from the GroupWise System

Request:  
DELETE https://localhost:9710/gwadmin-service/domains/testDom1/  
postoffices/testPO1/nicknames/testNicknameName1

Response Status:  
200 - OK

## Requesting the Client Options for a User

Request:  
GET https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/  
testPO1/users/testUser1/clientoptions

Response Status:  
200 - OK

JSON Response:

```
{
  "id" : null,
  "guid" : null,
  "name" : null,
  "links" : null,
  "timeCreated" : null,
  "timeLastMod" : null,
  "legacyDn" : null,
  "lastModifiedBy" : null,
  "lastModifiedOp" : null,
  "pendingOp" : null,
  "alarmDefaultTime" : {
    "lock" : null,
    "value" : {
      "hours" : 0,
      "minutes" : 5,
      "timeInMinutes" : 5
    },
    "restore" : false
  },
  "alarmWhenAccepted" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
```

```

        "lockAvailable" : true,
        "lockRights" : "LOCK_USER",
        "modifiable" : true
    },
    "value" : true,
    "restore" : false
},
"appointmentAcceptedNotification" : {
    "lock" : {
        "lockLevel" : "NONE",
        "itemLocked" : false,
        "lockAvailable" : true,
        "lockRights" : "LOCK_USER",
        "modifiable" : true
    },
    "value" : "NONE",
    "restore" : false
},
"appointmentCleanupAction" : {
    "lock" : {
        "lockLevel" : "NONE",
        "itemLocked" : false,
        "lockAvailable" : true,
        "lockRights" : "LOCK_USER",
        "modifiable" : true
    },
    "value" : "MANUAL_DELETE_ARCHIVE",
    "restore" : false
},
"appointmentCleanupDays" : {
    "lock" : null,
    "value" : 14,
    "restore" : false
},
"appointmentDefaultLength" : {
    "lock" : {
        "lockLevel" : "NONE",
        "itemLocked" : false,
        "lockAvailable" : true,
        "lockRights" : "LOCK_USER",
        "modifiable" : true
    },
    "value" : {
        "hours" : 1,
        "minutes" : 0,
        "timeInMinutes" : 60
    },
    "restore" : false
},
"appointmentDeletedNotification" : {
    "lock" : {
        "lockLevel" : "NONE",
        "itemLocked" : false,
        "lockAvailable" : true,
        "lockRights" : "LOCK_USER",

```

```

    "modifiable" : true
  },
  "value" : "NONE",
  "restore" : false
},
"appointmentDisplayMode" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : true,
    "lockRights" : "LOCK_USER",
    "modifiable" : true
  },
  "value" : "DURATION",
  "restore" : false
},
"appointmentIncludeSelf" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : true,
    "lockRights" : "LOCK_USER",
    "modifiable" : true
  },
  "value" : true,
  "restore" : false
},
"appointmentOpenedNotification" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : true,
    "lockRights" : "LOCK_USER",
    "modifiable" : true
  },
  "value" : "NONE",
  "restore" : false
},
"appointmentTrackingAction" : {
  "lock" : null,
  "value" : "ALL_INFORMATION",
  "restore" : false
},
"archiveLocationLinux" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : true,
    "lockRights" : "LOCK_USER",
    "modifiable" : true
  },
  "value" : "",
  "restore" : false
},
"archiveLocationUnc" : {

```

```

"lock" : {
  "lockLevel" : "NONE",
  "itemLocked" : false,
  "lockAvailable" : true,
  "lockRights" : "LOCK_USER",
  "modifiable" : true
},
"value" : "",
"restore" : false
},
"autoDeleteSentMail" : {
  "lock" : null,
  "value" : false,
  "restore" : false
},
"autoUpdateUrl" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : false,
    "lockRights" : "LOCK_USER",
    "modifiable" : true
  },
  "value" : "",
  "restore" : false
},
"autoUpdateEnabled" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : false,
    "lockRights" : "LOCK_USER",
    "modifiable" : true
  },
  "value" : true,
  "restore" : false
},
"autoUpdateForce" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : false,
    "lockRights" : "LOCK_USER",
    "modifiable" : true
  },
  "value" : false,
  "restore" : false
},
"autoUpdateGraceLogins" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : false,
    "lockRights" : "LOCK_USER",
    "modifiable" : true

```

```

    },
    "value" : 0,
    "restore" : false
  },
  "autoUpdateAlwaysPrompt" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : false,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : false,
    "restore" : false
  },
  "boxSizeLimit" : {
    "lock" : null,
    "value" : 0,
    "restore" : false
  },
  "boxSizeNotify" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : false,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : false,
    "restore" : false
  },
  "boxSizeWarningThreshold" : {
    "lock" : null,
    "value" : 0,
    "restore" : false
  },
  "boxThresholdNotify" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : false,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : false,
    "restore" : false
  },
  "busySearchAppointmentLength" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
  },

```

```

    "value" : {
      "hours" : 0,
      "minutes" : 15,
      "timeInMinutes" : 15
    },
    "restore" : false
  },
  "busySearchDays" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : [ "THURSDAY", "FRIDAY", "MONDAY", "TUESDAY", "WEDNESDAY" ],
    "restore" : false
  },
  "busySearchFromTime" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : {
      "hours" : 8,
      "minutes" : 0,
      "timeInMinutes" : 480
    },
    "restore" : false
  },
  "busySearchRange" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : 7,
    "restore" : false
  },
  "busySearchToTime" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : {
      "hours" : 17,
      "minutes" : 0,

```



```

        "timeInMinutes" : 1020
    },
    "restore" : false
},
"cachingGraceDays" : {
    "lock" : null,
    "value" : 14,
    "restore" : false
},
"cachingMode" : {
    "lock" : {
        "lockLevel" : "NONE",
        "itemLocked" : false,
        "lockAvailable" : false,
        "lockRights" : "LOCK_USER",
        "modifiable" : true
    },
    "value" : "ALLOW",
    "restore" : false
},
"calendarEndTime" : {
    "lock" : {
        "lockLevel" : "NONE",
        "itemLocked" : false,
        "lockAvailable" : true,
        "lockRights" : "LOCK_USER",
        "modifiable" : true
    },
    "value" : {
        "hours" : 17,
        "minutes" : 0,
        "timeInMinutes" : 1020
    },
    "restore" : false
},
"calendarFirstOfWeek" : {
    "lock" : {
        "lockLevel" : "NONE",
        "itemLocked" : false,
        "lockAvailable" : true,
        "lockRights" : "LOCK_USER",
        "modifiable" : true
    },
    "value" : "SUNDAY",
    "restore" : false
},
"calendarHighlightDays" : {
    "lock" : {
        "lockLevel" : "NONE",
        "itemLocked" : false,
        "lockAvailable" : true,
        "lockRights" : "LOCK_USER",
        "modifiable" : true
    },
    "value" : [ "SUNDAY", "SATURDAY" ],

```

```

    "restore" : false
  },
  "calendarShowWeekNumber" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : false,
    "restore" : false
  },
  "calendarStartTime" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : {
      "hours" : 8,
      "minutes" : 0,
      "timeInMinutes" : 480
    },
    "restore" : false
  },
  "calendarWorkdays" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : [ "THURSDAY", "FRIDAY", "MONDAY", "TUESDAY", "WEDNESDAY" ],
    "restore" : false
  },
  "certificateDownloadUrl" : {
    "lock" : null,
    "value" : "",
    "restore" : false
  },
  "checkSpelling" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : false,
    "restore" : false
  },
},

```

```

"checkSpellingAsYouType" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : true,
    "lockRights" : "LOCK_USER",
    "modifiable" : true
  },
  "value" : true,
  "restore" : false
},
"classification" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : true,
    "lockRights" : "LOCK_USER",
    "modifiable" : true
  },
  "value" : "NORMAL",
  "restore" : false
},
"clientLicense" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : true,
    "lockRights" : "LOCK_USER",
    "modifiable" : true
  },
  "value" : "FULL",
  "restore" : false
},
"collaborationSingleSignon" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : true,
    "lockRights" : "LOCK_USER",
    "modifiable" : true
  },
  "value" : false,
  "restore" : false
},
"colorScheme" : {
  "lock" : null,
  "value" : "SKY_BLUE",
  "restore" : false
},
"composeViews" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : false,
    "lockRights" : "LOCK_USER",

```

```

    "modifiable" : true
  },
  "value" : [ "TEXT", "HTML" ],
  "restore" : false
},
"conferencingUrl" : null,
"conferencingEnabled" : null,
"concealSubject" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : true,
    "lockRights" : "LOCK_USER",
    "modifiable" : true
  },
  "value" : false,
  "restore" : false
},
"convertAttachments" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : true,
    "lockRights" : "LOCK_USER",
    "modifiable" : true
  },
  "value" : false,
  "restore" : false
},
"createTrackingItem" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : true,
    "lockRights" : "LOCK_USER",
    "modifiable" : true
  },
  "value" : true,
  "restore" : false
},
"customViewsLocationUnc" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : true,
    "lockRights" : "LOCK_USER",
    "modifiable" : true
  },
  "value" : "",
  "restore" : false
},
"defaultComposeView" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,

```

```

        "lockAvailable" : true,
        "lockRights" : "LOCK_USER",
        "modifiable" : true
    },
    "value" : "HTML",
    "restore" : false
},
"defaultLibrary" : {
    "lock" : null,
    "value" : "",
    "restore" : false
},
"defaultReadView" : {
    "lock" : {
        "lockLevel" : "NONE",
        "itemLocked" : false,
        "lockAvailable" : true,
        "lockRights" : "LOCK_USER",
        "modifiable" : true
    },
    "value" : "HTML",
    "restore" : false
},
"delayDelivery" : {
    "lock" : {
        "lockLevel" : "NONE",
        "itemLocked" : false,
        "lockAvailable" : true,
        "lockRights" : "LOCK_USER",
        "modifiable" : true
    },
    "value" : -1,
    "restore" : false
},
"disableHTMLView" : {
    "lock" : {
        "lockLevel" : "NONE",
        "itemLocked" : false,
        "lockAvailable" : true,
        "lockRights" : "LOCK_USER",
        "modifiable" : true
    },
    "value" : false,
    "restore" : false
},
"displayFolderList" : {
    "lock" : {
        "lockLevel" : "NONE",
        "itemLocked" : false,
        "lockAvailable" : true,
        "lockRights" : "LOCK_USER",
        "modifiable" : true
    },
    "value" : true,
    "restore" : false
}

```

```

},
"displayMainMenu" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : true,
    "lockRights" : "LOCK_USER",
    "modifiable" : true
  },
  "value" : true,
  "restore" : false
},
"displayMainToolBar" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : true,
    "lockRights" : "LOCK_USER",
    "modifiable" : true
  },
  "value" : true,
  "restore" : false
},
"displayNavBar" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : true,
    "lockRights" : "LOCK_USER",
    "modifiable" : true
  },
  "value" : true,
  "restore" : false
},
"displayQuickViewer" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : true,
    "lockRights" : "LOCK_USER",
    "modifiable" : true
  },
  "value" : false,
  "restore" : false
},
"doNotPurgeBeforeBackup" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : true,
    "lockRights" : "LOCK_USER",
    "modifiable" : true
  },
  "value" : false,
  "restore" : false
}

```

```

},
"edirectoryAuthentication" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : true,
    "lockRights" : "LOCK_USER",
    "modifiable" : true
  },
  "value" : false,
  "restore" : false
},
"encryptForRecipients" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : true,
    "lockRights" : "LOCK_USER",
    "modifiable" : true
  },
  "value" : false,
  "restore" : false
},
"encryptionAlgorithm" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : true,
    "lockRights" : "LOCK_USER",
    "modifiable" : true
  },
  "value" : "NONE",
  "restore" : false
},
"encryptionKeySize" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : true,
    "lockRights" : "LOCK_USER",
    "modifiable" : true
  },
  "value" : "NONE",
  "restore" : false
},
"forceCacheCleanup" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : true,
    "lockRights" : "LOCK_USER",
    "modifiable" : true
  },
  "value" : false,
  "restore" : false
}

```

```

},
"frequentContacts" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : true,
    "lockRights" : "LOCK_USER",
    "modifiable" : true
  },
  "value" : null,
  "restore" : false
},
"folderListViewType" : {
  "lock" : null,
  "value" : [ "FAVORITES", "SIMPLE", "FULL" ],
  "restore" : false
},
"globalSignatureApplication" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : true,
    "lockRights" : "LOCK_USER",
    "modifiable" : true
  },
  "value" : "EXTERNAL_MESSAGES",
  "restore" : false
},
"globalSignatureList" : {
  "lock" : null,
  "value" : [ "Novell_Global_Signature" ],
  "restore" : false
},
"globalSignatureName" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : true,
    "lockRights" : "LOCK_USER",
    "modifiable" : true
  },
  "value" : "<Default Global Signature>",
  "restore" : false
},
"handleJunkMail" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : false,
    "lockRights" : "LOCK_USER",
    "modifiable" : true
  },
  "value" : true,
  "restore" : false
},

```



```

"internetMailTracking" : {
  "lock" : null,
  "value" : true,
  "restore" : false
},
"junkMailCleanupAction" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : true,
    "lockRights" : "LOCK_USER",
    "modifiable" : true
  },
  "value" : "AUTO_PURGE",
  "restore" : false
},
"junkMailCleanupDays" : {
  "lock" : null,
  "value" : 14,
  "restore" : false
},
"limitsApplyToCache" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : false,
    "lockRights" : "LOCK_USER",
    "modifiable" : true
  },
  "value" : false,
  "restore" : false
},
"longFolderList" : null,
"mailCleanupAction" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : true,
    "lockRights" : "LOCK_USER",
    "modifiable" : true
  },
  "value" : "MANUAL_DELETE_ARCHIVE",
  "restore" : false
},
"mailCleanupDays" : {
  "lock" : null,
  "value" : 30,
  "restore" : false
},
"mailDeletedNotification" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : true,
    "lockRights" : "LOCK_USER",

```

```

    "modifiable" : true
  },
  "value" : "NONE",
  "restore" : false
},
"mailOpenedNotification" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : true,
    "lockRights" : "LOCK_USER",
    "modifiable" : true
  },
  "value" : "NONE",
  "restore" : false
},
"mailTrackingAction" : {
  "lock" : null,
  "value" : "DELIVERED_OPENED",
  "restore" : false
},
"maxMessageSize" : {
  "lock" : null,
  "value" : 0,
  "restore" : false
},
"messageRetention" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : false,
    "lockRights" : "LOCK_USER",
    "modifiable" : true
  },
  "value" : false,
  "restore" : false
},
"mimeEncoding" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : true,
    "lockRights" : "LOCK_USER",
    "modifiable" : true
  },
  "value" : "UTF8",
  "restore" : false
},
"moveToPublishedCalendar" : {
  "lock" : {
    "lockLevel" : "SET_DOMAIN",
    "itemLocked" : false,
    "lockAvailable" : true,
    "lockRights" : "LOCK_USER",
    "modifiable" : true
  }
}

```

```

    },
    "value" : true,
    "restore" : false
  },
  "noteAcceptedNotification" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : "NONE",
    "restore" : false
  },
  "noteDeletedNotification" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : "NONE",
    "restore" : false
  },
  "noteOpenedNotification" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : "NONE",
    "restore" : false
  },
  "noteTrackingAction" : {
    "lock" : null,
    "value" : "DELIVERED_OPENED",
    "restore" : false
  },
  "notifyPollInterval" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : {
      "minutes" : 1,
      "seconds" : 0,
      "timeInSeconds" : 60
    }
  },

```

```

    "restore" : false
  },
  "openNewView" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : false,
    "restore" : false
  },
  "passwordCaching" : null,
  "performMaintenancePurges" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : false,
    "restore" : false
  },
  "personalAddressBookUserDefinedFields" : {
    "lock" : null,
    "value" : true,
    "restore" : false
  },
  "promptBeforePurge" : {
    "lock" : null,
    "value" : false,
    "restore" : false
  },
  "publishCalendar" : {
    "lock" : {
      "lockLevel" : "SET_DOMAIN",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : true,
    "restore" : false
  },
  "publishFreeBusySearch" : {
    "lock" : {
      "lockLevel" : "SET_DOMAIN",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : true,

```

```

    "restore" : false
  },
  "publishingHost" : {
    "lock" : {
      "lockLevel" : "SET_DOMAIN",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : "testCalPubHost1",
    "restore" : false
  },
  "HTMLReplyFormat" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : "GROUPWISE_CLASSIC",
    "restore" : false
  },
  "HTMLReplyFormatIncludeHeaders" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : false,
    "restore" : false
  },
  "HTMLReplyFormatTypePosition" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : "TOP",
    "restore" : false
  },
  "HTMLReplyFormatIncludeDate" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : true,

```

```

    "restore" : false
  },
  "HTMLReplyFormatIncludeID" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : true,
    "restore" : false
  },
  "HTMLReplyFormatIncludeName" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : true,
    "restore" : false
  },
  "HTMLReplyFormatIncludeAddress" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : false,
    "restore" : false
  },
  "HTMLReplyFormatIncludeSeparator" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : true,
    "restore" : false
  },
  "plainTextReplyFormat" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : "GROUPWISE_CLASSIC",

```

```

    "restore" : false
  },
  "plainTextReplyFormatSeparatorChar" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : ">",
    "restore" : false
  },
  "plainTextReplyFormatTypePosition" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : "TOP",
    "restore" : false
  },
  "plainTextReplyFormatIncludeAddress" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : false,
    "restore" : false
  },
  "plainTextReplyFormatIncludeName" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : true,
    "restore" : false
  },
  "plainTextReplyFormatIncludeDate" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : true,

```

```

    "restore" : false
  },
  "plainTextReplyFormatIncludeID" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : true,
    "restore" : false
  },
  "plainTextReplyFormatIncludeSeparator" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : true,
    "restore" : false
  },
  "quickViewerPosition" : {
    "lock" : null,
    "value" : "BOTTOM",
    "restore" : false
  },
  "readNext" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : true,
    "restore" : false
  },
  "readViews" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : false,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : [ "TEXT", "HTML" ],
    "restore" : false
  },
  "refreshInterval" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,

```



```

    "lockAvailable" : true,
    "lockRights" : "LOCK_USER",
    "modifiable" : true
  },
  "value" : {
    "minutes" : 1,
    "seconds" : 0,
    "timeInSeconds" : 60
  },
  "restore" : false
},
"remoteMode" : {
  "lock" : null,
  "value" : true,
  "restore" : false
},
"requirePassword" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : true,
    "lockRights" : "LOCK_USER",
    "modifiable" : true
  },
  "value" : false,
  "restore" : false
},
"ruleReplyAll" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : false,
    "lockRights" : "LOCK_USER",
    "modifiable" : true
  },
  "value" : false,
  "restore" : false
},
"ruleReplyLoop" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : true,
    "lockRights" : "LOCK_USER",
    "modifiable" : true
  },
  "value" : false,
  "restore" : false
},
"sendExpireDays" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : true,
    "lockRights" : "LOCK_USER",

```

```

    "modifiable" : true
  },
  "value" : 0,
  "restore" : false
},
"sendIllegalExtensions" : {
  "lock" : null,
  "value" : "",
  "restore" : false
},
"sendNotify" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : true,
    "lockRights" : "LOCK_USER",
    "modifiable" : true
  },
  "value" : true,
  "restore" : false
},
"sendPriority" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : true,
    "lockRights" : "LOCK_USER",
    "modifiable" : true
  },
  "value" : "STANDARD",
  "restore" : false
},
"sendRecipientLimit" : {
  "lock" : null,
  "value" : 0,
  "restore" : false
},
"sendReplyRequested" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : true,
    "lockRights" : "LOCK_USER",
    "modifiable" : true
  },
  "value" : 255,
  "restore" : false
},
"sharedAddressBook" : {
  "lock" : {
    "lockLevel" : "NONE",
    "itemLocked" : false,
    "lockAvailable" : true,
    "lockRights" : "LOCK_USER",
    "modifiable" : true
  }
}

```

```

    },
    "value" : true,
    "restore" : false
  },
  "sharedFolder" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : true,
    "restore" : false
  },
  "showMessengerPresence" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : true,
    "restore" : false
  },
  "signDigitally" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : false,
    "restore" : false
  },
  "singleSignon" : {
    "lock" : null,
    "value" : true,
    "restore" : false
  },
  "subscribeCalendar" : {
    "lock" : {
      "lockLevel" : "SET_DOMAIN",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : true,
    "restore" : false
  },
  "taskAcceptedNotification" : {
    "lock" : {

```

```

        "lockLevel" : "NONE",
        "itemLocked" : false,
        "lockAvailable" : true,
        "lockRights" : "LOCK_USER",
        "modifiable" : true
    },
    "value" : "NONE",
    "restore" : false
},
"taskCompletedNotification" : {
    "lock" : {
        "lockLevel" : "NONE",
        "itemLocked" : false,
        "lockAvailable" : true,
        "lockRights" : "LOCK_USER",
        "modifiable" : true
    },
    "value" : "NONE",
    "restore" : false
},
"taskDeletedNotification" : {
    "lock" : {
        "lockLevel" : "NONE",
        "itemLocked" : false,
        "lockAvailable" : true,
        "lockRights" : "LOCK_USER",
        "modifiable" : true
    },
    "value" : "NONE",
    "restore" : false
},
"taskOpenedNotification" : {
    "lock" : {
        "lockLevel" : "NONE",
        "itemLocked" : false,
        "lockAvailable" : true,
        "lockRights" : "LOCK_USER",
        "modifiable" : true
    },
    "value" : "NONE",
    "restore" : false
},
"taskTrackingAction" : {
    "lock" : null,
    "value" : "ALL_INFORMATION",
    "restore" : false
},
"trashCleanupAction" : {
    "lock" : {
        "lockLevel" : "NONE",
        "itemLocked" : false,
        "lockAvailable" : true,
        "lockRights" : "LOCK_USER",
        "modifiable" : true
    },

```

```

    "value" : "AUTO_PURGE",
    "restore" : false
  },
  "trashCleanupDays" : {
    "lock" : null,
    "value" : 7,
    "restore" : false
  },
  "treatImapLikeGW" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : false,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : null,
    "restore" : false
  },
  "tutorialUrl" : {
    "lock" : null,
    "value" : "",
    "restore" : false
  },
  "useBlockMailList" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : false,
    "restore" : false
  },
  "useColorSchemes" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : true,
    "restore" : false
  },
  "useJunkMailList" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : false,

```

```

    "restore" : false
  },
  "useNntpAccounts" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : false,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : false,
    "restore" : false
  },
  "usePersonalAddressBook" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : false,
    "restore" : false
  },
  "usePersonalAddressBookForCalendar" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : false,
    "restore" : false
  },
  "usePopImapAccounts" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : false,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : false,
    "restore" : false
  },
  "userLimits" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : false,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : false,

```

```

    "restore" : false
  },
  "userPasswordEnabled" : null,
  "userPassword" : null,
  "useSmime" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : false,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : true,
    "restore" : false
  },
  "vibeEnabled" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : false,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : false,
    "restore" : false
  },
  "vibeUrl" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : "",
    "restore" : false
  },
  "wildcardAddressing" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : "LIMITED_TO_POST_OFFICE",
    "restore" : false
  },
  "htmlreplyFormatIncludeHeaders" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    }
  }
}

```

```

    },
    "value" : false,
    "restore" : false
  },
  "htmlreplyFormatTypePosition" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : "TOP",
    "restore" : false
  },
  "htmlreplyFormatIncludeDate" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : true,
    "restore" : false
  },
  "htmlreplyFormatIncludeName" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : true,
    "restore" : false
  },
  "htmlreplyFormatIncludeAddress" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : false,
    "restore" : false
  },
  "htmlreplyFormatIncludeSeparator" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    }
  }
}

```



```

    },
    "value" : true,
    "restore" : false
  },
  "htmlreplyFormat" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : "GROUPWISE_CLASSIC",
    "restore" : false
  },
  "htmlreplyFormatIncludeID" : {
    "lock" : {
      "lockLevel" : "NONE",
      "itemLocked" : false,
      "lockAvailable" : true,
      "lockRights" : "LOCK_USER",
      "modifiable" : true
    },
    "value" : true,
    "restore" : false
  },
  "@type" : null,
  "@url" : null
}

```

XML Response:

```

<clientOptions>
  <forceNullOnAttrs/>
  <alarmDefaultTime>
    <value class="AttrNoUsed">
      <hours>0</hours>
      <minutes>5</minutes>
    </value>
    <restore>>false</restore>
  </alarmDefaultTime>
  <alarmWhenAccepted>
    <lock>
      <lockLevel>NONE</lockLevel>
      <itemLocked>>false</itemLocked>
      <lockAvailable>>true</lockAvailable>
      <lockRights>LOCK_USER</lockRights>
      <modifiable>>true</modifiable>
    </lock>
    <value class="boolean">>true</value>
    <restore>>false</restore>
  </alarmWhenAccepted>
  <appointmentAcceptedNotification>
    <lock>
      <lockLevel>NONE</lockLevel>
      <itemLocked>>false</itemLocked>

```

```

        <lockAvailable>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>true</modifiable>
    </lock>
    <value class="AttrNoUsed">NONE</value>
    <restore>>false</restore>
</appointmentAcceptedNotification>
<appointmentCleanupAction>
    <lock>
        <lockLevel>NONE</lockLevel>
        <itemLocked>>false</itemLocked>
        <lockAvailable>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>true</modifiable>
    </lock>
    <value class="AttrNoUsed">MANUAL_DELETE_ARCHIVE</value>
    <restore>>false</restore>
</appointmentCleanupAction>
<appointmentCleanupDays>
    <value class="long">14</value>
    <restore>>false</restore>
</appointmentCleanupDays>
<appointmentDefaultLength>
    <lock>
        <lockLevel>NONE</lockLevel>
        <itemLocked>>false</itemLocked>
        <lockAvailable>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>true</modifiable>
    </lock>
    <value class="AttrNoUsed">
        <hours>1</hours>
        <minutes>0</minutes>
    </value>
    <restore>>false</restore>
</appointmentDefaultLength>
<appointmentDeletedNotification>
    <lock>
        <lockLevel>NONE</lockLevel>
        <itemLocked>>false</itemLocked>
        <lockAvailable>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>true</modifiable>
    </lock>
    <value class="AttrNoUsed">NONE</value>
    <restore>>false</restore>
</appointmentDeletedNotification>
<appointmentDisplayMode>
    <lock>
        <lockLevel>NONE</lockLevel>
        <itemLocked>>false</itemLocked>
        <lockAvailable>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>true</modifiable>
    </lock>

```

```

    <value class="AttrNoUsed">DURATION</value>
    <restore>>false</restore>
</appointmentDisplayMode>
<appointmentIncludeSelf>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>true</value>
  <restore>>false</restore>
</appointmentIncludeSelf>
<appointmentOpenedNotification>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="AttrNoUsed">NONE</value>
  <restore>>false</restore>
</appointmentOpenedNotification>
<appointmentTrackingAction>
  <value class="AttrNoUsed">ALL_INFORMATION</value>
  <restore>>false</restore>
</appointmentTrackingAction>
<archiveLocationLinux>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="string"></value>
  <restore>>false</restore>
</archiveLocationLinux>
<archiveLocationUnc>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="string"></value>
  <restore>>false</restore>
</archiveLocationUnc>
<autoDeleteSentMail>
  <value class="boolean">>false</value>
  <restore>>false</restore>
</autoDeleteSentMail>

```

```

<autoUpdateUrl>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>false</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="string"></value>
  <restore>>false</restore>
</autoUpdateUrl>
<autoUpdateEnabled>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>false</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>true</value>
  <restore>>false</restore>
</autoUpdateEnabled>
<autoUpdateForce>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>false</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>false</value>
  <restore>>false</restore>
</autoUpdateForce>
<autoUpdateGraceLogins>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>false</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="long">0</value>
  <restore>>false</restore>
</autoUpdateGraceLogins>
<autoUpdateAlwaysPrompt>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>false</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>false</value>
  <restore>>false</restore>
</autoUpdateAlwaysPrompt>

```

```

<boxSizeLimit>
  <value class="long">0</value>
  <restore>>false</restore>
</boxSizeLimit>
<boxSizeNotify>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>false</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>false</value>
  <restore>>false</restore>
</boxSizeNotify>
<boxSizeWarningThreshold>
  <value class="long">0</value>
  <restore>>false</restore>
</boxSizeWarningThreshold>
<boxThresholdNotify>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>false</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>false</value>
  <restore>>false</restore>
</boxThresholdNotify>
<busySearchAppointmentLength>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="AttrNoUsed">
    <hours>0</hours>
    <minutes>15</minutes>
  </value>
  <restore>>false</restore>
</busySearchAppointmentLength>
<busySearchDays>
  <lock>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <modifiable>>true</modifiable>
    <lockLevel>NONE</lockLevel>
    <lockRights>LOCK_USER</lockRights>
  </lock>
  <value>WEDNESDAY</value>
  <value>TUESDAY</value>
  <value>MONDAY</value>

```

```

    <value>THURSDAY</value>
    <value>FRIDAY</value>
</busySearchDays>
<busySearchFromTime>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="AttrNoUsed">
    <hours>8</hours>
    <minutes>0</minutes>
  </value>
  <restore>>false</restore>
</busySearchFromTime>
<busySearchRange>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="long">7</value>
  <restore>>false</restore>
</busySearchRange>
<busySearchToTime>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="AttrNoUsed">
    <hours>17</hours>
    <minutes>0</minutes>
  </value>
  <restore>>false</restore>
</busySearchToTime>
<cachingGraceDays>
  <value class="long">14</value>
  <restore>>false</restore>
</cachingGraceDays>
<cachingMode>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>false</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="AttrNoUsed">ALLOW</value>

```

```

    <restore>>false</restore>
</cachingMode>
<calendarEndTime>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="AttrNoUsed">
    <hours>17</hours>
    <minutes>0</minutes>
  </value>
  <restore>>false</restore>
</calendarEndTime>
<calendarFirstOfWeek>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="AttrNoUsed">SUNDAY</value>
  <restore>>false</restore>
</calendarFirstOfWeek>
<calendarHighlightDays>
  <lock>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <modifiable>>true</modifiable>
    <lockLevel>NONE</lockLevel>
    <lockRights>LOCK_USER</lockRights>
  </lock>
  <value>SATURDAY</value>
  <value>SUNDAY</value>
</calendarHighlightDays>
<calendarShowWeekNumber>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>false</value>
  <restore>>false</restore>
</calendarShowWeekNumber>
<calendarStartTime>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>

```

```

    <modifiable>true</modifiable>
  </lock>
  <value class="AttrNoUsed">
    <hours>8</hours>
    <minutes>0</minutes>
  </value>
  <restore>false</restore>
</calendarStartTime>
<calendarWorkdays>
  <lock>
    <itemLocked>false</itemLocked>
    <lockAvailable>true</lockAvailable>
    <modifiable>true</modifiable>
    <lockLevel>NONE</lockLevel>
    <lockRights>LOCK_USER</lockRights>
  </lock>
  <value>WEDNESDAY</value>
  <value>TUESDAY</value>
  <value>MONDAY</value>
  <value>THURSDAY</value>
  <value>FRIDAY</value>
</calendarWorkdays>
<certificateDownloadUrl>
  <value class="string"></value>
  <restore>false</restore>
</certificateDownloadUrl>
<checkSpelling>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>false</itemLocked>
    <lockAvailable>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="boolean">>false</value>
  <restore>false</restore>
</checkSpelling>
<checkSpellingAsYouType>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>false</itemLocked>
    <lockAvailable>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="boolean">>true</value>
  <restore>false</restore>
</checkSpellingAsYouType>
<classification>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>false</itemLocked>
    <lockAvailable>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>

```



```

    </lock>
    <value class="AttrNoUsed">NORMAL</value>
    <restore>>false</restore>
</classification>
<clientLicense>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="AttrNoUsed">FULL</value>
  <restore>>false</restore>
</clientLicense>
<collaborationSingleSignon>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>false</value>
  <restore>>false</restore>
</collaborationSingleSignon>
<colorScheme>
  <value class="AttrNoUsed">SKY_BLUE</value>
  <restore>>false</restore>
</colorScheme>
<composeViews>
  <lock>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>false</lockAvailable>
    <modifiable>>true</modifiable>
    <lockLevel>NONE</lockLevel>
    <lockRights>LOCK_USER</lockRights>
  </lock>
  <value>TEXT</value>
  <value>HTML</value>
</composeViews>
<concealSubject>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>false</value>
  <restore>>false</restore>
</concealSubject>
<convertAttachments>
  <lock>
    <lockLevel>NONE</lockLevel>

```

```

        <itemLocked>>false</itemLocked>
        <lockAvailable>>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>>true</modifiable>
    </lock>
    <value class="boolean">>false</value>
    <restore>>false</restore>
</convertAttachments>
<createTrackingItem>
    <lock>
        <lockLevel>NONE</lockLevel>
        <itemLocked>>false</itemLocked>
        <lockAvailable>>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>>true</modifiable>
    </lock>
    <value class="boolean">>true</value>
    <restore>>false</restore>
</createTrackingItem>
<customViewsLocationUnc>
    <lock>
        <lockLevel>NONE</lockLevel>
        <itemLocked>>false</itemLocked>
        <lockAvailable>>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>>true</modifiable>
    </lock>
    <value class="string"></value>
    <restore>>false</restore>
</customViewsLocationUnc>
<defaultComposeView>
    <lock>
        <lockLevel>NONE</lockLevel>
        <itemLocked>>false</itemLocked>
        <lockAvailable>>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>>true</modifiable>
    </lock>
    <value class="AttrNoUsed">HTML</value>
    <restore>>false</restore>
</defaultComposeView>
<defaultLibrary>
    <value class="string"></value>
    <restore>>false</restore>
</defaultLibrary>
<defaultReadView>
    <lock>
        <lockLevel>NONE</lockLevel>
        <itemLocked>>false</itemLocked>
        <lockAvailable>>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>>true</modifiable>
    </lock>
    <value class="AttrNoUsed">HTML</value>
    <restore>>false</restore>

```

```

</defaultReadView>
<delayDelivery>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="long">-1</value>
  <restore>>false</restore>
</delayDelivery>
<disableHTMLView>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>false</value>
  <restore>>false</restore>
</disableHTMLView>
<displayFolderList>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>true</value>
  <restore>>false</restore>
</displayFolderList>
<displayMainMenu>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>true</value>
  <restore>>false</restore>
</displayMainMenu>
<displayMainToolBar>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>true</value>
  <restore>>false</restore>

```

```

</displayMainToolBar>
<displayNavBar>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>true</value>
  <restore>>false</restore>
</displayNavBar>
<displayQuickViewer>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>false</value>
  <restore>>false</restore>
</displayQuickViewer>
<doNotPurgeBeforeBackup>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>false</value>
  <restore>>false</restore>
</doNotPurgeBeforeBackup>
<edirectoryAuthentication>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>false</value>
  <restore>>false</restore>
</edirectoryAuthentication>
<encryptForRecipients>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>false</value>
  <restore>>false</restore>

```

```

</encryptForRecipients>
<encryptionAlgorithm>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="AttrNoUsed">NONE</value>
  <restore>>false</restore>
</encryptionAlgorithm>
<encryptionKeySize>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="AttrNoUsed">NONE</value>
  <restore>>false</restore>
</encryptionKeySize>
<forceCacheCleanup>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>false</value>
  <restore>>false</restore>
</forceCacheCleanup>
<frequentContacts>
  <lock>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <modifiable>>true</modifiable>
    <lockLevel>NONE</lockLevel>
    <lockRights>LOCK_USER</lockRights>
  </lock>
</frequentContacts>
<folderListViewType>
  <value>FAVORITES</value>
  <value>SIMPLE</value>
  <value>FULL</value>
</folderListViewType>
<globalSignatureApplication>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>

```

```

</lock>
  <value class="AttrNoUsed">EXTERNAL_MESSAGES</value>
  <restore>>false</restore>
</globalSignatureApplication>
<globalSignatureList>
  <value class="string-array">
    <string>Novell_Global_Signature</string>
  </value>
  <restore>>false</restore>
</globalSignatureList>
<globalSignatureName>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="string">&lt;Default Global Signature&gt;</value>
  <restore>>false</restore>
</globalSignatureName>
<handleJunkMail>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>false</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>true</value>
  <restore>>false</restore>
</handleJunkMail>
<internetMailTracking>
  <value class="boolean">>true</value>
  <restore>>false</restore>
</internetMailTracking>
<junkMailCleanupAction>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="AttrNoUsed">AUTO_PURGE</value>
  <restore>>false</restore>
</junkMailCleanupAction>
<junkMailCleanupDays>
  <value class="long">14</value>
  <restore>>false</restore>
</junkMailCleanupDays>
<limitsApplyToCache>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>

```

```

        <lockAvailable>>false</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>>true</modifiable>
    </lock>
    <value class="boolean">>false</value>
    <restore>>false</restore>
</limitsApplyToCache>
<mailCleanupAction>
    <lock>
        <lockLevel>NONE</lockLevel>
        <itemLocked>>false</itemLocked>
        <lockAvailable>>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>>true</modifiable>
    </lock>
    <value class="AttrNoUsed">MANUAL_DELETE_ARCHIVE</value>
    <restore>>false</restore>
</mailCleanupAction>
<mailCleanupDays>
    <value class="long">30</value>
    <restore>>false</restore>
</mailCleanupDays>
<mailDeletedNotification>
    <lock>
        <lockLevel>NONE</lockLevel>
        <itemLocked>>false</itemLocked>
        <lockAvailable>>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>>true</modifiable>
    </lock>
    <value class="AttrNoUsed">NONE</value>
    <restore>>false</restore>
</mailDeletedNotification>
<mailOpenedNotification>
    <lock>
        <lockLevel>NONE</lockLevel>
        <itemLocked>>false</itemLocked>
        <lockAvailable>>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>>true</modifiable>
    </lock>
    <value class="AttrNoUsed">NONE</value>
    <restore>>false</restore>
</mailOpenedNotification>
<mailTrackingAction>
    <value class="AttrNoUsed">DELIVERED_OPENED</value>
    <restore>>false</restore>
</mailTrackingAction>
<maxMessageSize>
    <value class="long">0</value>
    <restore>>false</restore>
</maxMessageSize>
<messageRetention>
    <lock>
        <lockLevel>NONE</lockLevel>

```

```

        <itemLocked>>false</itemLocked>
        <lockAvailable>>false</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>>true</modifiable>
    </lock>
    <value class="boolean">>false</value>
    <restore>>false</restore>
</messageRetention>
<mimeEncoding>
    <lock>
        <lockLevel>NONE</lockLevel>
        <itemLocked>>false</itemLocked>
        <lockAvailable>>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>>true</modifiable>
    </lock>
    <value class="AttrNoUsed">UTF8</value>
    <restore>>false</restore>
</mimeEncoding>
<moveToPublishedCalendar>
    <lock>
        <lockLevel>SET_DOMAIN</lockLevel>
        <itemLocked>>false</itemLocked>
        <lockAvailable>>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>>true</modifiable>
    </lock>
    <value class="boolean">>true</value>
    <restore>>false</restore>
</moveToPublishedCalendar>
<noteAcceptedNotification>
    <lock>
        <lockLevel>NONE</lockLevel>
        <itemLocked>>false</itemLocked>
        <lockAvailable>>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>>true</modifiable>
    </lock>
    <value class="AttrNoUsed">NONE</value>
    <restore>>false</restore>
</noteAcceptedNotification>
<noteDeletedNotification>
    <lock>
        <lockLevel>NONE</lockLevel>
        <itemLocked>>false</itemLocked>
        <lockAvailable>>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>>true</modifiable>
    </lock>
    <value class="AttrNoUsed">NONE</value>
    <restore>>false</restore>
</noteDeletedNotification>
<noteOpenedNotification>
    <lock>
        <lockLevel>NONE</lockLevel>

```



```

        <itemLocked>>false</itemLocked>
        <lockAvailable>>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>>true</modifiable>
    </lock>
    <value class="AttrNoUsed">NONE</value>
    <restore>>false</restore>
</noteOpenedNotification>
<noteTrackingAction>
    <value class="AttrNoUsed">DELIVERED_OPENED</value>
    <restore>>false</restore>
</noteTrackingAction>
<notifyPollInterval>
    <lock>
        <lockLevel>NONE</lockLevel>
        <itemLocked>>false</itemLocked>
        <lockAvailable>>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>>true</modifiable>
    </lock>
    <value class="AttrNoUsed">
        <minutes>1</minutes>
        <seconds>0</seconds>
    </value>
    <restore>>false</restore>
</notifyPollInterval>
<openNewView>
    <lock>
        <lockLevel>NONE</lockLevel>
        <itemLocked>>false</itemLocked>
        <lockAvailable>>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>>true</modifiable>
    </lock>
    <value class="boolean">>false</value>
    <restore>>false</restore>
</openNewView>
<performMaintenancePurges>
    <lock>
        <lockLevel>NONE</lockLevel>
        <itemLocked>>false</itemLocked>
        <lockAvailable>>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>>true</modifiable>
    </lock>
    <value class="boolean">>false</value>
    <restore>>false</restore>
</performMaintenancePurges>
<personalAddressBookUserDefinedFields>
    <value class="boolean">>true</value>
    <restore>>false</restore>
</personalAddressBookUserDefinedFields>
<promptBeforePurge>
    <value class="boolean">>false</value>
    <restore>>false</restore>

```

```

</promptBeforePurge>
<publishCalendar>
  <lock>
    <lockLevel>SET_DOMAIN</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>true</value>
  <restore>>false</restore>
</publishCalendar>
<publishFreeBusySearch>
  <lock>
    <lockLevel>SET_DOMAIN</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>true</value>
  <restore>>false</restore>
</publishFreeBusySearch>
<publishingHost>
  <lock>
    <lockLevel>SET_DOMAIN</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="string">testCalPubHost1</value>
  <restore>>false</restore>
</publishingHost>
<HTMLReplyFormat>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="AttrNoUsed">GROUPWISE_CLASSIC</value>
  <restore>>false</restore>
</HTMLReplyFormat>
<HTMLReplyFormatIncludeHeaders>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>false</value>
  <restore>>false</restore>

```

```

</HTMLReplyFormatIncludeHeaders>
<HTMLReplyFormatTypePosition>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="AttrNoUsed">TOP</value>
  <restore>>false</restore>
</HTMLReplyFormatTypePosition>
<HTMLReplyFormatIncludeDate>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>true</value>
  <restore>>false</restore>
</HTMLReplyFormatIncludeDate>
<HTMLReplyFormatIncludeID>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>true</value>
  <restore>>false</restore>
</HTMLReplyFormatIncludeID>
<HTMLReplyFormatIncludeName>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>true</value>
  <restore>>false</restore>
</HTMLReplyFormatIncludeName>
<HTMLReplyFormatIncludeAddress>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>false</value>
  <restore>>false</restore>

```

```

</HTMLReplyFormatIncludeAddress>
<HTMLReplyFormatIncludeSeparator>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>true</value>
  <restore>>false</restore>
</HTMLReplyFormatIncludeSeparator>
<plainTextReplyFormat>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="AttrNoUsed">GROUPWISE_CLASSIC</value>
  <restore>>false</restore>
</plainTextReplyFormat>
<plainTextReplyFormatSeparatorChar>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="string">&gt;</value>
  <restore>>false</restore>
</plainTextReplyFormatSeparatorChar>
<plainTextReplyFormatTypePosition>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="AttrNoUsed">TOP</value>
  <restore>>false</restore>
</plainTextReplyFormatTypePosition>
<plainTextReplyFormatIncludeAddress>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>false</value>
  <restore>>false</restore>

```

```

</plainTextReplyFormatIncludeAddress>
<plainTextReplyFormatIncludeName>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>true</value>
  <restore>>false</restore>
</plainTextReplyFormatIncludeName>
<plainTextReplyFormatIncludeDate>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>true</value>
  <restore>>false</restore>
</plainTextReplyFormatIncludeDate>
<plainTextReplyFormatIncludeID>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>true</value>
  <restore>>false</restore>
</plainTextReplyFormatIncludeID>
<plainTextReplyFormatIncludeSeparator>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>true</value>
  <restore>>false</restore>
</plainTextReplyFormatIncludeSeparator>
<quickViewerPosition>
  <value class="AttrNoUsed">BOTTOM</value>
  <restore>>false</restore>
</quickViewerPosition>
<readNext>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>

```

```

    <modifiable>true</modifiable>
  </lock>
  <value class="boolean">true</value>
  <restore>false</restore>
</readNext>
<readViews>
  <lock>
    <itemLocked>false</itemLocked>
    <lockAvailable>false</lockAvailable>
    <modifiable>true</modifiable>
    <lockLevel>NONE</lockLevel>
    <lockRights>LOCK_USER</lockRights>
  </lock>
  <value>TEXT</value>
  <value>HTML</value>
</readViews>
<refreshInterval>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>false</itemLocked>
    <lockAvailable>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="AttrNoUsed">
    <minutes>1</minutes>
    <seconds>0</seconds>
  </value>
  <restore>false</restore>
</refreshInterval>
<remoteMode>
  <value class="boolean">true</value>
  <restore>false</restore>
</remoteMode>
<requirePassword>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>false</itemLocked>
    <lockAvailable>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="boolean">false</value>
  <restore>false</restore>
</requirePassword>
<ruleReplyAll>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>false</itemLocked>
    <lockAvailable>false</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="boolean">false</value>
  <restore>false</restore>

```

```

</ruleReplyAll>
<ruleReplyLoop>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>false</value>
  <restore>>false</restore>
</ruleReplyLoop>
<sendExpireDays>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="long">0</value>
  <restore>>false</restore>
</sendExpireDays>
<sendIllegalExtensions>
  <value class="string"></value>
  <restore>>false</restore>
</sendIllegalExtensions>
<sendNotify>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>true</value>
  <restore>>false</restore>
</sendNotify>
<sendPriority>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="AttrNoUsed">STANDARD</value>
  <restore>>false</restore>
</sendPriority>
<sendRecipientLimit>
  <value class="long">0</value>
  <restore>>false</restore>
</sendRecipientLimit>
<sendReplyRequested>
  <lock>

```

```

        <lockLevel>NONE</lockLevel>
        <itemLocked>>false</itemLocked>
        <lockAvailable>>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>>true</modifiable>
    </lock>
    <value class="long">255</value>
    <restore>>false</restore>
</sendReplyRequested>
<sharedAddressBook>
    <lock>
        <lockLevel>NONE</lockLevel>
        <itemLocked>>false</itemLocked>
        <lockAvailable>>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>>true</modifiable>
    </lock>
    <value class="boolean">>true</value>
    <restore>>false</restore>
</sharedAddressBook>
<sharedFolder>
    <lock>
        <lockLevel>NONE</lockLevel>
        <itemLocked>>false</itemLocked>
        <lockAvailable>>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>>true</modifiable>
    </lock>
    <value class="boolean">>true</value>
    <restore>>false</restore>
</sharedFolder>
<showMessengerPresence>
    <lock>
        <lockLevel>NONE</lockLevel>
        <itemLocked>>false</itemLocked>
        <lockAvailable>>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>>true</modifiable>
    </lock>
    <value class="boolean">>true</value>
    <restore>>false</restore>
</showMessengerPresence>
<signDigitally>
    <lock>
        <lockLevel>NONE</lockLevel>
        <itemLocked>>false</itemLocked>
        <lockAvailable>>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>>true</modifiable>
    </lock>
    <value class="boolean">>false</value>
    <restore>>false</restore>
</signDigitally>
<singleSignon>
    <value class="boolean">>true</value>

```



```

    <restore>false</restore>
</singleSignon>
<subscribeCalendar>
  <lock>
    <lockLevel>SET_DOMAIN</lockLevel>
    <itemLocked>false</itemLocked>
    <lockAvailable>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="boolean">true</value>
  <restore>false</restore>
</subscribeCalendar>
<taskAcceptedNotification>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>false</itemLocked>
    <lockAvailable>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="AttrNoUsed">NONE</value>
  <restore>false</restore>
</taskAcceptedNotification>
<taskCompletedNotification>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>false</itemLocked>
    <lockAvailable>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="AttrNoUsed">NONE</value>
  <restore>false</restore>
</taskCompletedNotification>
<taskDeletedNotification>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>false</itemLocked>
    <lockAvailable>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="AttrNoUsed">NONE</value>
  <restore>false</restore>
</taskDeletedNotification>
<taskOpenedNotification>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>false</itemLocked>
    <lockAvailable>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="AttrNoUsed">NONE</value>

```

```

    <restore>>false</restore>
</taskOpenedNotification>
<taskTrackingAction>
  <value class="AttrNoUsed">ALL_INFORMATION</value>
  <restore>>false</restore>
</taskTrackingAction>
<trashCleanupAction>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="AttrNoUsed">AUTO_PURGE</value>
  <restore>>false</restore>
</trashCleanupAction>
<trashCleanupDays>
  <value class="long">7</value>
  <restore>>false</restore>
</trashCleanupDays>
<treatImapLikeGW>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>false</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <restore>>false</restore>
</treatImapLikeGW>
<tutorialUrl>
  <value class="string"></value>
  <restore>>false</restore>
</tutorialUrl>
<useBlockMailList>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>false</value>
  <restore>>false</restore>
</useBlockMailList>
<useColorSchemes>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>true</value>

```

```

    <restore>>false</restore>
  </useColorSchemes>
  <useJunkMailList>
    <lock>
      <lockLevel>NONE</lockLevel>
      <itemLocked>>false</itemLocked>
      <lockAvailable>>true</lockAvailable>
      <lockRights>LOCK_USER</lockRights>
      <modifiable>>true</modifiable>
    </lock>
    <value class="boolean">>false</value>
    <restore>>false</restore>
  </useJunkMailList>
  <useNntpAccounts>
    <lock>
      <lockLevel>NONE</lockLevel>
      <itemLocked>>false</itemLocked>
      <lockAvailable>>false</lockAvailable>
      <lockRights>LOCK_USER</lockRights>
      <modifiable>>true</modifiable>
    </lock>
    <value class="boolean">>false</value>
    <restore>>false</restore>
  </useNntpAccounts>
  <usePersonalAddressBook>
    <lock>
      <lockLevel>NONE</lockLevel>
      <itemLocked>>false</itemLocked>
      <lockAvailable>>true</lockAvailable>
      <lockRights>LOCK_USER</lockRights>
      <modifiable>>true</modifiable>
    </lock>
    <value class="boolean">>false</value>
    <restore>>false</restore>
  </usePersonalAddressBook>
  <usePersonalAddressBookForCalendar>
    <lock>
      <lockLevel>NONE</lockLevel>
      <itemLocked>>false</itemLocked>
      <lockAvailable>>true</lockAvailable>
      <lockRights>LOCK_USER</lockRights>
      <modifiable>>true</modifiable>
    </lock>
    <value class="boolean">>false</value>
    <restore>>false</restore>
  </usePersonalAddressBookForCalendar>
  <usePopImapAccounts>
    <lock>
      <lockLevel>NONE</lockLevel>
      <itemLocked>>false</itemLocked>
      <lockAvailable>>false</lockAvailable>
      <lockRights>LOCK_USER</lockRights>
      <modifiable>>true</modifiable>
    </lock>
    <value class="boolean">>false</value>

```

```

    <restore>>false</restore>
</usePopImapAccounts>
<userLimits>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>false</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>false</value>
</restore>false</restore>
</userLimits>
<useSmime>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>false</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>true</value>
</restore>false</restore>
</useSmime>
<vibeEnabled>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>false</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>false</value>
</restore>false</restore>
</vibeEnabled>
<vibeUrl>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="string"></value>

```

```

    <restore>false</restore>
  </vibeUrl>
  <wildcardAddressing>
    <lock>
      <lockLevel>NONE</lockLevel>
      <itemLocked>false</itemLocked>
      <lockAvailable>true</lockAvailable>
      <lockRights>LOCK_USER</lockRights>
      <modifiable>true</modifiable>
    </lock>
    <value class="AttrNoUsed">LIMITED_TO_POST_OFFICE</value>
  </wildcardAddressing>
</clientOptions>

```

## Updating the Client Options of a User

JSON Request:

```

PUT https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/
testPO1/users/testUser1/clientoptions
  trashCleanupDays={value=7, restore=false}
  sendReplyRequested={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=255,
restore=false}
  readViews={lock={lockLevel=NONE, itemLocked=false, lockAvailable=false,
lockRights=LOCK_USER, modifiable=true}, value=[TEXT, HTML], restore=false}
  appointmentDefaultLength={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true},
value={hours=1, minutes=0, timeInMinutes=60}, restore=false}
  taskDeletedNotification={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=NONE,
restore=false}
  junkMailCleanupAction={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true},
value=AUTO_PURGE, restore=false}
  publishFreeBusySearch={lock={lockLevel=LOCK_USER, itemLocked=true,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=false,
restore=false}
  cachingMode={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=false, lockRights=LOCK_USER, modifiable=true}, value=ALLOW,
restore=false}
  concealSubject={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=false,
restore=false}
  checkSpellingAsYouType={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=true,
restore=false}
  cachingGraceDays={value=14, restore=false}
  boxSizeWarningThreshold={value=0, restore=false}
  sharedFolder={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=true,
restore=false}
  messageRetention={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=false, lockRights=LOCK_USER, modifiable=true}, value=false,

```

```

restore=false}
  displayMainToolBar={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=true,
restore=false}
  autoUpdateUrl={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=false, lockRights=LOCK_USER, modifiable=true}, value=,
restore=false}
  plainTextReplyFormatIncludeID={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=true,
restore=false}
  appointmentIncludeSelf={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=true,
restore=false}
  boxThresholdNotify={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=false, lockRights=LOCK_USER, modifiable=true}, value=false,
restore=false}
  defaultComposeView={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=HTML,
restore=false}
  showMessengerPresence={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=true,
restore=false}
  plainTextReplyFormatIncludeDate={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=true,
restore=false}
  htmlreplyFormatIncludeID={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=true,
restore=false}
  usePersonalAddressBookForCalendar={lock={lockLevel=NONE,
itemLocked=false, lockAvailable=true, lockRights=LOCK_USER,
modifiable=true}, value=false, restore=false}
  vibeUrl={lock={lockLevel=SET_USER, itemLocked=false, lockAvailable=true,
lockRights=LOCK_USER, modifiable=true}, value=https://vibe.novell.com,
restore=false}
  plainTextReplyFormatIncludeName={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=true,
restore=false}
  promptBeforePurge={value=false, restore=false}
  archiveLocationUnc={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=,
restore=false}
  useBlockMailList={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=false,
restore=false}
  HTMLReplyFormatIncludeSeparator={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=true,
restore=false}
  frequentContacts={value=[SEND_SAVE_INT, RECV_SAVE_INT, RECV_SAVE_EXT,
SEND_SAVE_EXT, RECV_SAVE_TO_ME, AUTO_SAVE], restore=false}
  collaborationSingleSignon={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=false,
restore=false}
  alarmDefaultTime={value={hours=1, minutes=0, timeInMinutes=60},
restore=false}
  htmlreplyFormatIncludeAddress={lock={lockLevel=NONE, itemLocked=false,

```

```

lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=false,
restore=false}
  useSmime={lock={lockLevel=NONE, itemLocked=false, lockAvailable=false,
lockRights=LOCK_USER, modifiable=true}, value=true, restore=false}
  plainTextReplyFormatIncludeSeparator={lock={lockLevel=NONE,
itemLocked=false, lockAvailable=true, lockRights=LOCK_USER,
modifiable=true}, value=true, restore=false}
  sendPriority={lock={lockLevel=SET_USER, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=HIGH,
restore=false}
  plainTextReplyFormat={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true},
value=GROUPWISE_CLASSIC, restore=false}
  edirectoryAuthentication={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=false,
restore=false}
  noteAcceptedNotification={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=NONE,
restore=false}
  personalAddressBookUserDefinedFields={value=true, restore=false}
  appointmentCleanupDays={value=14, restore=false}
  calendarFirstOfWeek={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=SUNDAY,
restore=false}
  busySearchFromTime={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true},
value={hours=8, minutes=0, timeInMinutes=480}, restore=false}
  plainTextReplyFormatTypePosition={lock={lockLevel=NONE,
itemLocked=false, lockAvailable=true, lockRights=LOCK_USER,
modifiable=true}, value=TOP, restore=false}
  noteDeletedNotification={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=NONE,
restore=false}
  calendarWorkdays={lock={lockLevel=SET_USER, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true},
value=[THURSDAY, MONDAY, TUESDAY, WEDNESDAY], restore=false}
  mailDeletedNotification={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=NONE,
restore=false}
  noteOpenedNotification={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=NONE,
restore=false}
  plainTextReplyFormatSeparatorChar={lock={lockLevel=NONE,
itemLocked=false, lockAvailable=true, lockRights=LOCK_USER,
modifiable=true}, value=>, restore=false}
  sendNotify={lock={lockLevel=NONE, itemLocked=false, lockAvailable=true,
lockRights=LOCK_USER, modifiable=true}, value=true, restore=false}
  refreshInterval={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true},
value={minutes=1, seconds=0, timeInSeconds=60}, restore=false}
  plainTextReplyFormatIncludeAddress={lock={lockLevel=NONE,
itemLocked=false, lockAvailable=true, lockRights=LOCK_USER,
modifiable=true}, value=false, restore=false}
  appointmentAcceptedNotification={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=NONE,

```

```

restore=false}
  moveToPublishedCalendar={lock={lockLevel=SET_DOMAIN, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=true,
restore=false}
  userLimits={lock={lockLevel=NONE, itemLocked=false, lockAvailable=false,
lockRights=LOCK_USER, modifiable=true}, value=false, restore=false}
  useJunkMailList={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=false,
restore=false}
  encryptionAlgorithm={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=NONE,
restore=false}
  publishingHost={lock={lockLevel=SET_DOMAIN, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true},
value=testCalPubHost1, restore=false}
  limitsApplyToCache={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=false, lockRights=LOCK_USER, modifiable=true}, value=false,
restore=false}
  htmlreplyFormatTypePosition={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=TOP,
restore=false}
  usePopImapAccounts={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=false, lockRights=LOCK_USER, modifiable=true}, value=false,
restore=false}
  delayDelivery={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=-1,
restore=false}
  vibeEnabled={lock={lockLevel=SET_USER, itemLocked=false,
lockAvailable=false, lockRights=LOCK_USER, modifiable=true}, value=true,
restore=false}
  mailOpenedNotification={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=NONE,
restore=false}
  composeViews={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=false, lockRights=LOCK_USER, modifiable=true}, value=[TEXT,
HTML], restore=false}
  busySearchToTime={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true},
value={hours=17, minutes=0, timeInMinutes=1020}, restore=false}
  globalSignatureApplication={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true},
value=EXTERNAL_MESSAGES, restore=false}
  ruleReplyLoop={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=false,
restore=false}
  boxSizeLimit={value=0, restore=false}
  taskOpenedNotification={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=NONE,
restore=false}
  mailTrackingAction={value=DELIVERED_OPENED, restore=false}
  customViewsLocationUnc={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=,
restore=false}
  HTMLReplyFormatIncludeHeaders={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=false,

```



```

restore=false}
  HTMLReplyFormatIncludeDate={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=true,
restore=false}
  junkMailCleanupDays={value=14, restore=false}
  displayMainMenu={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=true,
restore=false}
  sendRecipientLimit={value=0, restore=false}
  appointmentCleanupAction={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true},
value=MANUAL_DELETE_ARCHIVE, restore=false}
  useNntpAccounts={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=false, lockRights=LOCK_USER, modifiable=true}, value=false,
restore=false}
  handleJunkMail={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=false, lockRights=LOCK_USER, modifiable=true}, value=true,
restore=false}
  globalSignatureName={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=<Default
Global Signature>, restore=false}
  displayNavBar={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=true,
restore=false}
  taskAcceptedNotification={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=NONE,
restore=false}
  certificateDownloadUrl={value=, restore=false}
  classification={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=NORMAL,
restore=false}
  sendExpireDays={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=0,
restore=false}
  encryptionKeySize={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=NONE,
restore=false}
  trashCleanupAction={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true},
value=AUTO_PURGE, restore=false}
  HTMLReplyFormatIncludeName={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=true,
restore=false}
  autoUpdateForce={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=false, lockRights=LOCK_USER, modifiable=true}, value=false,
restore=false}
  sharedAddressBook={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=true,
restore=false}
  calendarStartTime={lock={lockLevel=SET_USER, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true},
value={hours=7, minutes=30, timeInMinutes=450}, restore=false}
  displayFolderList={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=true,
restore=false}

```

```

mailCleanupDays={value=30, restore=false}
HTMLReplyFormat={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true},
value=GROUPWISE_CLASSIC, restore=false}
folderListViewType={value=[FAVORITES, SIMPLE, FULL], restore=false}
tutorialUrl={value=, restore=false}
subscribeCalendar={lock={lockLevel=SET_DOMAIN, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=true,
restore=false}
maxMessageSize={value=0, restore=false}
appointmentDisplayMode={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true},
value=DURATION, restore=false}
appointmentTrackingAction={value=ALL_INFORMATION, restore=false}
performMaintenancePurges={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=false,
restore=false}
notifyPollInterval={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true},
value={minutes=1, seconds=0, timeInSeconds=60}, restore=false}
ruleReplyAll={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=false, lockRights=LOCK_USER, modifiable=true}, value=false,
restore=false}
checkSpelling={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=false,
restore=false}
taskCompletedNotification={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=NONE,
restore=false}
requirePassword={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=false,
restore=false}
globalSignatureList={value=[Novell_Global_Signature], restore=false}
defaultLibrary={value=, restore=false}
openNewView={lock={lockLevel=NONE, itemLocked=false, lockAvailable=true,
lockRights=LOCK_USER, modifiable=true}, value=false, restore=false}
quickViewerPosition={value=BOTTOM, restore=false}
forceCacheCleanup={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=false,
restore=false}
autoUpdateGraceLogins={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=false, lockRights=LOCK_USER, modifiable=true}, value=0,
restore=false}
HTMLReplyFormatIncludeID={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=true,
restore=false}
busySearchDays={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true},
value=[THURSDAY, FRIDAY, MONDAY, TUESDAY, WEDNESDAY], restore=false}
treatImapLikeGW={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=false, lockRights=LOCK_USER, modifiable=true}, value=null,
restore=false}
htmlreplyFormatIncludeName={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=true,
restore=false}

```

```

    busySearchRange={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=7,
restore=false}
    busySearchAppointmentLength={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true},
value={hours=0, minutes=15, timeInMinutes=15}, restore=false}
    calendarEndTime={lock={lockLevel=SET_USER, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true},
value={hours=18, minutes=30, timeInMinutes=1110}, restore=false}
    boxSizeNotify={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=false, lockRights=LOCK_USER, modifiable=true}, value=false,
restore=false}
    publishCalendar={lock={lockLevel=SET_DOMAIN, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=true,
restore=false}
    htmlreplyFormatIncludeHeaders={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=false,
restore=false}
    sendIllegalExtensions={value=, restore=false}
    createTrackingItem={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=true,
restore=false}
    internetMailTracking={value=true, restore=false}
    signDigitally={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=false,
restore=false}
    alarmWhenAccepted={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=true,
restore=false}
    calendarShowWeekNumber={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=false,
restore=false}
    htmlreplyFormatIncludeSeparator={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=true,
restore=false}
    convertAttachments={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=false,
restore=false}
    HTMLReplyFormatTypePosition={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=TOP,
restore=false}
    autoDeleteSentMail={value=false, restore=false}
    doNotPurgeBeforeBackup={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=false,
restore=false}
    htmlreplyFormatIncludeDate={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=true,
restore=false}
    mimeEncoding={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=UTF8,
restore=false}
    archiveLocationLinux={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=,
restore=false}
    mailCleanupAction={lock={lockLevel=NONE, itemLocked=false,

```

```

lockAvailable=true, lockRights=LOCK_USER, modifiable=true},
value=MANUAL_DELETE_ARCHIVE, restore=false}
  noteTrackingAction={value=DELIVERED_OPENED, restore=false}
  disableHTMLView={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=false,
restore=false}
  useColorSchemes={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=true,
restore=false}
  colorScheme={value=SKY_BLUE, restore=false}
  htmlreplyFormat={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true},
value=GROUPWISE_CLASSIC, restore=false}
  singleSignon={value=true, restore=false}
  wildcardAddressing={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true},
value=LIMITED_TO_POST_OFFICE, restore=false}
  remoteMode={value=true, restore=false}
  displayQuickViewer={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=false,
restore=false}
  usePersonalAddressBook={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=false,
restore=false}
  clientLicense={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=FULL,
restore=false}
  readNext={lock={lockLevel=NONE, itemLocked=false, lockAvailable=true,
lockRights=LOCK_USER, modifiable=true}, value=true, restore=false}
  taskTrackingAction={value=ALL_INFORMATION, restore=false}
  calendarHighlightDays={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=[SUNDAY,
SATURDAY], restore=false}
  autoUpdateEnabled={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=false, lockRights=LOCK_USER, modifiable=true}, value=true,
restore=false}
  autoUpdateAlwaysPrompt={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=false, lockRights=LOCK_USER, modifiable=true}, value=false,
restore=false}
  defaultReadView={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=HTML,
restore=false}
  appointmentDeletedNotification={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=NONE,
restore=false}
  encryptForRecipients={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=false,
restore=false}
  HTMLReplyFormatIncludeAddress={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=false,
restore=false}
  appointmentOpenedNotification={lock={lockLevel=NONE, itemLocked=false,
lockAvailable=true, lockRights=LOCK_USER, modifiable=true}, value=NONE,
restore=false}

```

XML Request:

PUT https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/  
testPO1/users/testUser1/clientoptions

```
<clientOptions>
  <forceNullOnAttrs/>
  <alarmDefaultTime>
    <value class="AttrNoUsed">
      <hours>1</hours>
      <minutes>0</minutes>
    </value>
    <restore>>false</restore>
  </alarmDefaultTime>
  <alarmWhenAccepted>
    <lock>
      <lockLevel>NONE</lockLevel>
      <itemLocked>>false</itemLocked>
      <lockAvailable>>true</lockAvailable>
      <lockRights>LOCK_USER</lockRights>
      <modifiable>>true</modifiable>
    </lock>
    <value class="boolean">>true</value>
    <restore>>false</restore>
  </alarmWhenAccepted>
  <appointmentAcceptedNotification>
    <lock>
      <lockLevel>NONE</lockLevel>
      <itemLocked>>false</itemLocked>
      <lockAvailable>>true</lockAvailable>
      <lockRights>LOCK_USER</lockRights>
      <modifiable>>true</modifiable>
    </lock>
    <value class="AttrNoUsed">NONE</value>
    <restore>>false</restore>
  </appointmentAcceptedNotification>
  <appointmentCleanupAction>
    <lock>
      <lockLevel>NONE</lockLevel>
      <itemLocked>>false</itemLocked>
      <lockAvailable>>true</lockAvailable>
      <lockRights>LOCK_USER</lockRights>
      <modifiable>>true</modifiable>
    </lock>
    <value class="AttrNoUsed">MANUAL_DELETE_ARCHIVE</value>
    <restore>>false</restore>
  </appointmentCleanupAction>
  <appointmentCleanupDays>
    <value class="long">14</value>
    <restore>>false</restore>
  </appointmentCleanupDays>
  <appointmentDefaultLength>
    <lock>
      <lockLevel>NONE</lockLevel>
      <itemLocked>>false</itemLocked>
      <lockAvailable>>true</lockAvailable>
      <lockRights>LOCK_USER</lockRights>
```

```

        <modifiable>true</modifiable>
    </lock>
    <value class="AttrNoUsed">
        <hours>1</hours>
        <minutes>0</minutes>
    </value>
    <restore>false</restore>
</appointmentDefaultLength>
<appointmentDeletedNotification>
    <lock>
        <lockLevel>NONE</lockLevel>
        <itemLocked>false</itemLocked>
        <lockAvailable>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>true</modifiable>
    </lock>
    <value class="AttrNoUsed">NONE</value>
    <restore>false</restore>
</appointmentDeletedNotification>
<appointmentDisplayMode>
    <lock>
        <lockLevel>NONE</lockLevel>
        <itemLocked>false</itemLocked>
        <lockAvailable>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>true</modifiable>
    </lock>
    <value class="AttrNoUsed">DURATION</value>
    <restore>false</restore>
</appointmentDisplayMode>
<appointmentIncludeSelf>
    <lock>
        <lockLevel>NONE</lockLevel>
        <itemLocked>false</itemLocked>
        <lockAvailable>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>true</modifiable>
    </lock>
    <value class="boolean">true</value>
    <restore>false</restore>
</appointmentIncludeSelf>
<appointmentOpenedNotification>
    <lock>
        <lockLevel>NONE</lockLevel>
        <itemLocked>false</itemLocked>
        <lockAvailable>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>true</modifiable>
    </lock>
    <value class="AttrNoUsed">NONE</value>
    <restore>false</restore>
</appointmentOpenedNotification>
<appointmentTrackingAction>
    <value class="AttrNoUsed">ALL_INFORMATION</value>
    <restore>false</restore>

```

```

</appointmentTrackingAction>
<archiveLocationLinux>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="string"></value>
  <restore>>false</restore>
</archiveLocationLinux>
<archiveLocationUnc>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="string"></value>
  <restore>>false</restore>
</archiveLocationUnc>
<autoDeleteSentMail>
  <value class="boolean">>false</value>
  <restore>>false</restore>
</autoDeleteSentMail>
<autoUpdateUrl>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>false</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="string"></value>
  <restore>>false</restore>
</autoUpdateUrl>
<autoUpdateEnabled>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>false</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>true</value>
  <restore>>false</restore>
</autoUpdateEnabled>
<autoUpdateForce>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>false</lockAvailable>
    <lockRights>LOCK_USER</lockRights>

```

```

    <modifiable>true</modifiable>
  </lock>
  <value class="boolean">>false</value>
  <restore>>false</restore>
</autoUpdateForce>
<autoUpdateGraceLogins>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>false</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="long">0</value>
  <restore>>false</restore>
</autoUpdateGraceLogins>
<autoUpdateAlwaysPrompt>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>false</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="boolean">>false</value>
  <restore>>false</restore>
</autoUpdateAlwaysPrompt>
<boxSizeLimit>
  <value class="long">0</value>
  <restore>>false</restore>
</boxSizeLimit>
<boxSizeNotify>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>false</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="boolean">>false</value>
  <restore>>false</restore>
</boxSizeNotify>
<boxSizeWarningThreshold>
  <value class="long">0</value>
  <restore>>false</restore>
</boxSizeWarningThreshold>
<boxThresholdNotify>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>false</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="boolean">>false</value>

```



```

    <restore>>false</restore>
</boxThresholdNotify>
<busySearchAppointmentLength>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="AttrNoUsed">
    <hours>0</hours>
    <minutes>15</minutes>
  </value>
  <restore>>false</restore>
</busySearchAppointmentLength>
<busySearchDays>
  <lock>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <modifiable>>true</modifiable>
    <lockLevel>NONE</lockLevel>
    <lockRights>LOCK_USER</lockRights>
  </lock>
  <value>WEDNESDAY</value>
  <value>TUESDAY</value>
  <value>MONDAY</value>
  <value>THURSDAY</value>
  <value>FRIDAY</value>
</busySearchDays>
<busySearchFromTime>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="AttrNoUsed">
    <hours>8</hours>
    <minutes>0</minutes>
  </value>
  <restore>>false</restore>
</busySearchFromTime>
<busySearchRange>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="long">7</value>
  <restore>>false</restore>
</busySearchRange>

```

```

<busySearchToTime>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="AttrNoUsed">
    <hours>17</hours>
    <minutes>0</minutes>
  </value>
  <restore>>false</restore>
</busySearchToTime>
<cachingGraceDays>
  <value class="long">14</value>
  <restore>>false</restore>
</cachingGraceDays>
<cachingMode>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>false</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="AttrNoUsed">ALLOW</value>
  <restore>>false</restore>
</cachingMode>
<calendarEndTime>
  <lock>
    <lockLevel>SET_USER</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="AttrNoUsed">
    <hours>18</hours>
    <minutes>30</minutes>
  </value>
  <restore>>false</restore>
</calendarEndTime>
<calendarFirstOfWeek>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="AttrNoUsed">SUNDAY</value>
  <restore>>false</restore>
</calendarFirstOfWeek>
<calendarHighlightDays>

```

```

<lock>
  <itemLocked>>false</itemLocked>
  <lockAvailable>>true</lockAvailable>
  <modifiable>>true</modifiable>
  <lockLevel>NONE</lockLevel>
  <lockRights>LOCK_USER</lockRights>
</lock>
<value>SATURDAY</value>
<value>SUNDAY</value>
</calendarHighlightDays>
<calendarShowWeekNumber>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>false</value>
  <restore>>false</restore>
</calendarShowWeekNumber>
<calendarStartTime>
  <lock>
    <lockLevel>SET_USER</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="AttrNoUsed">
    <hours>7</hours>
    <minutes>30</minutes>
  </value>
  <restore>>false</restore>
</calendarStartTime>
<calendarWorkdays>
  <lock>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <modifiable>>true</modifiable>
    <lockLevel>SET_USER</lockLevel>
    <lockRights>LOCK_USER</lockRights>
  </lock>
  <value>WEDNESDAY</value>
  <value>TUESDAY</value>
  <value>MONDAY</value>
  <value>THURSDAY</value>
</calendarWorkdays>
<certificateDownloadUrl>
  <value class="string"></value>
  <restore>>false</restore>
</certificateDownloadUrl>
<checkSpelling>
  <lock>
    <lockLevel>NONE</lockLevel>

```

```

        <itemLocked>>false</itemLocked>
        <lockAvailable>>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>>true</modifiable>
    </lock>
    <value class="boolean">>false</value>
    <restore>>false</restore>
</checkSpelling>
<checkSpellingAsYouType>
    <lock>
        <lockLevel>NONE</lockLevel>
        <itemLocked>>false</itemLocked>
        <lockAvailable>>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>>true</modifiable>
    </lock>
    <value class="boolean">>true</value>
    <restore>>false</restore>
</checkSpellingAsYouType>
<classification>
    <lock>
        <lockLevel>NONE</lockLevel>
        <itemLocked>>false</itemLocked>
        <lockAvailable>>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>>true</modifiable>
    </lock>
    <value class="AttrNoUsed">NORMAL</value>
    <restore>>false</restore>
</classification>
<clientLicense>
    <lock>
        <lockLevel>NONE</lockLevel>
        <itemLocked>>false</itemLocked>
        <lockAvailable>>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>>true</modifiable>
    </lock>
    <value class="AttrNoUsed">FULL</value>
    <restore>>false</restore>
</clientLicense>
<collaborationSingleSignon>
    <lock>
        <lockLevel>NONE</lockLevel>
        <itemLocked>>false</itemLocked>
        <lockAvailable>>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>>true</modifiable>
    </lock>
    <value class="boolean">>false</value>
    <restore>>false</restore>
</collaborationSingleSignon>
<colorScheme>
    <value class="AttrNoUsed">SKY_BLUE</value>
    <restore>>false</restore>

```

```

</colorScheme>
<composeViews>
  <lock>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>false</lockAvailable>
    <modifiable>>true</modifiable>
    <lockLevel>NONE</lockLevel>
    <lockRights>LOCK_USER</lockRights>
  </lock>
  <value>TEXT</value>
  <value>HTML</value>
</composeViews>
<concealSubject>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>false</value>
  <restore>>false</restore>
</concealSubject>
<convertAttachments>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>false</value>
  <restore>>false</restore>
</convertAttachments>
<createTrackingItem>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>true</value>
  <restore>>false</restore>
</createTrackingItem>
<customViewsLocationUnc>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="string"></value>
  <restore>>false</restore>

```

```

</customViewsLocationUnc>
<defaultComposeView>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="AttrNoUsed">HTML</value>
  <restore>>false</restore>
</defaultComposeView>
<defaultLibrary>
  <value class="string"></value>
  <restore>>false</restore>
</defaultLibrary>
<defaultReadView>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="AttrNoUsed">HTML</value>
  <restore>>false</restore>
</defaultReadView>
<delayDelivery>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="long">-1</value>
  <restore>>false</restore>
</delayDelivery>
<disableHTMLView>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>false</value>
  <restore>>false</restore>
</disableHTMLView>
<displayFolderList>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>

```

```

    <modifiable>true</modifiable>
  </lock>
  <value class="boolean">true</value>
  <restore>false</restore>
</displayFolderList>
<displayMainMenu>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>false</itemLocked>
    <lockAvailable>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="boolean">true</value>
  <restore>false</restore>
</displayMainMenu>
<displayMainToolBar>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>false</itemLocked>
    <lockAvailable>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="boolean">true</value>
  <restore>false</restore>
</displayMainToolBar>
<displayNavBar>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>false</itemLocked>
    <lockAvailable>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="boolean">true</value>
  <restore>false</restore>
</displayNavBar>
<displayQuickViewer>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>false</itemLocked>
    <lockAvailable>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="boolean">false</value>
  <restore>false</restore>
</displayQuickViewer>
<doNotPurgeBeforeBackup>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>false</itemLocked>
    <lockAvailable>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>

```

```

    <modifiable>true</modifiable>
  </lock>
  <value class="boolean">>false</value>
  <restore>>false</restore>
</doNotPurgeBeforeBackup>
<edirectoryAuthentication>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="boolean">>false</value>
  <restore>>false</restore>
</edirectoryAuthentication>
<encryptForRecipients>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="boolean">>false</value>
  <restore>>false</restore>
</encryptForRecipients>
<encryptionAlgorithm>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="AttrNoUsed">NONE</value>
  <restore>>false</restore>
</encryptionAlgorithm>
<encryptionKeySize>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="AttrNoUsed">NONE</value>
  <restore>>false</restore>
</encryptionKeySize>
<forceCacheCleanup>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>

```



```

    <modifiable>true</modifiable>
  </lock>
  <value class="boolean">>false</value>
  <restore>>false</restore>
</forceCacheCleanup>
<frequentContacts>
  <value>RECV_SAVE_TO_ME</value>
  <value>RECV_SAVE_INT</value>
  <value>RECV_SAVE_EXT</value>
  <value>SEND_SAVE_INT</value>
  <value>SEND_SAVE_EXT</value>
  <value>AUTO_SAVE</value>
</frequentContacts>
<folderListViewType>
  <value>FAVORITES</value>
  <value>SIMPLE</value>
  <value>FULL</value>
</folderListViewType>
<globalSignatureApplication>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="AttrNoUsed">EXTERNAL_MESSAGES</value>
  <restore>>false</restore>
</globalSignatureApplication>
<globalSignatureList>
  <value class="string-array">
    <string>Novell_Global_Signature</string>
  </value>
  <restore>>false</restore>
</globalSignatureList>
<globalSignatureName>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="string">&lt;Default Global Signature&gt;</value>
  <restore>>false</restore>
</globalSignatureName>
<handleJunkMail>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>false</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="boolean">>true</value>

```

```

    <restore>false</restore>
</handleJunkMail>
<internetMailTracking>
  <value class="boolean">true</value>
  <restore>false</restore>
</internetMailTracking>
<junkMailCleanupAction>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>false</itemLocked>
    <lockAvailable>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="AttrNoUsed">AUTO_PURGE</value>
  <restore>false</restore>
</junkMailCleanupAction>
<junkMailCleanupDays>
  <value class="long">14</value>
  <restore>false</restore>
</junkMailCleanupDays>
<limitsApplyToCache>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>false</itemLocked>
    <lockAvailable>false</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="boolean">false</value>
  <restore>false</restore>
</limitsApplyToCache>
<mailCleanupAction>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>false</itemLocked>
    <lockAvailable>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="AttrNoUsed">MANUAL_DELETE_ARCHIVE</value>
  <restore>false</restore>
</mailCleanupAction>
<mailCleanupDays>
  <value class="long">30</value>
  <restore>false</restore>
</mailCleanupDays>
<mailDeletedNotification>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>false</itemLocked>
    <lockAvailable>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>

```

```

    <value class="AttrNoUsed">NONE</value>
    <restore>>false</restore>
</mailDeletedNotification>
<mailOpenedNotification>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="AttrNoUsed">NONE</value>
  <restore>>false</restore>
</mailOpenedNotification>
<mailTrackingAction>
  <value class="AttrNoUsed">DELIVERED_OPENED</value>
  <restore>>false</restore>
</mailTrackingAction>
<maxMessageSize>
  <value class="long">0</value>
  <restore>>false</restore>
</maxMessageSize>
<messageRetention>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>false</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>false</value>
  <restore>>false</restore>
</messageRetention>
<mimeEncoding>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="AttrNoUsed">UTF8</value>
  <restore>>false</restore>
</mimeEncoding>
<moveToPublishedCalendar>
  <lock>
    <lockLevel>SET_DOMAIN</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>true</value>
  <restore>>false</restore>
</moveToPublishedCalendar>

```

```

<noteAcceptedNotification>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="AttrNoUsed">NONE</value>
  <restore>>false</restore>
</noteAcceptedNotification>
<noteDeletedNotification>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="AttrNoUsed">NONE</value>
  <restore>>false</restore>
</noteDeletedNotification>
<noteOpenedNotification>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="AttrNoUsed">NONE</value>
  <restore>>false</restore>
</noteOpenedNotification>
<noteTrackingAction>
  <value class="AttrNoUsed">DELIVERED_OPENED</value>
  <restore>>false</restore>
</noteTrackingAction>
<notifyPollInterval>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="AttrNoUsed">
    <minutes>1</minutes>
    <seconds>0</seconds>
  </value>
  <restore>>false</restore>
</notifyPollInterval>
<openNewView>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>

```

```

        <lockAvailable>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>true</modifiable>
    </lock>
    <value class="boolean">>false</value>
    <restore>false</restore>
</openNewView>
<performMaintenancePurges>
    <lock>
        <lockLevel>NONE</lockLevel>
        <itemLocked>>false</itemLocked>
        <lockAvailable>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>true</modifiable>
    </lock>
    <value class="boolean">>false</value>
    <restore>false</restore>
</performMaintenancePurges>
<personalAddressBookUserDefinedFields>
    <value class="boolean">>true</value>
    <restore>false</restore>
</personalAddressBookUserDefinedFields>
<promptBeforePurge>
    <value class="boolean">>false</value>
    <restore>false</restore>
</promptBeforePurge>
<publishCalendar>
    <lock>
        <lockLevel>SET_DOMAIN</lockLevel>
        <itemLocked>>false</itemLocked>
        <lockAvailable>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>true</modifiable>
    </lock>
    <value class="boolean">>true</value>
    <restore>false</restore>
</publishCalendar>
<publishFreeBusySearch>
    <lock>
        <lockLevel>LOCK_USER</lockLevel>
        <itemLocked>true</itemLocked>
        <lockAvailable>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>true</modifiable>
    </lock>
    <value class="boolean">>false</value>
    <restore>false</restore>
</publishFreeBusySearch>
<publishingHost>
    <lock>
        <lockLevel>SET_DOMAIN</lockLevel>
        <itemLocked>>false</itemLocked>
        <lockAvailable>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>true</modifiable>
    </lock>

```

```

</lock>
  <value class="string">testCalPubHost1</value>
  <restore>>false</restore>
</publishingHost>
<HTMLReplyFormat>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="AttrNoUsed">GROUPWISE_CLASSIC</value>
  <restore>>false</restore>
</HTMLReplyFormat>
<HTMLReplyFormatIncludeHeaders>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>false</value>
  <restore>>false</restore>
</HTMLReplyFormatIncludeHeaders>
<HTMLReplyFormatTypePosition>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="AttrNoUsed">TOP</value>
  <restore>>false</restore>
</HTMLReplyFormatTypePosition>
<HTMLReplyFormatIncludeDate>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>true</value>
  <restore>>false</restore>
</HTMLReplyFormatIncludeDate>
<HTMLReplyFormatIncludeID>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>

```

```

</lock>
  <value class="boolean">true</value>
  <restore>false</restore>
</HTMLReplyFormatIncludeID>
<HTMLReplyFormatIncludeName>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">true</value>
  <restore>false</restore>
</HTMLReplyFormatIncludeName>
<HTMLReplyFormatIncludeAddress>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>false</value>
  <restore>false</restore>
</HTMLReplyFormatIncludeAddress>
<HTMLReplyFormatIncludeSeparator>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">true</value>
  <restore>false</restore>
</HTMLReplyFormatIncludeSeparator>
<plainTextReplyFormat>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="AttrNoUsed">GROUPWISE_CLASSIC</value>
  <restore>false</restore>
</plainTextReplyFormat>
<plainTextReplyFormatSeparatorChar>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>

```

```

</lock>
  <value class="string">&gt;</value>
  <restore>>false</restore>
</plainTextReplyFormatSeparatorChar>
<plainTextReplyFormatTypePosition>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="AttrNoUsed">TOP</value>
  <restore>>false</restore>
</plainTextReplyFormatTypePosition>
<plainTextReplyFormatIncludeAddress>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>false</value>
  <restore>>false</restore>
</plainTextReplyFormatIncludeAddress>
<plainTextReplyFormatIncludeName>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>true</value>
  <restore>>false</restore>
</plainTextReplyFormatIncludeName>
<plainTextReplyFormatIncludeDate>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>true</value>
  <restore>>false</restore>
</plainTextReplyFormatIncludeDate>
<plainTextReplyFormatIncludeID>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>

```



```

</lock>
  <value class="boolean">true</value>
  <restore>false</restore>
</plainTextReplyFormatIncludeID>
<plainTextReplyFormatIncludeSeparator>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="boolean">true</value>
  <restore>false</restore>
</plainTextReplyFormatIncludeSeparator>
<quickViewerPosition>
  <value class="AttrNoUsed">BOTTOM</value>
  <restore>false</restore>
</quickViewerPosition>
<readNext>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="boolean">true</value>
  <restore>false</restore>
</readNext>
<readViews>
  <lock>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>false</lockAvailable>
    <modifiable>true</modifiable>
    <lockLevel>NONE</lockLevel>
    <lockRights>LOCK_USER</lockRights>
  </lock>
  <value>TEXT</value>
  <value>HTML</value>
</readViews>
<refreshInterval>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="AttrNoUsed">
    <minutes>1</minutes>
    <seconds>0</seconds>
  </value>
  <restore>false</restore>
</refreshInterval>

```

```

<remoteMode>
  <value class="boolean">true</value>
  <restore>false</restore>
</remoteMode>
<requirePassword>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>false</itemLocked>
    <lockAvailable>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="boolean">false</value>
  <restore>false</restore>
</requirePassword>
<ruleReplyAll>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>false</itemLocked>
    <lockAvailable>false</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="boolean">false</value>
  <restore>false</restore>
</ruleReplyAll>
<ruleReplyLoop>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>false</itemLocked>
    <lockAvailable>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="boolean">false</value>
  <restore>false</restore>
</ruleReplyLoop>
<sendExpireDays>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>false</itemLocked>
    <lockAvailable>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="long">0</value>
  <restore>false</restore>
</sendExpireDays>
<sendIllegalExtensions>
  <value class="string"></value>
  <restore>false</restore>
</sendIllegalExtensions>
<sendNotify>
  <lock>
    <lockLevel>NONE</lockLevel>

```

```

        <itemLocked>>false</itemLocked>
        <lockAvailable>>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>>true</modifiable>
    </lock>
    <value class="boolean">>true</value>
    <restore>>false</restore>
</sendNotify>
<sendPriority>
    <lock>
        <lockLevel>SET_USER</lockLevel>
        <itemLocked>>false</itemLocked>
        <lockAvailable>>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>>true</modifiable>
    </lock>
    <value class="AttrNoUsed">HIGH</value>
    <restore>>false</restore>
</sendPriority>
<sendRecipientLimit>
    <value class="long">0</value>
    <restore>>false</restore>
</sendRecipientLimit>
<sendReplyRequested>
    <lock>
        <lockLevel>NONE</lockLevel>
        <itemLocked>>false</itemLocked>
        <lockAvailable>>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>>true</modifiable>
    </lock>
    <value class="long">255</value>
    <restore>>false</restore>
</sendReplyRequested>
<sharedAddressBook>
    <lock>
        <lockLevel>NONE</lockLevel>
        <itemLocked>>false</itemLocked>
        <lockAvailable>>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>>true</modifiable>
    </lock>
    <value class="boolean">>true</value>
    <restore>>false</restore>
</sharedAddressBook>
<sharedFolder>
    <lock>
        <lockLevel>NONE</lockLevel>
        <itemLocked>>false</itemLocked>
        <lockAvailable>>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>>true</modifiable>
    </lock>
    <value class="boolean">>true</value>
    <restore>>false</restore>

```

```

</sharedFolder>
<showMessengerPresence>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>true</value>
  <restore>>false</restore>
</showMessengerPresence>
<signDigitally>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>false</value>
  <restore>>false</restore>
</signDigitally>
<singleSignon>
  <value class="boolean">>true</value>
  <restore>>false</restore>
</singleSignon>
<subscribeCalendar>
  <lock>
    <lockLevel>SET_DOMAIN</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="boolean">>true</value>
  <restore>>false</restore>
</subscribeCalendar>
<taskAcceptedNotification>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>>true</modifiable>
  </lock>
  <value class="AttrNoUsed">NONE</value>
  <restore>>false</restore>
</taskAcceptedNotification>
<taskCompletedNotification>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>

```

```

    <modifiable>true</modifiable>
  </lock>
  <value class="AttrNoUsed">NONE</value>
  <restore>false</restore>
</taskCompletedNotification>
<taskDeletedNotification>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>false</itemLocked>
    <lockAvailable>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="AttrNoUsed">NONE</value>
  <restore>false</restore>
</taskDeletedNotification>
<taskOpenedNotification>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>false</itemLocked>
    <lockAvailable>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="AttrNoUsed">NONE</value>
  <restore>false</restore>
</taskOpenedNotification>
<taskTrackingAction>
  <value class="AttrNoUsed">ALL_INFORMATION</value>
  <restore>false</restore>
</taskTrackingAction>
<trashCleanupAction>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>false</itemLocked>
    <lockAvailable>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="AttrNoUsed">AUTO_PURGE</value>
  <restore>false</restore>
</trashCleanupAction>
<trashCleanupDays>
  <value class="long">7</value>
  <restore>false</restore>
</trashCleanupDays>
<treatingLikeGmail>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>false</itemLocked>
    <lockAvailable>false</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <restore>false</restore>

```

```

</treatImapLikeGW>
<tutorialUrl>
  <value class="string"></value>
  <restore>false</restore>
</tutorialUrl>
<useBlockMailList>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>false</itemLocked>
    <lockAvailable>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="boolean">false</value>
  <restore>false</restore>
</useBlockMailList>
<useColorSchemes>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>false</itemLocked>
    <lockAvailable>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="boolean">true</value>
  <restore>false</restore>
</useColorSchemes>
<useJunkMailList>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>false</itemLocked>
    <lockAvailable>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="boolean">false</value>
  <restore>false</restore>
</useJunkMailList>
<useNntpAccounts>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>false</itemLocked>
    <lockAvailable>false</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="boolean">false</value>
  <restore>false</restore>
</useNntpAccounts>
<usePersonalAddressBook>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>false</itemLocked>
    <lockAvailable>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>

```

```

    <modifiable>true</modifiable>
  </lock>
  <value class="boolean">>false</value>
  <restore>>false</restore>
</usePersonalAddressBook>
<usePersonalAddressBookForCalendar>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>true</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="boolean">>false</value>
  <restore>>false</restore>
</usePersonalAddressBookForCalendar>
<usePopImapAccounts>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>false</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="boolean">>false</value>
  <restore>>false</restore>
</usePopImapAccounts>
<userLimits>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>false</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="boolean">>false</value>
  <restore>>false</restore>
</userLimits>
<useSmime>
  <lock>
    <lockLevel>NONE</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>false</lockAvailable>
    <lockRights>LOCK_USER</lockRights>
    <modifiable>true</modifiable>
  </lock>
  <value class="boolean">>true</value>
  <restore>>false</restore>
</useSmime>
<vibeEnabled>
  <lock>
    <lockLevel>SET_USER</lockLevel>
    <itemLocked>>false</itemLocked>
    <lockAvailable>>false</lockAvailable>
    <lockRights>LOCK_USER</lockRights>

```

```

        <modifiable>true</modifiable>
    </lock>
    <value class="boolean">true</value>
    <restore>false</restore>
</vibeEnabled>
<vibeUrl>
    <lock>
        <lockLevel>SET_USER</lockLevel>
        <itemLocked>false</itemLocked>
        <lockAvailable>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>true</modifiable>
    </lock>
    <value class="string">https://vibe.novell.com</value>
    <restore>false</restore>
</vibeUrl>
<wildcardAddressing>
    <lock>
        <lockLevel>NONE</lockLevel>
        <itemLocked>false</itemLocked>
        <lockAvailable>true</lockAvailable>
        <lockRights>LOCK_USER</lockRights>
        <modifiable>true</modifiable>
    </lock>
    <value class="AttrNoUsed">LIMITED_TO_POST_OFFICE</value>
    <restore>false</restore>
</wildcardAddressing>
</clientOptions>

```

Response Status:  
200 - OK

## Setting the GroupWise Password of a User

JSON Request:  
PUT https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/  
testPO1/users/testUser1/clientoptions  
userPassword={value=novell2012, restore=false}

XML Request:  
PUT https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/  
testPO1/users/testUser1/clientoptions  
<clientOptions>  
 <forceNullOnAttrs/>  
 <userPassword>  
 <value class="string">novell2012</value>  
 <restore>false</restore>  
 </userPassword>  
</clientOptions>

Response Status:  
200 - OK



## Clearing the GroupWise Password of a User

JSON Request:  
PUT https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/  
testPO1/users/testUser1/clientoptions  
    userPassword={restore=true}

XML Request:  
PUT https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/  
testPO1/users/testUser1/clientoptions  
<clientOptions>  
    <forceNullOnAttrs/>  
    <userPassword>  
        <restore>true</restore>  
    </userPassword>  
</clientOptions>

Response Status:  
200 - OK

## Restoring the Compose Views of a User

JSON Request:  
PUT https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/  
testPO1/users/testUser1/clientoptions  
    composeViews={restore=true}

XML Request:  
PUT https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/  
testPO1/users/testUser1/clientoptions  
<clientOptions>  
    <forceNullOnAttrs/>  
    <composeViews>  
        <restore>true</restore>  
    </composeViews>  
</clientOptions>

Response Status:  
200 - OK

## Modifying the Send Priority Settings of a User

```
JSON Request:
PUT https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/
testPO1/users/testUser1/clientoptions
  sendPriority={value=HIGH, restore=false}
```

```
XML Request:
PUT https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/
testPO1/users/testUser1/clientoptions
<clientOptions>
  <forceNullOnAttrs/>
  <sendPriority>
    <value class="AttrNoUsed">HIGH</value>
    <restore>false</restore>
  </sendPriority>
</clientOptions>
```

```
Response Status:
200 - OK
```

## Modifying the Calendar Settings of a User

```
JSON Request:
PUT https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/
testPO1/users/testUser1/clientoptions
  calendarStartTime={value={hours=7, minutes=30, timeInMinutes=450},
restore=false}
  calendarEndTime={value={hours=18, minutes=30, timeInMinutes=1110},
restore=false}
  calendarShowWeekNumber={value=false, restore=false}
  calendarWorkdays={value=[THURSDAY, MONDAY, TUESDAY, WEDNESDAY],
restore=false}
```

```
XML Request:
PUT https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/
testPO1/users/testUser1/clientoptions
<clientOptions>
  <forceNullOnAttrs/>
  <calendarEndTime>
    <value class="AttrNoUsed">
      <hours>18</hours>
      <minutes>30</minutes>
    </value>
    <restore>false</restore>
  </calendarEndTime>
  <calendarShowWeekNumber>
    <value class="boolean">false</value>
    <restore>false</restore>
  </calendarShowWeekNumber>
  <calendarStartTime>
    <value class="AttrNoUsed">
      <hours>7</hours>
```

```
        <minutes>30</minutes>
      </value>
    <restore>false</restore>
  </calendarStartTime>
  <calendarWorkdays>
    <value>WEDNESDAY</value>
    <value>TUESDAY</value>
    <value>MONDAY</value>
    <value>THURSDAY</value>
  </calendarWorkdays>
</clientOptions>
```

Response Status:  
200 - OK

## Modifying the Alarm Settings of a User

JSON Request:

```
PUT https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/
testPO1/users/testUser1/clientoptions
  alarmDefaultTime={value={hours=1, minutes=0, timeInMinutes=60},
restore=false}
  alarmWhenAccepted={value=true, restore=false}
```

XML Request:

```
PUT https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/
testPO1/users/testUser1/clientoptions
<clientOptions>
  <forceNullOnAttrs/>
  <alarmDefaultTime>
    <value class="AttrNoUsed">
      <hours>1</hours>
      <minutes>0</minutes>
    </value>
    <restore>false</restore>
  </alarmDefaultTime>
  <alarmWhenAccepted>
    <value class="boolean">true</value>
    <restore>false</restore>
  </alarmWhenAccepted>
</clientOptions>
```

Response Status:  
200 - OK

## Disabling and Locking the Publish Free Busy Setting of a User

JSON Request:

```
PUT https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/
testPO1/users/testUser1/clientoptions
  publishFreeBusySearch={lock={itemLocked=true, lockAvailable=false,
modifiable=false}, value=false, restore=false}
```

XML Request:

```
PUT https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/
testPO1/users/testUser1/clientoptions
<clientOptions>
  <forceNullOnAttrs/>
  <publishFreeBusySearch>
    <lock>
      <itemLocked>true</itemLocked>
      <lockAvailable>false</lockAvailable>
      <modifiable>false</modifiable>
    </lock>
    <value class="boolean">false</value>
    <restore>false</restore>
  </publishFreeBusySearch>
</clientOptions>
```

Response Status:

200 - OK

## Enabling the Vibe Access and Configuring the Vibe URL of a User

```
JSON Request:
PUT https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/
testPO1/users/testUser1/clientoptions
  vibeEnabled={value=true, restore=false}
  vibeUrl={value=https://vibe.novell.com, restore=false}
```

```
XML Request:
PUT https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/
testPO1/users/testUser1/clientoptions
<clientOptions>
  <forceNullOnAttrs/>
  <vibeEnabled>
    <value class="boolean">true</value>
    <restore>false</restore>
  </vibeEnabled>
  <vibeUrl>
    <value class="string">https://vibe.novell.com</value>
    <restore>false</restore>
  </vibeUrl>
</clientOptions>
```

```
Response Status:
200 - OK
```

## Performing a Batch Operation to Add Members to a Group

```
JSON Request:
PUT https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/
testPO1/groups/testGroup1/members
  add=[{id=USER.testDom1.testPO1.testGroupMember4, participation=PRIMARY},
{id=USER.testDom1.testPO1.testGroupMember3, participation=PRIMARY},
{id=USER.testDom1.testPO1.testGroupMember6, participation=PRIMARY},
{id=USER.testDom1.testPO1.testGroupMember5, participation=PRIMARY},
{id=USER.testDom1.testPO1.testGroupMember2, participation=PRIMARY},
{id=USER.testDom1.testPO1.testGroupMember1, participation=PRIMARY}]
```

```
XML Request:
PUT https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/
testPO1/groups/testGroup1/members
<groupMemberListUpdate>
  <forceNullOnAttrs/>
  <add>
    <id>USER.testDom1.testPO1.testGroupMember4</id>
    <forceNullOnAttrs/>
    <participation>PRIMARY</participation>
  </add>
  <add>
    <id>USER.testDom1.testPO1.testGroupMember3</id>
    <forceNullOnAttrs/>
```

```

    <participation>PRIMARY</participation>
  </add>
  <add>
    <id>USER.testDom1.testPO1.testGroupMember6</id>
    <forceNullOnAttrs/>
    <participation>PRIMARY</participation>
  </add>
  <add>
    <id>USER.testDom1.testPO1.testGroupMember5</id>
    <forceNullOnAttrs/>
    <participation>PRIMARY</participation>
  </add>
  <add>
    <id>USER.testDom1.testPO1.testGroupMember2</id>
    <forceNullOnAttrs/>
    <participation>PRIMARY</participation>
  </add>
  <add>
    <id>USER.testDom1.testPO1.testGroupMember1</id>
    <forceNullOnAttrs/>
    <participation>PRIMARY</participation>
  </add>
</groupMemberListUpdate>

```

Response Status:

200 - OK

## Performing a Batch Operation to Modify Members of a Group

JSON Request:

```

PUT https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/
testPO1/groups/testGroup1/members
  update=[{id=USER.testDom1.testPO1.testGroupMember4,
participation=CARBON_COPY}, {id=USER.testDom1.testPO1.testGroupMember3,
participation=CARBON_COPY}]
  remove=[USER.testDom1.testPO1.testGroupMember5,
USER.testDom1.testPO1.testGroupMember6]
  add=[{id=USER.testDom1.testPO1.testGroupMember2, participation=PRIMARY},
{id=USER.testDom1.testPO1.testGroupMember1, participation=PRIMARY}]

```

XML Request:

```

PUT https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/
testPO1/groups/testGroup1/members
<groupMemberListUpdate>
  <forceNullOnAttrs/>
  <add>
    <id>USER.testDom1.testPO1.testGroupMember2</id>
    <forceNullOnAttrs/>
    <participation>PRIMARY</participation>
  </add>
  <add>
    <id>USER.testDom1.testPO1.testGroupMember1</id>

```

```

    <forceNullOnAttrs/>
    <participation>PRIMARY</participation>
  </add>
  <update>
    <id>USER.testDom1.testPO1.testGroupMember4</id>
    <forceNullOnAttrs/>
    <participation>CARBON_COPY</participation>
  </update>
  <update>
    <id>USER.testDom1.testPO1.testGroupMember3</id>
    <forceNullOnAttrs/>
    <participation>CARBON_COPY</participation>
  </update>
  <remove>USER.testDom1.testPO1.testGroupMember5</remove>
  <remove>USER.testDom1.testPO1.testGroupMember6</remove>
</groupMemberListUpdate>

```

Response Status:  
200 - OK

## Performing a Batch Operation to Add ACL Members to a Group

JSON Request:

```

PUT https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/
testPO1/groups/testGroup1/acl
  add=[{id=USER.testDom1.testPO1.testGroupMember4, rights=READ},
{id=USER.testDom1.testPO1.testGroupMember3, rights=READ},
{id=USER.testDom1.testPO1.testGroupMember6, rights=READ},
{id=USER.testDom1.testPO1.testGroupMember5, rights=READ}]

```

XML Request:

```

PUT https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/
testPO1/groups/testGroup1/acl
<accessControlListUpdate>
  <forceNullOnAttrs/>
  <add>
    <forceNullOnAttrs/>
    <id>USER.testDom1.testPO1.testGroupMember4</id>
    <rights>READ</rights>
  </add>
  <add>
    <forceNullOnAttrs/>
    <id>USER.testDom1.testPO1.testGroupMember3</id>
    <rights>READ</rights>
  </add>
</accessControlListUpdate>

```

```

<add>
  <forceNullOnAttrs/>
  <id>USER.testDom1.testPO1.testGroupMember6</id>
  <rights>READ</rights>
</add>
<add>
  <forceNullOnAttrs/>
  <id>USER.testDom1.testPO1.testGroupMember5</id>
  <rights>READ</rights>
</add>
</accessControlListUpdate>

```

Response Status:  
200 - OK

## Performing a Batch Operation to Modify ACL Members of a Group

JSON Request:

```

PUT https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/
testPO1/groups/testGroup1/acl
  update=[{id=USER.testDom1.testPO1.testGroupMember4, rights=WRITE},
{id=USER.testDom1.testPO1.testGroupMember3, rights=WRITE}]
  remove=[USER.testDom1.testPO1.testGroupMember5,
USER.testDom1.testPO1.testGroupMember6]
  add=[{id=USER.testDom1.testPO1.testGroupMember2, rights=READ},
{id=USER.testDom1.testPO1.testGroupMember1, rights=READ}]

```

XML Request:

```

PUT https://localhost:9710/gwadmin-service/domains/testDom1/postoffices/
testPO1/groups/testGroup1/acl
<accessControlListUpdate>
  <forceNullOnAttrs/>
  <add>
    <forceNullOnAttrs/>
    <id>USER.testDom1.testPO1.testGroupMember2</id>
    <rights>READ</rights>
  </add>
  <add>
    <forceNullOnAttrs/>
    <id>USER.testDom1.testPO1.testGroupMember1</id>
    <rights>READ</rights>
  </add>
</update>
<forceNullOnAttrs/>

```



```
<id>USER.testDom1.testPO1.testGroupMember4</id>
<rights>WRITE</rights>
</update>
<update>
  <forceNullOnAttrs/>
  <id>USER.testDom1.testPO1.testGroupMember3</id>
  <rights>WRITE</rights>
</update>
<remove>USER.testDom1.testPO1.testGroupMember5</remove>
<remove>USER.testDom1.testPO1.testGroupMember6</remove>
</accessControlListUpdate>
```

Response Status:  
200 - OK

## Creating a Trusted Application Record

JSON Request:  
POST https://localhost:9710/gwadmin-service/system/trustedapps  
NMAPEnabled=true  
enabled=false  
archiveServiceAddress=127.0.0.1  
queuingDisabled=false  
archiveServiceRequiresSsl=true  
providesRetentionService=true  
name=testTrustedApp1  
requiresSsl=true  
ipPort=123  
allowArchiveService=true  
nmapenabled=true  
archiveServicePort=456  
ipAddress=127.0.0.1

XML Request:  
POST https://localhost:9710/gwadmin-service/system/trustedapps  
<trustedapp>  
 <name>testTrustedApp1</name>  
 <forceNullOnAttrs/>  
 <allowArchiveService>true</allowArchiveService>  
 <archiveServiceAddress>127.0.0.1</archiveServiceAddress>  
 <archiveServicePort>456</archiveServicePort>  
 <archiveServiceRequiresSsl>true</archiveServiceRequiresSsl>

```
<providesRetentionService>true</providesRetentionService>
<ipAddress>127.0.0.1</ipAddress>
<ipPort>123</ipPort>
<requiresSsl>true</requiresSsl>
<enabled>false</enabled>
<NMAPEnabled>true</NMAPEnabled>
<queuingDisabled>false</queuingDisabled>
</trustedapp>
```

Response Status:  
201 - Created

Trusted App Key is =  
3E52134109EF0000B83CF42E441DDB433E52134209EF0000B5CEAD10E8D9F721

## Updating a Trusted Application Record

JSON Request:  
PUT https://localhost:9710/gwadmin-service/system/trustedapps/  
testTrustedApp1  
NMAPEnabled=true  
enabled=false  
archiveServiceAddress=127.0.0.1  
queuingDisabled=false  
providesRetentionService=true  
timeLastMod=1371072314000  
requiresSsl=false  
ipPort=123  
timeCreated=1371072314000  
nmapenabled=true  
archiveServicePort=456  
id=TRUSTED\_APP.testTrustedApp1  
lastModifiedOp=ADD  
archiveServiceRequiresSsl=true  
@url=/gwadmin-service/system/trustedapps/testTrustedApp1  
description=Trusted App is modified.  
name=testTrustedApp1  
lastModifiedBy=admin.testSystem1  
allowArchiveService=false  
ipAddress=127.0.0.1

XML Request:  
PUT https://localhost:9710/gwadmin-service/system/trustedapps/  
testTrustedApp1  
<trustedapp>  
 <id>TRUSTED\_APP.testTrustedApp1</id>  
 <name>testTrustedApp1</name>  
 <url>/gwadmin-service/system/trustedapps/testTrustedApp1</url>  
 <timeCreated>1371072577000</timeCreated>  
 <timeLastMod>1371072577000</timeLastMod>  
 <lastModifiedBy>admin.testSystem1</lastModifiedBy>  
 <lastModifiedOp>ADD</lastModifiedOp>  
 <forceNullOnAttrs/>  
 <allowArchiveService>false</allowArchiveService>

```
<archiveServiceAddress>127.0.0.1</archiveServiceAddress>
<archiveServicePort>456</archiveServicePort>
<archiveServiceRequiresSsl>true</archiveServiceRequiresSsl>
<description>Trusted App is modified.</description>
<providesRetentionService>true</providesRetentionService>
<ipAddress>127.0.0.1</ipAddress>
<ipPort>123</ipPort>
<requiresSsl>false</requiresSsl>
<enabled>false</enabled>
<NMAPEnabled>true</NMAPEnabled>
<queuingDisabled>false</queuingDisabled>
</trustedapp>
```

Response Status:  
200 - OK

## Deleting a Trusted Application Record

Request:  
DELETE https://localhost:9710/gwadmin-service/system/trustedapps/  
testTrustedApp1

Response Status:  
200 - OK



# B Invalid Characters

Although most characters in the languages supported by GroupWise can be used in GroupWise object names and Internet email addresses, some cannot.

- ♦ [“Invalid Characters in GroupWise Object Names” on page 245](#)
- ♦ [“Invalid Characters in Internet Email Addresses” on page 245](#)

## Invalid Characters in GroupWise Object Names

Do not use any of the characters listed below in the names of GroupWise objects:

- ♦ ASCII characters 0-31
- ♦ Asterisk \*
- ♦ At sign @
- ♦ Braces { }
- ♦ Colon :
- ♦ Comma ,
- ♦ Double quote "
- ♦ Extended ASCII characters that are graphical or typographical symbols

---

**IMPORTANT:** Accented characters in the extended range can be used in GroupWise object names.

---

- ♦ Parentheses ( )
- ♦ Period .

## Invalid Characters in Internet Email Addresses

Internet email addresses must include only RFC-compliant characters, which include:

- ♦ Numbers 0-9
- ♦ Uppercase letters A-Z
- ♦ Lowercase letters a-z
- ♦ Plus sign +
- ♦ Hyphen -
- ♦ Underscore \_
- ♦ Tilde ~

In the names of GroupWise objects that can appear in email addresses (users, distribution lists, and resources), use underscores (\_) rather than spaces as separators between words to facilitate addressing across the Internet.

If it is important for GroupWise object names to include characters that are invalid in email addresses, you can set up preferred email IDs for those objects in order to give them valid email addresses.

For instructions on providing valid email addresses for GroupWise objects, see the following sections in the [GroupWise 18 Administration Guide \(https://www.novell.com/documentation/groupwise18/gw18\\_guide\\_admin/data/admin\\_front.html\)](https://www.novell.com/documentation/groupwise18/gw18_guide_admin/data/admin_front.html):

- ◆ “Changing a User’s Internet Addressing Settings”
- ◆ “Changing a Group’s Internet Addressing Settings”
- ◆ “Changing a Resource’s Internet Addressing Settings”