



ZENworks 2020 Update 1 Registry Keys Reference

February 2021 June 2020

Legal Notice

For information about legal notices, trademarks, disclaimers, warranties, export and other use restrictions, U.S. Government rights, patent policy, and FIPS compliance, see <https://www.novell.com/company/legal/>.

© Copyright 2008 - 2020 Micro Focus or one of its affiliates.

The only warranties for products and services of Micro Focus and its affiliates and licensors ("Micro Focus") are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Micro Focus shall not be liable for technical or editorial errors or omissions contained herein. The information contained herein is subject to change without notice.

Contents

About This Guide	5
1 Registry Keys	7

About This Guide

This *ZENworks Registry Keys Reference* provides information about the registry keys used to control functionality on ZENworks devices (servers and workstations).

Audience

This guide is intended for ZENworks administrators.

Feedback

We want to hear your comments and suggestions about this manual and the other documentation included with this product. Please use the **comment on this topic** feature at the bottom of each page of the online documentation.

Additional Documentation

ZENworks is supported by other documentation (in both PDF and HTML formats) that you can use to learn about and implement the product. For additional documentation, see the [ZENworks documentation website](#).

1 Registry Keys

This section provides information about registry keys used to carry out general administrative tasks on ZENworks managed devices.

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
AllowAnonymousAccessToContentRepo	Windows: HKLM\Software\ Novell\ZCM Linux: /etc/opt/ novell/ zenworks/conf/ xplatzmd.prope rties	Allows the user to access the content-repo directory anonymously.	String	True
AllowDLUWithoutNovellClient	Windows XP (32-bit): HKLM\Software\ Novell\Nwgina Windows Vista/ Windows 7 or Windows 10 (32-bit and 64-bit) HKLM\Software\ Novell\Authent ication	To log a dynamic user with an e-directory account into a workstation using the Dynamic Local User policy. For more information, see “Implementing the Dynamic Local User Policy Without the Novell Client” in the ZENworks Configuration Policies Reference .	DWORD	1
AllowNonTaskbarExplorer	HKLM\Software\ Novell\ZCM\NAL \	Allows NalShell to load in the context of the non-task bar explorer. Prevents NalShell from being loaded in the context of the non-task bar explorer.	DWORD DWORD	1 0
AllowNonActiveNIC	HKLM\Software\ Novell\ZCM	To enable ZENworks agents to allow the non-active Network Interface Cards (NICs) while detecting the network on a Windows platform. Note: Not applicable on a ZENworks Xplat agent.	String	True

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
AllowPassiveModeLogin OnServers	HKLM\Software\ Novell\ZCM\Zen Lgn	To log in to the ZENworks console and to dynamically create user accounts for Windows 2003, Windows 2008, and Windows 2008 R2 devices. You can also use the DLU policy to create users dynamically. NOTE: Passthrough login is not supported on Windows 2003 64-bit devices.	DWORD	1
AllowTunnelInterface	HKLM\Software\ Nove ll\ZCM	To enable ZCM agents to consider the tunnel interface while detecting the network.	String	True/False
AllowZenInfoWithoutAd minPwd	HKLM\Software\ Novell\ZCM	When the value of this key is set to True, users other than administrators can run zac zeninfo For more information, see “zac for Windows(1)” in the ZENworks Command Line Utilities Reference .	String	True
AutoAcceptUnverifiable Certificate	HKEY_CURRENT_U SER\Software\ Novell\ZCM\Remo te Management\ Vie wer\Settings	If the value of the registry key is set to "0", the certificate acceptance option is displayed. If the registry key value is set to "1", the option is not displayed.	DWORD	0 or 1
autowindowresize	HKCU\Software\ Novell\ZCM\Rem ote Management\ Vie wer\History\de vice~50 *device can be IP address of hostname If no entry is found for device, then the registry value should be created under Default key.	In a remote control session, this registry key when set enables the resizing of the remote viewer on the management console without any borders or black spaces when switching back to auto.	DWORD	Any value other than zero.

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
BlankScreenFrequency	HKLM\Software\ Novell\ZCM\Remote Management\Agent	During a blank screen, the managed device's screen will flicker based on the configured time interval. The default time interval is 600 milliseconds.	DWORD	600 to 2000 milliseconds
BundleOrderingTimeSlice	HKLM\Software\ Novell\ZCM	Allows you to configure the time that the agent waits before reordering the assigned bundles on a Windows managed device. The default value is 5 seconds. For more information, see "Enabling Bundle Ordering" in the <i>ZENworks Software Distribution Reference</i> .	String	Any value greater than 0, in seconds
BUNDLE_ORDERING_TIME_LAG_SEC	/etc/opt/ novell/ zenworks/conf/ xplatzmd.properties	Allows you to configure the amount of time that the agent waits before reordering the assigned bundles on a Linux managed device. The default value is 5 seconds. For more information, see "Enabling Bundle Ordering" in the <i>ZENworks Software Distribution Reference</i> .	String	Any value greater than 0, in seconds
CancelOnNoResponse	Windows 32-bit HKLM\Software\ \Novell\ZCM\ ActionHandler\ CancelOnNoResponse Windows 64-bit HKLM\Software\ \Wow6432Node\ Novell\ZCM\ ActionHandler\ CancelOnNoResponse	Allows reboot control and prompt control to set the auto continue and auto cancel options. For more information, see "User Cancels Allowed" in the <i>ZENworks Software Distribution Reference</i> .	DWORD	1

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
CDPWebCallWaitTimeout	HKLM\Software\ Novell\ZCM	To modify the Web Service time out on a Satellite device for Windows, set this registry key value to the desired time you want. For more information, see “Manually Configuring the Web Service Timeout Advanced Content Replication Setting” in the <i>ZENworks Primary Server and Satellite Reference</i> .	String	Desired time in milliseconds
cleanUpStalePrintersAtPostDesktop	HKLM\SOFTWARE\ Novell\ZCM\PrinterPolicy	To remove printers of the previous user session when a new user logs in to the same device. NOTE: The printers of the previous user session will be removed only after the registry key is set and the device is rebooted. This is applicable only for Samba printers.	String	True
ContentDownloadFailureLogLevel	HKLM\Software\ novell\zcm	To log the content replication error messages as warnings or errors. Using this registry key on Satellite Servers, you can also prevent the logging of content replication errors by specifying the value as NoLogging.	String	NoLogging, Error, Warning
ContentCPRTempPath	HKLM\Software\ novell\zcm	To change the location of the checkpoint content (.tmp) files from the default Windows temp file location to another folder on the device. You need to specify the new folder path where the .tmp files should be stored. If the registry entry is missing or if there are any issues or exceptions in creating a configured folder path for the *.tmp files, the *.tmp files will be stored in the default Windows temp location.	String	<Folder path>

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
defaultUICulture	HKLM\Software\ Novell\ZCM	<p>ZENworks Agent reads this registry key and loads the corresponding language resources.</p> <p>If a language pack is installed on a device and the display language is set to an installed language pack that is not supported by ZENworks, then you can load resources for any of the ZENworks supported languages by setting the <code>defaultUICulture</code> registry key to the appropriate culture value. For example, to load English (United States) set it to <code>en-US</code>, or to load French (France) set it to <code>fr-FR</code>.</p> <p>NOTE: The display language takes the following order of precedence:</p> <ol style="list-style-type: none"> 1. Installed language pack: If you install a language pack that is supported by ZENworks and make it the default language, then the Technician UI is displayed in the default language. 2. <code>defaultUICulture</code> registry key: If the default language pack is not supported by ZENworks, and if you define a supported, language locale value, for this registry key, then the Technician UI is displayed based on the registry key value. 3. OS supported language: If the default language pack is not supported, and the registry key value is not specified or if the specified value is not supported, then the UI is displayed in the OS language. However, if the OS language is also not supported, then the Technician UI is displayed in English. 	String	<p>Specify the Language Locale value.</p> <p>Example for English language (United States): <code>en-US</code></p>

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
DefaultRealm	HKLM\Software\ Novell\ZCM\Zen Lgn\	To reduce the device login time, specify the user source in this registry key. For more information, see “Reducing Device Login Time by Specifying the Default User Source” in the ZENworks User Source and Authentication Reference .	String	Desired User source The DefaultRealm value is case sensitive since the realm name is case sensitive.
DeleteCustomGroups	HKLM\Software\ Novell\ZCM\Dynamic Local User	This registry key will delete the Custom Groups created by the DLU policy. If the registry key is not set then Custom groups will never get deleted.	String	True
DisableCDPRestartIntervalDoubling	HKLM\SOFTWARE\ Novell\ZCM	Based on your requirements, set the registry to True or False: <ul style="list-style-type: none"> ◆ On Linux and Mac operating systems, configure the setting in the /etc/opt/Novell/zenworks/conf/xplatzmd.properties file. ◆ On a Windows operating system, use the Registry Editor and configure the registry key: HKLM\SOFTWARE\Novell\ZCM <ul style="list-style-type: none"> ◆ True: The CDP restart interval will get reset to the initial value (governed by CDPRestartInterval setting) and remain constant till the setting is changed to False. ◆ False: The CDP restart interval will double if no content is available. 	String	True/False

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
disableCachedLogin	HKLM\Software\ Novell\ZCM	You can use this key to turn on the Disconnected Mode Login feature on Citrix or terminal servers. By default, this feature is disabled on Citrix or terminal servers and enabled on desktop machines. To improve the login performance, disable the caching of credentials for disconnected mode login on terminal server class machine, by setting the value of this registry key to True.	String	True / False
DisableChangePassword Prompt	HKLM\SOFTWARE \Novell\ZCM\ \ZenLgn	You can use this key to disable the change password prompt displayed by the ZENworks agent, when the password expires.	DWORD	1
DisableExplorerRestart	HKLM\Software\ Novell\ZCM\Gro upPolicy	This registry key ensures that ZENworks Configuration Management does not restart the Windows explorer.	String	True / False
DisableForegroundLockTime outReset	HKLM\Software\ Novell\ZCM\NAL	This registry key is a Windows setting designed to prevent newly launched applications from moving into the foreground. By default, the ZCM agent will reset the registry key to 0 on every boot so that the ZCM applications are moved to the foreground. Setting up this registry key will prevent ZCM from resetting the ForeGroundLockTimeout registry key to 0. This helps the administrator to set the ForeGroundLockTimeout registry key to either a default value or a required value.	DWORD	0
DisablePassiveModeLogin	HKLM\Software\ Novell\ZCM\Zen Lgn	To disable login to the Management Zone when the user logs in through the Microsoft or Novell client.	DWORD	Any value other than zero

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
DisablePassiveModeLoginPrompt	HKLM\Software\Novell\ZCM\ZenLgn	To disable the ZENworks login prompt that appears if login through the Microsoft client or Novell client fails. For more information, see “Locate the following key in the registry on the user’s device:” in the ZENworks User Source and Authentication Reference .	DWORD	Any value other than zero
DisableShortcutScanning	HKLM\Software\Novell\ZCM\	To prevent the scan, during every refresh, for bundle icons that are pinned or unpinned by the end-user in the Start menu and the Taskbar. Applicable for Windows 10 and later.	DWORD	Any value other than zero
DisableZENCredentialProvider	HKLM\Software\Novell\ZCM\ZenLgn	The ZENworks Credential Provider filters the Windows Password Credential Provider. When you install the ZENworks Agent on the Windows Vista or later versions and Windows 2008 Server or later versions device that has third-party products with Credential Providers installed, multiple user tiles are displayed. For more information, see <i>“Disabling the ZENWorks Credential Provider on a Device”</i> in the ZENworks User Source and Authentication Reference .	DWORD	1
DomainLogin	HKLM\Software\Novell\ZCM\ZenLgn	This key helps you to identify the login domain of the user. If the value is set to 1, the user is in Microsoft Active Directory.	DWORD	1

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
DonotFetchUserGroups	HKLM\Software\Novell\ZCM\AgentSettings	To significantly improve the time taken to log in to a managed device, if a Dynamic Local User policy that has no login restrictions configured is assigned to the device. For more information, see “Dynamic Local User Policy” in the <i>ZENworks Configuration Policies Reference</i> .	String	True
Dontdisplaylastusername	HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Windows\CurrentVersion\Policies\System	This key removes any user account names from the Windows logon welcome screen and forces user to enter password and user name when logging in.	DWORD	1
DontUpdateGroupMemberships	Windows 32-bit: HKLM\Software\Novell\Nwgina\DynamicLocalUser Windows 64-bit: HKLM\Software\Wow6432Node\Novell\Nwgina\DynamicLocalUser	To update group memberships of the user on the managed device. For more information, see “Unable to update the group membership of the user on the managed device ” in the <i>ZENworks Configuration Policies Reference</i> .	String	0
DisableBlankScreen	HKLM\Software\Novell\ZCM\RemoteManagement\Agent	To disable the blank screen option during remote management.	DWORD	Any value other than zero
DraggableWhenZAPPAshell	HKEY_LOCAL_MACHINE\SOFTWARE\Novell\ZCM\ZAPP	This key helps the user to move or drag the ZAPP window when launched as a shell.	String	True
eDIRLogin	HKLM\Software\Novell\ZCM\ZenLgn\	This key helps you to identify the login domain of the user. If the value is set to 1, the user is in Novell eDirectory.	DWORD	1

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
EnableBatchRefresh	HKLM\Software\ Novell\ZCM\	To refresh the user sessions on a device in batches, set this registry key value to 1. For more information, see “The partial or the general refresh of a terminal server might cause high usage of system resources and take considerable time to refresh the server” in the ZENworks Agent Reference .	String	1
EnableCredManForceLogin	HKLM\Software\ Novell\ZCM	To enable Credential Manager force login.	String	True
EnableEDirPasswordForFA	Windows 32-bit: HKLM\Software\ Novell\Nwgina\ DynamicLocalUser Windows 64-bit: HKLM\Software\ Wow6432Node\ Novell\Nwgina\ DynamicLocalUser	To enable a Dynamic Local User in logging in to a device again after logging out of the managed device that is disconnected from the network. For more information, see “Dynamic Local User Policy Troubleshooting” in the ZENworks Configuration Policies Reference .	DWORD	1
EnableSeamlessLogin	HKLM\Software\ Novell\ZCM\Zen Lgn\	Enables seamless authentication for a user on a device. This registry key will ensure that all user sources are searched to identify the user who has logged in. For more information, see “Enabling Seamless Authentication on a Device” in the ZENworks User Source and Authentication Reference .	DWORD	1

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
EnableSecretStore	HKLM\Software\ Novell\ZCM\Zen Lgn\	To log in to a ZENworks server that has a Secret Store configured, set this registry key value to 1. For more information, see “Authenticating in to a ZENworks Server That Has Novell SecretStore Configured” in the ZENworks User Source and Authentication Reference .	DWORD	1
EnableStatusMessages	HKLM\Software\ Novell\Authent ication	To disable the login status messages on a device screen, set this registry key value to 0. For more information, see “Disabling the Login Status Messages Display on the Device Screen” in the ZENworks User Source and Authentication Reference .	DWORD	0

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
EnableTraditionalCasa	HKLM\Software\ Novell\ZCM	<p>To enable the older Casa Auth Client component and micasa as secret store, by setting the value of this registry key to True.</p> <p>This registry key is used in the following scenarios:</p> <ul style="list-style-type: none"> ◆ When you do not want to change the existing CASA Auth Client and micasa component to newly added CASA components. ◆ If a user has issues due to the newly added CASA Auth Client component, the user can switch to the older CASA components. <p>IMPORTANT: ZENworks Agent maintains the following secret stores for caching the user credentials:</p> <ul style="list-style-type: none"> ◆ HKLM\Software\Novell\ZCM\EnableTraditionalCasa (Reg_SZ) : A successful log in is required after setting to True and log off or log in again. This will ensure that credentials will be cached in old CASA store and will be used for further cache logins using old CASA store. ◆ HKLM\Software\Novell\ZCM\EnableTraditionalCasa (Reg_SZ) : A successful log in is required after setting to False and log off or log in again. This will ensure that credentials will be cached in newly added CASA store and will be used for further cache logins using old CASA store. 	String	True / False

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
EnableZENMemoryCache	HKLM\Software\Novell\ZCM	To improve the login performance on Terminal servers, enable the caching of objects in memory.	String	True / False
EnableZENMemoryKeyCache	HKLM\Software\Novell\ZCM	This registry key creates a memory cache for storing keys of all the cached entries. You can use this memory cache to look up if a particular entry is cached or not, in a Terminal server multiuser login scenario. If the entry is not cached, then the unnecessary access to the persistent cache can be avoided.	String	True / False
EndUserSettingMaxAgeDays	HKLM\Software\Novell\ZCM	This registry key retains the end-user pin or unpin settings for 30 days by default. You can change default settings. If any bundles are not getting used, after certain period the user location preferences for those bundles are cleared. Applicable for Windows 10 or later.	DWORD	
ForceHKLMandNoDPAPI	HKLM\Software\Protocom\SecurityLogin	To log into the ZENworks Server, while logging into a Windows Vista device, set this registry key value to 1.	DWORD	1
Full	HKLM\Software\Novell\ZCM\Migration\MSIOptions\	Displays a full user interface (Wizard dialog boxes, progress information, error messages and prompts, and so forth).	String	/qf
HonorActionHandlerSetting	HKEY_LOCAL_MACHINE\SOFTWARE\Novell\ZCM\ActionHandler\	Helps environment variables to get resolved in different bundle action context. For example: If the bundle action is set to run as system user, then all the environment variables in the bundle action data will be resolved in the system context.	String	True

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
HonorClient32WorkstationOnlyCheckbox	HKLM\Software\Novell\ZCM\ZenLgn	To log in directly into a Windows XP workstation that has both the Novell Client and the ZENworks Agent installed, set this registry key value to 1. For more information, see “Logging Directly in to a Workstation That has Both Novell Client and ZENworks Agent Installed” in the ZENworks User Source and Authentication Reference.	DWORD	1
HonorTESSFireSchedule	HKLM\Software\Novell\ZCM\	If the <code>pastdue</code> schedule is not enabled, prior to triggering the event, the Scheduler will check if the current time is within the configured schedule. If it is not, the schedule will be skipped.	String	True
HonorWorkstationOnlyLogin	HKLM\Software\Novell\ZCM\ HKLM\SOFTWARE\Novell\ZCM\INV_CDF	To log in directly into a Windows Vista/ Windows 7/ Windows 8 or Windows 10 workstation that has both the Novell Client and the ZENworks Agent installed, set this registry key value to 1. For more information, see “Logging Directly in to a Workstation That has Both Novell Client and ZENworks Agent Installed” in the ZENworks User Source and Authentication Reference. To launch the Collection Data Form (CDF) in the background. By default the CDF will appear in front of an active application. Use this registry key to reverse the default behavior.	DWORD	1

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
IgnorePrezenworksSecuritySettings(REG_SZ)	HKLM\Software\Novell\ZCM\GroupPolicy	To exclude the local group policy security settings from being backed-up and restored.	String	True
IsNalLoggingDisabled	HKLM\Software\Novell\ZCM\NALL\	To disable debug logging for Nalshell. NOTE: This registry key can be used only when the managed device logging is set to Debug and above.	DWORD	1
LocalAccountTokenFilterPolicy	HKLM\Software\Microsoft\Windows\CurrentVersion\Policies\System\LocalAccountTokenFilterPolicy	Allows remote users to log in and not be forced to be guest. For more information see, “ Enabling Classic File Sharing ” in the <i>ZENworks Discovery, Deployment, and Retirement Reference</i> .	DWORD	1
	Windows Vista (32-bit)			
	Windows Server 2008(32-bit)			
	Windows 7 and Windows Server 2008 R2(32-bit)			
LogoffCheckSysModules	HKLM\System\CurrentControlSet\Control\Citrix\wfshell\TWI	To completely terminate a session on the Citrix server and ensure that policies are unenforced on the device. For more information, see “ Closing a published application or logging out of the shared desktop of a Citrix server fails to terminate the session on the Citrix server ” in the <i>ZENworks Configuration Policies Reference</i> .	String	Change the value from ZCMUMHelper.exe to ZenUserDaemon.exe, ZCMUMHelper.exe

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
ManualDeviceRefresh	HKLM\Software\ Novell\ZCM\	To disable the general refresh for a device session on a Windows device, set this registry key value to Disabled. For more information, see “By default, the general refresh on a Windows device refreshes both the device and user sessions.” in the ZENworks Agent Reference .	String	Enabled/Disabled
MigrateWithParentOptions	HKLM\Software\ Novell\ZCM\Mig ration\MSIOpti ons\	MSPs are migrated in Silent mode.	String	0
MaxValue	HKLM\Software\ Novell\ZCM\Zen Lgn\History\Ze nCacheLimit	To specify the number of credentials that can be cached on a device at any point of time, use this registry key.	DWORD	Specify a number from 1 to 100
MaxLogFileSize	HKLM\Software\ Novell\ZCM\Zen Lgn\MaxLogFile Size	To retain the old logs and append the new logs in the zenlgn.log file, specify in Kilo Bytes.	DWORD	1024
MaxLogFileSize	HKLM\Software\ Novell\NWGINA\ MaxLogFileSize	To retain the old logs and append the new logs in the nwgina.log file, specify in Kilo Bytes.	DWORD	1024
MaxZenPrinterProcessingTimeout		To set a default value that forces the Printer policy handler to wait for a set amount of time. For more information, see “Printer Policy Troubleshooting” in the ZENworks Configuration Policies Reference .	String	Specify an appropriate timeout value in seconds.
MergedCacheRequired	HKLM\Software\ Novell\ZCM\Gro upPolicy	To enable the merged cache feature, set this registry key to a non-zero value.	String	Any value other than zero

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
maxinitialscreen	HKCU\Software\ Novell\ZCM\Remote Management\Viewer\History\device~50 *device can be IP name or hostname If no entry is found for device, then the registry value should be created under Default key.	Before launching remote control session, enable the registry key to auto-fit the remote viewer in the Management Console screen, when the scale by setting is set to auto in the ZENworks Remote Management Viewer options window.	DWORD	Any value other than zero.
NalShellDelay	HKLM\Software\ Novell\ZCM\NAL	Configure delay time in seconds for NalShell in the registry key. Based on the configured time in the registry parameter explorer delays the loading process of Nalshell.	DWORD	Specify any value in seconds other than zero.
PassiveMode	HKLM\Software\ Novell\NWGINA	To start Novell SecureLogin seamlessly, set this registry key value to 1. For more information, see “Troubleshooting User Sources” in the ZENworks User Source and Authentication Reference .	DWORD	1
PERMISSION_MSG_POS TPONES_REMAINING	HKLM\Software\ Novell\ZCM\System Update	The value of this key determines the number of times the user can postpone an update. For more information, see “Configuring the System Update Behavior of the ZENworks Agent” in the ZENworks System Updates Reference .	String	Specify the number of times you need to postpone the update.

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
PersistPolicyatUserLogout	HKLM\Software\Novell\ZCM\GroupPolicy	To persist the user association with the Group Policy Object (GPO) even after logging out of the device. The settings persists only if the same user logs into the device all the time. For more information, see User associated Group Policy Object does not persist after logging out of the device	String	Any value other than null
PingRetryCount	HKLM\Software\Novell\ZCM\	Controls the number of retries the ZENworks Agent attempts after failing to connect to a ZENworks Server during a device refresh. The default is 1 retry. For more information, see “Troubleshooting the ZENworks Agent” in the ZENworks Agent Reference .	String	Any value. Use 0 to specify no retries.
PreferredCollectionRollUpServer	64 bit Windows (Windows Server 2008, Windows Vista, Windows Server 2003, and Windows XP): HKLM\Software\Wow6432Node\Novell\ZCM\Satellite\PreferredCollectionRollUpServer 32 and 64 bit Windows (Windows 7 and Windows Server 2008 R2, and later): HKLM\Software\Novell\ZCM\Satellite\PreferredCollectionRollUpServer	To assign a different Primary Server to the Satellite, to roll up collection items instead of using a parent Primary Server. NOTE: The server URL should use the HTTPS scheme, as the communication between Satellite Servers and Primary Servers is over SSL. If the server URL does not begin with any scheme, by default, the communication is over HTTPS.	String	Multiple URLs delimited by ‘;’ Examples: <ul style="list-style-type: none">◆ https://rrt-sles11sp3.epm.blr.novell.com:443/◆ https://10.71.56.94 If the port number is 443, specifying it is optional. However, if the port number is any other value, then you need to specify it.

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
PrintWaitTime	HKLM\Software\ Novell\ZCM\PrinterPolicy	To install a Samba or a network printer by using a Printer policy. For more information, see “Printer Policy Troubleshooting” in the ZENworks Configuration Policies Reference .	String	200
ProceedPatchUninstallSetting	HKLM\SOFTWARE\ Novell\ZCM\PatchManagement	Allows you to uninstall a patch bundle. From ZENworks 11.3.1 onwards, the Uninstall application if not used within_days option in the Uninstall Options dialog will not be honored for Patch bundles. Use this registry key to honor this option for Patch bundles.	String	True
Progress	HKLM\Software\ Novell\ZCM\Migration\MSIOptions\	Displays simple progress information and error messages/prompts.	String	/qb!
read-timeout	Windows: HKLM\Software\ Novell\ZCM Linux: /etc/opt/ novell/ zenworks/conf/ xplatzmd.properties	To set the read time out value of an Agent on a device, set this registry key value to 100. For more information, see “Troubleshooting the ZENworks Agent” in the ZENworks Agent Reference .	String	100

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
ReadCachedDN	HKLM\Software\ Novell\ZCM\Zen Lgn	<p>Enables the ZENworks agent to avoid using the cached Distinguished Name (DN) on the managed device when the user attempts to log into ZENworks Server.</p> <p>This registry key needs to be used when the sAMAccountName and the Common Name for the user objects are different in ActiveDirectory. If this key is not used on the managed device, ZENworks login might fail when a change is made to the user object (Example: Moving an object to a different container or renaming the user name.)</p>	DWORD	0 - To avoid using the cached DN.1 - To use the cached DN.
ReApplyPolicyatDeviceStartup	HKLM\Software\ Novell\ZCM\GroupPolicy	<p>To apply Group policy again at device startup even if there is no change in the group policy. This is useful when group policy has security settings, which are not registry configurable. For example: Deny local login.</p> <p>For more information, see “Windows Group Policy Troubleshooting” in the <i>ZENworks Configuration Policies Reference</i>.</p>	String	Any value other than null
ReApplyPolicyatUserPre desktop	HKLM\Software\ Novell\ZCM\GroupPolicy	<p>If you have assigned Group Policy settings to a user, they might not always apply on the device.</p> <p>For more information, see “Windows Group Policy Troubleshooting” in the <i>ZENworks Configuration Policies Reference</i>.</p>	String	Any value other than null

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
REBOOT_MSG_POSTPONED_REMAINING	HKLM\Software\Novell\ZCM\System Update	This key specifies the number of times that you can postpone a reboot of an update. For more information, see “Configuring the System Update Behavior of the ZENworks Agent” in the ZENworks System Updates Reference .	String	Specify the number of times to postpone an update.
Reduced	HKLM\Software\Novell\ZCM\Migration\MSIOptions\	Displays a full user interface with wizard dialog boxes suppressed	String	/qr
RemoveZenPrintersAtLogout	HKLM\SOFTWARE\Novell\ZCM	To uninstall all installed user assigned printers at logout.You cannot uninstall the user assigned printers at logout, If the value is False. For more information, see “The user-assigned printers are not uninstalled at logout” in the ZENworks Configuration Policies Reference .	String	False/True
runBookmarksMappedDrive	HKLM\SOFTWARE\Novell\ZCM	To enforce Browser Bookmarks policy on a managed device, which has redirected home directory for saving bookmarks. For more information, see “Bookmark policy fails with a redirected home directory” in the ZENworks Configuration Policies Reference .	String	True

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
ScheduleRetries	HKLM\Software\ Novell\ZCM\	If a bundle with an assignment schedule fails to execute on a device, an attempt to execute the bundle on the device is made five times, by default. For more information, see “Assigning Existing Bundles to Devices” in the <i>ZENworks Software Distribution Reference</i> .	String	0
seticonondesktop	HKLM\Software\ Novell\ZCM\NAL	Allows you to create the shortcut icons for bundles.	String	1
SendRegKeyOnEveryRefresh	HKLM\Software\ Novell\ZCM\	Sends the registration key in the initial-web-service file on every refresh. If this value is not set to True, the agent will send the registration key only during initial registration, and during a network connect or disconnect.	String	True
ShowCancelInPrompt	HKEY_LOCAL_MACHINE\SOFTWARE\ Novell\ZCM\ActionHandler\ShowCancelInPrompt	Displays the Cancel button when the Prompt User action is configured with the Users Canceled Allowed value set as 1 or more. If the value of this registry key is set to True then the Cancel button is displayed, else, the Postpone button is displayed.	String	True
ShowDefaultNotifications	HKLM\SOFTWARE\ Novell\ZCM\SystemUpdate	By enabling this key, the explorer will not be restarted during System Update and all the System Update notifications will be displayed as metro notifications. This key is applicable only for Windows 10 (version 1903) or later platforms.	String	True

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
ShowPowerOptions	SOFTWARE\Novell\ZCM\ZAPP	To avoid the display of the power options when zapp is launched in shell mode or launched using the /s command line parameter. If the value is set to False, the power options will not be displayed in the shell mode or when launched using the /s parameter.	String	False
ShowToolTips	HKLM\SOFTWARE\Novell\ZCM\ZAPP	To prevent the display of tooltips in ZENworks Application (ZAPP). If the registry key is set to False, tooltips will not appear in ZAPP. If the registry key is set to anything other than False, tooltips will appear in ZAPP	String	False
ShutdownOnTimeout	Windows: HKEY_LOCAL_MACHINE\SOFTWARE\Novell\ZCM\ActionHandler Linux: etc/opt/novell/zenworks/conf/xplatzmd.properties	To cancel the reboot or shutdown action on a device when the value of this registry key is set to No and the user does not act on User Cancel prompt. To reboot a device when the value of ShutdownOnTimeout registry key is set to Yes .	String	Yes/No
Silent	HKLM\Software\Novell\ZCM\Migration\MSIOptions\	Displays no user interface.	String	/qn
SkipIPrintClientValidation	HKLM\Software\Novell\ZCM\Migration	To migrate an iPrint policy that does not have the policy setup file associated with it, set the value of this registry key to false.	String	False/True

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
SkipUserPermissionOnDeviceLock	HKLM\Software\Novell\ZCM\RemoteManagement\Agent	If the registry value is set to 1 on the managed device, it skips the permission from local Windows user (even with "Ask User Permission" setting enabled in the effective remote management policy) when remote operator initiates remote management operation to the same device in the locked state. After adding the registry key, restart the Remote Management services or restart the device.	DWORD	1/0
SkipZAPPLaunch	HKEY_LOCAL_MACHINE\SOFTWARE\Novell\ZCM\ZAPP\SkipZAPPLaunch	To ensure that ZAPP is not launched by the policy handler.	String	True
SortDLUPolicies	HKLM\SOFTWARE\Novell\ZCM\Dynamic Local User	By enabling this registry key, the ZENworks agent is forced to select the first policy by alphabetically ordering the DLU policies that are assigned to a user.	String	True
SqliteAsyncIOExtension	HKLM\Software\Novell\ZCM\	To improve the response of the cache memory on a managed device, enable the Asynchronous IO feature, by setting the value of this registry key to True.	String	True/False
SqliteCacheSeconds	HKLM\Software\Novell\ZCM\	To allow data to persist in the cache memory, set this registry key value to 10000. This allows the data to be present in the cache memory for 10000 milliseconds.	String	10000
SqliteCacheLimit	HKLM\Software\Novell\ZCM\	To allow a certain number of key-value pairs to persist in the Buffer cache, set this registry value to 500. This allows 500 key-value pairs to persist in the Buffer cache.	String	500

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
TurnOffDFSCheckForUNC	HKEY_LOCAL_MACHINE\SOFTWARE\Novell\ZCM	This registry key is enabled to skip the DFS verification on the UNC path. Enables faster access of CIFS shares.	String	True
UMUserFullName	HKLM\Software\Novell\ZCM\Usage	For user login name, to change the setting from User ID to Full Name mode, set this registry value to 1. For more information, see “Troubleshooting the ZENworks Agent” in the ZENworks Agent Reference .	String	1 / 0
upload-timeout	Windows: HKLM\Software\Novell\ZCM\ Linux:/etc/opt/novell/zenworks/conf/xplatzmd.properties	To set the default upload timeout value of an Agent on a managed device, set this registry key value to 200. For more information, see “Troubleshooting the ZENworks Agent” in the ZENworks Agent Reference .	String	200
USBChanges	HKLM\Software\Novell-ZES\Debug	Works in conjunction with the VolumeChanges registry key to disable scanning of USB devices. Activates previously unrecognized USB devices.	DWORD	0

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
UseProxyForRoles	HKLM\Software\ Novell\ZCM\	Determines the usage of HTTP proxy for the following server roles: Configuration, Collection, Content or Authentication.	String	A comma-separated list of server roles. The server roles could be any of the following: CONFIGURATION, CONTENT, AUTHENTICATION or COLLECTION. Example: For the CONTENT role (single role), the registry key value should be "CONTENT" and for the CONFIGURATION, COLLECTION and AUTHENTICATION roles (multiple roles), the value should be "CONFIGURATION ,COLLECTION, AUTHENTICATION".
UserDaemonRetries	HKEY_LOCAL_MACHINE\SOFTWARE\ Novell\ZCM\UserDaemonRetries	If user is not logged in to the device, then this configuration determines how many times the HKCU bundle system requirement retries to get the user daemon.	DWORD	Specify a number.
VolumeChanges	HKLM\Software\ Novell- ZES\Debug	Works in conjunction with the USBChanges registry key to disable scanning of USB devices. Activates previously unrecognized USB devices.	DWORD	0
WaitForDesktopToUnlock	HKEY_LOCAL_MACHINE\Software\ Novell\zcm\SystemUpdate	To postpone the reboot of the device, after a system update, till a user logs into the device.	String	True/False

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
WaitToKillServiceTimeout	HKLM\Software\Novell\ZCM\ActionHandler	Allows you to configure the service timeout value for services managed by ZENworks. If this registry key is not configured, then default Windows timeout values will be used.	String	Any positive integer value. (Example: 30000 for 30 seconds)
WaitForWatcher	HKLM\SOFTWARE\Novell\ZCM\SystemUpdate	Forces a device reboot after the device is updated, even if the user is not logged-in.	String	False
WEBUSAGE_FIREFOX	HKLM\Software\Novel1\ZCM\	To Enable or Disable Web Usage Tracking on Firefox. By default Web Usage Tracking will be enabled on Firefox.	String	True/False
WEBUSAGE_IE	HKLM\Software\Novel1\ZCM\	To Enable or Disable Web Usage Tracking on Internet Explorer. By default Web Usage Tracking will be enabled on Internet Explorer.	String	True/False
WEBUSAGE_CHROME	HKLM\Software\Novel1\ZCM\	To Enable or Disable Web Usage Tracking on Chrome. By default Web Usage Tracking will be disabled on Chrome. NOTE: If you enable web application usage on the Chrome browser, the browser might hang intermittently.	String	True/False
WEBUSAGE_EDGE	HKLM\Software\Novel1\ZCM\	To Enable or Disable Web Usage Tracking on the Edge browser. By default Web Usage Tracking will be disabled on the Edge browser. NOTE: If you enable web application usage on the Edge browser, the browser might hang intermittently.	String	True/False
WEB_SERVER_PORT	HKEY_LOCAL_MACHINE\SOFTWARE\Novell\ZCM\	To set the QuickTask port on the ZENworks managed device. For more information, refer to TID 7016363 in the knowledgebase .	DWORD	A 32-bit number.

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
ZENCachePersistObjectsAsynchronously	HKLM\Software\ Novell\ZCM	To improve the login performance on Terminal servers, enable the asynchronous persistence of objects.	String	True / False
ZenNotifyConnectionTimeOut	HKEY_LOCAL_MACHINE\SOFTWARE\ Novell\ZCM\	<p>To configure the timeout value in seconds for a ZENworks service to update the ZenNotifyIcon Progress window.</p> <p>The ZENworks service calls the <code>ZenNotifyIcon</code> process to update the bundle's progress in the ZenNotifyIcon Progress window, and waits for <code>ZenNotifyIcon</code> to update the bundle's progress and return the call.</p> <p>If the <code>ZenNotifyIcon</code> process does not return the call to the ZENworks service within the timeout period, then the ZENworks service will proceed to the next action in the bundle schedule.</p>	DWORD	Any value greater than zero (in seconds).
ZENThreadPoolMax	HKLM\Software\ Novell\ZCM\	This registry key defines the maximum thread count in ZENworks thread pool. The default value is 150 on a Terminal server and 50 on other devices.	String	Specify a number.
ZENThreadPoolMin	HKLM\Software\ Novell\ZCM	This registry key defines the minimum thread count in ZENworks thread pool. The default minimum thread count is 3. Specify a number greater than the default value.	String	Specify a number.

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
IMPORTANT: ZISWINClear	HKLM\Software\ Novell\ZCM	When this string value is set to 1, ZISWIN clears all the Image Safe data and exits without performing any other task. For more information, see <i>Novell ZENworks ISD Service in .ZENworks Preboot Services and Imaging Reference</i>	String	1
ZISWIN Disabled	HKLM\Software\ Novell\ZCM	When this string value is set to 1, ZISWIN exits without performing any task. For more information, see <i>ZENworks Preboot Services and Imaging Reference</i> .	String	1
ZISWIN Reset Flag	HKLM\Software\ Novell\ZCM	When this string value is set to 1, ZISWIN sets the Just Imaged flag to FALSExits without performing any other task. For more information, see the <i>ZENworks Preboot Services and Imaging Reference</i> .	String	1
ZISWIN Do Not Restore Mask	HKLM\Software\ Novell\ZCM	You can use this DWORD to specify the Image Safe data component that you do not want ZISWIN to restore to the Windows registry after a successful completion of an image. This value is interpreted as a mask. For more information, see the <i>ZENworks Preboot Services and Imaging Reference</i> .	DWORD	Desired value of the Image Safe data component.

Registry Key Name	Registry Key Path	Description	Registry Key Type	Registry Key Value
ZISWIN SYSPrep Restore Mask	HKLM\Software\ Novell\ZCM	If you are using the SYSPrep process to mask the Image Safe data components, then use this registry key. For more information, see “ZENworks Imaging Engine Commands” in the ZENworks Preboot Services and Imaging Reference .	DWORD	Desired value of the Image Safe data component.
ZISWIN Do Not Collect Mask	HKLM\Software\ Novell\ZCM	You can use this DWORD to specify the components that you do not want ZISWIN to collect in the Image Safe data. For more information, see “Component Masks” in the ZENworks Preboot Services and Imaging Reference .	DWORD	Desired value of the Image Safe data component.
ZISWIN Clear Mask	HKLM\Software\ Novell\ZCM	You can use this DWORD to specify the components that you want ZISWIN to clear from the Image Safe data. For more information, see “Component Masks” in the ZENworks Preboot Services and Imaging Reference .	DWORD	Desired value of the Image Safe data component.