ZENworks Mobile Management 3.2.x

Integrating the ZENworks Mobile Management Dashboard into ZENworks Control Center

Novell

If you use ZENworks Control Center to manage one or more ZENworks 11 products, you can integrate the ZENworks Mobile Management dashboard into ZENworks Control Center. This allows you, or other administrators, to log in to ZENworks Control Center to manage both ZENworks 11 and ZENworks Mobile Management.

Novell. ZENworks. ^{Zone: ZONE_1124}				Welcome, jenos Help+ Logout
Policies Bundles Patch Management Show Help	Users Organizaton Reporting	System	Wełcome, j	ienos \Lambda O Aleris Help Logout
 ■ Deployment ■ Reports ■ Configuration ■ Asset Management ■ Endpoint Security ■ Mobile Management ■ Mobile Management ■ Mobile Management ■ Custom Co ■ Custom Co ■ Device Cor ■ Current Session ■ All Sessions ■ Novel Zčilwarts 1000 	Servers Com tive LDAP & File 9 lumns & Grou nection & Mobi es de Oper	bliance Manager 🤤	CalDAV Servers CardDAV Servers Exchange Servers DAP Servers Mail Servers SCEP Servers Subscribed Calendars VPNs Web Clips	Android Corporate Resources

Review the information and complete the tasks in the following sections to integrate the ZENworks Mobile Management dashboard into ZENworks Control Center:

- Section 1, "Integration through OpenID," on page 2
- Section 2, "Administrator Support," on page 2
- Section 3, "Requirements," on page 2
- Section 4, "Configuring ZENworks Mobile Management," on page 2
- Section 5, "Configuring ZENworks 11," on page 7
- Section 6, "Accessing the Mobile Management Dashboard in ZENworks Control Center," on page 8
- Section 7, "Legal Notices," on page 9

1 Integration through OpenID

The OpenID standard is used to integrate the ZENworks Mobile Management dashboard into ZENworks Control Center.

The ZENworks 11 Server functions as an OpenID provider. When an administrator logs in to ZENworks Control Center and clicks the Mobile Management link, the ZENworks 11 Server authenticates the administrator to ZENworks Mobile Management and displays the dashboard.

2 Administrator Support

ZENworks Mobile Management provides two levels of administrators: System Administrator and Organization Administrator. A System Administrator can manage the system and all organizations. An Organization Administrator can manage a single organization.

You can support login through ZENworks Control Center for all System Administrators or for the Organization Administrators of one organization. Login for both System Administrators and Organization Administrators is not supported, and login for Organization Administrators from multiple organizations is not supported.

3 Requirements

- Version Support: The minimum versions required for integration are:
 - ZENworks 11.2.4 You must download and apply a patch to enable integration in ZENworks 11.2.4. The patch is not required for newer ZENworks versions. For details, see Novell TID 7014106 (http://www.novell.com/support/kb/doc.php?id=7014106).
 - ZENworks Mobile Management 2.7
- Administrator Accounts: An administrator must have both a ZENworks Control Center account and a ZENworks Mobile Management account. The ZENworks Mobile Management account can be either a System Administrator account or an Organization Administrator account. The two accounts do not need to have the same username and password.

4 Configuring ZENworks Mobile Management

Complete the following configuration tasks in the ZENworks Mobile Management dashboard:

- Section 4.1, "Configuring a ZENworks OpenID Provider," on page 2
- Section 4.2, "Enabling OpenID Login for Administrators," on page 4

4.1 Configuring a ZENworks OpenID Provider

To enable System Administrators to access the ZENworks Mobile Management dashboard through ZENworks Control Center, you configure the ZENworks OpenID provider at the system level.

To enable the Organization Administrators for an organization to access the dashboard through ZENworks Control Center, you configure the ZENworks OpenID provider at the organization level.

The following sections provide instructions:

- Section 4.1.1, "Configuring a ZENworks OpenID Provider for the System," on page 3
- Section 4.1.2, "Configuring a ZENworks OpenID Provider for an Organization," on page 3

4.1.1 Configuring a ZENworks OpenID Provider for the System

In order for ZENworks Mobile Management System Administrators to access the ZENworks Mobile Management dashboard from ZENworks Control Center, you must configure a ZENworks OpenID provider for the system.

- 1 Launch the ZENworks Mobile Management dashboard as a System Administrator with full rights.
- 2 Click System > System Administration > OpenID Provider.

Settings > System Administration > O	penID Provider	
OpenID Provider		
Enabled:		
Predefined Providers:	ZENworks	
OpenID Provider URL:		
OpenID Return URL:		Use Default
OpenID Pin:	Reset All Pins	
OpenID Provider Description		
Notes for OpenID Provider		

- 3 Configure the following settings:
 - Enabled: Select the checkbox to enable the provider.
 - Predefined Providers: Select ZENworks.
 - OpenID Provider URL: Specify the ZENworks Primary Server address in the following form:

https://server:port/zenworks/?requestHandler=ZENOpenIDHandler

Replace *server.port* with the hostname (or IP address) and port of the ZENworks Primary Server. The port is required only if the server is using a non-standard port.

- **OpenID Return URL:** Click *Use Default* to populate the field with the address of the current ZENworks Mobile Management server.
- 4 Click Save Changes.

4.1.2 Configuring a ZENworks OpenID Provider for an Organization

In order for ZENworks Mobile Management Organization Administrators to access the ZENworks Mobile Management dashboard from ZENworks Control Center, you must configure a ZENworks OpenID provider for the organization.

- 1 Launch the ZENworks Mobile Management dashboard as a System Administrator with full rights.
- 2 Click Organization > OpenID Providers (under Organization Control).
- 3 Click Add OpenID Provider.

4 In the Predefined Providers list, select ZENworks.

🚺 Add Organization Ope	enID Provider X
Add OpenID Provider	OpenID Providers allow admins to authenticate without entering a password on the dashboard.
	Organization Alias: Novell
	Predefined Providers: * ZENworks
	Zone: *
	OpenID Provider URL: *
	OpenID Return URL: *
	Finish

- 5 Configure the following settings:
 - **Zone:** Specify a name for the ZENworks OpenID provider. This name is used in the ZENworks 11 system to authenticate to this organization via the OpenID provider.
 - OpenID Provider URL: Specify the ZENworks Primary Server address in the following form:

https://server:port/zenworks/?requestHandler=ZENOpenIDHandler

Replace *server.port* with the hostname/IP address and port of the ZENworks Primary Server. The port is required only if the server is using a non-standard port.

- **OpenID Return URL:** Click *Use Default* to populate the field with the address of the current ZENworks Mobile Management server.
- 6 Click Finish.

4.2 Enabling OpenID Login for Administrators

You must enable OpenID login for each administrator who plans to access the ZENworks Mobile Management dashboard through ZENworks Control Center.

- Section 4.2.1, "Enabling Existing System Administrators," on page 4
- Section 4.2.2, "Creating and Enabling New System Administrators," on page 5
- Section 4.2.3, "Enabling Existing Organization Administrators," on page 6
- Section 4.2.4, "Creating and Enabling New Organization Administrators," on page 6

4.2.1 Enabling Existing System Administrators

- 1 Launch the ZENworks Mobile Management dashboard as a System Administrator with full rights.
- 2 Click System > System Administration > System Administrators.
- **3** In the *System Administrators* list, select the administrator for whom you want to enable OpenID login.

4 Select the Use OpenID check box.

em Administrators			
System Administrators	Administrator Groups		
Display Name	Administrator Username	OpenID Identity	Contact E-Mail Address
admin@zmm.net	admin@zmm.net		admin@zmm.net
Jenny Wright	jwright@zmm.net		jwright@zmm.net
			Þ
Use OpenID: Not OpenID Identity: Op Display Name: * Je	te: It is recommended to have at least enID could make your account unavails enID has not been set yet. nny Wright right@zmm.net	, one local System Administrator. S ble if the provider is down.	
Use OpenID: Not OpenID Identity: Op Display Name: * Je	enID could make your account unavails enID has not been set yet. nny Wright	ne local System Administrator. Die if the provider is down.	iwitching to
Use OpenID: VeropenID: Use OpenID Identity: Op Display Name: * Je E-mail Address: * jw Pin:	enID could make your account unavails enID has not been set yet. nny Wright right@zmm.net	ne local System Administrator. S ble if the provider is down.	
Use OpeniD: OpeniD Identity: Op Display Name: * Je E-mail Address: * jiw Pin: Role: * Fin	enD could make your account unavaila tenID has not been set yet. nny Wright rright@zmm.net Reset Pin	, one local System Administrator. S ble if the provider is down.	
Use OpeniD: OpeniD Identity: Op Display Name: * Je E-mail Address: * jiw Pin: Role: * [Fe Default View: * §	enID could make your account unavails enID has not been set yet. nny Wright tright@zmm.net Reset Pin 41 Admin • stem •	, one local System Administrator. ble if the provider is down.	
Use OpenID: OpenID Identity: Op Display Name: * / Ie E-mail Address: * jw Pin: Role: * Fw Default View: * Sy stem Timeout (minutes): * 20	enD Could make your account unavaila enID has not been set yet. nny Wright right@zmm.net Reset Pin III Admin v	ne local System Administrator. S ble if the provider is down.	
Use OpenID: OpenID Identity: Op Display Name: * Je E-mail Address: * jiw Pin: Role: * Fu	enID could make your account unavails enID has not been set yet. nny Wright right@zmm.net Reset Pin til Admin v stem v	ne local System Administrator. S ble if the provider is down.	

5 Click Save Changes.

The administrator is sent an e-mail with the OpenID PIN needed the first time he or she logs in to ZENworks Mobile Management through ZENworks Control Center. For information about this login process, see Section 6, "Accessing the Mobile Management Dashboard in ZENworks Control Center," on page 8.

4.2.2 Creating and Enabling New System Administrators

- **1** Launch the ZENworks Mobile Management dashboard as a System Administrator with full rights.
- 2 Click System > System Administration > System Administrators.
- 3 Click Add System Administrator.

🧨 Add System Administr	rator X
Welcome	Welcome to the Add New Administrator Wizard
	Choose how the administrator(s) will be authenticated:
	(Manual) (DAP) (OpenID)

4 Click OpenID.

5 Follow the prompts to define the OpenID details and account settings.

After you click *Finish*, the administrator account is created and the administrator is sent an e-mail with the OpenID PIN needed the first time he or she logs in to ZENworks Mobile Management through ZENworks Control Center. For information about this login process, see Section 6, "Accessing the Mobile Management Dashboard in ZENworks Control Center," on page 8.

4.2.3 Enabling Existing Organization Administrators

- 1 Launch the ZENworks Mobile Management dashboard as a System Administrator with full rights.
- 2 Click System > Organization Administrators.
- **3** In the *Organization Administrators* list, select the administrator for whom you want to enable OpenID login.
- 4 Select the Use OpenID check box.
- 5 In the OpenID Provider field, select the ZENworks OpenID provider.

Organization Administrators	Administrator Groups		
Display Name	Administrator Username	OpenID Identity	Contact E-Mail Address
kburnett		https://www.google.com/accounts/o	kburnett@novell.com
Jon Enos	jenos@zmm.net		jenos@zmm.net
Bob Jones	bjones@zmm.net		bjones@zmm.net
4			
	D has not been set yet.		
	T NOS		
OpenID Identity: OpenI OpenID Provider: <u>novell</u> Display Name: Jon E E-mail Address: jenos Carrier: <u>None</u> Phone Number:	nos @zmm.net		
OpenID Identity: OpenI OpenID Provider: <u>newell</u> Display Name: <u> </u> <u>Jon E</u> E-mail Address: <u> </u> <u>jenos</u> Carrier: <u>None</u> Phone Number: <u> </u> dd to Alert Recipients List: <u> </u>	nos @zmm.net		
OpenID Identity: OpenI OpenID Provider: <u>newell</u> Display Name: <u> </u> <u>Jon E</u> E-mail Address: <u> </u> <u>jenos</u> Carrier: <u>None</u> Phone Number: <u> </u> dd to Alert Recipients List: <u> </u>			
OpenID Identity: OpenI OpenID Provider: novell Display Name: + Jon E E-mail Address: + Jene Carrier: None Phone Number: dd to Alert Recipients List: Pin:	v nos @zmm.net v Reset Pin		
OpenID Identify: O penI OpenID Provider: <u>novell</u> Display Name: <u>(jon E</u> E-mail Address: <u>(jenos</u> Carrier: <u>None</u> Phone Number: <u>(</u>) dd to Alert Recipients List: <u>)</u> Pin: <u>(jon E</u> Role: <u>(jon Euro</u>)	v nos @zmm.net v Reset Pin		

6 Click Save Changes.

The administrator is sent an e-mail with the OpenID PIN needed the first time he or she logs in to ZENworks Mobile Management through ZENworks Control Center. For information about this login process, see Section 6, "Accessing the Mobile Management Dashboard in ZENworks Control Center," on page 8.

4.2.4 Creating and Enabling New Organization Administrators

- 1 Launch the ZENworks Mobile Management dashboard as a System Administrator with full rights.
- 2 Click System > System Administration > System Administrators.

3 Click Add Administrator.

🧨 Add Organization Add	inistrator		×
Welcome	Welcome to the Add New Adminis	strator Wizard	
	Choose how the administrator(s)	will be authenticated:	
	(Manual) LDAP	OpenID	

- 4 Click OpenID.
- 5 Follow the prompts to define the OpenID details and account settings.

After you click *Finish*, the administrator account is created and the administrator is sent an e-mail with the OpenID PIN needed the first time he or she logs in to ZENworks Mobile Management through ZENworks Control Center. For information about this login process, see Section 6, "Accessing the Mobile Management Dashboard in ZENworks Control Center," on page 8.

5 Configuring ZENworks 11

1 Log in to ZENworks Control Center as an administrator who has rights to modify Management Zone settings.

Super administrators and any administrators with the *Zone Rights - Modify Settings* right can modify zone settings.

- 2 Click Configuration.
- 3 In the Management Zone Settings panel, click *Mobile Management > Mobile Management Zone* Registration.

Novell. ZENworks. Zone: ZONE_1124		Welcome, Administrator	Help∗	Logout	5
 Home Devices Users 	Configuration > Mobile Management Zone Registration			œ) 🗸
Policies	Mobile Management Zone Registration				×
g Bundles	Register a Mobile Management Zone with ZENworks Control Center				
🕴 Patch Management					
Deployment	Mobile Management Zone Registration				~
Reports	Register ZENworks Mobile Management Server				
A Configuration					
Asset Management	Mobile Management server hostname or IP address: *				
Endpoint Security					
Full Disk Encryption Configuration Tasks	Mobile Management zone name:				
Message Cleanup					
Password Key Generator					
Frequently Used	* Fields marked with an asterisk are required.				
Quick Tasks	OK Apply Reset Cancel				
Display Quick Tasks for:					
Current Session					
All Sessions					

- 4 Enable the Register ZENworks Mobile Management Server option, then fill in the following fields:
 - Mobile Management Server Hostname or IP Address: Specify the hostname or IP address of the ZENworks Mobile Management server.
 - **Mobile Management Zone Name:** Leave this field blank to enable login by ZENworks Mobile Management System Administrators.

To enable login by Organization Administrators, specify the zone name that is assigned to the ZENworks OpenID provider in the administrators' organization.

5 Click *OK* to save the settings.

6 Accessing the Mobile Management Dashboard in ZENworks Control Center

- 1 Log in to ZENworks Control Center.
- 2 Click Mobile Management to display the Admin Setup Pin Code prompt:

Novell. ZENworks. Zane: ZONE_1124		Welcome, jenos Help+ Logout 🔨
	Noveli. Doveli. Doveri. Doveri.	

3 Enter the OpenID PIN you were e-mailed, then click *OK* to authenticate to ZENworks Mobile Management and display the dashboard.

Parton Management Reports Configuration Asset Management Endpoint Security Pull Disk Encryption Mobile Management Mobile Apps Mobile Apps Mobile Apps Mobile Management Mobile Management Mobile Management Mobile Apps SMTP Servers <	 Home Devices Users Policies Bundles 	Activity Monitor	n Reporting System	Welcome,	jenos 🗥 0 Alerts Help Logout
Pedpoint Security Pull Disk Encryption Image: Compliance Manager Image: Access Point Names Image: Wi-Fi Networks Administrative LDAP Image: File Share Image: ColDAV Servers CalDAV Servers wobile Management Image: Compliance Manager Image: ColDAV Servers CalDAV Servers wobile Management Image: ColDAV Servers Image: ColDAV Servers Image: ColDAV Servers Image: ColDAV Servers Image: ColDAV Servers Image: ColDAV Servers Image: ColDAV Servers Image: ColDAV Servers Image: ColDAV Servers Image: ColDAV Servers Image: ColDAV Servers Image: ColDAV Servers Image: ColDAV Servers Image: ColDAV Servers Image: ColDAV Servers Image: ColDAV Servers Image: ColDAV Servers Image: ColDAV Servers Image: ColDAV Servers Image: ColDAV Servers Image: ColDAV Servers Image: ColDAV Servers Image: ColDAV Servers Image: ColDAV Servers Image: Source Image: ColDAV Servers Image: ColDAV Servers Image: ColDAV Servers Image: Source Image: ColDAV Servers Image: ColDAV Servers Image: ColDAV Servers Image: Source Image: ColDAV Servers Image: ColDAV Servers Image: ColDAV Servers <	Deployment Reports		Organization Control	iOS Corporate Resources	Android Corporate Resources
Subscribed Calendars	Endpoint Security Full Disk Encryption Mobile Management quently Used & ck Tasks & splay Quick Tasks for: & Current Session	Administrative LDAP Servers Custom Columns Device Connection Schedules	File Share Group E-mailing Mobile Apps	CalDAV Servers	™∰ Wi-Fi Networks
			SMTP Server	SCEP Servers	

Your ZENworks Control Center administrator account is now linked to your ZENworks Mobile Management administrator account. Whenever you are in ZENworks Control Center and click *Mobile Management*, you will be automatically authenticated to the ZENworks Mobile Management dashboard.

7 Legal Notices

Novell, Inc. makes no representations or warranties with respect to the contents or use of this documentation, and specifically disclaims any express or implied warranties of merchantability or fitness for any particular purpose. Further, Novell, Inc. reserves the right to revise this publication and to make changes to its content, at any time, without obligation to notify any person or entity of such revisions or changes.

Further, Novell, Inc. makes no representations or warranties with respect to any software, and specifically disclaims any express or implied warranties of merchantability or fitness for any particular purpose. Further, Novell, Inc. reserves the right to make changes to any and all parts of Novell software, at any time, without any obligation to notify any person or entity of such changes.

Any products or technical information provided under this Agreement may be subject to U.S. export controls and the trade laws of other countries. You agree to comply with all export control regulations and to obtain any required licenses or classification to export, re-export, or import deliverables. You agree not to export or re-export to entities on the current U.S. export exclusion lists or to any embargoed or terrorist countries as specified in the U.S. export laws. You agree to not use deliverables for prohibited nuclear, missile, or chemical biological weaponry end uses. Please refer to the Novell International Trade Services Web page (http://www.novell.com/info/exports/) for more information on exporting Novell software. Novell assumes no responsibility for your failure to obtain any necessary export approvals.

Copyright © 2013-15 Novell, Inc. All rights reserved. No part of this publication may be reproduced, photocopied, stored on a retrieval system, or transmitted without the express written consent of the publisher.

For Novell trademarks, see the Novell Trademark and Service Mark list (http://www.novell.com/ company/legal/trademarks/tmlist.html).

All third-party trademarks are the property of their respective owners.