Functionality by Device Platform

ZENworks. Mobile Management 2.6.x

February 2013

Legal Notices

Novell, Inc., makes no representations or warranties with respect to the contents or use of this documentation, and specifically disclaims any express or implied warranties of merchantability or fitness for any particular purpose. Further, Novell, Inc., reserves the right to revise this publication and to make changes to its content, at any time, without obligation to notify any person or entity of such revisions or changes.

Further, Novell, Inc., makes no representations or warranties with respect to any software, and specifically disclaims any express or implied warranties of merchantability or fitness for any particular purpose. Further, Novell, Inc., reserves the right to make changes to any and all parts of Novell software, at any time, without any obligation to notify any person or entity of such changes.

Any products or technical information provided under this Agreement may be subject to U.S. export controls and the trade laws of other countries. You agree to comply with all export control regulations and to obtain any required licenses or classification to export, re-export or import deliverables. You agree not to export or re-export to entities on the current U.S. export exclusion lists or to any embargoed or terrorist countries as specified in the U.S. export laws. You agree to not use deliverables for prohibited nuclear, missile, or chemical biological weaponry end uses. See the Novell International Trade Services Web page (http://www.novell.com/info/exports/) for more information on exporting Novell software. Novell assumes no responsibility for your failure to obtain any necessary export approvals.

Copyright © 2012-13 Novell, Inc. All rights reserved. No part of this publication may be reproduced, photocopied, stored on a retrieval system, or transmitted without the express written consent of the publisher.

Novell, Inc. 1800 South Novell Place Provo, UT 84606 U.S.A. www.novell.com

Online Documentation: To access the latest online documentation for this and other Novell products, see the Novell Documentation Web page (http://www.novell.com/documentation).

Novell Trademarks

For Novell trademarks, see the Novell Trademark and Service Mark list (http://www.novell.com/company/legal/trademarks/tmlist.html).

Third-Party Materials

All third-party trademarks are the property of their respective owners.

TABLE OF CONTENTS

| Policy Rules: All Devices | ŧ. |
|--------------------------------|----|
| Policy Rules: iOS Devices | 16 |
| Policy Rules: TouchDown | 19 |
| Security: All Devices | 30 |
| Device Statistics: All Devices | 34 |
| Compliance Manager | 39 |

▶ Policy Rules: All Devices

Audit Tracking

Device Control

- Device Features
- Email
- ActiveSync Synchronization

Files Share Permissions

Mobile Apps Permissions

Security Settings

- Password
- Encryption
- Device Inactivity and Locking
- Emergency Calling

S/MIME Settings

► Policy Rules: iOS Device

- Device Features
- Applications
- Safari Browser
- Ratings
- Security

▶ Policy Rules: TouchDown

- Installation
- General
- Signature
- Widgets
- Phone Book
- Suppression Rules

► Security: All Devices

- Security Commands
- Network Connection Security and Configuration

▶ Device Statistics: All Devices

Device Statistics

▶ Compliance Manager

- Access Policies and Device Restrictions
- Non-Access Policy Based and Event Based Alerts

The information in these tables describes functionality supported by each device platform for ZENworks Mobile Management, version 2.6.x.

Device platforms supported by *ZENworks Mobile Management* are Android, BlackBerry with *NotifySync*, iOS, Symbian S60 3rd edition, webOS, Windows Mobile 6, and Windows Phone. Supported device operating system versions are listed below.

| Anrd | TD/A | NS/BB | iOS | TD/iOS | S60 | wOS | WM | WP |
|----------------------------------|--|---|--|---|--|---|--|---|
| • | 4 | <u>=</u> | 105 | 4 | S60° | web | Att . | • |
| Android devices OS v2.2 – 4.0 | Android devices OS v2.0 - 4.0 with TouchDown v7.3.x | BlackBerry devices OS v4.5 – 7.1 with NotifySync v4.9 or greater | iOS 4.3 – 6.0.1 multitasking devices | iOS 4.3 – 6.0.1 multitasking devices with TouchDown v1.3.8 | Symbian S60 3rd edition devices OS v 9.1 | WebOS devices OS v1.4.3/1.4.5, 2.0.0/2.0.1, 2.1.2 | Windows Mobile devices OS v6.1/6.5 | Windows Phone devices OS v7, 7.5, 8 |

The ZENworks Mobile Management Device Application

Android, iOS, Symbian S60 3rd Edition, and Window Mobile devices use the *ZENworks Mobile Management* device application to provide additional functionality and enforce policies that are not handled by ActiveSync. The *NotifySync for BlackBerry* application, which interfaces with *ZENworks Mobile Management*, has an MDM component that enforces ActiveSync policies and provides additional functionality for BlackBerry devices. (Requires an additional *NotifySync* license.)

The device platforms listed above also require a native ActiveSync protocol or an application that uses the ActiveSync protocol, such as *NotifySync for BlackBerry* or *TouchDown for Android*.

- On Android OS 2.2 or greater devices, the ActiveSync protocol native to the device is sufficient; although the TouchDown application, offers greater functionality. See <u>Policy Rules: TouchDown</u>
 - For devices running OS versions 2.0 or 2.1, the *TouchDown* application (available from the Play Store) is required to handle the ActiveSync policies. On OS 2.0/2.1 devices, ActiveSync policies affect only the TouchDown account and data.
- On BlackBerry devices, *NotifySync for BlackBerry* v4.9.x or greater is the ActiveSync application required to handle the ActiveSync policies. The application has an MDM component that interfaces with *ZENworks Mobile Management* and provides additional functionality. (Requires an additional *NotifySync* license.)
- On iOS 4 6 devices with multitasking capabilities, the ActiveSync policies are enforced by using Apple configuration profiles.
- On Symbian S60 3rd Edition devices, *Mail for Exchange* is required to handle the ActiveSync policies.
- On Windows Mobile 6.1/6.5 devices, the ActiveSync protocol native to the device is sufficient.

Enrolling Android, iOS, Symbian, or Windows Mobile 6 devices without the *ZENworks Mobile Management* app is not recommended, because only ActiveSync policies supported by the device platform or model can be enforced. BlackBerry devices do not have native ActiveSync capabilities and are not supported without the *NotifySync* app.

ActiveSync Only Devices

webOS and Windows Phone platforms, for which there are no ZENworks Mobile Management applications, are also supported. Because these devices utilize the native ActiveSync protocol alone, only ActiveSync policies supported by the device platform or model can be enforced.

POLICY RULES: ALL DEVICES

ZENworks Mobile Management is a trademark of Novell, Inc. The abbreviation "ZMM" is not a Novell trademark, but is used in these tables because of space constraints.

• A red dot indicates **ActiveSync only** - Currently, there is no *ZENworks Mobile Management* app available for WP or wOS. Devices support the feature via the native ActiveSync app on the device. BlackBerry devices have no native ActiveSync app and are only supported with the NotifySync app

| Policy Suite Rules: All Devices | Description | Anrd | Anrd w/o ZMM | TD/A | NS/BB | iOS | TD/ iOS | iOS w/o ZMM | S60 | S60 w/o ZMM | wOS | WM | WM w/o ZMM | WP |
|---------------------------------------|---|------|--------------------|------|-------|-----|------------|-------------------|-----|-------------------|-----|----|------------------|----|
| Audit Tracking | | | | | | | | | | | | | | |
| Archive Files on Device | Requires the device to periodically send a list of all folders and files stored on the device and the SD card to the server. Displayed on the server in the User Profile: File Archive Symbian devices: Sends most files, with | | | _ | _ | | | | | | | | | |
| | the exception of those in the device's X:\private and X:\sys folders, which normally contain system files or sensitive application data. The administrator defines the frequency of the file archiving. | • | | • | • | | | | • | | | | | |
| Record Phone Log | Requires the device to send all telephone log information to the server. For BlackBerry devices with NotifySync, tracks only calls made after ZENworks Mobile Management enrollment. | • | | • | • | | | | • | | | | | |
| Record Text/Multimedia Message Log | Requires the device to send all Short Message Service (SMS) and Multimedia Messaging Service (MMS) information to server. BlackBerry devices with NotifySync: | • | | • | • | | | | • | | | | | |
| | Do not track MMS messages | | | | | | | | | | | | | |
| | Track only texts made after ZENworks | | | | | | | | | | | | | |

| Policy Suite Rules: All Devices | Description | Anrd | Anrd w/o ZMM | TD/A | NS/BB | iOS | TD/ iOS | iOS w/o ZMM | S60 | S60 w/o ZMM | wOS | WM | WM w/o ZMM | WP |
|--|---|------|--------------------|------|-------|-----|------------|-------------------|-----|-------------------|-----|----|------------------|----|
| | Mobile Management enrollment Some devices use only MMS, so text messaging is not tracked Android devices: Text and MMS logging functionality might vary based on the device manufacturer or carrier. (See the SMS & MMS Capabilities document.) Symbian S60 3 and Windows Mobile devices: Records only SMS messages. | | | | | | | | | | | | | |
| Record Location of Device (Latitude / Longitude) | Uses GPS or triangulation on the device to locate where a user's device is at all times. Information is displayed using Google Maps. The device reports longitude and latitude as two separate values. | • | | • | • | • | • | | • | | | | | |
| GPS Location Accuracy | Allows administrators to specify a level of location accuracy. Accuracy primarily depends on using a cell tower vs. GPS (satellite) location methods; additional factors may be involved depending on the device type. Because improved accuracy generally results in increased battery usage, the level can be adjusted to facilitate a more efficient use of a device battery. Set levels via the policy suite. | • | | • | • | • | • | | | | | | | |
| Device Controls: Device Features | | | | | | | | | | | | | | |
| Allow Bluetooth (ActiveSync) | Determines whether Bluetooth is allowed to operate on the device. There are three settings: Don't allow Bluetooth Allow only Bluetooth headsets | | | | | | | | | | | • | • | |
| Allow Browser (ActiveSync) | Allow all Bluetooth Determines whether the use of the native Web browser is allowed on the device. This setting might also prevent | | | | | • | • | • | | | | • | • | |

| Policy Suite Rules: All Devices | Description | Anrd | Anrd w/o ZMM | TD/A | NS/BB | iOS | TD/ iOS | iOS w/o ZMM | S60 | S60 w/o ZMM | wOS | WM | WM w/o ZMM | WP |
|---|--|------|--------------------|------|-------|-----|------------|-------------------|-----|-------------------|-----|----|------------------|----|
| | the use of third-party browsers that use the native browser as a basis for operation. | | | | | | | | | | | | | |
| Allow Camera (ActiveSync) | Determines whether the use of the device camera is allowed. Disabling the camera might limit the functionality of third-party apps that use the camera such as: Photoshop. | • | • | • | | • | • | • | | | | • | • | |
| | For Android: supported on devices with OS 4.0 and ZENworks Mobile Management device application. | | | | | | | | | | | | | |
| Allow Infrared (ActiveSync) | Determines whether infrared connections are allowed to and from the device. | | | | | | | | | | | • | • | |
| Allow Internet Sharing from the Device (Tethering) | Determines whether the device can be used as a modem for a desktop or a portable computer. | | | | | | | | | | | • | • | |
| (ActiveSync) | portable compared. | | | | | | | | | | | | | |
| Allow Remote Desktop (ActiveSync) | Determines whether a remote desktop connection can be created from the device. | | | | | | | | | | | • | • | |
| Allow SD Card (ActiveSync) | Determines whether using an SD Card is allowed on the device. | | | | | | | | | | | | | |
| | For Android w/ TouchDown: Allows or disallows SD card access for the TouchDown application only. | | | • | | | | | | | | • | • | |
| Allow Synchronization from a Desktop (ActiveSync) | Determines whether the device can synchronize with a computer through a cable, Bluetooth, or IrDA connection. | | | | | | | | | | | • | • | |
| Allow Text Messaging (ActiveSync) | Determines whether the device can send or receive text messages. | | | | | | | | | | | • | • | |
| Allow Wi-Fi (ActiveSync) | Determines whether wireless Internet access is allowed on the device. | | | | | | | | | | | • | • | |
| Device Controls: Email | | | | | | | | | | | | | | |
| Allow HTML formatted Email | Determines whether email synchronized to the device can be in HTML format. | | | • | • | | • | | | | | • | • | |

| Description | Anrd | Anrd w/o ZMM | TD/A | NS/BB | iOS | TD/ iOS | iOS w/o ZMM | S60 | S60 w/o ZMM | wOS | WM | WM w/o ZMM | WP |
|---|--|--|--|--|---|--|--|---|---|---|--|---|--|
| Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. | | | | | | | | | | | | | |
| Defines the maximum HTML email body size of messages received on the device. | | | | | | | | | | | | | |
| Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. | | | | • | | | | | | | | • | |
| Determines whether the user can use Windows Live services, such as Hotmail, Office, or Spaces. | | | | | | | | | | | • | • | |
| Determines whether the device can access POP3 or IMAP4 email. | | | | | | | | | | | • | • | |
| Defines the maximum email body size of plain text messages received on the device. | | | • | • | | • | | | | | • | • | |
| | | | | | | | | | | | | | |
| Defines the maximum look-back age of calendar events. Events older than the maximum age are automatically removed from the device. Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. | | | • | • | | • | | | | | • | • | • |
| Defines the maximum age of email on the device. Email older than the maximum age is automatically removed from the device. | | | • | • | • | • | • | | | | • | • | • |
| Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. | | | | | | | | | | | | | |
| Enforces the use of manual synchronization on the device while roaming to avoid the higher data costs that are often incurred with automatic | | | • | • | • | • | • | | | | • | • | |
| | Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Defines the maximum HTML email body size of messages received on the device. Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Determines whether the user can use Windows Live services, such as Hotmail, Office, or Spaces. Determines whether the device can access POP3 or IMAP4 email. Defines the maximum email body size of plain text messages received on the device. Defines the maximum look-back age of calendar events. Events older than the maximum age are automatically removed from the device. Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Defines the maximum age of email on the device. Email older than the maximum age is automatically removed from the device. Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Enforces the use of manual synchronization on the device while roaming to avoid the higher data costs | Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Defines the maximum HTML email body size of messages received on the device. Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Determines whether the user can use Windows Live services, such as Hotmail, Office, or Spaces. Determines whether the device can access POP3 or IMAP4 email. Defines the maximum email body size of plain text messages received on the device. Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Defines the maximum age of email on the device. Email older than the maximum age is automatically removed from the device. Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Enforces the use of manual synchronization on the device while roaming to avoid the higher data costs | Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Defines the maximum HTML email body size of messages received on the device. Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Determines whether the user can use Windows Live services, such as Hotmail, Office, or Spaces. Determines whether the device can access POP3 or IMAP4 email. Defines the maximum email body size of plain text messages received on the device. Defines the maximum look-back age of calendar events. Events older than the maximum age are automatically removed from the device. Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Defines the maximum age of email on the device. Email older than the maximum age is automatically removed from the device. Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Enforces the use of manual synchronization on the device while roaming to avoid the higher data costs | Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Defines the maximum HTML email body size of messages received on the device. Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Determines whether the user can use Windows Live services, such as Hotmail, Office, or Spaces. Determines whether the device can access POP3 or IMAP4 email. Defines the maximum email body size of plain text messages received on the device. Defines the maximum look-back age of calendar events. Events older than the maximum age are automatically removed from the device. Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Defines the maximum age of email on the device. Email older than the maximum age is automatically removed from the device. Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Enforces the use of manual synchronization on the device while roaming to avoid the higher data costs | Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Defines the maximum HTML email body size of messages received on the device. Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Determines whether the user can use Windows Live services, such as Hotmail, Office, or Spaces. Determines whether the device can access POP3 or IMAP4 email. Defines the maximum email body size of plain text messages received on the device. Defines the maximum look-back age of calendar events. Events older than the maximum age are automatically removed from the device. Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Defines the maximum age of email on the device. Email older than the maximum age is automatically removed from the device. Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Enforces the use of manual synchronization on the device while roaming to avoid the higher data costs | Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Defines the maximum HTML email body size of messages received on the device. Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Determines whether the user can use Windows Live services, such as Hotmail, Office, or Spaces. Determines whether the device can access POP3 or IMAP4 email. Defines the maximum email body size of plain text messages received on the device. Defines the maximum look-back age of calendar events. Events older than the maximum age are automatically removed from the device. Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Defines the maximum age of email on the device. Email older than the maximum age is automatically removed from the device. Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Enforces the use of manual synchronization on the device while roaming to avoid the higher data costs | Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Defines the maximum HTML email body size of messages received on the device. Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Determines whether the user can use Windows Live services, such as Hotmail, Office, or Spaces. Determines whether the device can access POP3 or IMAP4 email. Defines the maximum email body size of plain text messages received on the device. Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Defines the maximum age of email on the device. Email older than the maximum age is automatically removed from the device. Email older than the maximum age is automatically removed from the device. Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Defines the maximum age of email on the device. Email older than the maximum age is automatically removed from the device. Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Enforces the use of manual synchronization on the device while roaming to avoid the higher data costs | Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Defines the maximum HTML email body size of messages received on the device. Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Determines whether the user can use Windows Live services, such as Hotmail, Office, or Spaces. Determines whether the device can access POP3 or IMAP4 email. Defines the maximum email body size of plain text messages received on the device. Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Defines the maximum age of email on the device. Email older than the maximum age is automatically removed from the device. Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Defines the waximum age of email on the device. Email older than the maximum age is automatically removed from the device. Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Enforces the use of manual synchronization on the device while roaming to avoid the higher data costs | Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Defines the maximum HTML email body size of messages received on the device. Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Determines whether the user can use Windows Live services, such as Hotmail, Office, or Spaces. Determines whether the device can access POP3 or IMAP4 email. Defines the maximum email body size of plain text messages received on the device. Defines the maximum dook-back age of calendar events. Events older than the maximum age are automatically removed from the device. Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Defines the maximum age of email on the device. Email older than the maximum age is automatically removed from the device. Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Defines the use of manual synchronization on the device while roaming to avoid the higher data costs | Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Defines the maximum HTML email body size of messages received on the device. Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Determines whether the user can use Windows Live services, such as Hotmail, Office, or Spaces. Determines whether the device can access POP3 or IMAP4 email. Defines the maximum email body size of plain text messages received on the device. Defines the maximum look-back age of calendar events. Events older than the maximum age are automatically removed from the device. Defines the maximum age of email on the device. Email older than the maximum age is automatically removed from the device. Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Enforces the use of manual synchronization on the device while roaming to avoid the higher data costs | Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Defines the maximum HTML email body size of messages received on the device. Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Determines whether the user can use Windows Live services, such as Hotmail, Office, or Spaces. Determines whether the device can access POP3 or IMAP4 email. Defines the maximum email body size of plain text messages received on the device. Defines the maximum look-back age of calendar events. Events older than the maximum age are automatically removed from the device. Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Defines the maximum age of email on the device. Email older than the maximum age is automatically removed from the device. Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Enforces the use of manual synchronization on the device while roaming to avoid the higher data costs | Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Defines the maximum HTML email body size of messages received on the device. Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Determines whether the user can use Windows Live services, such as Hotmall, Office, or Spaces. Determines whether the device can access POP3 or IMAP4 email. Defines the maximum email body size of plain text messages received on the device. Defines the maximum look-back age of calendar events. Events older than the maximum age are automatically removed from the device. Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Defines the maximum age of email on the device. Email older than the maximum age is automatically removed from the device. Remail older than the maximum age is automatically removed from the device. Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Enforces the use of manual synchronization on the device while roaming to avoid the higher data costs | Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Defines the maximum HTML email body size of messages received on the device. Not supported with systems operating with Active Sync protocol 2.5, such as Exchange 2003. Determines whether the user can use Windows Live services, such as Hotmail, Office, or Spaces. Determines whether the device can access POP3 or IMAP4 email. Defines the maximum email body size of plain text messages received on the device. Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Defines the maximum look-back age of calendar events. Events older than the maximum age are automatically removed from the device. Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Defines the maximum age of email on the device with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. Enforces the use of manual synchronization on the device while roaming to avoid the higher data costs |

| Policy Suite Rules: All Devices | Description | Anrd | Anrd w/o ZMM | TD/A | NS/BB | iOS | TD/ iOS | iOS w/o ZMM | S60 | S60 w/o ZMM | wOS | WM | WM w/o ZMM | WP |
|---------------------------------------|---|------|--------------------|------|-------|-----|------------|-------------------|-----|-------------------|-----|----|------------------|----|
| Device Control: Multiple Devices | | | | | | | | | | | | | | |
| Allow Multiple Devices | Determines whether users can enroll multiple devices against a single user account. | • | • | • | • | • | • | • | • | • | • | • | • | • |
| File and Application Management | | | | | | | | | | | | | | |
| File Share | Creates a directory of folders and files to make accessible to users. Users access files directly through the ZENworks Mobile Management app. Sets permissions for access per policy suite. | • | | • | • | • | • | | • | | | • | | |
| Mobile Apps | Creates a list of recommended apps. The list might consist of apps that users access directly through ZENworks Mobile Management or through links to the apps in device application stores. Available mobile applications are determined by device type. Sets permissions for access per policy suite. | • | | • | • | • | • | | • | | | • | | |
| Security: Password | | | | | | | | | | | | | | |
| Require Password (ActiveSync) | Forces the device to require a lock password. | • | • | • | • | • | • | • | • | • | • | • | • | • |
| Enable password recovery (ActiveSync) | This allows or disallows a user to use the device to issue a request for a temporary recovery password if they have forgotten their unlock password. The recovery password can be retrieved from the MDM User Self Administration Portal or the administrative dashboard. Requires ActiveSync protocol 12.0 or 12.1 For Android w/TouchDown, gives | | | • | • | | | | | | | | | |
| | temporary unlock password only for the TouchDown application; does not provide temporary unlock password when the lock is imposed by the device's native OS. | | | | | | | | | | | | | |

| Policy Suite Rules: All Devices | Description | Anrd | Anrd w/o ZMM | TD/A | NS/BB | iOS | TD/ iOS | iOS w/o ZMM | S60 | S60 w/o ZMM | wOS | WM | WM w/o ZMM | WP |
|---|---|------|--------------------|------|-------|-----|------------|-------------------|-----|-------------------|-----|----|------------------|----|
| Allow Simple Password (ActiveSync) | Determines whether or not a password can consist of only repeating or sequential characters, such as "1111" or "abcd". Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. | • | • | • | • | • | • | • | • | • | | • | • | • |
| Require Minimum Password Length (ActiveSync) | Forces the device to require a password with a specified minimum length. | • | • | • | • | • | • | • | • | • | • | • | • | • |
| Minimum Password Length (ActiveSync) | Defines the minimum password length. | • | • | • | • | • | • | • | • | • | • | • | • | • |
| Require Alphanumeric Password (ActiveSync) | Forces the device to require a device password to contain both letters and numbers. | • | • | • | • | • | • | • | • | • | • | • | • | |
| Minimum Number of Complex Characters (ActiveSync) | Forces the device to require a minimum number of complex characters (symbols) in the password. If an alphanumeric password is not required, this is not enforced. | | | | | | | | | | | | | |
| | For Android (native): Supported on devices with OS 3.0 and selected OS 2.x devices. For BlackBerry w/ NotifySync: Minimum number of each type of character required in an alphanumeric password. (Example: If minimum is 2, password | • | • | • | • | • | • | • | | | | • | • | |
| Require Device Password | must have 2 uppercase, 2 lowercase, 2 numeric, and 2 symbol characters.) | | | | | | | | | | | | | |
| Expiration (ActiveSync) | Forces the device to require users to update their passwords after a number of days. Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. | • | • | • | • | • | • | • | | | | • | • | • |
| | For Android: Supported on devices with ZENworks Mobile Management device application and OS 3.0 (and selected devices with OS 2.x). | | | | | | | | | | | | | |

| Policy Suite Rules: All Devices | Description | Anrd | Anrd w/o ZMM | TD/A | NS/BB | iOS | TD/ iOS | iOS w/o ZMM | S60 | S60 w/o ZMM | wOS | WM | WM w/o ZMM | WP |
|--|---|------|--------------------|------|-------|-----|------------|-------------------|-----|-------------------|-----|----|------------------|----|
| Password expiration in days (ActiveSync) | Defines the number of days a password can be used before it expires. For Android: Supported on devices with ZENworks Mobile Management device application and OS 3.0 (and selected | • | • | • | • | • | • | • | | | | • | • | • |
| Require Device Password History (ActiveSync) | devices with OS 2.x). Forces the device to disallow passwords that have been used in the recent past to be re-used. The number of stored past passwords is configurable. Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. For Android (native): Supported on devices with OS 3.0 and selected OS 2.x devices. For Android w/ TouchDown: Applies to the password associated with the | • | • | • | • | • | • | • | | | | • | • | • |
| Number of passwords stored (ActiveSync) | TouchDown application only. Defines the number of device passwords stored to prevent users from reusing them too soon. | | | | • | • | • | • | | | | • | • | • |
| Enable Password Echo | After the specified number of password entry attempts are made, the last password entered is unmasked to allow the user to see the error they are making. | | | | • | | | | | | | | | |
| Begin password echo after attempts | Defines the number of unlock attempts before echoing begins. | | | | • | | | | | | | | | |
| Security: Encryption | | | | | | | | | | | | | | |
| Require Device Encryption (ActiveSync) | Determines whether the device encrypts stored data. Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003. iOS devices (3GS and 4) have hardware encryption that is always enabled. The ActiveSync policy is not used to enable/disable. | • | • | • | • | • | • | • | | | | • | • | |

| Policy Suite Rules: All Devices | Description | Anrd | Anrd w/o ZMM | TD/A | NS/BB | iOS | TD/ iOS | iOS w/o ZMM | S60 | S60 w/o ZMM | wOS | WM | WM w/o ZMM | WP |
|---|--|------|--------------------|------|-------|-----|------------|-------------------|-----|-------------------|-----|----|------------------|----|
| | For Android w/ native ActiveSync account, supported on the Motorola Droid Pro (OS 2.2) and devices with OS 3.0.0 or greater. | | | | | | | | | | | | | |
| | For Android w/ TouchDown, only TouchDown data is encrypted (email, calendar, contacts, tasks). | | | | | | | | | | | | | |
| | With NotifySync for BlackBerry, only NotifySync data is encrypted (email). | | | | | | | | | | | | | |
| Require Encryption on the Storage Card | Forces the device to encrypt the file system of a storage card. | | | | | | | | | | | | | |
| (ActiveSync) | For Android w/ TouchDown, only TouchDown files are encrypted (email attachments that have been downloaded are encrypted by using AES (256); attachments are still unreadable if the card is moved to another device). | | | • | | | | | | | | • | • | |
| Security: Device Inactivity and Locking | | | | | | | | | | | | | | |
| Require Max Inactivity Time Device Lock (ActiveSync) | Forces the device to lock after a set number of minutes of user inactivity. This value serves as a maximum. | | | | | | | | | | | | | |
| (Active Syric) | This is also known as "Time without user input before password must be reentered." | | • | • | | | | • | | • | • | | | |
| Max Inactivity Timeout (in minutes) (ActiveSync) | Defines the maximum value a user can set for the numbers of minutes of inactivity before the device locks. If the Challenge Timeout is being enforced, the Max Inactivity Timeout should be less than the Challenge Timeout. | • | • | • | • | • | • | • | • | • | • | • | • | • |
| Require Device Challenge Timeout | Forces the device to enable a challenge timeout. A lock is initiated regardless of activity and is intended to challenge the use of a lost or stolen device. | | | | • | | | | | | | | | |
| Max Device Challenge Timeout | Defines the maximum value a user can set for the number of minutes before the | | | | • | | | | | | | | | |

| Policy Suite Rules: All Devices | Description | Anrd | Anrd w/o ZMM | TD/A | NS/BB | iOS | TD/ iOS | iOS w/o ZMM | S60 | S60 w/o ZMM | wOS | WM | WM w/o ZMM | WP |
|--|---|------|--------------------|------|-------|-----|------------|-------------------|-----|-------------------|-----|----|------------------|----|
| | device initiates a challenge lock. This lock is initiated regardless of activity and is intended to challenge the use of a lost or stolen device. If the Max Inactivity Timeout is being enforced, the Challenge Timeout should be greater than the Max Inactivity Timeout. | | | | | | | | | | | | | |
| Customizable Lock Message | Enable the lock message and enter the text to be displayed when device is locked. | | | | • | | | | | | | | | |
| Audible Alert On Lock | This setting enables a device to constantly emit a loud noise when a server-initiated device lock has been issued. The intent is to draw attention to the missing device and the device thief. The noise continues while the device is powered on, until the device is unlocked. | | | | • | | | | | | | • | | |
| Maximum grace period (in minutes) | Determines how soon the device can be unlocked again after use, without reprompting for the password. The administrator can also disallow a grace period by selecting Immediately or choose not to impose a limit by selecting None. | | | | | • | • | | | | | | | |
| Wipe device on Failed Unlock Attempts (ActiveSync) | After the specified number of password entry attempts are made, data is cleared from the device. Functionality varies by device. Android or Android w/TouchDown (requires OS v2.2 or greater): The device returns to factory settings. This entails deleting all data and applications from the device. The device returns to the state it was in when purchased. Does not erase the SD card. Android w/TouchDown (using OS v2.1 or older): Wipes only ZENworks Mobile Management information. BlackBerry: Removes all mail and PIM data associated with the NotifySync application and removes the NotifySync | • | • | • | • | • | • | • | • | • | • | • | • | • |

| Policy Suite Rules: All Devices | Description | Anrd | Anrd w/o ZMM | TD/A | NS/BB | iOS | TD/ iOS | iOS w/o ZMM | S60 | S60 w/o ZMM | wOS | WM | WM w/o ZMM | WP |
|---|---|------|--------------------|------|-------|-----|------------|-------------------|-----|-------------------|-----|----|------------------|----|
| | account. Locks the device if Require Password is enabled. Erases NotifySync data from the SD card, including saved attachments. | | | | | | | | | | | | | |
| | iOS: The device returns to factory settings. This entails deleting all data and applications from the device. The device returns to the state it was in when purchased. | | | | | | | | | | | | | |
| | Symbian: The device returns to factory settings. This entails deleting all data and applications from the device. The device returns to the state in was in when purchased. Erases the SD card. | | | | | | | | | | | | | |
| | WM: The device returns to factory settings. This entails deleting all data and applications from the device. The device returns to the state it was in when purchased. Erases SD card only on Professional devices. | | | | | | | | | | | | | |
| | webOS and WP: The device returns to factory settings. This entails deleting all data and applications from the device. The device returns to the state in was in when purchased. | | | | | | | | | | | | | |
| Maximum number of unlock attempts (ActiveSync) | Defines the number of unlock attempts before the device-initiated wipe is performed. | • | • | • | • | • | • | • | • | • | • | • | • | • |
| Security: Emergency Calls | | | | | | | | | | | | | | |
| Enable emergency calls when locked | Allows the device to make emergency calls in a locked state. Allows emergency numbers to be specified for allowed calls on a locked device: ambulance, fire, police, and one other emergency number. | | | | • | | | | | | | | | |
| S/MIME Settings | | | | | | | | | | | | | | |
| Require signed SMIME messages | This setting forces the device to send digitally signed S/MIME messages. | | | | | | | | | | | • | • | • |

| Policy Suite Rules: All Devices | Description | Anrd | Anrd w/o ZMM | TD/A | NS/BB | iOS | TD/ iOS | iOS w/o ZMM | S60 | S60 w/o ZMM | wOS | WM | WM w/o ZMM | WP |
|--|--|------|--------------------|------|-------|-----|------------|-------------------|-----|-------------------|-----|----|------------------|----|
| Require encrypted SMIME messages | This setting forces the device to send encrypted S/MIME messages. | | | | | | | | | | | • | • | • |
| Require signed SMIME algorithm | This setting specifies the algorithm to be used for signing messages. Options are SHA1, MD5. | | | | | | | | | | | • | • | • |
| Require encryption SMIME algorithm | This setting specifies the algorithm to be used for encrypting messages. Options are TripleDES, DES, RC2128bit, RC264bit, RC240bit. | | | | | | | | | | | • | • | • |
| Allow SMIME Encryption algorithm negotiation | This setting enables/disables the device from negotiating the encryption algorithm used for signing messages. Options are Do not negotiate, Negotiate only strong algorithms, Negotiate any algorithm. | | | | | | | | | | | • | • | • |
| Allow SMIME soft certs | This setting enables/disables the device from using soft certificates to sign outgoing messages. | | | | | | | | | | | • | • | • |

POLICY RULES: IOS DEVICES

| Policy Suite Rules: iOS | Description | iOS | TD/ | iOS w/o |
|--------------------------------------|--|-----|-----|---------|
| Device Features | | | 100 | |
| Allow FaceTime | Determines whether the user can receive or place video calls. Allow Camera in the Device Controls must be enabled as well. | • | • | |
| Allow Voice Dialing | Determines whether the user can dial their phone using voice commands. | • | • | |
| Allow Screenshot | Determines whether or not the user can save a screenshot of the device display. | • | • | |
| Allow Explicit Content | Determines whether or not explicit music or video content purchased from the iTunes store is hidden. | • | • | |
| Allow Automatic Sync When Roaming | When disabled, devices that are roaming synchronize only when an account is accessed by the user. | • | • | |
| Allow Siri | Determines whether iPhone 4S devices allow the Siri speech recognition personal assistant. | • | • | |
| Allow Siri while device locked | Determines whether Siri is disabled when the device is locked with a password. Enabling Allow Siri is a prerequisite for enabling this option. Requires iOS 5.1 or higher. | • | • | |
| Enable Siri Profanity Filter | Filters out profanity from Siri, preventing it from recognizing or interpreting profanity. Enabling Allow Siri is a prerequisite for enabling this option. Requires iOS 5.1 or higher. | • | • | |
| Allow Multiplayer Gaming | Determines whether the device will allow multiplayer gaming between iOS devices via Bluetooth or Wi-Fi. When this option is disabled, users cannot play multiplayer games in the Game Center. | • | • | |
| Allow Adding Game Center Friends | Determines whether the device allows adding friends or building a social gaming network associated with the Game Center app. | • | • | |
| Force iTunes Store Password Entry | Determines whether the device will require a password to access the iTunes store. Requires users to enter their Apple ID before making any purchase. Normally, there is a brief grace period after a purchase is made before users must authenticate for subsequent purchases. (Requires iOS 5.0 or higher.) | • | • | |

| Policy Suite Rules: iOS | Description | iOS | TD/ | iOS w/o |
|------------------------------------|--|-----|-----|---------|
| Force Encrypted Backup | When disabled, users can choose whether or not device backups performed in iTunes, are stored in encrypted format on the computer. | • | • | |
| Allow Location Services | Determines whether Location Services can be enabled on the device. Requires iOS 5.1 or higher. | • | • | |
| Allow Passbook while device locked | Allows use of the Apple Passbook app when the device is locked, giving users access to their boarding passes, tickets, store cards, coupons, etc. Requires iOS 6.0 or higher. | • | • | |
| Applications | | | | |
| Allow Application Installation | When disabled, the App Store is disabled and the icon is removed from the device Home screen. In addition, users are prevented from installing applications made available through the ZENworks Mobile Apps list. | • | • | |
| Allow In App Purchases | Determines whether or not users can make in-app purchases. | • | • | |
| Allow YouTube | Determines whether the use of YouTube is allowed on the device. If disabled, the icon is removed from the Home screen. | • | • | |
| Allow iTunes | Determines whether the use of iTunes is allowed on the device. If disabled, the icon is removed from the Home screen and users cannot preview, purchase, or download content. | • | • | |
| Safari Browser | | | | |
| Allow Safari | Determines whether use of the Safari Web browser is allowed on the device. If disabled, the Safari icon is removed from the Home screen and it prevents users from opening Web clips. Disabling Safari might also prevent the use of third-party browsers. | • | • | |
| | Allow Browser in the Device Controls must also be enabled. | | | |
| Accept Cookies | Determines the Safari cookie policy – Whether the device accepts all cookies, no cookies, or only cookies from sites that were directly accessed. | • | • | |
| Allow Auto-fill | Determines whether Safari remembers what users enter in Web forms. | • | • | |
| Allow JavaScript | Determines whether Safari ignores JavaScript on Websites. | • | • | |
| Block Pop-ups | Determines whether Safari's pop-up blocking feature is enabled. | • | • | |
| Force Fraud Warning | Determines whether Safari attempts to prevent the user form visiting Websites identified as being fraudulent of compromised. | • | • | |
| Ratings | | | | |
| Rating Region | Determines the media content rating scale used by a particular region. | • | | |
| Application Ratings | Determines the maximum allowed ratings for apps. | • | • | |

| Policy Suite Rules: iOS | Description | iOS | TD/ | iOS w/o |
|----------------------------------|--|-----|-----|---------|
| Movie Ratings | Determines the maximum allowed ratings for movies. | • | • | |
| TV Show Ratings | Determines the maximum allowed ratings for TV shows. | • | • | |
| Security | Jan San San San San San San San San San S | | | |
| Allow Profile Removal | Determines whether an iOS user can delete the ZENworks Mobile Management configuration profile from the device. Includes an option to allow deletion with the use of a password. | • | • | |
| Profile Removal Password | Defines the password with which a user can remove the profile. | • | • | |
| Allow Untrusted TLS Prompt | Determines whether users are asked if they want to trust certifications that cannot be verified. This setting applies to Safari and to Mail, Contacts, and Calendar accounts. (Requires iOS 5.0 or higher.) | • | • | |
| Allow Diagnostic Submission Text | Determines whether the device sends iOS diagnostic data to Apple. When this option is disabled, iOS diagnostic information is not sent to Apple. | • | • | |
| iCloud | | | | |
| Allow iCloud Backup | Determines whether the device is permitted to back up to and restore from iCloud. | • | • | |
| Allow Document Sync | Determines whether the device allows document synchronization to iCloud. When this option is enabled, users can store documents in iCloud. | • | • | |
| Allow Photo Stream | Determines whether the device allows Photo Stream. If enabled, iCloud automatically pushes (via Wi-Fi) a copy of any photo taken on or imported to an iOS device, to the user's other iOS devices, iPhoto or Aperture on a Mac, Pictures Library on a PC, and Apple TV. | _ | | |
| | When this option is disabled, installing a configuration profile with this restriction erases Photo Stream photos from the user's device and prevents photos from the Camera Roll from being sent to Photo Stream. If there are no other copies of these photos, they might be lost. | • | • | |
| Allow Shared Photo Streams | Determines whether an administrator has the ability to manage apps for users in a particular policy suite. Requires iOS 6.0 or higher. | • | • | |
| iOS MDM | | | | |
| Record Installed Applications | Accesses and records applications installed on devices. | • | • | |
| Manage Mobile Apps | Determines whether an administrator can manage apps for users in a particular policy suite. | • | • | |

POLICY RULES: TOUCHDOWN

| Policy Suite Rules: TouchDown Specific | Description | TD/A | TD/A w/o ZMM | TD/iOS | TD/iOS w/o ZMM |
|---|---|------|-----------------|--------|----------------------|
| Installation | | | | | |
| Allow any server certificate | Currently, ZENworks Mobile Management requires a CA signed certificate and does not support self-signed certificates. For the present, this option should be disabled. | • | | | |
| Initiate enrollment | At the completion of the ZENworks Mobile Management enrollment, the user is prompted to configure TouchDown. When the user confirms, this automatically registers TouchDown and creates an ActiveSync account with the user credentials provided during ZENworks Mobile Management enrollment. If disabled, the user is not prompted and must initiate the TouchDown configuration by opening the ZENworks Mobile Management app and selecting Settings > TouchDown Settings. | • | | | |
| General | management app and ecosoming cominger | | | | |
| Allow copy/paste in emails | Determines whether users can copy text from a received email and paste it elsewhere. | • | | • | |
| Allow easy PIN recovery | Allows users to reset the TouchDown PIN (password) by using their Exchange account password. With Exchange 2007 or 2010, this does not function when Security Settings > Enable Password Recovery is enabled. The ActiveSync password recovery method is used instead. | • | | | |
| Allow speak notification option | When enabled, users can choose to have the device issue spoken email and appointment notifications. When disabled, the option is not visible and the function is disabled. | • | | | |
| | At least one of two suppression rules must be enabled in order for this to function: Allow appointment alert configuration or Allow email alert configuration. | | | | |
| Show TouchDown PIN | This setting is dependent upon the ActiveSync Require Password policy. | | | | |
| | When Require Password is disabled, this setting has no effect and neither the device nor the TouchDown app locks or requires a password. | | | | |
| | When Require Password is enabled, behavior varies: | • | | • | |
| | For Android OS 2.2 or higher – The device locks and requires a password. The Show TouchDown PIN setting determines whether the | | | | |

| Policy Suite Rules: TouchDown Specific | Description | TD/A | TD/A w/o ZMM | TD/iOS | TD/iOS w/o ZMM |
|---|--|------|-----------------|--------|----------------------|
| | TouchDown app locks/requires a password as well. When enabled, TouchDown locks. When disabled, TouchDown does not lock. | | | | |
| | For Android OS 2.1 or less – When the Show TouchDown PIN setting is enabled, the device does not lock, but TouchDown does. When it is disabled, neither the device nor the TouchDown app locks; however, the user is still prompted to create a PIN/password. | | | | |
| | iOS devices: The device locks and requires a password. The Show TouchDown PIN setting determines whether the TouchDown app locks/requires a password as well. When enabled, TouchDown locks. When disabled, TouchDown does not lock. | | | | |
| Show calendar info on notification bar | Determines whether appointment subjects are displayed in the device notification bar when reminders are shown. | | | | |
| | To successfully display notifications, the following TouchDown settings must also be configured on the device: In the Advanced TouchDown Settings, enable the Appointment reminders at non-peak times options and configure Appointment Alerts to Use system settings. | • | | • | |
| Show email info on notification bar | Determines whether the email sender and subject are displayed in the device notification bar when email notifications are shown. | | | | |
| | To successfully display notifications, the following TouchDown settings must also be configured on the device: In the Advanced TouchDown Settings, enable the Notify on new mail option and configure Email Alerts to Use system settings. | • | | • | |
| Show task info on notification bar | Determines whether task subjects are displayed in the device notification bar when task notifications are shown. | | | | |
| | To successfully display notifications, the following TouchDown settings must also be configured on the device: In the Advanced TouchDown Settings, enable the Appointment reminders at non-peak times options and configure Appointment Alerts to Use system settings. | • | | • | |
| Disable Printing | Disables printing from TouchDown. | • | | | |
| Forced SMIME Pin Timeout | The timeout interval before a user is required to re-enter an SMIME certificate PIN, when the certificate has been configured to require a PIN for signing or encrypting/decrypting messages. | • | | • | |
| Signature | | | | | |
| Allow change signature on device | When enabled, allows user to change the signature which accompanies email sent from the device. This option does not function unless the | • | | • | |

| Policy Suite Rules: TouchDown Specific | Description | TD/A | TD/A w/o ZMM | TD/iOS | TD/iOS w/o ZMM |
|--|--|------|-----------------|--------|----------------------|
| | Suppression > Allow signature line field is enabled. | | | | |
| Set signature (Corporate / Individual) | Allows the entry of a signature determined by the administrator. | • | | • | |
| Widgets | | | | | |
| Allow export to third party widgets | Determines whether or not TouchDown data can be communicated to third-party widgets that request it. | • | | | |
| Allow TouchDown calendar widget | Determines whether or not the TouchDown calendar widget shows data. | • | | | |
| Allow TouchDown email widget | Determines whether or not the TouchDown email widget shows data. | • | | | |
| Allow TouchDown task widget | Determines whether or not the TouchDown task widget shows data. | • | | | |
| Allow TouchDown universal widget | Determines whether or not the TouchDown universal widget shows email, calendar and task data. | • | | | |
| Show widget data when TouchDown is locked | Determines whether widget data is locked when TouchDown is locked. This option does not function unless Security Settings >Require Password; TouchDown-General > Show TouchDown PIN; and at least one widget (calendar, email, third-party, task, or universal) are enabled. | • | | | |
| Phone Book | | | | | |
| Phone book fields to copy | Choose which fields of a contact synchronize when users copy contacts to the device phone book. | | | | |
| | Choosing all or some of the fields is a prerequisite for the suppression rules: Allow copy phone format options and Allow update contact changes to phone options. | • | | • | |
| User Configurable Settings: Calendar | About User Configurable Settings: Users can configure these policies according to preference. Administrators choose the setting for initial device configuration. Changes to these settings do affect existing TouchDown users. | | | | |
| Show All-day events in the Calendar Widget | Determines whether all-day events display in the TouchDown Calendar Widget. | • | | | |
| Show upcoming events only | Determines whether the only appointments displayed in the current day's Agenda are those that have not passed. | • | | | |
| Enable meeting resource field | Determines whether a field is enabled for specifying resources such as conference rooms or equipment when creating a new meeting. | • | | | |

| Policy Suite Rules: TouchDown Specific | Description | TD/A | TD/A w/o ZMM | TD/iOS | TD/iOS w/o ZMM |
|--|---|------|-----------------|--------|----------------------|
| Show calendar tasks in the Agenda | Determines whether calendar tasks display in the Agenda view. | • | | • | |
| Show overdue tasks in the Agenda | Determines whether overdue tasks display in the Agenda view. | • | | | |
| Customize the start and end days for the week | Determines whether user has the ability to define the first and last days of the week to display in the calendar Week view. | • | | • | |
| First day of a week to show in Calendar | Define the first day of the week to display in the calendar Week view. | • | | • | |
| Last day of a week to show in Calendar | Define the last day of the week to display in the calendar Week view. | • | | • | |
| Start time of the work day | Times that fall between the work day's start time and end time display in a different color on Day and Week calendar views. | • | | • | |
| End time of the work day | Times that fall between the work day's start time and end time display in a different color on Day and Week calendar views. | • | | • | |
| Default reminder for each new event | Defines the default reminder time to assign to each new event unless otherwise specified for the event. | • | | • | |
| Default privacy status for each new event | Defines the default privacy status to assign to each new event unless otherwise specified for the event. | • | | • | |
| Default availability status for each new event | Defines the default availability status to assign to each new event unless otherwise specified for the event. | • | | • | |
| Calendar zoom size | Shows the Day and Week calendar views in a larger text size. | • | | • | |
| User Configurable Settings: Device Control | | | | | |
| Show a compact PIN screen (NEW 7.1) | Determines whether a compact PIN screen is shown, fitting the PIN buttons over half of the available screen space. | • | | | |
| Default theme (NEW 7.1) | Defines a default display theme for the TouchDown User Interface. | • | | | |
| User Configurable Settings: Email | | | | | |
| Enable email selectors | Adds a radio button beside each item in the email list, enabling the user to select multiple emails for various actions, such as delete, mark as read, move, etc. | • | | | |
| Show email summary | Determines whether part of the body of each email displays in the email list. | • | | | |

| Policy Suite Rules: TouchDown Specific | Description | TD/A | TD/A w/o ZMM | TD/iOS | TD/iOS w/o ZMM |
|--|--|------|-----------------|--------|----------------------|
| Highlight email senders | Determines whether the sender of any email displays in a larger and bolder type than the subject field. | • | | • | |
| Enable search as you type | Determines whether the search tool used in the email list begins to filter messages as the user types a string, as opposed to the user having to initiate the search after typing. | • | | | |
| Automatically download embedded images | Determines whether embedded images automatically download for an HTML email. | • | | • | |
| Enable move to any folder option | Determines whether a user can move email messages to folders that have not been selected for synchronization, as opposed to only being able to move email to folders that have already synchronized. | • | | • | |
| Highlight unread messages | When enabled, Email list displays read email in grey and unread email fully lit and in bold. | • | | | |
| Enable preview attachments option | When enabled, a thumbnail view of downloaded attachments displays before they are opened. | • | | | |
| Always expand folders | When enabled, the folder tree automatically expands when <i>Choose Folders</i> is used or when the user switches folders. | • | | | |
| Enable confirm deletes prompt | Determines whether a confirmation prompt displays when the user deletes an email. | • | | • | |
| Enable confirm move prompt | Determines whether a confirmation prompt displays when the user moves an email. | • | | • | |
| Toolbar mode | Determines whether the tool bar that appears when viewing an email will display, be hidden, or can be toggled on and off. | • | | | |
| After delete go to | Defines what is displayed after an email is deleted. | • | | • | |
| Enable email alerts at non-peak times | Determines whether email notifications are sent when email arrives during non-peak times. | • | | | |
| Confirm move to Junk prompt | Determines whether a confirmation prompt displays when the user moves an email to the Junk folder. | • | | • | |
| User Configurable Settings: Synchronization | | | | | |
| Enable push email mode | When enabled, switches the device from checking email at scheduled frequencies to a Push Email mode in which the device connects with the server for sustained intervals to retrieve email. | • | | • | |
| Off-peak polling interval | Defines the polling interval for retrieving new mail during non-peak times. | • | | | |

| Policy Suite Rules: TouchDown Specific | Description | TD/A | TD/A w/o ZMM | TD/iOS | TD/iOS w/o ZMM |
|--|--|------|-----------------|--------|----------------------|
| Suppressions | About Suppressions: An enabled suppression gives the user control of the setting. | | | | |
| | A disabled suppression removes the setting from user devices. When the suppression has a control setting the administrator can configure it. When a control setting is not provided, the setting is locked as it was previously set on the device. | | | | |
| Suppression configuration | Choose which options to hide or expose to TouchDown users. Select <i>All</i> to enable all suppressions, giving users control. Select <i>None</i> to disable all suppressions or <i>Custom</i> to set each suppression individually. | • | | • | |
| Suppressions: Calendar, Contacts, Tasks | | | | | |
| Allow appointment alert configuration | Enables users to customize the alerts displayed for appointment reminders. | • | | • | |
| Allow appointment reminders at non-peak times option | Enables users to allow appointment reminders during periods when the device is not synchronizing. | | | | |
| Enable appointment reminders at non-peak times | Control setting determines whether appointment reminders display during non-peak times. | • | | • | |
| Allow appointment synchronization option | Enables users to set how many days of appointments to keep on the device. | • | | • | |
| Allow category configuration | Enables users to select colors for contact, event, and task categories. | • | | • | |
| Allow copy to phone format options Name format for contacts | Enables users to select the format of contacts (First or Last Name placed first) copied from TouchDown to the Android phone book. Choosing all or some of the fields in the Phone Book > Phone book fields to copy rule is a prerequisite. | • | | • | |
| copied to phone | Control setting defines the format in which contacts are copied to the phone from TouchDown Exchange contacts. First MI Last, Last First MI, or File as is | | | | |
| Allow enable appointment reminders option | Allows users to enable appointment reminders. | | | | |
| Enable appointment reminders | Control setting determines whether a notification displays when an appointment has a reminder. | • | | • | |
| Allow include phone contacts in picklist option | Enables users to determine whether the contact list displayed when composing email or SMS includes contacts from the Android Phone Book. | • | | | |
| Include phone contacts in picklist | Control setting determines whether contacts from the Android phone book are included in the contact picklist that can be accessed while | - | | | |

| Policy Suite Rules: TouchDown Specific | Description | TD/A | TD/A w/o ZMM | TD/iOS | TD/iOS w/o ZMM |
|--|---|------|-----------------|--------|----------------------|
| | composing email. | | | | |
| Allow normalize phone numbers option | Enables users to determine how contact phone numbers retrieved from the server are formatted. | | | | |
| Normalize phone numbers | Control setting defines the format of contact phone numbers retrieved from the server as follows: | | | | |
| | X/x/ext (extension) becomes ; | | | | |
| | P/p (pause) becomes ; | | | | |
| | W/w (tone wait) becomes , | | | | |
| Allow reminders configuration | Enables users to configure repeating reminders for calendar events. | | | | |
| Set reminders (in min) | Use the control setting to configure the repeating reminders. | | | | |
| | 0 = No repeats; X<0 = reminders start at set reminder time and continue every X minutes until event starts; X>0 = reminders repeat every X minutes after event starts | • | • | | |
| Allow update contact changes to phone option | Enables users to determine whether updates made to contacts in TouchDown also update the phone book database. For iOS devices, updates occur when the user manually synchronizes contacts. Choosing all or some of the fields in the Phone Book > Phone book fields to copy rule is a prerequisite. | • | | • | |
| Update contact changes to phone | Determine whether updates made to contacts in TouchDown also update the phone book database. For iOS devices, updates occur when the user manually synchronizes contacts. | | | | |
| Suppressions: Device Control | | | | | |
| Allow ActiveSync device type string field ActiveSync device type string | Enables users to modify the ActiveSync device type the device reports to the ZENworks Mobile Management server. In order for the server to maintain accurate information, this should be disabled. | • | | • | |
| field | Use the control setting to set the ActiveSync device type string to the TouchDown option. | | | | |
| Allow backup database (menu option) | Enables users to back up the TouchDown database to the SD card. | • | | | |
| Allow backup settings | Enables users to back up the TouchDown settings to the SD card. | • | | | |
| Allow disable tablet mode (tablet devices only) option | Allows tablet users to disable the automatic switch to tablet mode. | | | | |
| Disable tablet mode (tablet devices only) | Use the control setting to disable the automatic switch to Tablet Mode for tablet users. | • | | • | |

| Policy Suite Rules: TouchDown Specific | Description | TD/A | TD/A w/o ZMM | TD/iOS | TD/iOS w/o ZMM |
|--|---|------|-----------------|--------|----------------------|
| Allow exclude attachments from gallery option | Enables users to determine whether Android Gallery scans the SD card for TouchDown media files. | | | | |
| Exclude attachments from gallery | Control setting determines whether or not Android Gallery scans the SD card for TouchDown media files. | • | | | |
| Allow export settings | Enables users to do an SD card export for a .pcf configuration file with the settings required to connect to the server. | • | | | |
| Allow filtered tasks on home screen and widgets option | Enables users to filter tasks shown on the Home screen and on the Task Widget just as they are on the TouchDown Tasks screen. | | | | |
| Display tasks on home screen and widgets | Control setting determines whether tasks shown on the Home screen and on the Task Widget are filtered just as they are on the TouchDown Tasks screen. | • | | | |
| Allow login ID, email address, domain fields | Displays the user's ActiveSync account information and allows user to edit. | • | | • | |
| Allow quick configuration | Enables users to use the Quick Configuration option to create the ActiveSync account. | • | | | |
| Allow restore database (menu option) | Enables users to restore a backup of the TouchDown database from the SD card. | • | | | |
| Allow restore settings | Enables users to restore TouchDown settings they have backed up to the SD card. | • | | | |
| Allow server name fields | Displays the address of the ZENworks Mobile Management server and allows the user to edit it. This option also controls the following device options: Uses SSL and Fetch and Trust Certificate. | • | | • | |
| Allow show emails on startup option | Enables users to open TouchDown to the email list instead of the main display pane. | _ | | _ | |
| Show email list on startup | Control setting determines whether TouchDown will open to the Email list instead of TouchDown's main screen. | • | | • | |
| Allow use system background data setting option | Determines whether TouchDown honors how the user has configured the Android <i>Background Data</i> setting, which controls whether the app updates in the background or only on demand. | | | | |
| Use system background data setting | When control setting is disabled, TouchDown synchronizes in the background regardless of how the Android <i>Background Data</i> setting is configured. | • | | | |
| Suppressions: Email | | | | | |
| Allow always BCC myself option | Enables the user to send a copy of all outgoing emails to his or her own email address. | | | | |
| Enable always BCC myself | Control setting determines whether a copy of all outgoing email is sent to | | | | |

| Policy Suite Rules: TouchDown Specific | Description | TD/A | TD/A w/o ZMM | TD/iOS | TD/iOS w/o ZMM |
|---|---|------|-----------------|--------|----------------------|
| option | the user's own email address. | | | | |
| Allow choose folders | Enables users to select the folders TouchDown synchronizes with the server. In addition to <i>Choose Folders</i> , this also controls the following device options: Selected Email Folders and Refresh Folders. | • | | • | |
| Allow disable SmartReplies and SmartForwards option | Enables users to turn off SmartReplies and SmartForwards. | | | | |
| Disable SmartReplies and SmartForwards | Control setting disables the SmartReplies/SmartForwards functionality. This should only be disabled if the server does not support Smart Replies/Forwards. | • | | • | |
| Allow don't delete emails on server option | Enables users to prevent email they delete on the device from being deleted on the server. | | | | |
| Do not delete email on server | Control setting determines whether email on the server will be deleted when email is deleted on the device. | | | | |
| Allow don't mark read on server | Enables users to prevent email, marked read/unread on the device, from being marked as read/unread on the server. | | | | |
| Do not mark email read on server | Control setting determines whether email marked read/unread on the device will be marked as read/unread on the server. | • | | • | |
| Allow email alerts configuration | Enables users to customize the alerts displayed for new email. | • | | • | |
| Allow email body style options Email body style | Enables users to choose font, size, color, and style of the HTML email they compose. | | | | |
| (Corporate/Individual) | Use control setting to define the font, size, color, and style of text used for composing HTML email. | • | | • | |
| Allow email checking frequency options | Enables users to determine how often the device checks for new email. | | | | |
| Email checking frequency (in minutes) | When Push Email is not enabled, this control setting defines the frequency at which the device checks the server for new mail. The recommended value is 15 minutes, as more frequent checks can increase battery drain. | • | | • | |
| Allow email download size options | Enables users to determine the size of downloaded email messages. An email larger than this value displays an option to download the remainder. (Zimbra users - value must be no greater than 10 KB.) | • | | • | |
| Allow email view text size options | Enables users to select the text size of email they view. | | | | |
| Email text size | | • | | • | |
| | Use the control setting to define the text size for viewing emails. | | | | |

| Policy Suite Rules: TouchDown Specific | Description | TD/A | TD/A w/o ZMM | TD/iOS | TD/iOS w/o ZMM |
|--|---|------|-----------------|--------|----------------------|
| Allow emails to synchronize options | Enables users to set how many days of email to keep on the device. | • | | • | |
| Allow enable HTML email options | TouchDown attempts to download and display email in HTML format. Mail servers other than Exchange should leave this disabled. | • | | • | |
| Allow folder language options | Enables users to choose the language used for folder labeling. | • | | • | |
| Allow manage rules option | Enables users to create and manage rules for incoming email. | • | | • | |
| Allow notify on new mail option Send new mail notifications | Enables users to determine whether a notification displays when new email arrives. | _ | | | |
| Send new mail notifications | Control setting determines whether a notification displays when new mail arrives. | • | | | |
| Allow out of office configuration | Enables users to configure automatic Out of Office replies. | • | | • | |
| Allow signature line field | Enables users to enter their own signature for email sent from the device. | • | | • | |
| Suppressions: Security | | | | | |
| Allow clean SD card on remote wipe option | Enables users to determine whether all files on the SD card are deleted when a remote Wipe is issued. | | | | |
| Clean SD card on remote wipe | Control setting determines whether all files on the SD card are deleted when a remote Wipe is issued. | • | | | |
| Allow client certs configuration | Enables users to import a client certificate, which TouchDown uses to authenticate with the server. | • | | | |
| Allow remote kill configuration | Enables users to configure the device to allow a remote wipe of TouchDown data. An email sent to the device with a designated code in the subject field initiates the wipe. | • | | • | |
| Remote kill code | Define the designated code that will initiate a wipe. | | | | |
| Allow security policy display | Displays the security policies imposed by the server, which are governing the device. | • | | • | |
| Allow S/MIME settings configuration | Enables users to adjust the settings of the S/MIME options for their device. | • | | • | |
| Allow wipe data (menu option) | Enables users to choose a device option to erase all TouchDown data and return TouchDown to a pre-registration state. | • | | • | |

| Policy Suite Rules: TouchDown Specific | Description | TD/A | TD/A w/o ZMM | TD/iOS | TD/iOS w/o ZMM |
|--|---|------|-----------------|--------|----------------------|
| Suppressions: Synchronization | | | | | |
| Allow defer server updates option Enable defer server updates | Enables users to determine whether TouchDown updates will synchronize to the server in batches or as they occur. Batches are sent only when the next scheduled sync occurs, an item arrives via direct push, or the user initiates a manual sync. When control setting is enabled, TouchDown updates synchronize to the server in batches instead of as they occur. Batches are sent only when the next scheduled sync occurs, an item arrives via direct push, or the user initiates a manual sync. | • | | • | |
| Allow enable SMS syncing (Exchange 2010 Only) option | Enables users to synchronize SMS messages to Outlook. | • | | | |
| Allow manual sync when roaming option | When enabled, automatic synchronization stops when the device is roaming, but users can initiate a manual sync. | • | | • | |
| Allow notify on password failure option Send password failure notifications | Enables users to determine whether a notification displays if synchronization fails due to a user password issue. Control setting determines whether a notification displays if synchronization fails due to a user password issue. | • | | • | |
| Allow notify on polling failure option Send failed polling notifications | Enables users to determine whether a notification displays if synchronization has failed. Control setting determines whether a notification displays if synchronization has failed. | • | | • | |
| Allow notify on successful polling option Send successful polling notifications | Enables users to determine whether a notification displays when synchronization is successful. Control setting determines whether a notification displays when synchronization is successful. | • | | • | |
| Allow peak time configuration | Enables users to set the hours during which TouchDown synchronizes with the server. | • | | • | |
| Allow poll during off-peak times option | Enables users to determine whether TouchDown synchronizes with the server during non-peak times when email is sent, replied to, or forwarded from the device. | | | | |
| Enable polling at off-peak times | Control setting determines whether TouchDown synchronizes with the server during non-peak times when the user sends an email, a reply, or forward from the device. | • | | | |

SECURITY: ALL DEVICES

| Security: All Devices | Description | Anrd | Anrd w/o ZMM | TD/A | NS/BB | iOS or TD/iOS | iOS w/o ZMM | S60 | S60 w/o ZMM | wOS | WM | WM w/o ZMM | WP |
|-----------------------|---|------|--------------------|------|-------|---------------------|-------------------|-----|-------------------|-----|----|------------------|----|
| Security Commands | | | | | | 15/100 | | | | | | | |
| Disable/Enable Device | Disables or enables device connection with the ZENworks Mobile Management server. | • | • | • | • | • | • | • | • | • | • | • | • |
| Selective Wipe | Administrators or end users can issue a selective wipe command. Functionality varies by device. | | | | | | | | | | | | |
| | Android w/ native ActiveSync account (requires OS v2.2 or greater): Removes the ZENworks Mobile Management account information. | | | | | | | | | | | | |
| | Android w/TouchDown (using any supported OS): Removes all mail and PIM (calendar, contact, tasks) data associated with the TouchDown application and returns TouchDown to a pre-registration state. Erases TouchDown data from the SD card. Removes the ZENworks Mobile Management account information. When the Clean SD card on Remote Wipe option in the TouchDown Advanced Settings is enabled, the SD card is completely erased. | • | | • | • | • | | • | | | | | |
| | BlackBerry: Removes all mail and PIM data associated with the NotifySync application. Locks the device if Require Password is enabled. | | | | | | | | | | | | |
| | iOS: Removes all mail and PIM (calendar and contacts) data controlled by ZENworks Mobile Management. The command is applied immediately; however, the device is capable of postponing the | | | | | | | | | | | | |

| Security: All Devices | Description | Anrd | Anrd w/o ZMM | TD/A | NS/BB | iOS or TD/iOS | iOS w/o ZMM | S60 | S60 w/o ZMM | wOS | WM | WM w/o ZMM | WP |
|-----------------------|---|------|--------------------|------|-------|---------------------|-------------------|-----|-------------------|-----|----|------------------|----|
| | action. | | | | | | | | | | | | |
| | Symbian: Removes the ZENworks Mobile Management account information. | | | | | | | | | | | | |
| Wipe Storage Card | Administrators or end users can remotely wipe all data from the device's storage card. | | | | | | | | | | | | |
| | Android w/native ActiveSync account and Android w/ TouchDown using OS 3.2-4.1.2: Wipes the internal storage card, but does not wipe the external storage card – an OS limitation. | • | | • | • | | | | | | • | | |
| Full Wipe | Administrators or end users can issue a full wipe command. Functionality varies by device. | | | | | | | | | | | | |
| | Android w/ native ActiveSync account (requires OS v2.2 or greater): The device returns to factory settings. This entails deleting all data and applications from the device. The device returns to the state it was in when purchased. Does not erase the SD card. | | | | | | | | | | | | |
| | Android w/TouchDown (requires OS v2.2 or greater): Device returns to factory settings. This entails deleting all data and applications from the device. The device returns to the state it was in when purchased. Does not erase SD card. Note: When the Clean SD card on Remote Wipe option in the TouchDown Advanced Settings is enabled, the SD card is completely erased. | • | • | • | • | • | • | • | • | • | • | • | • |
| | Android w/TouchDown using OS v2.0 or 2.1: Full Wipe is not available – use the Selective Wipe option. | | | | | | | | | | | | |
| | BlackBerry: Removes all mail and PIM data associated with the NotifySync application and removes the NotifySync account. Locks the device if Require Password is enabled. | | | | | | | | | | | | |

| Security: All Devices | Description | Anrd | Anrd w/o ZMM | TD/A | NS/BB | iOS or TD/iOS | iOS w/o ZMM | S60 | S60 w/o ZMM | wOS | WM | WM w/o ZMM | WP |
|---|---|------|--------------------|------|-------|---------------------|-------------------|-----|-------------------|-----|----|------------------|----|
| | Erases the entire SD card, including saved attachments. | | | | | | | | | | | | |
| | iOS: The device returns to factory settings. This entails deleting all data and applications from the device. The device returns to the state it was in when purchased. | | | | | | | | | | | | |
| | Symbian: The device returns to factory settings. This entails deleting all data and applications from the device. The device returns to the state it was in when purchased. Some models (N95 and 6120c) wipe only Mail for Exchange data. Erases the SD card. | | | | | | | | | | | | |
| | WM: The device returns to factory settings. This entails deleting all data and applications from the device. The device returns to the state it was in when purchased. Erases the SD card only on Professional devices. | | | | | | | | | | | | |
| | webOS and WP: The device returns to factory settings. This entails deleting all data and applications from the device. The device returns to the state it was in when purchased. | | | | | | | | | | | | |
| Lock Device | Administrators or end users can remotely lock the device, requiring an unlock password to be entered before the device can be used. | • | | • | • | • | | | | | • | | |
| | Android or Android w/TouchDown: requires OS v2.2 or greater. | | | | | | | | | | | | |
| Clear Passcode | The passcode is cleared. If a passcode is required by the user's policy, the user will be prompted to enter a new passcode. | | | | | • | | | | | | | |
| Network Connection Security and Configuration | | | | | | | | | | | | | |
| SCEP (Simple Certification Enrollment | Sets up SCEP settings for devices. | | | | | • | | | | | | | |

| Security: All Devices | Description | Anrd | Anrd w/o ZMM | TD/A | NS/BB | iOS or TD/iOS | iOS w/o ZMM | S60 | S60 w/o ZMM | wOS | WM | WM w/o ZMM | WP |
|----------------------------------|--|------|--------------------|------|-------|---------------------|-------------------|-----|-------------------|-----|----|------------------|----|
| Protocol | | | | | | | | | | | | | |
| VPN (Virtual Private Network) | Sets up VPNs for devices. Current Functionality: IPSec (Cisco protocol) | | | | | • | | | | | | | |
| Wi-Fi | Sets up Wi-Fi settings, using various levels of security including WEP, WPA, and WPA2. | | | | | • | | | | | | | |

DEVICE STATISTICS: ALL DEVICES

| Device Statistics: All Devices | Description | Anrd | Anrd w/o ZMM | TD/A | NS/BB | iOS or TD/iOS | iOS w/o ZMM | S60 | S60 w/o ZMM | wOS | WM | WM w/o ZMM | WP |
|-----------------------------------|---|------|--------------------|------|-------|---------------------|-------------------|-----|-------------------|-----|----|------------------|----|
| ZENworks Sync | The date and time of the last successful synchronization with the ZENworks Mobile Management server. | • | | • | • | • | | • | | | • | | |
| ActiveSync Sync | The date and time of the last successful synchronization with the ActiveSync server. | • | • | • | • | • | • | • | • | • | • | • | • |
| iOS APN Sync | The date and time of the last successful synchronization with the Apple Push Notification server. | | | | | • | | | | | | | |
| Last Boot Time | The date and time of the last device boot. | • | | • | • | • | | | | | • | | |
| Device Time Zone | The time zone setting on the device. | • | | • | • | • | | | | | • | | |
| Device GMT Offset | The time difference between the device's time zone and Greenwich Mean Time. | • | | • | • | • | | | | | • | | |
| AS User Agent | The device's native ActiveSync application version, which corresponds to the device's operating system version. | • | • | • | • | • | • | • | • | • | • | • | • |
| AS Version | ActiveSync protocol version used by the device. | • | • | • | • | • | • | • | • | • | • | • | • |
| Battery Level | Displays the percentage of battery life left for the device. | • | | • | • | • | | • | | | • | | |
| Battery Status | Displays whether the device battery is charging or unplugged. | • | | • | • | • | | • | | | • | | |
| ZENworks Application Language | Name of the language the ZENworks Mobile Management device application is using. | • | | • | • | • | | • | | | • | | |
| ZENworks Application | Displays the version number of the | • | | • | • | • | | • | | | • | | |

| Device Statistics: All Devices | Description | Anrd | Anrd w/o ZMM | TD/A | NS/BB | iOS or TD/iOS | iOS w/o ZMM | S60 | S60 w/o ZMM | wOS | WM | WM w/o ZMM | WP |
|---------------------------------------|---|------|--------------------|------|-------|---------------------|-------------------|-----|-------------------|-----|----|------------------|----|
| Version | ZENworks Mobile Management device application. | | | | | | | | | | | | |
| Downloaded Data (any network) | Data usage statistics for data going out from the device over the network since the last device boot time. The sum-total of all networks. BlackBerry with NotifySync: Limited to | • | | • | • | • | | • | | | | | |
| Downloaded Data (cellular network) | Data usage statistics for data coming in to the device over the network since the last device boot time. The subtotal for the cellular network alone. | • | | • | | • | | • | | | | | |
| Downloaded Data (Wi-Fi) | Data usage statistics for data coming in to the device over the network since the last device boot time. The subtotal for Wi-Fi alone. | • | | • | | • | | • | | | | | |
| Uploaded Data (any network) | Data usage statistics for data going out from the device over the network since the last device boot time. The sum-total of all networks. BlackBerry with NotifySync: Limited to | • | | • | • | • | | • | | | | | |
| Uploaded Data (cellular network) | Data usage statistics for data going out from the device over the network since the last device boot time. The subtotal for the cellular network alone. | • | | • | | • | | • | | | | | |
| Uploaded Data (Wi-Fi) | Data usage statistics for data going out from the device over the network since the last device boot time. The subtotal for Wi-Fi alone. | • | | • | | • | | • | | | | | |
| Jailbroken | Whether or not an iOS or Android device has been jailbroken/rooted. | • | | • | | • | | | | | | | |
| Device IMEI | The International Mobile Equipment Identify number. See http://en.wikipedia.org/wiki/Internation al_Mobile_Equipment_Identity | • | | • | • | • | | • | | | • | | |
| | BlackBerry with NotifySync: Limited to GSM devices. | | | | | | | | | | | | |

| Device Statistics: All Devices | Description | Anrd | Anrd w/o ZMM | TD/A | NS/BB | iOS or TD/iOS | iOS w/o ZMM | S60 | S60 w/o ZMM | wOS | WM | WM w/o ZMM | WP |
|--------------------------------|---|------|--------------------|------|-------|---------------------|-------------------|-----|-------------------|-----|----|------------------|----|
| Device Model | Displays the device model. | • | | • | • | • | | • | | | • | | |
| Device UID | Displays the device UID. | | | | | | | | | | | | |
| | Symbian: The device UID is the same as the device IMEI. | | | | • | | | • | | | • | | |
| Device Type | Displays the device type as reported by the device. | • | | • | • | • | | • | | | • | | |
| Device Memory Capacity | Displays the total of the used and unused memory on the device. | • | | • | • | • | | • | | | • | | |
| Device Free Memory | Displays the amount of free memory left on the device. (Labeled Available Device Capacity for iOS devices.) | • | | • | • | • | | • | | | • | | |
| Network Type | Displays the network type the device is using. | • | | • | • | • | | • | | | • | | |
| OS Language | Name of the language the device OS is using. | • | | • | • | | | • | | | • | | |
| OS Version | Displays the device OS version. | • | | • | • | • | | • | | | • | | |
| Phone Number | Displays device phone number. | • | | • | • | • | | | | | • | | |
| Device Ownership | Tracks whether the device is a company device or personal device. | • | | • | • | • | | • | | | • | | |
| Phone Usage | Displays the phone minutes used in the last 30 days. This is calculated from phone logs. | • | | • | • | | | • | | | • | | |
| Roaming | Displays a simple yes or no if the device is roaming. | • | | • | • | • | | • | | | • | | |
| SD Card Status | Displays if there is an SD card in the device. | | | | | | | | | | | | |
| | iOS devices do not have SD card capability. | _ | | _ | | | | | | | | | |
| SD Card Free Memory | Displays the amount of free memory left on the device's storage card. | | | | | | | | | | | | |
| | iOS devices do not have SD card capability. | • | | • | • | | | • | | | • | | |
| SD Card Total Memory | Displays the total of the used and unused memory on the device storage card. | • | | • | • | | | • | | | • | | |

| Device Statistics: All Devices | Description | Anrd | Anrd w/o ZMM | TD/A | NS/BB | iOS or TD/iOS | iOS w/o ZMM | S60 | S60 w/o ZMM | wOS | WM | WM w/o ZMM | WP |
|---------------------------------------|---|------|--------------------|------|-------|---------------------|-------------------|-----|-------------------|-----|----|------------------|----|
| Signal Level | Displays the signal strength using a percentage value. | • | | • | • | | | • | | | • | | |
| Device Encrypted | Whether the data stored in the device's local memory is encrypted. | • | • | • | • | • | • | | | | • | | |
| SD Card Encrypted | Whether the data stored on the device's storage card is encrypted. | | | • | | | | | | | • | | |
| TouchDown Registered | Whether the TouchDown application is registered on an Android device. | • | | • | | | | | | | | | |
| SD Card IMSI Number | The ID number of the SD card: International Mobile Subscriber Identity. | • | | • | • | | | | | | • | | |
| Device Name | The name given via iTunes. | | | | | | | | | | | | |
| Build Version | iOS build number. | | | | | • | | | | | | | |
| Model Name | Name of the device model. | | | | | • | | | | | | | |
| Model | The device's internal model number. | | | | | • | | | | | | | |
| Product Name | The model code for the device. | | | | | • | | | | | | | |
| Serial Number | The device's serial number. | | | | | | | | | | | | |
| Cellular Technology | Cellular technology 0 = none 1 = GSM 2 = CDMA | | | | | • | | | | | | | |
| MEID | The device's MEID (CDMA). | | | | | • | | | | | | | |
| Modem Firmware Version | The baseband firmware version. | | | | | • | | | | | | | |
| ICCID | The ICC identifier for the installed SIM card (if applicable). | | | | | • | | | | | | | |
| Bluetooth MAC | Bluetooth MAC address. | | | | | | | | | | | | |
| Wi-Fi MAC | Wi-Fi MAC address. | | | | | • | | | | | | | |
| Current Carrier Network | Name of current carrier network. | | | | | • | | | | | | | |
| SIM Carrier Network | Name of the home carrier network. (Note: Applies to CDMA in spite of its name.) | | | | | • | | | | | | | |
| Carrier Settings Version | Version of currently installed carrier settings file. | | | | | • | | | | | | | |

| Device Statistics: All Devices | Description | Anrd | Anrd w/o ZMM | TD/A | NS/BB | iOS or TD/iOS | iOS w/o ZMM | S60 | S60 w/o ZMM | wOS | WM | WM w/o ZMM | WP |
|---------------------------------------|------------------------------------|------|--------------------|------|-------|---------------------|-------------------|-----|-------------------|-----|----|------------------|----|
| Voice Roaming Enabled | Current setting for Voice Roaming. | | | | | • | | | | | | | |
| Data Roaming Enabled | Current setting for Data Roaming. | | | | | • | | | | | | | |
| Subscriber MCC | Home Mobile Country Code | | | | | • | | | | | | | |
| Subscriber MNC | Home Mobile Network Code | | | | | • | | | | | | | |
| Current MCC | Current Mobile Country Code | | | | | • | | | | | | | |
| Current MNC | Current Mobile Network Code | | | | | • | | | | | | | |

COMPLIANCE MANAGER

| Compliance Manager | Description | Anrd | Anrd w/o ZMM | TD/A | NS/BB | iOS | TD/ iOS | iOS w/o ZMM | S60 | S60 w/o ZMM | wOS | WM | WM w/o ZMM | WP |
|---|--|------|--------------------|------|-------|-----|------------|-------------------|-----|-------------------|-----|----|------------------|----|
| Access Restriction | | | | | | | | | | | | | | |
| Restrict on ActiveSync authorization failures | A device passes invalid credentials for the ActiveSync account of a known user to the server a number of times that exceeds the set limit. | • | • | • | • | • | • | • | • | • | • | • | • | • |
| Restrict ActiveSync protocol | A device cannot support sufficient ActiveSync policies, because of ActiveSync version support limitations with the device or server. | • | • | • | • | • | • | • | • | • | • | • | • | • |
| Restrict cellular connection | A device is using a cellular network connection and is in violation of the enabled Restrict Cellular Connection access policy. | | | | • | | | | | | | | | |
| Restrict Liability | A device enrolls with a liability status specifically restricted by the Restrict Liability access policy. | • | • | • | • | • | • | • | • | • | • | • | • | • |
| Restrict on ZENworks authorization failures | A device passes invalid credentials for the ZENworks Mobile Management account of a known user to the server a number of times that exceeds the set limit. | • | NA | • | • | • | • | NA | • | NA | NA | • | NA | NA |
| Restrict BlackBerrys without NotifySync | A BlackBerry device that does not have the NotifySync application has enrolled. | NA | NA | NA | • | NA | NA | NA | NA | NA | NA | NA | NA | NA |
| Restrict if roaming detected | A device is roaming and is in violation of the Restrict if Roaming Detected access policy. | • | | • | • | • | • | | • | | | • | | |
| Restrict if SIM Card removed or changed | A user has removed or changed the SIM card in a device and is in violation of the Restrict if SIM Card is Removed or Changed access policy. | • | | • | • | • | • | | | | | • | | |

| Compliance Manager | Description | Anrd | Anrd w/o ZMM | TD/A | NS/BB | iOS | TD/ iOS | iOS w/o ZMM | S60 | S60 w/o ZMM | wOS | WM | WM w/o ZMM | WP |
|--|--|------|--------------------|------|-------|-----|------------|-------------------|-----|-------------------|-----|----|------------------|----|
| Restrict TouchDown for Android | TouchDown is required and either an Android device does not have the TouchDown application or the TouchDown version does not meet the minimum requirement. | • | • | • | NA | NA | NA | NA | NA | NA | NA | NA | NA | NA |
| Restrict user ActiveSync connections | A device's Last ActiveSync Sync time stamp has not updated within the set interval. | • | • | • | • | • | • | • | • | • | • | • | • | • |
| Restrict Wi-Fi connection | A device is using a Wi-Fi connection and is in violation of the enabled Restrict Wi-Fi Connection access policy. | | | | • | | | | | | | | | |
| Single Devices | A specific device, identified by phone number or UID number, has been denied access. | • | | • | • | • | • | | • | | | | | |
| Single Users | A specific user, identified by User Name, has been denied access. | • | • | • | • | • | • | • | • | • | • | • | • | • |
| Device Platform Restriction | | | | | | | | | | | | | | |
| Restrict if ZENworks app is not enrolled | A device enrolls via the native ActiveSync agent alone and without the ZENworks Mobile Management application. | • | • | • | • | • | • | • | • | • | • | • | | |
| Restrict if location not updated | A device's location has not updated within the defined interval. | • | | • | • | • | • | | • | | | • | | |
| Restrict user ZENworks connections | A device's Last ZENworks Sync time stamp has not updated within the set interval. | • | | • | • | • | • | | • | | | • | | |
| Restrict if policy out of date | A policy has been updated on the server, but a device has not updated within the set grace period. | • | • | • | • | • | • | • | • | • | • | • | • | • |
| Restrict rooted devices | A rooted Android device connects to the server. | • | | • | NA | NA | NA | NA | NA | NA | NA | NA | NA | NA |
| Restrict jailbroken devices | A jailbroken iOS device connects to the server. | NA | NA | NA | NA | • | • | | NA | NA | NA | NA | NA | NA |
| Restrict if iOS passcode not initiated | The user's policy suite requires a password, but the iOS device does not have a passcode initiated. | NA | NA | NA | NA | • | • | | NA | NA | NA | NA | NA | NA |

| Compliance Manager | Description | Anrd | Anrd w/o ZMM | TD/A | NS/BB | iOS | TD/ iOS | iOS w/o ZMM | S60 | S60 w/o ZMM | wOS | WM | WM w/o ZMM | WP |
|--|---|------|--------------------|------|-------|-----|------------|-------------------|-----|-------------------|-----|----|------------------|----|
| Restrict if iOS passcode is not compliant with requirements | The user's policy suite requires a password, but the iOS device does not have a passcode compliant with the requirements. | NA | NA | NA | NA | • | • | | NA | NA | NA | NA | NA | NA |
| Restrict if iOS passcode is not compliant with data protection | The iOS device does not have a passcode and thus is not compliant with iOS "data protection," which enhances the built-in hardware encryption by protecting the hardware encryption keys with the passcode. | NA | NA | NA | NA | • | • | | NA | NA | NA | NA | NA | NA |
| Restrict if iOS unmanaged configuration profile is on device | An iOS device has an unmanaged configuration profile. | NA | NA | NA | NA | • | • | | NA | NA | NA | NA | NA | NA |
| Restrict if iOS APN profiles are not enrolled | An iOS device has not loaded the iOS APN configuration profile and has never synchronized through the Apple MDM API. | NA | NA | NA | NA | • | • | | NA | NA | NA | NA | NA | NA |
| Restrict if no iOS APN connectivity | A device's Last iOS APN Sync time stamp has not updated within the set interval. | NA | NA | NA | NA | • | • | | NA | NA | NA | NA | NA | NA |
| Non-Access Policy Based Alerts | | | | | | | | | | | | | | |
| Low battery detection | A device's battery level has fallen below a specified warning level. | • | | • | • | • | • | | • | | | • | | |
| Low memory detection | A device's memory level has fallen below the greater of the two specified levels. | • | | • | • | • | • | | • | | | • | | |
| Low on redemption codes | The number of redemption codes (for iOS devices installing an app obtained through the Apple Volume Purchase Program) available on the server has fallen below a specified amount. | NA | NA | NA | NA | • | • | | NA | NA | NA | NA | NA | NA |
| ZENworks app is not enrolled | A device of any platform type connects to the server via ActiveSync and does not have the ZENworks Mobile Management application enrolled. | • | • | • | • | • | • | • | • | • | • | • | • | • |

| Compliance Manager | Description | Anrd | Anrd w/o ZMM | TD/A | NS/BB | iOS | TD/ iOS | iOS w/o ZMM | S60 | S60 w/o ZMM | wos | WM | WM w/o ZMM | WP |
|---|---|------|--------------------|------|-------|-----|------------|-------------------|-----|-------------------|-----|----|------------------|----|
| Organization-wide ActiveSync connectivity | The Last ActiveSync Sync time stamp has not updated for any users within the set interval. | • | • | • | • | • | • | • | • | • | • | • | • | • |
| Organization-wide ZENworks connectivity | The Last ZENworks Sync time stamp has not updated for any users within the set interval. | • | | • | • | • | • | | • | | | • | | |
| Watch List | A user or policy suite on the Watch List grid has exceeded the time for which it was being monitored. | • | • | • | • | • | • | • | • | • | • | • | • | • |
| User's e-mail not set | A user's email address has not been set. Because a user's email address cannot always be determined during Hands-Off provisioning, this alerts the administrator that an email address for the user should be manually set. | • | • | • | • | • | • | • | • | • | • | • | • | • |
| Event Based Alerts | | | | | | | | | | | | | | |
| ActiveSync Account Already Enrolled | An iOS profile included an ActiveSync payload that could not be installed because an identical ActiveSync account was already enrolled. | NA | NA | NA | NA | • | • | | NA | NA | NA | NA | NA | NA |
| Clear device enrollment | An administrator has issued a Clear Device Enrollment command from the dashboard to a device. | • | • | • | • | • | • | • | • | • | • | • | • | • |
| Clear passcode issued by Admin | An administrator has issued a Clear Passcode from the dashboard to an iOS device. | NA | NA | NA | NA | • | • | | NA | NA | NA | NA | NA | NA |
| Full wipe issued by Admin | An administrator has issued a Full Wipe command from the dashboard to a device. | • | • | • | • | • | • | • | • | • | • | • | • | • |
| Full wipe issued by user | A user has issued a Full Wipe command from the User Self Administration Portal to their device. | • | • | • | • | • | • | • | • | • | • | • | • | • |
| Lock device issued by Admin | An administrator has issued a Lock Device command from the dashboard to a device. | • | | • | • | • | • | | • | | | • | | |
| Lock device issued by user | A user has issued a Lock Device command from the User Self Administration Portal to their device. | • | | • | • | • | • | | | | | • | | |

| Compliance Manager | Description | Anrd | Anrd w/o ZMM | TD/A | NS/BB | iOS | TD/ iOS | iOS w/o ZMM | S60 | S60 w/o ZMM | wOS | WM | WM w/o ZMM | WP |
|---------------------------------------|---|------|--------------------|------|-------|-----|------------|-------------------|-----|-------------------|-----|----|------------------|----|
| New Hands-Off Provisioned device | Any time a new device uses Hands-Off enrollment to connect to the system. | • | • | • | • | • | • | • | • | • | • | • | • | • |
| New Hands-Off Provisioned user | Any time a new user uses Hands-Off enrollment to connect to the system. | • | • | • | • | • | • | • | • | • | • | • | • | • |
| Recovery password requested by device | A user requests a temporary recovery password form a device's locked screen. | | | • | • | | | | | | | | | |
| Recovery Password viewed by Admin | An administrator has attempted to view a temporary recovery password issued for a user from the dashboard. | | | • | • | | | | | | | | | |
| Recovery Password viewed by user | A user has attempted to view a temporary recovery password from the User Self Administration Portal. (This does not detect when the recovery password has been viewed through OWA.) | | | • | • | | | | | | | | | |
| Restricted device attempts to connect | A restricted device tries to access ActiveSync, File Share, or Mobile Apps when these resources have been blocked. | • | • | • | • | • | • | • | • | • | • | • | • | • |
| Selective wipe issued by Admin | An administrator has issued a Selective Wipe command from the dashboard to a device. | • | | • | • | • | • | | • | | | • | | |
| Selective wipe issued by user | A user has issued a Selective Wipe command from the User Self Administration Portal to a device. | • | | • | • | • | • | | • | | | • | | |
| TouchDown policy override detection | The system issues a warning if it detects that a user has overridden the TouchDown settings governed by ZENworks Mobile Management. | NA | NA | • | NA | NA | | NA | NA | NA | NA | NA | NA | NA |
| User restricted | A user becomes restricted for any reason. | • | • | • | • | • | | • | • | • | • | • | • | • |
| Wipe storage card | An administrator has issued a Wipe Storage Card command from the dashboard to a device. | • | | • | • | NA | | NA | | | | • | | |