## **Functionality by Device Platform**

**ZENworks**. Mobile Management 2.9.x

July 2014

#### **Legal Notices**

Novell, Inc., makes no representations or warranties with respect to the contents or use of this documentation, and specifically disclaims any express or implied warranties of merchantability or fitness for any particular purpose. Further, Novell, Inc., reserves the right to revise this publication and to make changes to its content, at any time, without obligation to notify any person or entity of such revisions or changes.

Further, Novell, Inc., makes no representations or warranties with respect to any software, and specifically disclaims any express or implied warranties of merchantability or fitness for any particular purpose. Further, Novell, Inc., reserves the right to make changes to any and all parts of Novell software, at any time, without any obligation to notify any person or entity of such changes.

Any products or technical information provided under this Agreement may be subject to U.S. export controls and the trade laws of other countries. You agree to comply with all export control regulations and to obtain any required licenses or classification to export, re-export or import deliverables. You agree not to export or re-export to entities on the current U.S. export exclusion lists or to any embargoed or terrorist countries as specified in the U.S. export laws. You agree to not use deliverables for prohibited nuclear, missile, or chemical biological weaponry end uses. See the Novell International Trade Services Web page (http://www.novell.com/info/exports/) for more information on exporting Novell software. Novell assumes no responsibility for your failure to obtain any necessary export approvals.

Copyright © 2012-14 Novell, Inc. All rights reserved. No part of this publication may be reproduced, photocopied, stored on a retrieval system, or transmitted without the express written consent of the publisher.

Novell, Inc. 1800 South Novell Place Provo, UT 84606 U.S.A. www.novell.com

Online Documentation: To access the latest online documentation for this and other Novell products, see the Novell Documentation Web page (http://www.novell.com/documentation).

#### **Novell Trademarks**

For Novell trademarks, see the Novell Trademark and Service Mark list (http://www.novell.com/company/legal/trademarks/tmlist.html).

#### **Third-Party Materials**

All third-party trademarks are the property of their respective owners.

## **TABLE OF CONTENTS**

Policy Rules: All Devices		5	
Policy Rules: iOS Devices		19	
Policy Rules: TouchDown		27	
Security: All Devices		39	
Device Statistics: All Devices		44	
Compliance Manager		51	
▶ Policy Rules: All Devices	▶ Policy Rules: iOS Device		
Audit Tracking	Device Features	<b>⊳</b> Se	curity: All Devices
Device Control	Applications		
Device Features	Safari Browser		
Email	Ratings	·	Network Confidence of County and Configuration
ActiveSync Synchronization	• Security	<b>►</b> Do	vice Statistics: All Devices
File Share Permissions			
Managed Apps Permissions	• <u>iCloud</u>	•	Device Statistics
Whitelists/Blacklists Permissions	• <u>Management</u>		
Resource Control	Supervised Mode	► Co	mpliance Manager
Security Settings	► Policy Rules: TouchDown	•	Access Policies and Device Restrictions
Password	• <u>Installation</u>	•	Non-Access Policy Based Alerts
Encryption	• <u>General</u>	•	Event Based Alerts
Device Inactivity and Locking	• <u>Signature</u>	•	System Alerts
	• <u>Widgets</u>		
Emergency Calls  S/MINE Settings	Phone Book		
S/MIME Settings	User Configurable Settings		
	Suppression Rules		

The information in these tables describes functionality supported by each device platform for ZENworks Mobile Management, version 2.9.x.

Device platforms supported by *ZENworks Mobile Management* are Android, BlackBerry (4.5-7.1) with *GO!NotifySync*, BlackBerry (OS 10), iOS, Symbian S60 3<sup>rd</sup> edition, webOS, Windows Mobile 6, and Windows Phone. Supported device operating system versions are listed below.

Anrd	TD/A	BB10	NS/BB	iOS	TD/iOS	S60	wos	WM	WP	
•	<b>₽</b>	<u>=</u>	塦	ios	40	S60 <sup>*</sup>	web	At .	•	
Android devices OS v2.2 – 4.4	Android devices OS v2.2 - 4.4 with TouchDown v8.4.x	BlackBerry devices OS 10	BlackBerry devices OS v4.5 – 7.1 with GO!NotifySync v4.9 or greater	iOS 5 – 7.1.2 multitasking devices	iOS 5 – 7.1.2 multitasking devices with latest TouchDown app version	Symbian S60 3rd edition devices OS v 9.1	WebOS devices OS v1.4.3/1.4.5, 2.0.0/2.0.1, 2.1.2	Windows Mobile devices OS v6.1/6.5	Windows Phone devices OS v7, 7.5, 8	

### The ZENworks Mobile Management Device Application

Android, iOS, Symbian S60 3<sup>rd</sup> Edition, and Window Mobile devices use the *ZENworks Mobile Management* device application to provide additional functionality and enforce policies that are not handled by ActiveSync. The *GO!NotifySync for BlackBerry* application, which interfaces with *ZENworks Mobile Management*, has an MDM component that enforces ActiveSync policies and provides additional functionality for BlackBerry 4.5-7.1 devices. (Requires an additional *GO!NotifySync* license.)

The device platforms listed above also require a native ActiveSync protocol or an application that uses the ActiveSync protocol, such as GO!NotifySync for BlackBerry or TouchDown for Android.

- On Android OS 2.2 or greater devices, the ActiveSync protocol native to the device is sufficient; although the TouchDown application, offers greater functionality. See Policy Rules: TouchDown
- On BlackBerry devices (OS 4.5-7.1), GO!NotifySync for BlackBerry v4.9.x or greater is the ActiveSync application required to handle the ActiveSync policies. The application has an MDM component that interfaces with ZENworks Mobile Management and provides additional functionality. (Requires an additional GO!NotifySync license.)
- On iOS 5, 6, and 7 devices with multitasking capabilities, the ActiveSync policies are enforced by using Apple configuration profiles.
- On Symbian S60 3<sup>rd</sup> Edition devices, *Mail for Exchange* is required to handle the ActiveSync policies.
- On Windows Mobile 6.1/6.5 devices, the ActiveSync protocol native to the device is sufficient.

Enrolling Android, iOS, Symbian, or Windows Mobile 6 devices without the ZENworks Mobile Management app is not recommended, because only ActiveSync policies supported by the device platform or model can be enforced. BlackBerry devices do not have native ActiveSync capabilities and are not supported without the GO!NotifySync app.

### **ActiveSync Only Devices**

BlackBerry (OS 10), webOS and Windows Phone platforms, for which there are no *ZENworks Mobile Management* applications, are also supported. Because these devices utilize the native ActiveSync protocol alone, only ActiveSync policies supported by the device platform or model can be enforced.

## **POLICY RULES: ALL DEVICES**

ZENworks Mobile Management is a trademark of Novell, Inc. The abbreviation "ZMM" is not a Novell trademark, but is used in these tables because of space constraints.

• Red text or dots indicate **ActiveSync only** - Currently, there is no *ZENworks Mobile Management* app available for BB10, WP or wOS. Devices support the feature via the native ActiveSync app on the device. BlackBerry 4.5-7.1 devices have no native ActiveSync app and are only supported with the GO!NotifySync app.

Policy Suite Rules: All Devices	Description	Anrd	Anrd w/ AS only	TD/A	NS/BB	iOS	TD/ iOS	iOS w/ AS only	iOS Config Devices	S60	S60 w/ AS only	WM	WM w/ AS only	AS only
Audit Tracking														
Archive Device File List	Requires the device to periodically send a list of all folders and files stored on the device and the SD card to the server. Displayed on the server in the User Profile: File Archive													
	Symbian devices: Sends most files, with the exception of those in the device's X:\private and X:\sys folders, which normally contain system files or sensitive application data. The administrator defines the frequency of the file archiving.	•		•	•					•				
Record Phone Log	Requires the device to send all telephone log information to the server.  For BlackBerry devices with GO!NotifySync, tracks only calls made after ZENworks Mobile Management enrollment.	•		•	•					•				
Record Text Message Log	Requires the device to send all Short Message Service (SMS) and Multimedia Messaging Service (MMS) information to server.  BlackBerry devices with GO!NotifySync:  Do not track MMS messages	•		•	•					•				

Policy Suite Rules: All Devices	Description	Anrd	Anrd w/ AS only	TD/A	NS/BB	iOS	TD/ iOS	iOS w/ AS only	iOS Config Devices	S60	S60 w/ AS only	WM	WM w/ AS only	AS only
	Track only texts made after ZENworks Mobile Management enrollment													
	Some devices use only MMS, so text messaging is not tracked													
	Android devices: Text and MMS logging functionality might vary based on the device manufacturer or carrier. (See the SMS & MMS Capabilities document.)													
	Symbian S60 3 and Windows Mobile devices: Records only SMS messages.													
Record Installed Applications	Requires the device to send app information with data usage statistics for all applications installed on the device. Usage statistics are displayed in the Apps section of the User Profile.	•		•										
Record Managed Applications	Requires the device to send app information with data usage statistics for managed applications. Usage statistics are displayed in the Apps section of the User Profile.	•		•										
Record Location of Device (Latitude / Longitude)	Uses GPS or triangulation on the device to locate where a user's device is at all times. Information is displayed using Google Maps. The device reports longitude and latitude as two separate values.	•		•	•	•	•			•				
GPS Location Accuracy	Allows administrators to specify a level of location accuracy. Accuracy primarily depends on using a cell tower vs. GPS (satellite) location methods; additional factors may be involved depending on the device type. Because improved accuracy generally results in increased battery usage, the level can be adjusted to facilitate a more efficient use of a device battery. Set levels via the policy suite.	•		•	•	•	•							

Policy Suite Rules: All Devices	Description	Anrd	Anrd w/ AS only	TD/A	NS/BB	iOS	TD/ iOS	iOS w/ AS only	iOS Config Devices	S60	S60 w/ AS only	WM	WM w/ AS only	AS only
Device Controls: Device Features														
Allow Bluetooth (ActiveSync)	Determines whether Bluetooth is allowed to operate on the device. There are three settings:  Don't allow Bluetooth  Allow only Bluetooth headsets											•	•	
Allow Browser (ActiveSync)	Allow all Bluetooth  Determines whether the use of the native Web browser is allowed on the device. This setting might also prevent the use of third-party browsers that use the native browser as a basis for operation.					•	•	•	•			•	•	
Allow Camera (ActiveSync)	Determines whether the use of the device camera is allowed. Disabling the camera might limit the functionality of third-party apps that use the camera such as: Photoshop.  For Android: supported on devices with OS 4.0 and KNOX Standard compatible devices.	•	•	•		•	•	•	•			•	•	
Allow Infrared (ActiveSync)	Determines whether infrared connections are allowed to and from the device.											•	•	
Allow Internet Sharing from the Device (Tethering)  (ActiveSync)	Determines whether the device can be used as a modem for a desktop or a portable computer.											•	•	
Allow Remote Desktop (ActiveSync)	Determines whether a remote desktop connection can be created from the device.											•	•	
Allow SD Card (ActiveSync)	Determines whether using an SD Card is allowed on the device.  For Android w/ TouchDown: Allows or disallows SD card access for the TouchDown application only.			•								•	•	

Policy Suite Rules: All Devices	Description	Anrd	Anrd w/ AS only	TD/A	NS/BB	iOS	TD/ iOS	iOS w/ AS only	iOS Config Devices	S60	S60 w/ AS only	WM	WM w/ AS only	AS only
Allow Synchronization from a Desktop (ActiveSync)	Determines whether the device can synchronize with a computer through a cable, Bluetooth, or IrDA connection.											•	•	
Allow Text Messaging (ActiveSync)	Determines whether the device can send or receive text messages.											•	•	
Allow Wi-Fi (ActiveSync)	Determines whether wireless Internet access is allowed on the device.								•			•	•	
Initiate Selective Wipe when user removes MDM app account	If the user removes the MDM account on the device, a selective wipe is executed. Selective Wipe functionality varies by device platform.	•	•	•	•	•	•	•	•	•	•	•	•	BB10 wOS WP
Device Controls: Email	·													
Allow HTML formatted Email (ActiveSync)	Determines whether email synchronized to the device can be in HTML format.  Not supported with systems operating with ActiveSync protocol 2.5, such as			•	•		•					•	•	BB10
Maximum HTML email body truncation size (in KB)  (ActiveSync)	Defines the maximum HTML email body size of messages received on the device.  Not supported with systems operating with ActiveSync protocol 2.5, such as				•							•	•	
Allow Consumer Email (ActiveSync)	Determines whether the user can use Windows Live services, such as Hotmail, Office, or Spaces.											•	•	
Allow POP/IMAP Email (ActiveSync)	Determines whether the device can access POP3 or IMAP4 email.											•	•	
Maximum plain text email body truncation size (in KB)  (ActiveSync)	Defines the maximum email body size of plain text messages received on the device.			•	•		•					•	•	
Device Control: ActiveSync Synchronization														
Maximum calendar age for	Defines the maximum look-back age of			•	•		•					•	•	BB10

Policy Suite Rules: All Devices	Description	Anrd	Anrd w/ AS only	TD/A	NS/BB	iOS	TD/ iOS	iOS w/ AS only	iOS Config Devices	S60	S60 w/ AS only	WM	WM w/ AS only	AS only
synchronization (ActiveSync)	calendar events. Events older than the maximum age are automatically removed from the device.  Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003.													WP
Specific calendar age for synchronization	Determines a specific number of calendar days that can be synchronized. The value should be lower than the Maximum calendar age for synchronization.			•			•							
Maximum email age for synchronization  (ActiveSync)	Defines the maximum age of email on the device. Email older than the maximum age is automatically removed from the device.			•	•	•	•	•	•			•	•	BB10 WP
	Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003.													
Specific Email age for synchronization	Determines a specific age for emails to synchronize. The value should be lower than the <i>Maximum Email age for synchronization</i> .			•			•							
Require manual sync when roaming  (ActiveSync)	Enforces the use of manual synchronization on the device while roaming to avoid the higher data costs that are often incurred with automatic			•	•	•	•	•	•			•	•	
File and Application Management	synchronization.													
File Share Permissions	Creates a directory of folders and files to make accessible to users. Users access files directly through the ZENworks Mobile Management app. Sets permissions for access per policy suite.	•		•	•	•	•			•		•		
Managed Apps Permissions	Creates a list of recommended apps. The list might consist of apps that users access directly through ZENworks Mobile Management or through links to the apps in device application stores. Available mobile applications are determined by device type.	•		•	•	•	•		•	•		•		

Policy Suite Rules: All Devices	Description	Anrd	Anrd w/ AS only	TD/A	NS/BB	iOS	TD/ iOS	iOS w/ AS only	iOS Config Devices	S60	S60 w/ AS only	WM	WM w/ AS only	AS only
	Administrators can force push apps on the list to Android and iOS users.													
	iOS Configurator devices: Apps can only be made available on the device by an administrator via force push.													
Whitelists/Blacklists Permissions	Create a list of strings that will filter either by blacklisting or whitelisting applications.													
	Blacklist - When one or more blacklisted applications are installed on a device, the user's access to email, shared files, app lists, or other organization resources can be blocked.	•		•		•	•	•	•					
	Whitelist – When one or more applications are installed on a device that are not on the Whitelist, the user's access to email, shared files, app lists, or other organization resources can be blocked.													
Resource Control														
Allow ActiveSync	Determines whether users are permitted to make ActiveSync connections.	•	•	•	•	•	•	•		•	•	•	•	BB10 wOS WP
Allow File Share	Determines whether users are permitted to access the File Share.	•		•	•	•	•		•	•		•		
Allow Managed Apps	Determines whether users are permitted to access the Managed Apps list.	•		•	•	•	•		•	•		•		
Security: Password														
Require Device Password	Forces the device to require a password													BB10
(ActiveSync)	to unlock the device.	•	•	•	•	•	•	•	•	•	•	•	•	wOS WP
Require TouchDown PIN	Determines whether a PIN is required to access the TouchDown app. Can be used in addition to or in place of the Require Device Password option.			•			•							
Enable password recovery	This allows or disallows a user to use the device to issue a request for a			•	•									

Policy Suite Rules: All Devices	Description	Anrd	Anrd w/ AS only	TD/A	NS/BB	iOS	TD/ iOS	iOS w/ AS only	iOS Config Devices	S60	S60 w/ AS only	WM	WM w/ AS only	AS only
(ActiveSync)	temporary recovery password if they have forgotten their unlock password. The recovery password can be retrieved from the MDM User Self Administration Portal or the administrative dashboard. Requires ActiveSync protocol 12.0 or 12.1													
	For Android w/TouchDown, gives temporary unlock password only for the TouchDown application; does not provide temporary unlock password when the lock is imposed by the device's native OS.													
Allow Simple Password (ActiveSync)	Determines whether or not a password can consist of only repeating or sequential characters, such as "1111" or "abcd". Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003.	•	•	•	•	•	•	•	•	•	•	•	•	WP
Require Minimum Password Length  (ActiveSync)	Forces the device to require a password with a specified minimum length.	•	•	•	•	•	•	•	•	•	•	•	•	BB10 wOS WP
Minimum Password Length (ActiveSync)	Defines the minimum password length.	•	•	•	•	•	•	•	•	•	•	•	•	BB10 wOS WP
Require complex password	User must create a password containing at least a letter, a numerical digit, and a special symbol.  Requires Android OS 3.0 or greater. If this requirement is set and a device does not support it, the next level of security, which is alphanumeric will be implemented.	•	•	•										***
Require Alphanumeric Password  (ActiveSync)	Forces the device to require a device password to contain both letters and numbers.	•	•	•	•	•	•	•	•	•	•	•	•	wOS
Minimum Number of Complex Characters	Forces the device to require a minimum	•	•	•	•	•	•	•	•			•	•	

		Anrd w/ AS only	TD/A	NS/BB	iOS	TD/ iOS	iOS w/ AS only	iOS Config Devices	S60	S60 w/ AS only	WM	WM w/ AS only	AS only
er of complex characters (symbols) password. If an alphanumeric word is not required, this is not ced.													
ndroid (native): Supported on es with OS 3.0, selected OS 2.x es, and KNOX Standard atible devices.													
lackBerry w/ GO!NotifySync: lum number of each type of cter required in an alphanumeric word. (Example: If minimum is 2, word must have 2 uppercase, 2 case, 2 numeric, and 2 symbol cters.)													
must create a password containing st alphabetic (or other symbol) cters.	•	•	•										
must create a password containing st numeric characters.	•	•	•										
s for low-security biometric (face) nition technology. Uses ologies that can recognize the sy of an individual to about a 3 digit alse detection is less than 1 in ).	•	•	•										
res Android OS 4.0 or greater.													
s the device to require users to e their passwords after a number vs. Not supported with systems ting with ActiveSync protocol 2.5, as Exchange 2003.													BB10
oid: Supported on devices with OS elected devices with OS 2.x, and C Standard compatible devices.	•	•	•	•	•	•	•	•			•	•	WP
Berry 10: Not supported on Q5 and													
es the number of days a password e used before it expires.	•	•	•	•	•	•	•	•			•	•	BB10 WP
	password. If an alphanumeric yord is not required, this is not sed.  Indroid (native): Supported on es with OS 3.0, selected OS 2.x es, and KNOX Standard atible devices.  IackBerry w/ GO!NotifySync:  Ium number of each type of cter required in an alphanumeric yord. (Example: If minimum is 2, yord must have 2 uppercase, 2 case, 2 numeric, and 2 symbol cters.)  Indust create a password containing est alphabetic (or other symbol) cters.  Indust create a password containing est numeric characters.  Is for low-security biometric (face) inition technology. Uses cologies that can recognize the ey of an individual to about a 3 digit alse detection is less than 1 in also in the device to require users to be their passwords after a number es. Not supported with systems ting with ActiveSync protocol 2.5, as Exchange 2003.  Indicidication is supported on devices with OS elected devices with OS 2.x, and a Standard compatible devices.  Berry 10: Not supported on Q5 and	password. If an alphanumeric yord is not required, this is not sed.  Indroid (native): Supported on es with OS 3.0, selected OS 2.x es, and KNOX Standard estible devices.  IackBerry w/ GO!NotifySync:  IackBerry w/ GO!NotifySync:  Iam number of each type of other required in an alphanumeric yord. (Example: If minimum is 2, yord must have 2 uppercase, 2 case, 2 numeric, and 2 symbol others.)  Indust create a password containing est alphabetic (or other symbol) others.  Indust create a password containing est numeric characters.  Indust create a password containing est alphabetic (or other symbol) others.  Industrial this industrial th	password. If an alphanumeric yord is not required, this is not sed.  Indroid (native): Supported on ses with OS 3.0, selected OS 2.x ses, and KNOX Standard atible devices.  IdackBerry w/ GO!NotifySync:  Immumber of each type of cter required in an alphanumeric yord. (Example: If minimum is 2, yord must have 2 uppercase, 2 case, 2 numeric, and 2 symbol cters.)  Immust create a password containing st alphabetic (or other symbol) cters.  Immust create a password containing st numeric characters.  Is for low-security biometric (face) inition technology. Uses ploigies that can recognize the ty of an individual to about a 3 digit alse detection is less than 1 in also in the device to require users to be their passwords after a number res. Not supported with systems thing with ActiveSync protocol 2.5, as Exchange 2003.  Indic Supported on devices with OS as Exchange 2003.  Indic Supported on devices with OS elected devices with OS 2.x, and a standard compatible devices.  Berry 10: Not supported on Q5 and est the number of days a password	password. If an alphanumeric yord is not required, this is not sed.  Indroid (native): Supported on es with OS 3.0, selected OS 2.x es, and KNOX Standard atible devices.  IackBerry w/ GO!NotifySync:  Immumber of each type of ceter required in an alphanumeric yord. (Example: If minimum is 2, yord must have 2 uppercase, 2 case, 2 numeric, and 2 symbol ceters.)  Immust create a password containing est alphabetic (or other symbol) ceters.  Immust create a password containing est alphabetic (or other symbol) ceters.  Immust create a password containing est numeric characters.  Is for low-security biometric (face) est of individual to about a 3 digit alse detection is less than 1 in hold.  In the device to require users to be their passwords after a number res. Not supported with systems ting with ActiveSync protocol 2.5, as Exchange 2003.  Indi: Supported on devices with OS elected devices with OS 2.x, and destandard compatible devices.  Berry 10: Not supported on Q5 and est the number of days a password est the num	password. If an alphanumeric yord is not required, this is not seed.  Indroid (native): Supported on es with OS 3.0, selected OS 2.x es, and KNOX Standard eatible devices.  IackBerry w/ GO!NotifySync:  Immumeric devices.  IackBerry w/ GO!NotifySync:  Immumeric devices.  IackBerry w/ GO!NotifySync:  Immumeric devices.  Immust create a password containing est alphabetic (or other symbol) oters.  Immust create a password containing est numeric characters.  Is for low-security biometric (face) inition technology. Uses pologies that can recognize the yof an individual to about a 3 digit alse detection is less than 1 in also their passwords after a number in middle in the systems the est their passwords after a number in middle in the systems the device to require users to be their passwords after a number in my individual to about a 3 digit alse detection is less than 1 in also in the systems the device to require users to be their passwords after a number in the systems the device of the systems the device of the systems the device with OS 2.x, and also in the systems the systems the devices with OS 2.x, and also in the systems the systems the systems that compatible devices.  In the system is not required in the systems that the systems that also in the systems that compatible devices with OS 2.x, and also in the systems that the	password. If an alphanumeric yord is not required, this is not sed.  Indroid (native): Supported on as with OS 3.0, selected OS 2.x as, and KNOX Standard atible devices.  Indroid (native): Supported on as with OS 3.0, selected OS 2.x as, and KNOX Standard atible devices.  Indroid (Example: If minimum is 2, yord must have 2 uppercase, 2 case, 2 numeric, and 2 symbol oters.)  Indust create a password containing at alphabetic (or other symbol) oters.  Indust create a password containing at numeric characters.  In of or low-security biometric (face) inition technology. Uses pologies that can recognize the yof an individual to about a 3 digit alse detection is less than 1 in alphabetic or require users to be their passwords after a number is. Not supported with systems ting with ActiveSync protocol 2.5, as Exchange 2003.  Indicided the support of the sup	password. If an alphanumeric vord is not required, this is not ved.  Indroid (native): Supported on se with OS 3.0, selected OS 2.x se, and KNOX Standard atible devices.  IdackBerry w/ GO!NotifySync:  Immumber of each type of cter required in an alphanumeric vord. (Example: If minimum is 2, vord must have 2 uppercase, 2 case, 2 numeric, and 2 symbol cters.)  Inust create a password containing st alphabetic (or other symbol) cters.  Inust create a password containing st numeric characters.  In so for low-security biometric (face) inition technology. Uses plogies that can recognize the yof an individual to about a 3 digit alse detection is less than 1 in land.  In see Android OS 4.0 or greater.  Is the device to require users to be their passwords after a number so. Not supported with systems ting with ActiveSync protocol 2.5, as Exchange 2003.  Individual to about a 3 digit alse detected devices with OS elected devices with OS and less the number of days a password set the number of days a pass	password. If an alphanumeric ord is not required, this is not sed.  adroid (native): Supported on es with OS 3.0, selected OS 2.x se, and KNOX Standard atible devices.  ackBerry w/ GO!NotifySync: um number of each type of other required in an alphanumeric ord. (Example: If minimum is 2, ord must have 2 uppercase, 2 case, 2 numeric, and 2 symbol others.)  must create a password containing st alphabetic (or other symbol) others.  must create a password containing st numeric characters.  for low-security biometric (face) inition technology. Uses ologies that can recognize the y of an individual to about a 3 digit alse detection is less than 1 in late of the systems they of an individual to about a 3 digit alse detection is less than 1 in late of the systems iting with ActiveSync protocol 2.5, as Exchange 2003.  id: Supported on devices with OS elected devices with OS 2.x, and (Standard compatible devices.)  Berry 10: Not supported on Q5 and est the number of days a password	password. If an alphanumeric vord is not required, this is not sed.  Indroid (native): Supported on se with OS 3.0, selected OS 2.x se, and KNOX Standard atible devices.  Indroid (native): Supported on se with OS 3.0, selected OS 2.x se, and KNOX Standard atible devices.  Indroid (Example: If minimum is 2, vord (Exam	password. If an alphanumeric vard is not required, this is not ved.  Indroid (native): Supported on se with OS 3.0, selected OS 2.x se, and KNOX Standard atible devices.  Indroid (native): Supported on se with OS 1.0, selected OS 2.x se, and KNOX Standard atible devices.  Indroid (Example: If minimum is 2, vord must have 2 uppercase, 2 case, 2 numeric, and 2 symbol cters.)  Indust create a password containing st alphabetic (or other symbol) cters.  Industrial characters.  In Individual to about a 3 digit alse detection is less than 1 in low.  In Individual to about a 3 digit alse detection is less than 1 in low.  In Individual to about a 3 digit alse detection is less than 1 in low.  In Individual to about a 3 digit alse detection is less than 1 in low.  In Individual to about a 3 digit alse detection is less than 1 in low.  In Individual to about a 3 digit alse detection is less than 1 in low.  In Individual to about a 3 digit alse detection is less than 1 in low.  In Individual to about a 3 digit alse detection is less than 1 in low.  In Individual to about a 3 digit alse detection is less than 1 in low.  In Individual to about a 3 digit alse detection is less than 1 in low.  In Individual to about a 3 digit alse detection is less than 1 in low.  In Individual to about a 3 digit alse detection is less than 1 in low.  In Individual to about a 3 digit alse detection is less than 1 in low.  In Individual to about a 3 digit alse detection is less than 1 in low.  In Individual to about a 3 digit alse detection is less than 1 in low.  In Individual to about a 3 digit alse detection is less than 1 in low.  In Individual to about a 3 digit alse detection is less than 1 in low.  In Individual to about a 3 digit alse detection is less than 1 in low.  In Individual to about a 3 digit alse detection is less than 1 in low.  In Individual to about a 3 digit alse detection is less than 1 in low.  In Individual to about a 3 digit alse detection is less than 1 in low.  In Individual to about a 3 digit alse detection is less t	er of complex characters (symbols) password. If an alphanumeric vord is not required, this is not ved.  Android (native): Supported on ss with OS 3.0, selected OS 2.x se, and KNOX Standard attible devices.  ackBerry w/ GO!NotifySync: um number of each type of teter required in an alphanumeric vord. (Example: If minimum is 2, vord must have 2 uppercase, 2 case, 2 numeric, and 2 symbol cters.)  must create a password containing st alphabetic (or other symbol) cters.  must create a password containing st numeric characters.  s for low-security biometric (face) nition technology. Uses plogies that can recognize the y of an individual to about a 3 digit alse detection is less than 1 in h.  res Android OS 4.0 or greater. s the device to require users to e their passwords after a number s. Not supported with systems ting with ActiveSync protocol 2.5, as Exchange 2003.  id: Supported on devices with OS elected devices with OS 2.x, and (Standard compatible devices.  Berry 10: Not supported on QS and es the number of days a password	er of complex characters (symbols) password. If an alphanumeric yord is not required, this is not you do not not you with OS 3.0, selected OS 2.x s., and KNOX Standard attible devices.  ackBerry w/ GOINotifySync: unn rumber of each type of test required in an alphanumeric yord. (Example: If minimum is 2, yord must have 2 uppercase, 2 case, 2 numeric, and 2 symbol cters.)  must create a password containing at alphabetic (or other symbol) cters.  Insust create a password containing at alphabetic (or other symbol) cters.  Insust create a password containing at alphabetic (or other symbol) citers.  Insust create a password containing at alphabetic (or other symbol) citers.  Insust create a password containing at alphabetic (or other symbol) citers.  Insust create a password containing at alphabetic (or other symbol) citers.  Insust create a password containing at alphabetic (or other symbol) citers.  Insust create a password containing at alphabetic (or other symbol) citers.  Insust create a password containing at alphabetic (or other symbol) citers.  Insust create a password containing at alphabetic (or other symbol) citers.  Insust create a password containing at alphabetic (or other symbol) citers.  Insust create a password containing at alphabetic (or other symbol) citers.  Insust create a password containing at alphabetic (architecture) at a password at a password and a password at a password and a password	er of complex characters (symbols) password. If an alphanumeric ord is not required, this is not sed.  Indroid (native): Supported on se with OS 3.0, selected OS 2.x se, and KNDX Standard atible devices.  ackBerry w/ GOINotifySync: um number of each type of cter required in an alphanumeric ord. (Example: If minimum is 2, ord must have 2 uppercase, 2 zase, 2 numeric, and 2 symbol cters.)  must create a password containing st alphabetic (or other symbol) cters.  st or low-security biometric (face) nition technology. Uses logies that can recognize the y of an individual to about a 3 digit alse detection is less than 1 in ,  res Android OS 4.0 or greater.  s the device to require users to e their passwords after a number s. Not supported with systems ting with ActiveSync protocol 2.5, as Exchange 2003.  id: Supported on devices with OS elected devices with OS 2.x, and (Standard compatible devices. Berry 10: Not supported on Q5 and es the number of days a password

Policy Suite Rules: All Devices	Description	Anrd	Anrd w/ AS only	TD/A	NS/BB	iOS	TD/ iOS	iOS w/ AS only	iOS Config Devices	S60	S60 w/ AS only	WM	WM w/ AS only	AS only
	Android: Supported on devices with OS 3.0, selected devices with OS 2.x, and KNOX Standard compatible devices.													
	BlackBerry 10: Not supported on Q5 and Z30													
Require Device Password History (ActiveSync)	Forces the device to disallow passwords that have been used in the recent past to be re-used. The number of stored past passwords is configurable. Not supported with systems operating with ActiveSync protocol 2.5, such as Exchange 2003.													
	Android (native): Supported on devices with OS 3.0, selected OS 2.x devices, and KNOX Standard compatible devices.	•	•	•	•	•	•	•	•			•	•	BB10 WP
	Android w/ TouchDown: Applies to the password associated with the TouchDown application only.													
	BlackBerry 10: Not supported on Q5 and Z30													
Number of passwords stored (ActiveSync)	Defines the number of device passwords stored to prevent users from reusing them too soon.				•	•	•	•	•			•	•	BB10
	BlackBerry 10: Not supported on Q5 and Z30													WP
Enable Password Echo	After the specified number of password entry attempts are made, the last password entered is unmasked to allow the user to see their entry error.				•									
Begin password echo after attempts	Defines the number of unlock attempts before echoing begins.				•									
Security: Encryption														
Require Encryption on the	Determines whether the device encrypts													
Device (ActiveSync)	stored data.  Not supported with systems operating with ActiveSync protocol 2.5, such as	•	•	•	•	•	•	•	•			•	•	BB10

Policy Suite Rules: All Devices	Description	Anrd	Anrd w/ AS only	TD/A	NS/BB	iOS	TD/ iOS	iOS w/ AS only	iOS Config Devices	S60	S60 w/ AS only	WM	WM w/ AS only	AS only
	Exchange 2003.													
	iOS devices (iPhone and iPad) have hardware encryption that is always enabled. The ActiveSync policy is not used to enable/disable.													
	Android (native): Supported on the Motorola Droid Pro (OS 2.2), devices with OS 3.0.0 or greater, and KNOX Standard compatible devices. Gives repeated reminders until the user initiates encryption.													
	Android w/ TouchDown, TouchDown data is encrypted (email, calendar, contacts, tasks). Use Require TouchDown encryption instead, to require encryption of TouchDown data only. Gives repeated reminders until the user initiates encryption.													
	GO!NotifySync for BlackBerry: only GO!NotifySync data is encrypted (email).													
Require Encryption on the Storage Card	Forces the device to encrypt the file system of a storage card.													
(ActiveSync)	Android: Requires KNOX Standard compatibility.													
	Android w/ TouchDown: only TouchDown files are encrypted (email attachments that have been downloaded are encrypted by using AES (256); attachments are still unreadable if the card is moved to another device).	•		•								•	•	BB10
Security: Device Inactivity and Locking														
Require Max Inactivity Time Device Lock	Forces the device to lock after a set number of minutes of user inactivity. This value serves as a maximum.													BB10 wOS
(ActiveSync)	This is also known as "Time without user input before password must be reentered."	•	•	•	•	•	•	•	•	•	•	•	•	WP

Policy Suite Rules: All Devices	Description	Anrd	Anrd w/ AS only	TD/A	NS/BB	iOS	TD/ iOS	iOS w/ AS only	iOS Config Devices	S60	S60 w/ AS only	WM	WM w/ AS only	AS only
Max Inactivity Timeout (in minutes)  (ActiveSync)	Defines the maximum value a user can set for the numbers of minutes of inactivity before the device locks. If the Challenge Timeout is being enforced, the Max Inactivity Timeout should be less than the Challenge Timeout.	•	•	•	•	•	•	•	•	•	•	•	•	BB10 wOS WP
Require Device Challenge Timeout	Forces the device to enable a challenge timeout. A lock is initiated regardless of activity and is intended to challenge the use of a lost or stolen device.				•									
Max Device Challenge Timeout	Defines the maximum value a user can set for the number of minutes before the device initiates a challenge lock. This lock is initiated regardless of activity and is intended to challenge the use of a lost or stolen device. If the Max Inactivity Timeout is being enforced, the Challenge Timeout should be greater than the Max Inactivity Timeout.				•									
Enable Customizable Lock Message	Enable the lock message and enter the text to be displayed when device is locked.				•	•	•		•					
Customizable lock message	Enter text to be displayed when device locks.				•	•	•		•					
Lock message phone number	Enter a contact phone number to be displayed when the device locks. A user can tap the displayed phone to initiate dialing.					•	•		•					
Audible Alert On Lock	Requires iOS 7 or later.  This setting enables a device to constantly emit a loud noise when a server-initiated device lock has been issued. The intent is to draw attention to the missing device and the device thief. The noise continues while the device is powered on, until the device is unlocked.				•							•		
Maximum grace period (in minutes)	Determines how soon the device can be unlocked again after use, without reprompting for the password. The	•				•	•		•					

Policy Suite Rules: All Devices	Description	Anrd	Anrd w/ AS only	TD/A	NS/BB	iOS	TD/ iOS	iOS w/ AS only	iOS Config Devices	S60	S60 w/ AS only	WM	WM w/ AS only	AS only
	administrator can also disallow a grace period by selecting Immediately or choose not to impose a limit by selecting None.													
	Android: Requires KNOX Standard compatibility.													
Wipe device on Failed Number of Unlock Attempts  (ActiveSync)	After the specified number of password entry attempts are made, data is cleared from the device. Functionality varies by device.													
	Android or Android w/TouchDown: The device returns to factory settings. This entails deleting all data and applications from the device. The device returns to the state it was in when purchased. Does not erase the SD card.													
	BlackBerry: Removes all mail and PIM data associated with the GO!NotifySync application and removes the GO!NotifySync account. Locks the device if Require Password is enabled. Erases GO!NotifySync data from the SD card, including saved attachments.													BB10
	iOS: The device returns to factory settings. This entails deleting all data and applications from the device. The device returns to the state it was in when purchased.	•	•	•	•	•	•	•	•	•	•	•	•	wOS WP
	Symbian: The device returns to factory settings. This entails deleting all data and applications from the device. The device returns to the state in was in when purchased. Erases the SD card.													
	WM: The device returns to factory settings. This entails deleting all data and applications from the device. The device returns to the state it was in when purchased. Erases SD card only on Professional devices.													
	BB10, webOS and WP or any device without ZENworks Mobile Management													

Policy Suite Rules: All Devices	Description	Anrd	Anrd w/ AS only	TD/A	NS/BB	iOS	TD/ iOS	iOS w/ AS only	iOS Config Devices	S60	S60 w/ AS only	WM	WM w/ AS only	AS only
	app: The device returns to factory settings. This entails deleting all data and applications from the device. The device returns to the state in was in when purchased.													
Maximum number of unlock attempts  (ActiveSync)	Defines the number of unlock attempts before the device-initiated wipe is performed.	•	•	•	•	•	•	•	•	•	•	•	•	BB10 wOS WP
Security: Emergency Calls														
Enable emergency calls when locked	Allows the device to make emergency calls in a locked state. Allows emergency numbers to be specified for allowed calls on a locked device: ambulance, fire, police, and one other emergency number.				•									
Allow dialing of any number	Gives the user an option to manually enter and call any number when the device is locked.				•									
S/MIME Settings														
Require signed SMIME messages	This setting forces the device to send digitally signed S/MIME messages.											•	•	WP
Require encrypted SMIME messages	This setting forces the device to send encrypted S/MIME messages.											•	•	WP
Require signed SMIME algorithm	This setting specifies the algorithm to be used for signing messages. Options are SHA1, MD5.											•	•	WP
Require encryption SMIME algorithm	This setting specifies the algorithm to be used for encrypting messages. Options are TripleDES, DES, RC2128bit, RC264bit, RC240bit.											•	•	WP
Allow SMIME Encryption algorithm negotiation	This setting enables/disables the device from negotiating the encryption algorithm used for signing messages. Options are Do not negotiate, Negotiate only strong algorithms, Negotiate any algorithm.											•	•	WP

Policy Suite Rules: All Devices	Description	Anrd	Anrd w/ AS only	TD/A	NS/BB	iOS	TD/ iOS	iOS w/ AS only	iOS Config Devices	S60	S60 w/ AS only	WM	WM w/ AS only	AS only
Allow SMIME soft certs	This setting enables/disables the device from using soft certificates to sign outgoing messages.											•	•	WP

# **POLICY RULES: IOS DEVICES**

Policy Suite Rules: iOS	Description	iOS	TD/ iOS	iOS w/ AS only	iOS Config Devices
Device Features				J. J	
Allow FaceTime	Determines whether the user can receive or place video calls. Allow Camera in the Device Controls must be enabled as well.	•	•		•
Allow Voice Dialing	Determines whether the user can dial their phone using voice commands. Require Password in Security Settings must be enabled as well.	•	•		•
Allow Screenshot	Determines whether or not the user can save a screenshot of the device display.	•	•		•
Allow Explicit Content	Determines whether or not explicit music or video content purchased from the iTunes store is hidden.	•	•		•
Allow Automatic Sync When Roaming	When disabled, devices that are roaming synchronize only when an account is accessed by the user.	•	•		•
Allow Siri	Determines whether iPhone 4S devices allow the Siri speech recognition personal assistant.	•	•		•
Allow Siri Profanity Filter	Determines whether profanity is filtered on the device. Functional on devices in Supervised mode only. <i>Allow Siri</i> must be enabled in order to enable this policy.				•
Allow Siri while device locked	Determines whether Siri is disabled when the device is locked with a password. Enabling Allow Siri is a prerequisite for enabling this option. Requires iOS 5.1 or higher.	•	•		•
Allow Game Center	Determines whether the Game Center is accessible. When disabled, the icon is removed from the Home screen. Functional on devices in Supervised mode only. Disabling this policy also disables Allow Multiplayer Gaming and Allow Adding Game Center Friends.				•
Allow Multiplayer Gaming	Determines whether the device will allow multiplayer gaming between iOS devices via Bluetooth or Wi-Fi. When this option is disabled, users cannot play multiplayer games in the Game Center.	•	•		•
Allow Adding Game Center Friends	Determines whether the device allows adding friends or building a social gaming network associated with the Game Center app.	•	•		•

Policy Rules: iOS Devices • 19

Policy Suite Rules: iOS	Description	iOS	TD/ iOS	iOS w/ AS only	iOS Config Devices
Force iTunes Store Password Entry	Determines whether the device will require a password to access the iTunes store. Requires users to enter their Apple ID before making any purchase. Normally, there is a brief grace period after a purchase is made before users must authenticate for subsequent purchases.	•	•		•
Force Encrypted Backup	When disabled, users can choose whether or not device backups performed in iTunes, are stored in encrypted format on the computer.	•	•		•
Allow Passbook while device locked	Allows use of the Apple Passbook app when the device is locked, giving users access to their boarding passes, tickets, store cards, coupons, etc. Requires iOS 6.0 or higher.	•	•		•
Allow Over-the-Air PKI Updates	Determines if over-the-air if Public Key Infrastructure (PKI) updates are permitted.	•	•		•
Force Limited Ad Tracking	Requires iOS 7 or later.  Determines if advertisers' tracking of a user's habits is limited. Enabling this does not eliminate ad tracking, but may reduce it to some degree.	•	•		•
Allow Fingerprint for Unlock	Requires iOS 7 or later.  Determines whether the user's Touch ID can be used to unlock the device.	•	•		•
	iOS 7 or later required				
Allow Lock Screen Control Center	Determines whether Control Center appears on the Lock screen. Control Center appears with a swipe up from any screen giving the user quick access to controls and apps.	•	•		•
	iOS 7 or later required				
Allow Lock Screen Notification View	Determines whether the Notifications view in Notification Center can be accessed from the Lock screen.	•	•		•
Allow Lock Screen Today View	iOS 7 or later required  Determines whether the Today view in Notification Center can be accessed from the Lock screen.  iOS 7 or later required	•	•		•
Applications	100 7 of later required				
Allow Application Installation	When disabled, the App Store is disabled and the icon is removed from the device Home screen. In addition, users are prevented from installing applications made available through the ZENworks Managed Apps list.	•	•		•
Allow App Management	Determines whether an administrator has the ability to give user access to iOS apps or force push iOS apps to users in a particular policy suite.	•	•		•
	iOS Configurator devices: Apps can only be made available on the device by an administrator via force push.				

Policy Suite Rules: iOS	Description	iOS	TD/ iOS	iOS w/ AS only	iOS Config Devices
Allow Bookstore	When disabled, iBookstore is disable and users are prevented from accessing it from the iBooks app. Functional on devices in Supervised mode only. Disabling this policy also disables the non-supervised policy Allow Bookstore Erotica.				•
Allow Bookstore Erotica	Determines whether users can purchase books categorized as Erotica from iBookstore.				•
Allow In App Purchases	Determines whether or not users can make in-app purchases.	•	•		•
Allow YouTube	Determines whether the use of YouTube is allowed on the device. If disabled, the icon is removed from the Home screen.	•	•		•
Allow iTunes	Determines whether the use of iTunes is allowed on the device. If disabled, the icon is removed from the Home screen and users cannot preview, purchase, or download content.	•	•		•
Allow Managed App Documents to Open in Unmanaged Apps	Determines if documents in managed apps and accounts will only open in other managed apps and accounts.	•	•		•
	Requires iOS 7 or later.				
Allow Unmanaged App Documents to Open in Managed	Determines if documents in unmanaged apps and accounts will only open in other unmanaged apps and accounts.	•	•		•
Apps	Requires iOS 7 or later.				
Record Installed Applications	Access and record applications installed on devices.	•	•		•
Safari Browser					
Allow Safari	Determines whether use of the Safari Web browser is allowed on the device. If disabled, the Safari icon is removed from the Home screen and it prevents users from opening Web clips. Disabling Safari might also prevent the use of third-party browsers.	•	•		•
Assault Cashina	Allow Browser in the Device Controls must also be enabled.				
Accept Cookies	Determines the Safari cookie policy – Whether the device accepts all cookies, no cookies, or only cookies from sites that were directly accessed.	•	•		•
Allow Auto-fill	Determines whether Safari remembers what users enter in Web forms.	•	•		•
Allow JavaScript	Determines whether Safari ignores JavaScript on Websites.	•	•		•
Block Pop-ups	Determines whether Safari's pop-up blocking feature is enabled.	•	•		•
Force Fraud Warning	Determines whether Safari attempts to prevent the user form visiting Websites identified as being fraudulent of compromised.	•	•		•
Ratings					
Rating Region	Determines the media content rating scale used by a particular region.	•	•		•

Policy Suite Rules: iOS	Description	iOS	TD/ iOS	iOS w/ AS only	iOS Config Devices
Application Ratings	Determines the maximum allowed ratings for apps.	•	•		•
Movie Ratings	Determines the maximum allowed ratings for movies.	•	•		•
TV Show Ratings	Determines the maximum allowed ratings for TV shows.	•	•		•
Security	<u> </u>				
Allow Profile Removal	Determines whether or not an iOS user can delete individual profiles delivered after the MDM configuration profile. Should the MDM configuration profile be removed, all other individual profiles will be removed as well. Includes an option to allow deletion with the use of a password.  Note: This option is disabled when an APNs certificate is in use, since individual profiles would automatically resynchronize to the device on the next sync cycle.	•	•		•
Profile Removal Password	Defines the password with which a user can remove the profile.	•	•		•
Allow Untrusted TLS Prompt	Determines whether users are asked if they want to trust certifications that cannot be verified. This setting applies to Safari and to Mail, Contacts, and Calendar accounts.	•	•		•
Allow Diagnostic Submission Text	Determines whether the device sends iOS diagnostic data to Apple. When this option is disabled, iOS diagnostic information is not sent to Apple. Requires iOS 6.0 or higher.	•	•		•
iCloud					
Allow iCloud Backup	Determines whether the device is permitted to back up to and restore from iCloud.	•	•		•
Allow Document Sync	Determines whether the device allows document synchronization to iCloud. When this option is enabled, users can store documents in iCloud.	•	•		•
Allow Photo Stream	Determines whether the device allows Photo Stream. If enabled, iCloud automatically pushes (via Wi-Fi) a copy of any photo taken on or imported to an iOS device, to the user's other iOS devices, iPhoto or Aperture on a Mac, Pictures Library on a PC, and Apple TV.  When this option is disabled, installing a configuration profile with this restriction erases Photo Stream photos from the user's device and prevents photos from the Camera Roll from being sent to Photo Stream. If there are no other copies of these photos, they might be lost.	•	•		•
Allow Shared Photo Streams	Determines whether an administrator has the ability to manage apps for users in a particular policy suite.  Requires iOS 6.0 or higher.	•	•		•

Policy Suite Rules: iOS	Description	iOS	TD/ iOS	iOS w/ AS only	iOS Config Devices
Allow Cloud Keychain Sync	Determines if iCloud Keychain sync is permitted. Stores 256-bit AES encrypted user passwords in iCloud so they can be synced across trusted devices. Helps users create strong passwords.	•	•		•
	Requires iOS 7 or later.				
Management					
Allow Management of Settings	Determines whether the voice and data roaming settings can be managed.	•	•		•
	Applies only to iPhone 4 devices.				
Allow Voice Roaming	Determines if the device will allow voice calls and SMS messages while roaming.	•	•		•
	Applies only to iPhone 4 devices.				
Allow Data Roaming	Determines if the device will allow data or video while roaming.				
	Applies only to iPhone 4 devices.	•	•		•
Enable personal hotspot	Enables the personal hotspot feature on user devices, which allows the user to connect computers and other devices to the Internet using the device's cellular data connection. A user can change this setting on the device, but it will revert back to the setting from the server each time the device synchronizes.	•	•		•
	Requires iOS 7 or later.				
Supervised Mode					
Allow Account Modification	Determines whether the user can modify the iTunes & App Stores account.				•
	Requires iOS 7 or later.				
Allow App Cellular Data Modification	Determines whether changes to cellular data usage settings for apps are permitted.				•
	Requires iOS 7 or later.				
Allow App Removal	Determines whether users can remove apps from the device. This does not include apps that are included with iOS, such as App Store and iTunes. Functional on devices in Supervised mode only. If this is disabled, it does not prevent managed apps from being removed via the MDM API.				•
Allow Configuration Profile Installation	Determines whether users can install additional configuration profiles onto the device. Functional on devices in Supervised mode only. If this is disabled, it does not prevent the MDM API from installing configuration profiles on the device.				•
Allow Find My Friends	Determines whetehr changes to Find My Friends settings are permitted.				•

Policy Suite Rules: iOS	Description	iOS	TD/ iOS	iOS w/ AS only	iOS Config Devices
Modification	Allows users to locate friends and family that also have the Find My Friends app.			,	
	Requires iOS 7 or later.				
Allow Host Pairing	Determines whether host pairing, other than the supervision host, is disabled. If a supervision host has not been configured, all pairing is disabled.				•
	Requires iOS 7 or later.				
Allow iMessage	Determines whether users can send or receive messages using iMessage. It does not prevent messaging through third party apps. If the device does not support text messaging, disabling this policy will remove the Messages icon from the Home screen. Functional on devices in Supervised mode only.				•
Allow AirDrop	Determines whether AirDrop is enabled or disabled. AirDrop allows users to easily share, via Wi-Fi or Bluetooth, photos, videos, contacts or anything else from any app with a Share button.				•
	iOS 7 or later required				
Allow Assistant User Generated Content	Determines whether Siri can query web sources, such as Bing, Wikipedia, and Twitter, to answer user questions.				•
	iOS 7 or later required				
Global HTTP Proxy	This payload allows the administrator to specify global HTTP proxy settings: Proxy Type, Proxy Server, Proxy Server Port, Proxy Username, and Proxy Password. Configuring the settings incorrectly can prevent the Apple API from functioning altogether on the device.				•
	There can only be one of this payload at any time and it can only be installed on supervised devices.				
Single App Mode	This payload allows administrators to specify an app to which supervised devices will be locked. The device is locked to a single application until the payload is removed. The Home button is disabled and the device returns to the specified application automatically upon wake or reboot.				
	There can only be one of this payload at any time and it can only be installed on supervised devices.				
	Requires iOS 6.0 or higher.				
Single App Mode:	Determines if the touch screen is operational.				
Disable Touch Screen	Requires iOS 7 or later.				•
Single App Mode:	Determines if device rotation sensing is operational.				
Disable Device Rotation	Requires iOS 7 or later.				•

Policy Suite Rules: iOS	Description	iOS	TD/ iOS	iOS w/ AS only	iOS Config Devices
Single App Mode:	Determines if volume buttons are operational.				
Disable Volume Buttons	Requires iOS 7 or later.				_
Single App Mode:	Determines if the ringer switch is operational.				
Disable Ringer Switch	Requires iOS 7 or later.				•
Single App Mode: Disable Sleep/Wake Button	Determines if the sleep/wake button is operational.  Requires iOS 7 or later.				•
Single App Mode: Disable AutoLock	Determines if the device will automatically go to sleep after an idle period.				•
Single App Mode: Enable VoiceOver	Determines if VoiceOver, a feature that audibly assists a user in navigating the touch screen, is on or off. VoiceOver enables a blind or low vision user to touch the screen to hear what is under their finger, then gesture to control the device. Works with apps that come with the iOS device.  Requires iOS 7 or later.				•
Single App Mode: Allow VoiceOver Adjustments	Determines if the user is permitted to adjust VoiceOver settings. Enable Voice Over must be on.				•
Single App Mode: Enable Zoom	Requires iOS 7 or later.  Determines if Zoom, an assistive built in magnifier is turned on or off. A double tap with three fingers instantly zooms 100-500 percent.  Requires iOS 7 or later.				•
Single App Mode: Allow Zoom Adjustments	Determines if the user is permitted to adjust Zoom settings. Enable Zoom must be on.				•
Single App Mode: Enable Invert Colors	Requires iOS 7 or later.  Determines if Invert Colors, an assistive feature that inverts colors for a higher contrast, is turned on or off. Once colors are set, the settings apply systemwide, even to video.				•
	Requires iOS 7 or later.				
Single App Mode: Allow Invert Colors Adjustments	Determines if the user is permitted to adjust Invert Colors settings. Enable Invert Colors must be on.				•
	Requires iOS 7 or later.				
Single App Mode:	Determines if the AssistiveTouch, a feature that provides alternatives to				•

Policy Suite Rules: iOS	Description	iOS	TD/ iOS	iOS w/ AS only	iOS Config Devices
Enable Assistive Touch	the standard navigation gestures, is turned on or off. Alternatives or customization can be created for gestures such as pinch, pressing the Home button, rotate, or shake.				
	Requires iOS 7 or later.				
Single App Mode: Allow Assistive Touch	Determines if the user is permitted to adjust Assistive Touch. Enable Assistive Touch must be on.				•
Adjustments	Requires iOS 7 or later.				
Single App Mode: Enable Speak Selection	Determines if Speak Selection, an assistive feature that reads text, is turned on or off. Speak Selection allows a user to highlight text in any application and tap Speak to have the selection read aloud.				•
	Requires iOS 7 or later.				
Single App Mode: Enable Mono Audio	Determines if Mono Audio, an assistive feature that plays left and right audio channels in both headphone earbuds, is turned on or off.				•
	Requires iOS 7 or later.				

# **POLICY RULES: TOUCHDOWN**

Policy Suite Rules: TouchDown Specific	Description	TD/A	TD/A w/ AS only	TD/iOS	TD/iOS w/ AS only
Installation					J,
Allow any server certificate	Currently, ZENworks Mobile Management requires a CA signed certificate and does not support self-signed certificates. For the present, this option should be disabled.	•			
Initiate enrollment	At the completion of the ZENworks Mobile Management enrollment, the user is prompted to configure TouchDown. When the user confirms, this automatically registers TouchDown and creates an ActiveSync account with the user credentials provided during ZENworks Mobile Management enrollment. If disabled, the user is not prompted and must initiate the TouchDown configuration by opening the ZENworks Mobile Management app and selecting Settings > TouchDown Settings.	•			
Require TouchDown encryption	Allows an organization to require the encryption of TouchDown data only on the device. Enable this option and disable the <i>Require encryption on the device</i> option, under Security Settings, so that the entire device is not encrypted. Gives repeated reminders until the user initiates encryption.	•		•	
	iOS devices (iPhone and iPad) have hardware encryption that is always enabled. The policy is not used to enable/disable.				
Push TD volume license key to device	The TouchDown license entered for the organization will be pushed to Android devices using TouchDown.	•			
General	<b>3</b>				
Allow copy/paste in emails	Determines whether users can copy text from a received email and paste it elsewhere.	•		•	
Allow easy PIN recovery	Allows users to reset the TouchDown PIN (password) by using their Exchange account password. With Exchange 2007 or 2010, this does not function when Security Settings > Enable Password Recovery is enabled. The ActiveSync password recovery method is used instead.	•			
Allow speak notification option	When enabled, users can choose to have the device issue spoken email and appointment notifications. When disabled, the option is not visible and the function is disabled.	•			
	At least one of two suppression rules must be enabled in order for this to function: Allow appointment alert configuration or Allow email alert				

Policy Suite Rules: TouchDown Specific	Description	TD/A	TD/A w/ AS only	TD/iOS	TD/iOS w/ AS only
	configuration.				
Require TouchDown PIN (Link)	Links to the <i>Require TouchDown PIN</i> option in Security Settings > Password, which determines whether a PIN is required to access the TouchDown app. Can be used in addition to or in place of the <i>Require Device Password</i> option.	•		•	
Show calendar info on notification bar	Determines whether appointment subjects are displayed in the device notification bar when reminders are shown.				
	To successfully display notifications, the following TouchDown settings must also be configured on the device: In the Advanced TouchDown Settings, enable the Appointment reminders at non-peak times options and configure Appointment Alerts to Use system settings.	•		•	
Show email info on notification bar	Determines whether the email sender and subject are displayed in the device notification bar when email notifications are shown.				
	To successfully display notifications, the following TouchDown settings must also be configured on the device: In the Advanced TouchDown Settings, enable the Notify on new mail option and configure Email Alerts to Use system settings.	•		•	
Show task info on notification bar	Determines whether task subjects are displayed in the device notification bar when task notifications are shown.				
	To successfully display notifications, the following TouchDown settings must also be configured on the device: In the Advanced TouchDown Settings, enable the Appointment reminders at non-peak times options and configure Appointment Alerts to Use system settings.	•		•	
Disable Printing	Disables printing from TouchDown.	•			
Forced SMIME Pin Timeout	The timeout interval before a user is required to re-enter an SMIME certificate PIN, when the certificate has been configured to require a PIN for signing or encrypting/decrypting messages.	•		•	
Signature					
Allow change signature on device	When enabled, allows user to change the signature which accompanies email sent from the device. This option does not function unless the Suppression > Allow signature line field is enabled.	•		•	
Set signature (Corporate / Individual)	Allows the entry of a signature determined by the administrator.	•		•	
Widgets					
Allow export to third party widgets	Determines whether or not TouchDown data can be communicated to third-party widgets that request it.	•			

Policy Suite Rules: TouchDown Specific	Description	TD/A	TD/A w/ AS only	TD/iOS	TD/iOS w/ AS only
Allow TouchDown calendar widget	Determines whether or not the TouchDown calendar widget shows data.	•			J,
Allow TouchDown email widget	Determines whether or not the TouchDown email widget shows data.	•			
Allow TouchDown task widget	Determines whether or not the TouchDown task widget shows data.	•			
Allow TouchDown universal widget	Determines whether or not the TouchDown universal widget shows email, calendar and task data.	•			
Show widget data when TouchDown is locked	Determines whether widget data is locked when TouchDown is locked. This option does not function unless Security Settings >Require Password; TouchDown-General > Show TouchDown PIN; and at least one widget (calendar, email, third-party, task, or universal) are enabled.	•			
Phone Book					
Phone book fields to copy	Choose which fields of a contact synchronize when users copy contacts to the device phone book.				
	Choosing all or some of the fields is a prerequisite for the suppression rules: Allow copy phone format options and Allow update contact changes to phone options.	•		•	
User Configurable Settings: Calendar	About User Configurable Settings: Users can configure these policies according to preference. Administrators choose the setting for initial device configuration. Changes to these settings do affect existing TouchDown users.				
Show All-day events in the Calendar Widget	Determines whether all-day events display in the TouchDown Calendar Widget.	•			
Show upcoming events only	Determines whether the only appointments displayed in the current day's Agenda are those that have not passed.	•			
Enable meeting resource field	Determines whether a field is enabled for specifying resources such as conference rooms or equipment when creating a new meeting.	•			
Show calendar tasks in the Agenda	Determines whether calendar tasks display in the Agenda view.	•		•	
Show overdue tasks in the Agenda	Determines whether overdue tasks display in the Agenda view.	•			
Customize the start and end days for the week	Determines whether user has the ability to define the first and last days of the week to display in the calendar Week view.	•		•	
First day of a week to show in Calendar	Define the first day of the week to display in the calendar Week view.	•		•	

Policy Suite Rules: TouchDown Specific	Description	TD/A	TD/A w/ AS only	TD/iOS	TD/iOS w/ AS only
Last day of a week to show in Calendar	Define the last day of the week to display in the calendar Week view.	•		•	
Start time of the work day	Times that fall between the work day's start time and end time display in a different color on Day and Week calendar views.	•		•	
End time of the work day	Times that fall between the work day's start time and end time display in a different color on Day and Week calendar views.	•		•	
Default reminder for each new event	Defines the default reminder time to assign to each new event unless otherwise specified for the event.	•		•	
Default privacy status for each new event	Defines the default privacy status to assign to each new event unless otherwise specified for the event.	•		•	
Default availability status for each new event	Defines the default availability status to assign to each new event unless otherwise specified for the event.	•		•	
Calendar zoom size	Shows the Day and Week calendar views in a larger text size.	•		•	
User Configurable Settings: Device Control					
Show a compact PIN screen (NEW 7.1)	Determines whether a compact PIN screen is shown, fitting the PIN buttons over half of the available screen space.	•			
Default theme (NEW 7.1)	Defines a default display theme for the TouchDown User Interface.	•			
User Configurable Settings: Email					
Enable email selectors	Adds a radio button beside each item in the email list, enabling the user to select multiple emails for various actions, such as delete, mark as read, move, etc.	•			
Show email summary	Determines whether part of the body of each email displays in the email list.	•			
Highlight email senders	Determines whether the sender of any email displays in a larger and bolder type than the subject field.	•		•	
Enable search as you type	Determines whether the search tool used in the email list begins to filter messages as the user types a string, as opposed to the user having to initiate the search after typing.	•			
Automatically download embedded images	Determines whether embedded images automatically download for an HTML email.	•		•	

Policy Suite Rules: TouchDown Specific	Description	TD/A	TD/A w/ AS only	TD/iOS	TD/iOS w/ AS only
Enable move to any folder option	Determines whether a user can move email messages to folders that have not been selected for synchronization, as opposed to only being able to move email to folders that have already synchronized.	•		•	
Highlight unread messages	When enabled, Email list displays read email in grey and unread email fully lit and in bold.	•			
Enable preview attachments option	When enabled, a thumbnail view of downloaded attachments displays before they are opened.	•			
Always expand folders	When enabled, the folder tree automatically expands when <i>Choose Folders</i> is used or when the user switches folders.	•			
Enable confirm deletes prompt	Determines whether a confirmation prompt displays when the user deletes an email.	•		•	
Enable confirm move prompt	Determines whether a confirmation prompt displays when the user moves an email.	•		•	
Toolbar mode	Determines whether the tool bar that appears when viewing an email will display, be hidden, or can be toggled on and off.	•			
After delete go to	Defines what is displayed after an email is deleted.	•		•	
Enable email alerts at non-peak times	Determines whether email notifications are sent when email arrives during non-peak times.	•			
Confirm move to Junk prompt	Determines whether a confirmation prompt displays when the user moves an email to the Junk folder.	•		•	
User Configurable Settings: Synchronization					
Enable push email mode	When enabled, switches the device from checking email at scheduled frequencies to a Push Email mode in which the device connects with the server for sustained intervals to retrieve email.	•		•	

Policy Suite Rules: TouchDown Specific	Description	TD/A	TD/A w/ AS only	TD/iOS	TD/iOS w/ AS only
Off-peak polling interval	Defines the polling interval for retrieving new mail during non-peak times.	•			
Suppressions	<b>About Suppressions:</b> An enabled suppression gives the user control of the setting.				
	A disabled suppression removes the setting from user devices.  When the suppression has a control setting the administrator can configure it. When a control setting is not provided, the setting is locked as it was previously set on the device.				
Suppression configuration	Choose which options to hide or expose to TouchDown users. Select <i>All</i> to enable all suppressions, giving users control. Select <i>None</i> to disable all suppressions or <i>Custom</i> to set each suppression individually.	•		•	
Suppressions: Calendar, Contacts, Tasks					
Allow appointment alert configuration	Enables users to customize the alerts displayed for appointment reminders.	•		•	
Allow appointment reminders at non-peak times option	Enables users to allow appointment reminders during periods when the device is not synchronizing.				
Enable appointment reminders at non-peak times	Control setting determines whether appointment reminders display during non-peak times.	•		•	
Allow appointment synchronization options	Enables users to choose how many days worth of appointments to keep on the device. From Device Control options, an administrator can set a maximum or allow users to choose a specific number of days.	•		•	
Allow category configuration	Enables users to select colors for contact, event, and task categories.	•		•	
Allow copy to phone format options	Enables users to select the format of contacts (First or Last Name placed first) copied from TouchDown to the Android phone book. Choosing all or some of the fields in the Phone Book > Phone book fields to copy rule is a prerequisite.				
Name format for contacts copied to phone	Control setting defines the format in which contacts are copied to the phone from TouchDown Exchange contacts. First MI Last, Last First MI, or File as is	•		•	
Allow enable appointment reminders option	Allows users to enable appointment reminders.				
Enable appointment reminders	Control setting determines whether a notification displays when an appointment has a reminder.	•		•	

Policy Suite Rules: TouchDown Specific	Description	TD/A	TD/A w/ AS only	TD/iOS	TD/iOS w/ AS only
Allow include phone contacts in picklist option	Enables users to determine whether the contact list displayed when composing email or SMS includes contacts from the Android Phone Book.				
Include phone contacts in picklist	Control setting determines whether contacts from the Android phone book are included in the contact picklist that can be accessed while composing email.	•			
Allow normalize phone numbers option	Enables users to determine how contact phone numbers retrieved from the server are formatted.				
Normalize phone numbers	Control setting defines the format of contact phone numbers retrieved from the server as follows:				
	X/x/ext (extension) becomes ;				
	P/p (pause) becomes ;				
	W/w (tone wait) becomes ,				
Allow reminders configuration	Enables users to configure repeating reminders for calendar events.				
Set reminders (in min)	Use the control setting to configure the repeating reminders.				
	0 = No repeats; X<0 = reminders start at set reminder time and continue every X minutes until event starts; X>0 = reminders repeat every X minutes after event starts	•		•	
Allow update contact changes to phone option	Enables users to determine whether updates made to contacts in TouchDown also update the phone book database. For iOS devices, updates occur when the user manually synchronizes contacts. Choosing all or some of the fields in the Phone Book > Phone book fields to copy rule is a prerequisite.	•		•	
Update contact changes to phone	Determine whether updates made to contacts in TouchDown also update the phone book database. For iOS devices, updates occur when the user manually synchronizes contacts.				
<b>Suppressions: Device Control</b>					
Allow ActiveSync device type string field	Enables users to modify the ActiveSync device type the device reports to the ZENworks Mobile Management server. In order for the server to maintain accurate information, this should be disabled.	•		•	
ActiveSync device type string field	Use the control setting to set the ActiveSync device type string to the TouchDown option.				
Allow backup database (menu option)	Enables users to back up the TouchDown database to the SD card.	•			
Allow backup settings	Enables users to back up the TouchDown settings to the SD card.	•			

Policy Suite Rules: TouchDown Specific	Description	TD/A	TD/A w/ AS only	TD/iOS	TD/iOS w/ AS only
Allow disable tablet mode (tablet devices only) option	Allows tablet users to disable the automatic switch to tablet mode.				
Disable tablet mode (tablet devices only)	Use the control setting to disable the automatic switch to Tablet Mode for tablet users.	•		•	
Allow exclude attachments from gallery option	Enables users to determine whether Android Gallery scans the SD card for TouchDown media files.				
Exclude attachments from gallery	Control setting determines whether or not Android Gallery scans the SD card for TouchDown media files.	•			
Allow export settings	Enables users to do an SD card export for a .pcf configuration file with the settings required to connect to the server.	•			
Allow filtered tasks on home screen and widgets option	Enables users to filter tasks shown on the Home screen and on the Task Widget just as they are on the TouchDown Tasks screen.				
Display tasks on home screen and widgets	Control setting determines whether tasks shown on the Home screen and on the Task Widget are filtered just as they are on the TouchDown Tasks screen.	•			
Allow login ID, email address, domain fields	Displays the user's ActiveSync account information and allows user to edit.	•		•	
Allow quick configuration	Enables users to use the Quick Configuration option to create the ActiveSync account.	•			
Allow restore database (menu option)	Enables users to restore a backup of the TouchDown database from the SD card.	•			
Allow restore settings	Enables users to restore TouchDown settings they have backed up to the SD card.	•			
Allow server name fields	Displays the address of the ZENworks Mobile Management server and allows the user to edit it. This option also controls the following device options: Uses SSL and Fetch and Trust Certificate.	•		•	
Allow show emails on startup option	Enables users to open TouchDown to the email list instead of the main display pane.	_		_	
Show email list on startup	Control setting determines whether TouchDown will open to the Email list instead of TouchDown's main screen.	•		•	
Allow use system background data setting option	Determines whether TouchDown honors how the user has configured the Android <i>Background Data</i> setting, which controls whether the app updates in the background or only on demand.				
Use system background data setting	When control setting is disabled, TouchDown synchronizes in the background regardless of how the Android <i>Background Data</i> setting is configured.	•			

Policy Suite Rules: TouchDown Specific	Description	TD/A	TD/A w/ AS only	TD/iOS	TD/iOS w/ AS only
Suppressions: Email					
Allow always BCC myself option  Enable always BCC myself option	Enables the user to send a copy of all outgoing emails to his or her own email address.  Control setting determines whether a copy of all outgoing email is sent to the user's own email address.	•		•	
Allow choose folders	Enables users to select the folders TouchDown synchronizes with the server. In addition to <i>Choose Folders</i> , this also controls the following device options: <i>Selected Email Folders</i> and <i>Refresh Folders</i> .	•		•	
Allow disable SmartReplies and SmartForwards option  Disable SmartReplies and	Enables users to turn off SmartReplies and SmartForwards.  Control setting disables the SmartReplies/SmartForwards functionality.	•		•	
SmartForwards	This should only be disabled if the server does not support Smart Replies/Forwards.				
Allow don't delete emails on server option	Enables users to prevent email they delete on the device from being deleted on the server.	_			
Do not delete email on server	Control setting determines whether email on the server will be deleted when email is deleted on the device.	•		•	
Allow don't mark read on server  Do not mark email read on	Enables users to prevent email, marked read/unread on the device, from being marked as read/unread on the server.				
server	Control setting determines whether email marked read/unread on the device will be marked as read/unread on the server.	•		•	
Allow email alerts configuration	Enables users to customize the alerts displayed for new email.	•		•	
Allow email body style options  Email body style	Enables users to choose font, size, color, and style of the HTML email they compose.	•			
(Corporate/Individual)	Use control setting to define the font, size, color, and style of text used for composing HTML email.				
Allow email checking frequency options	Enables users to determine how often the device checks for new email.				
Email checking frequency (in minutes)	When Push Email is not enabled, this control setting defines the frequency at which the device checks the server for new mail. The recommended value is 15 minutes, as more frequent checks can increase battery drain.	•		•	
Allow email download size options	Enables users to determine the size of downloaded email messages. An	•		•	

Policy Suite Rules: TouchDown Specific	Description	TD/A	TD/A w/ AS only	TD/iOS	TD/iOS w/ AS only
	email larger than this value displays an option to download the remainder. (Zimbra users - value must be no greater than 10 KB.)				
Allow email view text size options	Enables users to select the text size of email they view.				
Email text size	Use the control setting to define the text size for viewing emails.	•		•	
Allow email synchronization options	Enables users to set the age of email to be synchronized to the device. From Device Control options, an administrator can set a maximum or allow users to choose a specific age.	•		•	
Allow enable HTML email options	TouchDown attempts to download and display email in HTML format.  Mail servers other than Exchange should leave this disabled.	•		•	
Allow folder language options	Enables users to choose the language used for folder labeling.	•		•	
Allow manage rules option	Enables users to create and manage rules for incoming email.	•		•	
Allow notify on new mail option  Send new mail notifications	Enables users to determine whether a notification displays when new email arrives.				
Send new mail notifications	Control setting determines whether a notification displays when new mail arrives.				
Allow out of office configuration	Enables users to configure automatic Out of Office replies.	•		•	
Allow signature line field	Enables users to enter their own signature for email sent from the device.	•		•	
Suppressions: Security					
Allow clean SD card on remote wipe option	Enables users to determine whether all files on the SD card are deleted when a remote Wipe is issued.				
Clean SD card on remote wipe	Control setting determines whether all files on the SD card are deleted when a remote Wipe is issued.	•			
Allow client certs configuration	Enables users to import a client certificate, which TouchDown uses to authenticate with the server.	•			
Allow remote kill configuration	Enables users to configure the device to allow a remote wipe of TouchDown data. An email sent to the device with a designated code in the subject field initiates the wipe.	•		•	
Remote kill code	Define the designated code that will initiate a wipe.				

Policy Suite Rules: TouchDown Specific	Description	TD/A	TD/A w/ AS only	TD/iOS	TD/iOS w/ AS only
Allow security policy display	Displays the security policies imposed by the server, which are governing the device.	•		•	
Allow S/MIME settings configuration	Enables users to adjust the settings of the S/MIME options for their device.	•		•	
Allow wipe data (menu option)	Enables users to choose a device option to erase all TouchDown data and return TouchDown to a pre-registration state.	•		•	
Suppressions: Synchronization					
Allow defer server updates option  Enable defer server updates	Enables users to determine whether TouchDown updates will synchronize to the server in batches or as they occur. Batches are sent only when the next scheduled sync occurs, an item arrives via direct push, or the user initiates a manual sync.				
	When control setting is enabled, TouchDown updates synchronize to the server in batches instead of as they occur. Batches are sent only when the next scheduled sync occurs, an item arrives via direct push, or the user initiates a manual sync.	•		•	
Allow enable SMS syncing (Exchange 2010 Only) option	Enables users to synchronize SMS messages to Outlook.	•			
Allow manual sync when roaming option	When enabled, automatic synchronization stops when the device is roaming, but users can initiate a manual sync.	•		•	
Allow notify on password failure option	Enables users to determine whether a notification displays if synchronization fails due to a user password issue.				
Send password failure notifications	Control setting determines whether a notification displays if synchronization fails due to a user password issue.	•		•	
Allow notify on polling failure option	Enables users to determine whether a notification displays if synchronization has failed.				
Send failed polling notifications	Control setting determines whether a notification displays if synchronization has failed.	•		•	
Allow notify on successful polling option	Enables users to determine whether a notification displays when synchronization is successful.	•		•	
Send successful polling	Control setting determines whether a notification displays when synchronization is successful.				

Policy Suite Rules: TouchDown Specific	Description	TD/A	TD/A w/ AS only	TD/iOS	TD/iOS w/ AS only
notifications					
Allow peak time configuration	Enables users to set the hours during which TouchDown synchronizes with the server.	•		•	
Allow poll during off-peak times option	Enables users to determine whether TouchDown synchronizes with the server during non-peak times when email is sent, replied to, or forwarded from the device.				
Enable polling at off-peak times	Control setting determines whether TouchDown synchronizes with the server during non-peak times when the user sends an email, a reply, or forward from the device.	•		•	

## **SECURITY: ALL DEVICES**

Security: All Devices	Description	Anrd	Anrd w/ AS only	TD/A	NS/BB	iOS or TD/iOS	iOS w/ AS only	iOS Config Devices	S60	S60 w/ AS only	WM	WM w/ AS only	AS only
Security Commands													
Disable/Enable Device	Device is unmanaged while disabled and thus blocked from all communication with the server. It does not occupy a license seat in this state.	•	•	•	•	•	•	•	•	•	•	•	BB10 wOS WP
Suspend/Resume Device	Device is managed (it can be wiped and continues to send statistics) while suspended, but blocked from corporate resources. User cannot access the application's Config, Managed Apps, and File Share options and must enter a password to gain full functionality when suspension is lifted.	•	•	•	•	•	•	•	•	•	•	•	BB10 wOS WP
Selective Wipe	Un-enrolls the device. Un-enrollment selectively wipes the device, removing mail/PIM associated with the mail application, along with any managed apps or profiles; clears the ZENworks Mobile Management account; and deletes the device from the grid. Functionality varies by device platform.	•	•	•	•	•	•	•	•	•	•	•	BB10 wOS
	Android (native): Devices with native mail app only wipe the ZENworks account. Mail/PIM is not wiped.  Android (TouchDown): Returns TouchDown to a pre-registration state. Erases only the TouchDown data from the SD card. If the Clean SD Card on												WP

Security: All Devices	Description	Anrd	Anrd w/ AS only	TD/A	NS/BB	iOS or TD/iOS	iOS w/ AS only	iOS Config Devices	S60	S60 w/ AS only	WM	WM w/ AS only	AS only
	Remote Wipe option in the TouchDown Advanced Settings is enabled, then the SD card is completely erased.												
	BlackBerry (OS 4.5-7.1): Removes mail and PIM data associated with the GO!NotifySync application. Locks the device if Require Password is enabled.												
	iOS: Removes managed iOS profiles, thus removing corporate resources and managed apps designated to be removed when the APN profile is removed. (Manually created mail profiles and user-installed apps are not removed.)												
	iOS 7.0.3+ devices enrolled in the Volume Purchase Program: VPP licenses are reclaimed and the user is retired from the program when it is the last iOS 7.0.3+ device associated with the user.												
	Symbian and WM: Wipes only the ZENworks account. Mail/PIM is not wiped.												
	BB10, webOS and WP or any device without the ZENworks app: The only action performed is to remove device from the ZENworks server and dashboard grid.												
Remove User	Stops managing all devices associated with the user and subsequently removes the user from the ZENworks Mobile Management server and dashboard grid.	•	•	•	•	•	•	•	•	•	•	•	BB10 wOS WP
	iOS 7.0.3+ devices enrolled in the Volume Purchase Program : VPP licenses are reclaimed and the user is												

Security: All Devices	Description	Anrd	Anrd w/ AS only	TD/A	NS/BB	iOS or TD/iOS	iOS w/ AS only	iOS Config Devices	S60	S60 w/ AS only	WM	WM w/ AS only	AS only
	retired from the program.												
Wipe Storage Card	Administrators or end users can remotely wipe all data from the device's storage card.												
	Android w/native ActiveSync account and Android w/ TouchDown using OS 3.2-4.1.2: Wipes the internal storage card, but does not wipe the external storage card – an OS limitation.	•		•	•						•		
Full Wipe	Administrators or end users can issue a full wipe command. Once the wipe is completed, the device is removed from the dashboard User Grid. Functionality varies by device platform.												
	(Once the device has been wiped, the administrator might also want to issue the <i>Disable</i> or <i>Suspend Device</i> command to temporarily block the device.)												
	Android w/ native ActiveSync account: The device returns to factory settings. This entails deleting all data and applications from the device. The device returns to the state it was in when purchased. Does not erase the SD card. KNOX Standard compatible devices wipe both internal and external memory.	•	•	•	•	•	•	•	•	•	•	•	BB10 wOS WP
	Android w/TouchDown: Device returns to factory settings. This entails deleting all data and applications from the device. The device returns to the state it was in when purchased. Does not erase SD card. Note: When the Clean SD card on Remote Wipe option in the TouchDown Advanced Settings is enabled, the SD card is completely erased.												
	BlackBerry: Removes all mail and PIM data associated with the GO!NotifySync application and												

Security: All Devices	Description	Anrd	Anrd w/ AS only	TD/A	NS/BB	iOS or TD/iOS	iOS w/ AS only	iOS Config Devices	S60	S60 w/ AS only	WM	WM w/ AS only	AS only
	removes the GO!NotifySync account. Locks the device if Require Password is enabled. Erases the entire SD card, including saved attachments.												
	iOS: The device returns to factory settings. This entails deleting all data and applications from the device. The device returns to the state it was in when purchased.												
	iOS 7.0.3+ devices enrolled in the Volume Purchase Program: VPP licenses are reclaimed and the user is retired from the program when it is the last iOS 7.0.3+ device associated with the user.												
	Symbian: The device returns to factory settings. This entails deleting all data and applications from the device. The device returns to the state it was in when purchased. Some models (N95 and 6120c) wipe only Mail for Exchange data. Erases the SD card.												
	WM: The device returns to factory settings. This entails deleting all data and applications from the device. The device returns to the state it was in when purchased. Erases the SD card only on Professional devices.												
	BB10, webOS and WP or any device without ZENworks Mobile Management app: The device returns to factory settings. This entails deleting all data and applications from the device. The device returns to the state it was in when purchased.												
Lock Device	Administrators or end users can remotely lock the device, requiring an unlock password to be entered before the device can be used.	•		•	•	•		•			•		
Clear Passcode	The passcode is cleared. If a passcode is required by the user's policy, the user will be prompted to					•							

Security: All Devices	Description	Anrd	Anrd w/ AS only	TD/A	NS/BB	iOS or TD/iOS	iOS w/ AS only	iOS Config Devices	S60	S60 w/ AS only	WM	WM w/ AS only	AS only
	enter a new passcode.												
Network Connection Security and Configuration													
SCEP (Simple Certification Enrollment Protocol	Sets up SCEP settings for devices.					•							
VPN (Virtual Private Network)	Sets up VPNs for devices.  Current Functionality: IPSec (Cisco protocol)					•		•					
Wi-Fi	Sets up Wi-Fi settings, using various levels of security including WEP, WPA, and WPA2.					•		•					

## **DEVICE STATISTICS: ALL DEVICES**

Device Statistics: All Devices	Description	Anrd	Anrd w/ AS only	TD/A	NS/BB	iOS or TD/iOS	iOS w/ AS only	iOS Config Devices	S60	S60 w/ AS only	WM	WM w/ AS only	AS only
Status: Last Connections													
Device App	The date and time of the last successful synchronization with the ZENworks Mobile Management server.	•		•	•	•			•		•		
ActiveSync	The date and time of the last successful synchronization with the ActiveSync server.	•	•	•	•	•	•		•	•	•	•	BB10 wOS WP
iOS APN Sent	The last date and time an APN was sent from the Apple Push Notification server.					•		•					***
iOS APN Check-In	The last date and time the device acknowledged an APN from the Apple Push Notification server.					•		•					
Status: Battery													
Level	Displays the percentage of battery life left for the device.	•		•	•	•		•	•		•		
Status	Displays whether the device battery is charging or unplugged.	•		•	•	•		•	•		•		
Last Boot Time	The date and time of the last device boot.	•		•	•	•					•		
Status: Encryption													
Device Encrypted	Whether the data stored in the device's local memory is encrypted.	•	•	•	•	•	•				•		
Storage Card Encrypted	Whether the data stored on the device's storage card is encrypted.			•							•	•	
	iOS devices do not have SD card												

Device Statistics: All Devices	Description	Anrd	Anrd w/ AS only	TD/A	NS/BB	iOS or TD/iOS	iOS w/ AS only	iOS Config Devices	S60	S60 w/ AS only	WM	WM w/ AS only	AS only
Status: Device Memory	capability.												
Capacity	Displayed the detail of the cored and												
	Displays the total of the used and unused memory on the device.	•		•	•	•		•	•		•		
Available	Displays the amount of free memory left on the device. (Labeled Available Device Capacity for iOS devices.)	•		•	•	•		•	•		•		
Percent Free	Displays the percentage of free memory left on the device.	•		•	•	•		•	•		•		
Status: External Storage Card													
Capacity	Displays the total of the used and unused memory on the device storage card.				•						•		
	iOS devices do not have SD card capability.												
Available	Displays the amount of free memory left on the device's storage card.	•		•									
	iOS devices do not have SD card capability.												
Percent Free	Displays the percentage of free memory left on the device's storage card.	•			•						•		
	iOS devices do not have SD card capability.												
Status: Jailbroken													
Jailbroken	Whether or not an iOS or Android device has been jailbroken/rooted.	•		•		•							
Status: TouchDown													
TouchDown Enrolled	Whether the TouchDown application is registered on an Android device.	•		•									
Status: Roaming													
Currently Roaming	Displays a simple yes or no if the device is roaming.	•		•	•	•		•	•		•		

<b>Device Statistics:</b> All Devices	Description	Anrd	Anrd w/ AS only	TD/A	NS/BB	iOS or TD/iOS	iOS w/ AS only	iOS Config Devices	S60	S60 w/ AS only	WM	WM w/ AS only	AS only
Voice Roaming Enabled	Current setting for Voice Roaming.					•		•					
Data Roaming Enabled	Current setting for Data Roaming.					•		•					
Status: Supervised													
Is Supervised	Whether or not the device is in Supervised mode.					•		•					
Status: Device Locator	Requires iOS 6 or later.												
Service Service													
Device Locator Service Enabled	Whether the device has a device locator service (such as Find My iPhone) enabled.					•		•					
	Requires iOS 7 or later.												
Status: Do Not Disturb													
Is Do Not Disturbed in Effect	Whether the device's <i>Do Not Disturb</i> option is enabled, silencing calls, alerts, and notifications.					•		•					
	Requires iOS 7 or later.												
Network: Downloaded Data													
Any	Data usage statistics for data coming in to the device over the network since the last device boot time. The sumtotal of all networks.	•		•	•	•			•				
	BlackBerry with GO!NotifySync: Limited to GSM devices.												
Cellular	Data usage statistics for data coming in to the device over the network since the last device boot time. The subtotal for the cellular network alone.	•		•		•			•				
Downloaded Data: Wi-Fi	Data usage statistics for data coming in to the device over the network since the last device boot time. The subtotal for Wi-Fi alone.	•		•		•			•				

Device Statistics: All Devices	Description	Anrd	Anrd w/ AS only	TD/A	NS/BB	iOS or TD/iOS	iOS w/ AS only	iOS Config Devices	S60	S60 w/ AS only	WM	WM w/ AS only	AS only
Network: Uploaded Data													
Any	Data usage statistics for data going out from the device over the network since the last device boot time. The sum-total of all networks.  BlackBerry with GO!NotifySync: Limited to GSM devices.	•		•	•	•			•				
Cellular	Data usage statistics for data going out from the device over the network since the last device boot time. The subtotal for the cellular network alone.	•		•		•			•				
Wi-Fi	Data usage statistics for data going out from the device over the network since the last device boot time. The subtotal for Wi-Fi alone.	•		•		•			•				
Network: Network Details													
Network Type	Displays the network type the device is using.	•		•	•	•		•	•		•		
Signal Strength	Displays the signal strength using a percentage value.	•		•	•				•		•		
SIM Card IMSI Number	The ID number of the SIM card: International Mobile Subscriber Identity.	•		•	•						•		
Cellular Technology	Cellular technology 0 = none 1 = GSM 2 = CDMA					•		•					
Current Carrier Network	Name of current carrier network.  Android devices: Requires KNOX Standard compatibility	•				•		•					
SIM Carrier Network	Name of the home carrier network. (Note: Applies to CDMA in spite of its name.)					•		•					

Device Statistics: All Devices	Description	Anrd	Anrd w/ AS only	TD/A	NS/BB	iOS or TD/iOS	iOS w/ AS only	iOS Config Devices	S60	S60 w/ AS only	WM	WM w/ AS only	AS only
Carrier Settings Version	Version of currently installed carrier settings file.					•		•					
Ethernet MACs	Ethernet MAC addresses. Requires iOS 7 or later.					•		•					
Network: Hotspot	requires 100 7 of later.												
Personal Hotspot Enabled	Whether the device connected to the Internet over a cellular data network is sharing the Internet connection with a computer or other iOS device connected to it via Wi-Fi or a computer connected to it via Bluetooth or USB.  Requires iOS 7 or later.					•		•					
About: Device Application	required recording to												
Device Application Version	Displays the version number of the ZENworks Mobile Management device application.	•		•	•	•			•		•		
Device Application Language	Name of the language the ZENworks Mobile Management device application is using.	•		•	•	•			•		•		
About: ActiveSync													
ActiveSync: Version	ActiveSync protocol version used by the device.	•	•	•	•	•	•		•	•	•	•	BB10 wOS WP
ActiveSync: User Agent	The device's native ActiveSync application version, which corresponds to the device's operating system version.	•	•	•	•	•	•		•	•	•	•	BB10 wOS WP
About: Operating System													
Operating System: Language	Name of the language the device OS is using.	•		•	•				•		•		
Operating System: Version	Displays the device OS version.	•		•	•	•		•	•		•		

Device Statistics: All Devices	Description	Anrd	Anrd w/ AS only	TD/A	NS/BB	iOS or TD/iOS	iOS w/ AS only	iOS Config Devices	S60	S60 w/ AS only	WM	WM w/ AS only	AS only
Operating System: OS	The base operating system used for the device platform.												
	Android devices: Requires KNOX Standard compatibility.	•											
Operating System: Kernel Version	The version of the kernel portion of the device platform's base operating system.	•											
	Android devices: Requires KNOX Standard compatibility.												
About: Device													
Model	Device's internal model number.												
	Android devices: Requires KNOX Standard compatibility.	•				•		•					
Model Name	Name of the device model.												
	Android devices: Requires KNOX Standard compatibility.	•				•		•					
Device Name	The name of the device.												
	iOS devices: Given via iTunes												
	Android devices: Given via KNOX Standard API; Requires KNOX Standard compatibility.	•				•		•					
Maker	The device manufacturer.												
	Android devices: Requires KNOX Standard compatibility.	•											
Ownership	Tracks whether the device is a company device or personal device.	•		•	•	•		•	•		•		
Platform	Displays the device platform type as reported by the device.	•		•	•	•		•	•		•		BB10
Platform Version Name	The name of the device platform version.												
	Android devices: Requires KNOX Standard compatibility.	•											
UID	Displays the device UID.												
	Symbian: The device UID is the same as the device IMEI.				•			•	•		•		

Device Statistics: All Devices	Description	Anrd	Anrd w/ AS only	TD/A	NS/BB	iOS or TD/iOS	iOS w/ AS only	iOS Config Devices	S60	S60 w/ AS only	WM	WM w/ AS only	AS only
IMEI	The International Mobile Equipment Identify number. See http://en.wikipedia.org/wiki/Internation al_Mobile_Equipment_Identity	•		•	•	•		•	•		•		WP
	BlackBerry with GO!NotifySync: Limited to GSM devices.												
Phone Number	Displays device phone number.	•		•	•	•		•			•		
Time Zone	The time zone setting on the device.	•		•	•	•					•		
GMT Offset	The time difference between the device's time zone and Greenwich Mean Time.	•		•	•	•					•		
Build Version	iOS build number.					•		•					
Product Name	The model code for the device.					•		•					
Serial Number	Device's serial number.	•		•	•	•		•					
Modem Firmware Version	The baseband firmware version.												
	Android devices: Requires KNOX Standard compatibility.												
MEID	The device's MEID (CDMA).					•							
ICCID	The ICC identifier for the installed SIM card (if applicable).					•		•					
Bluetooth MAC	Bluetooth MAC address.												
	Android devices: Requires KNOX Standard compatibility.	•				•		•					
Wi-Fi MAC	Wi-Fi MAC address.	•		•		•		•					
Subscriber MCC	Home Mobile Country Code					•		•					
Subscriber MNC	Home Mobile Network Code					•		•					
Current MCC	Current Mobile Country Code					•		•					
Current MNC	Current Mobile Network Code					•		•					
iTunes Account Active	Whether the device is currently using an iTunes account.					•		•					
	Requires iOS 7 or later.												

## **COMPLIANCE MANAGER**

Compliance Manager	Description	Anrd	Anrd w/ AS only	TD/A	NS/BB	iOS	TD/ iOS	iOS w/ AS only	iOS Config Devices	S60	S60 w/ AS only	WM	WM w/ AS only	AS only
Access Restriction											Jy		oy	
Restrict on ActiveSync authorization failures	A device passes invalid credentials for the ActiveSync account of a known user to the server a number of times that exceeds the set limit.	•	•	•	•	•	•	•		•	•	•	•	BB10 wOS WP
Restrict ActiveSync protocol	A device cannot support sufficient ActiveSync policies, because of ActiveSync version support limitations with the device or server.	•	•	•	•	•	•	•		•	•	•	•	BB10 wOS WP
Restrict cellular connection	A device is using a cellular network connection and is in violation of the enabled Restrict Cellular Connection access policy.				•									
Restrict if Android user disables Device Administrators	An Android user has not granted device administration privileges to the ZENworks Mobile Management app.	•		•										
Restrict Liability	A device enrolls with a liability status specifically restricted by the Restrict Liability access policy.	•	•	•	•	•	•	•	•	•	•	•	•	BB10 wOS WP
Restrict on ZENworks authorization failures	A device passes invalid credentials for the ZENworks Mobile Management account of a known user to the server a number of times that exceeds the set limit.	•	NA	•	•	•	•	NA	NA	•	NA	•	NA	NA
Restrict BlackBerrys without GO!NotifySync	A BlackBerry device that does not have the GO!NotifySync application has enrolled.	NA	NA	NA	•	NA	NA	NA	NA	NA	NA	NA	NA	BB10
Restrict if roaming detected	A device is roaming and is in violation of the Restrict if Roaming Detected access policy.	•		•	•	•	•			•		•		
Restrict if SIM Card removed or	A user has removed or changed the SIM	•		•	•	•	•					•		

Compliance Manager	Description	Anrd	Anrd w/ AS only	TD/A	NS/BB	iOS	TD/ iOS	iOS w/ AS only	iOS Config Devices	S60	S60 w/ AS only	WM	WM w/ AS only	AS only
changed	card in a device and is in violation of the Restrict if SIM Card is Removed or Changed access policy.													
Restrict TouchDown for Android	TouchDown is required and either an Android device does not have the TouchDown application or the TouchDown version does not meet the minimum requirement.	•	•	•	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
Restrict user ActiveSync connections	A device's Last ActiveSync Sync time stamp has not updated within the set interval.	•	•	•	•	•	•	•		•	•	•	•	BB10 wOS WP
Restrict when Blacklist App detected	A device has a blacklisted application installed.	•		•		•	•	•	•					
Restrict when non-Whitelist App detected	A device has an application that does not match the whitelist criteria.	•		•		•	•	•	•					
Restrict Wi-Fi connection	A device is using a Wi-Fi connection and is in violation of the enabled Restrict Wi-Fi Connection access policy.				•									
Single Devices	A specific device, identified by phone number or UID number, has been denied access.	•		•	•	•	•		•	•				
Single Users	A specific user, identified by User Name, has been denied access.	•	•	•	•	•	•	•	•	•	•	•	•	BB10 wOS WP
<b>Device Platform Restriction</b>														
Restrict if ZENworks app is not enrolled	A device enrolls via the native ActiveSync agent alone and without the ZENworks Mobile Management application.	•	•	•	•	•	•	•	•	•	•	•		BB10 wOS WP
Restrict if location services are off	A device's location has not updated within the defined interval.	•		•	•	•	•			•		•		
Restrict user ZENworks connections	A device's Last ZENworks Sync time stamp has not updated within the set interval.	•		•	•	•	•		NA	•		•		
Restrict if policy out of date	A policy has been updated on the server, but a device has not updated within the set grace period.	•	•	•	•	•	•	•		•	•	•	•	BB10 wOS WP

Compliance Manager	Description	Anrd	Anrd w/ AS only	TD/A	NS/BB	iOS	TD/ iOS	iOS w/ AS only	iOS Config Devices	S60	S60 w/ AS only	WM	WM w/ AS only	AS only
Restrict rooted devices	A rooted Android device connects to the server.	•		•	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
Restrict jailbroken devices	A jailbroken iOS device connects to the server.	NA	NA	NA	NA	•	•			NA	NA	NA	NA	NA
Restrict if iOS passcode not initiated	The user's policy suite requires a password, but the iOS device does not have a passcode initiated.	NA	NA	NA	NA	•	•		•	NA	NA	NA	NA	NA
Restrict if iOS passcode is not compliant with requirements	The user's policy suite requires a password, but the iOS device does not have a passcode compliant with the requirements.	NA	NA	NA	NA	•	•		•	NA	NA	NA	NA	NA
Restrict if iOS passcode is not compliant with data protection	The iOS device does not have a passcode and thus is not compliant with iOS "data protection," which enhances the built-in hardware encryption by protecting the hardware encryption keys with the passcode.	NA	NA	NA	NA	•	•		•	NA	NA	NA	NA	NA
Restrict if iOS unmanaged configuration profile is on device	An iOS device has an unmanaged configuration profile.	NA	NA	NA	NA	•	•		•	NA	NA	NA	NA	NA
Restrict if iOS APN profiles are not enrolled	An iOS device has not loaded the iOS APN configuration profile and has never synchronized through the Apple MDM API.	NA	NA	NA	NA	•	•			NA	NA	NA	NA	NA
Restrict if no iOS APN connectivity	A device's Last iOS APN Sync time stamp has not updated within the set interval.	NA	NA	NA	NA	•	•		•	NA	NA	NA	NA	NA
Non-Access Policy Based Alerts														
Low battery detection	A device's battery level has fallen below a specified warning level.	•		•	•	•	•			•		•		
Low memory detection	A device's memory level has fallen below the greater of the two specified levels.	•		•	•	•	•			•		•		
Low on redemption codes	The number of redemption codes (for iOS devices installing an app obtained through the Apple Volume Purchase Program) available on the server has fallen below a specified amount.	NA	NA	NA	NA	•	•			NA	NA	NA	NA	NA

Compliance Manager	Description	Anrd	Anrd w/ AS only	TD/A	NS/BB	iOS	TD/ iOS	iOS w/ AS only	iOS Config Devices	S60	S60 w/ AS only	WM	WM w/ AS only	AS only
ZENworks app is not enrolled	A device of any platform type connects to the server via ActiveSync and does not have the ZENworks Mobile Management application enrolled.	•	•	•	•	•	•	•	•	•	•	•	•	BB10 wOS WP
Organization-wide ActiveSync connectivity	The Last ActiveSync Sync time stamp has not updated for any users within the set interval.	•	•	•	•	•	•	•		•	•	•	•	BB10 wOS WP
Organization-wide ZENworks connectivity	The Last ZENworks Sync time stamp has not updated for any users within the set interval.	•		•	•	•	•			•		•		BB10
Watch List	A user or policy suite on the Watch List grid has exceeded the time for which it was being monitored.	•	•	•	•	•	•	•		•	•	•	•	BB10 wOS WP
User's e-mail not set	A user's email address has not been set. Because a user's email address cannot always be determined during Hands-Off provisioning, this alerts the administrator that an email address for the user should be manually set.	•	•	•	•	•	•	•		•	•	•	•	BB10 wOS WP
<b>Event Based Alerts</b>														
ActiveSync Account Already Enrolled	An iOS profile included an ActiveSync payload that could not be installed because an identical ActiveSync account was already enrolled.	NA	NA	NA	NA	•	•			NA	NA	NA	NA	NA
Reset for Enrollment	An administrator has issued a <i>Reset for Enrollment</i> command from the dashboard to a device.	•	•	•	•	•	•	•	•	•	•	•	•	BB10 wOS WP
Clear passcode issued by Admin	An administrator has issued a Clear Passcode from the dashboard to an iOS device.	NA	NA	NA	NA	•	•		•	NA	NA	NA	NA	NA
Full wipe issued by Admin	An administrator has issued a Full Wipe command from the dashboard to a device.	•	•	•	•	•	•	•	•	•	•	•	•	BB10 wOS WP
Full wipe issued by user	A user has issued a Full Wipe command from the User Self Administration Portal to their device.	•	•	•	•	•	•	•		•	•	•	•	BB10 wOS WP
Lock device issued by Admin	An administrator has issued a Lock	•		•	•	•	•		•	•		•		

Compliance Manager	Description	Anrd	Anrd w/ AS only	TD/A	NS/BB	iOS	TD/ iOS	iOS w/ AS only	iOS Config Devices	S60	S60 w/ AS only	WM	WM w/ AS only	AS only
	Device command from the dashboard to a device.													
Lock device issued by user	A user has issued a Lock Device command from the User Self Administration Portal to their device.	•		•	•	•	•					•		
New Hands-Off Enrolled device	Any time a new device uses Hands-Off enrollment to connect to the system.	•	•	•	•	•	•	•		•	•	•	•	BB10 wOS WP
New Hands-Off Enrolled user	Any time a new user uses Hands-Off enrollment to connect to the system.	•	•	•	•	•	•	•		•	•	•	•	BB10 wOS
Recovery password requested by device	A user requests a temporary recovery password form a device's locked screen.			•	•									
Recovery Password viewed by Admin	An administrator has attempted to view a temporary recovery password issued for a user from the dashboard.			•	•									
Recovery Password viewed by user	A user has attempted to view a temporary recovery password from the User Self Administration Portal. (This does not detect when the recovery password has been viewed through OWA.)			•	•									
Restricted device attempts to connect	A restricted device tries to access ActiveSync, File Share, or Managed Apps when these resources have been blocked.	•	•	•	•	•	•	•		•	•	•	•	BB10 wOS WP
Stop managing device issued by Admin	An administrator has issued a <i>Stop Managing Device</i> command from the dashboard to a device.	•		•	•	•	•		•	•		•		BB10 wOS WP
Stop managing device issued by user	A user has issued a <i>Stop Managing Device</i> command from the User Self Administration Portal to a device.	•		•	•	•	•			•		•		BB10 wOS WP
TouchDown policy override detection	The system issues a warning if it detects that a user has overridden the TouchDown settings governed by ZENworks Mobile Management.	NA	NA	•	NA	NA		NA	NA	NA	NA	NA	NA	NA

Compliance Manager	Description	Anrd	Anrd w/ AS only	TD/A	NS/BB	iOS	TD/ iOS	iOS w/ AS only	iOS Config Devices	S60	S60 w/ AS only	WM	WM w/ AS only	AS only
User restricted	A user becomes restricted for any reason.	•	•	•	•	•		•	•	•	•	•	•	BB10 wOS WP
Wipe storage card	An administrator has issued a Wipe Storage Card command from the dashboard to a device.	•		•	•	NA		NA	NA			•		
System Alerts														
Apple Push Notification (APNs) Certificate Expiration	Enable and set parameters to keep track of the APNs certificate expiration. Default settings are to issue the reminder 30 days prior to the expiration and repeat it every day.	NA	NA	NA	NA	•	•	•	•	NA	NA	NA	NA	NA