

Novell ZENworks® Linux Management

7.2

August 23, 2007

TRUBLESHOOTING GUIDE

www.novell.com



Novell®

Legal Notices

Novell, Inc. makes no representations or warranties with respect to the contents or use of this documentation, and specifically disclaims any express or implied warranties of merchantability or fitness for any particular purpose. Further, Novell, Inc. reserves the right to revise this publication and to make changes to its content, at any time, without obligation to notify any person or entity of such revisions or changes.

Further, Novell, Inc. makes no representations or warranties with respect to any software, and specifically disclaims any express or implied warranties of merchantability or fitness for any particular purpose. Further, Novell, Inc. reserves the right to make changes to any and all parts of Novell software, at any time, without any obligation to notify any person or entity of such changes.

Any products or technical information provided under this Agreement may be subject to U.S. export controls and the trade laws of other countries. You agree to comply with all export control regulations and to obtain any required licenses or classification to export, re-export, or import deliverables. You agree not to export or re-export to entities on the current U.S. export exclusion lists or to any embargoed or terrorist countries as specified in the U.S. export laws. You agree to not use deliverables for prohibited nuclear, missile, or chemical biological weaponry end uses. See the [Novell International Trade Services Web page \(http://www.novell.com/info/exports/\)](http://www.novell.com/info/exports/) for more information on exporting Novell software. Novell assumes no responsibility for your failure to obtain any necessary export approvals.

Copyright © 2007 Novell, Inc. All rights reserved. No part of this publication may be reproduced, photocopied, stored on a retrieval system, or transmitted without the express written consent of the publisher.

Novell, Inc. has intellectual property rights relating to technology embodied in the product that is described in this document. In particular, and without limitation, these intellectual property rights may include one or more of the U.S. patents listed on the [Novell Legal Patents Web page \(http://www.novell.com/company/legal/patents/\)](http://www.novell.com/company/legal/patents/) and one or more additional patents or pending patent applications in the U.S. and in other countries.

Novell, Inc.
404 Wyman Street, Suite 500
Waltham, MA 02451
U.S.A.
www.novell.com

Online Documentation: To access the online documentation for this and other Novell products, and to get updates, see the [Novell Documentation Web page \(http://www.novell.com/documentation/\)](http://www.novell.com/documentation/).

Novell Trademarks

For Novell Trademarks, see the [Novell Trademark and Service Mark list \(http://www.novell.com/company/legal/trademarks/tmlist.html\)](http://www.novell.com/company/legal/trademarks/tmlist.html)

Third-Party Materials

All third-party trademarks are the property of their respective owners.

Contents

About This Guide	9
Part I Installation, Upgrade, and ZENworks Database	11
1 Installation and Upgrade Troubleshooting Strategies	13
1.1 Troubleshooting the Installation	13
1.2 Troubleshooting the Upgrade Scripts	15
2 ZENworks Database Troubleshooting Strategies	17
2.1 Troubleshooting the ZENworks Database	17
Part II Policy Handlers	19
3 Policy Handlers Error Messages	21
3.1 General Error Messages	21
3.2 Remote Execute Policy Error Messages	27
4 Policy Handlers Troubleshooting Strategies	29
4.1 General Troubleshooting Strategies	29
4.2 Troubleshooting the Epiphany Policy	32
4.3 Troubleshooting the Generic GNOME Policy	32
4.4 Troubleshooting the Remote Execute Policy	33
4.5 Troubleshooting the Text File Policy	34
Part III Event Monitoring	37
5 Event Monitoring Troubleshooting Strategies	39
5.1 Troubleshooting Event Monitoring	39
Part IV Inventory	41
6 Inventory Roll-Up Error Messages	43
7 Inventory Troubleshooting Strategies	47
7.1 Troubleshooting Inventory Roll-Up	47
7.2 Troubleshooting Hardware Inventory	48

Part V Disaster Recovery	51
8 Disaster Recovery	53
8.1 Safeguarding Your System through Backups	53
8.1.1 The Data Store	53
8.1.2 The Object Store	53
8.1.3 The Package Repository	53
8.1.4 The zlmirror Configuration Files	54
8.2 Safeguarding Your System through Server Configuration	54
8.2.1 Data Store	54
8.2.2 Object Store	54
8.2.3 Package Repository	55
8.2.4 Message Logger	55
8.3 Restoring Your System after a Primary Server Failure.	55
8.3.1 Converting a Secondary Server to a Primary Server	56
8.4 Moving Devices to the New Primary Server	57
9 Disaster Recovery Error Messages	59
Part VI Remote Management	61
10 Remote Management Error Messages	63
11 Remote Management Troubleshooting Strategies	67
12 Frequently Asked Questions	71
12.1 How do I secure my Remote Management session?	71
12.2 How can I improve Remote Management performance on a slow link?	72
12.3 Why do I get a black screen when I perform the Remote Control operation?	72
12.4 Why does the Remote Management Viewer show only a toolbar at the center of the applet window?	73
12.5 Why is the Novell Remote Management Viewer Applet signed?	73
12.6 Why do I get a warning indicating that an unsecure download is in progress on Internet Explorer?	73
12.7 I rejected the Novell Remote Management certificate and now I am unable to perform Remote Management operations.	73
12.8 Can I use any other third-party VNC viewer to connect to the ZENworks 7 Linux managed device?	73
12.9 Can I use the Novell ZENworks Remote Management Viewer window to Remote Control any third-party VNC server?	74
12.10 Why is the certificate is not displayed while trying to start the Remote Management session for a managed device?	74

Part VII Dell DTK	75
13 Dell Configuration Bundle Troubleshooting Strategies	77
Part VIII Package and Content Management	79
14 Package and Content Management Error Messages	81
15 Package and Content Management Troubleshooting Strategies	83
A Documentation Updates	87
A.1 August 23, 2007.....	87
A.1.1 Inventory	87
A.2 May 21, 2007.....	87
A.2.1 Inventory	87

About This Guide

This guide includes troubleshooting strategies that you can use and error messages that might be displayed for problems that could occur as you use Novell® ZENworks® 7.2 Linux Management in your production environment.

As administrators gain experience using Linux Management, some unusual or previously untested implementation scenarios and undocumented product limitations might surface. We will gather this feedback from Novell customers and add it to this guide as it becomes practical to do so.

The guide is intended for network administrators and is divided into the following sections:

- ◆ Part I, “Installation, Upgrade, and ZENworks Database,” on page 11
- ◆ Part II, “Policy Handlers,” on page 19
- ◆ Part III, “Event Monitoring,” on page 37
- ◆ Part IV, “Inventory,” on page 41
- ◆ Part V, “Disaster Recovery,” on page 51
- ◆ Part VI, “Remote Management,” on page 61
- ◆ Part VII, “Dell DTK,” on page 75
- ◆ Part VIII, “Package and Content Management,” on page 79
- ◆ Appendix A, “Documentation Updates,” on page 87

Documentation Conventions

In Novell documentation, a greater-than symbol (>) is used to separate actions within a step and items in a cross-reference path.

A trademark symbol (®, ™, etc.) denotes a Novell trademark. An asterisk (*) denotes a third-party trademark.

When a single pathname can be written with a backslash for some platforms or a forward slash for other platforms, the pathname is presented with a backslash. Users of platforms that require a forward slash, such as Linux* or UNIX*, should use forward slashes as required by your software.

User Comments

We want to hear your comments and suggestions about this manual and the other documentation included with this product. Please use the User Comment feature at the bottom of each page of the online documentation, or go to www.novell.com/documentation/feedback.html and enter your comments there.

Additional Documentation

For the latest documentation on installing or upgrading to ZENworks 7.2 Linux Management, see the *Novell ZENworks 7.2 Linux Management Installation Guide*.

For the latest documentation on configuring and managing ZENworks 7 Linux Management, see the *Novell ZENworks 7.2 Linux Management Administration Guide*.

Installation, Upgrade, and ZENworks Database

The following section provides solutions to problems you might encounter when installing the Novell® ZENworks® 7.2 Linux Management, or working with the ZENworks Database:

- ♦ [Chapter 1, “Installation and Upgrade Troubleshooting Strategies,” on page 13](#)
- ♦ [Chapter 2, “ZENworks Database Troubleshooting Strategies,” on page 17](#)

Installation and Upgrade Troubleshooting Strategies

1

The following sections provide solutions to the problems you might encounter when installing or upgrading to Novell® ZENworks® Linux Management:

- ♦ [Section 1.1, “Troubleshooting the Installation,” on page 13](#)
- ♦ [Section 1.2, “Troubleshooting the Upgrade Scripts,” on page 15](#)

1.1 Troubleshooting the Installation

- ♦ [“Install randomly fails when zlm-config fails to complete” on page 13](#)
- ♦ [“Zmd hangs randomly on the managed device” on page 13](#)
- ♦ [“Installation of signed packages using rug fails on SLES 9, NLD, and Red Hat platforms” on page 13](#)
- ♦ [“ZENworks Server installation on SLES 10 fails with the error, “Resolvable not found”” on page 14](#)
- ♦ [“How do I recover the password for the ZENworks Server?” on page 14](#)
- ♦ [“Executing the rug ref command on the PPC, IPF, and zSeries devices results in exceptions related to Inventory” on page 14](#)

Install randomly fails when zlm-config fails to complete

Source: ZENworks Linux Management, Installation of the ZENworks Agent.

Action: Re-run `zlm-config`.

Zmd hangs randomly on the managed device

Source: ZENworks Linux Management, Installation of the ZENworks Agent.

Explanation: The ZENworks Agent (`zmd`) hangs on the managed device and displays the message “`zmd inactive`” when the managed device is kept idle for more than a day.

Action: Restart `zmd` on the managed device.

Installation of signed packages using rug fails on SLES 9, NLD, and Red Hat platforms

Source: ZENworks Linux Management, Installation

Explanation: If the `zmd security-level` preference is set to `signature`, the installation of a signed package using `rug` would fail with the following error: `Unable to verify package signature`.

Action: Do the following:

- 1 Verify signature manually using the following `rpm` command:

```
rpm --checksig -v package_name
```

- 2 Change the security- level preference to checksum or none as shown below:

```
rug set security-level checksum
```

ZENworks Server installation on SLES 10 fails with the error, “Resolvable not found”

Source: ZENworks Linux Management, ZENworks Server

Action: Do the following:

- 1 Remove the `openldap2` package from the system by executing `rpm -e openldap2` command.
- 2 Install the ZENworks Server. For detailed information on installing the ZENworks Server, see “Installation” in the *Novell ZENworks 7.2 Linux Management Installation Guide*.

How do I recover the password for the ZENworks Server?

Source: ZENworks Linux Management, ZENworks Server

Action: Do the following:

- 1 After successfully installing the ZENworks Server components, take a reliable backup of the following files:
 - ♦ `/etc/opt/novell/zenworks/hibernate.cfg.xml`
 - ♦ `/etc/opt/novell/zenworks/tomcat/server.xml`
 - ♦ `/etc/opt/novell/zenworks/serversecret`
- 2 Replace `/etc/opt/novell/zenworks/serversecret` with the `serversecret` file that you have backed up in Step 1.
- 3 In `/etc/opt/novell/zenworks/tomcat/server.xml`, change the value of `keystorePass` and `connectionPassword` to the values configured in backed up `serversecret` file.
- 4 In `/etc/opt/novell/zenworks/hibernate.cfg.xml`, change the value of `<property name="connection.password">` to the values configured in backed up `serversecret` file.

Executing the `rug ref` command on the PPC, IPF, and zSeries devices results in exceptions related to Inventory

Source: ZENworks Linux Management; ZENworks Agent

Possible Cause: On the PPC, IPF, and zSeries devices, the `rug set hardware-inventory-enabled` preference is set to `True`.

Action: Do one of the following:

- ♦ Ignore the exceptions because Inventory is not supported for the PPC, IPF, and zSeries devices.
- ♦ To avoid the exceptions, set the `rug set hardware-inventory-enabled` preference is set to `False`.

1.2 Troubleshooting the Upgrade Scripts

- ♦ “Execution of the Upgrade Script Fails on Managed Devices Other Than SLES 10 and SLED 10” on page 15
- ♦ “Execution of the Upgrade Script Fails on the SLES 10 or SLED 10 Managed Devices” on page 15

Execution of the Upgrade Script Fails on Managed Devices Other Than SLES 10 and SLED 10

Source: ZENworks Linux Management, Upgrade.

Possible Cause: The Remote Execute policy is not implemented on the device. To verify that the policy has not been implemented, check that the `/var/opt/novell/zenworks/cache/zmd/policymanager/policies.xml` file does not have reference to the Remote Execute policy.

Action: Do the following on the managed device:

- 1 Ensure that the zmd version is 7.1.100 by executing `rpm -qi novell-zenworks-zmd`.
- 2 Restart the zmd service by executing `/etc/init.d/novell-zmd restart`.

Execution of the Upgrade Script Fails on the SLES 10 or SLED 10 Managed Devices

Source: ZENworks Linux Management, Upgrade.

Action: Do the following on the managed device:

- 1 Ensure that the zmd version is 7.1.100 by executing `rpm -zmd`.
- 2 Restart the zmd service by executing `/etc/init.d/novell-zmd restart`.

ZENworks Database Troubleshooting Strategies

2

The following sections provide solutions to the problems you might encounter when working with the ZENworks® Database:

- ♦ [Section 2.1, “Troubleshooting the ZENworks Database,” on page 17](#)

2.1 Troubleshooting the ZENworks Database

- ♦ [“Unable to use dbrestore to restore the ZENworks database installed on a RHEL device” on page 17](#)

Unable to use dbrestore to restore the ZENworks database installed on a RHEL device

Source: ZENworks Linux Management, ZENworks Database

Explanation: Using the `zlm_dbrestore.sh` script to restore the ZENworks database installed on a RHEL device might fail.

Action: Do the following before executing the `zlm_dbrestore.sh` script:

- 1 Open the `novell-zenloader` script file from the `/etc/init.d` directory.
- 2 Search for the `status ()` function.
- 3 Change the last return statement in status function from `return 0` to `return 3`, and save the file.

The modified script should contain the `status ()` function as follows:

```
status ( )
{
    echo -n "Checking for Novell ZENworks Loader"
    if [ -n "$RUNPID" ]; then
        return 0
    elif [ -f $PIDLOC ] ; then
        zenloaderpid=`cat $PIDLOC`
        te=`ps --pid $zenloaderpid | grep java`
        if [ -z "$te" ] ; then
            return 1
        fi
        return 0
    else
        return 3
    fi
}
```


Policy Handlers



If the Policy Handlers component of Novell® ZENworks® Linux Management displays an error message, you can look it up in the Error Messages section. If a problem is not accompanied by an error message, or if specific instructions for an error message are not available, you can try more general troubleshooting strategies to resolve the problem.

This section contains the following topics:

- ◆ [Chapter 3, “Policy Handlers Error Messages,” on page 21](#)
- ◆ [Chapter 4, “Policy Handlers Troubleshooting Strategies,” on page 29](#)

Policy Handlers Error Messages

3

This section contains detailed explanations of the error messages you might encounter using the Novell® ZENworks® Linux Management Policy Handler component:

- ♦ “General Error Messages” on page 21
- ♦ “Remote Execute Policy Error Messages” on page 27

3.1 General Error Messages

- ♦ “The policy_name could not be enforced because it contains invalid keys” on page 22
- ♦ “The policy_name could not be enforced because few keys defined in the policy could not be cleared appropriately before enforcement” on page 22
- ♦ “The policy_name could not be enforced because the format of the policy data was invalid” on page 22
- ♦ “The policy_name could not be enforced because the user specified was invalid” on page 22
- ♦ “The policy_name could not be enforced because the username has not been specified in the policy” on page 23
- ♦ “The GConfEnforcer could not find any settings to read from the device” on page 23
- ♦ “The GConfEnforcer could not read the requested settings from the device for the specified user” on page 23
- ♦ “The settings made by the policy_name enforcers could not be cleared completely. Settings made by policies of this type might still be in effect on the device” on page 23
- ♦ “The policy_name could not be enforced because there was an error in setting or unsetting the values into the configuration source” on page 24
- ♦ “The read settings operation could not be performed by the enforcer GConf Enforcer because there was an error in reading from the configuration source” on page 24
- ♦ “The enforcement of policy_name was unsuccessful and the application is not installed/compatible. The version of name of the application should be >= minimum required version” on page 24
- ♦ “The enforcement of name of the policy was unsuccessful and the operating system distribution is not compatible. The distribution should be >= distribution required version. Only some keys might be enforced” on page 25
- ♦ “The policy_name will not be enforced because the name of the application is not installed” on page 25
- ♦ “The policy_name will not be enforced because the operating system is not required distribution version or higher” on page 25
- ♦ “The policy_name was requested to be enforced, however, it is already executing, therefore, we will not start it again.” on page 25
- ♦ “Rescheduling the enforcement of name of the policy for 2 minutes later, because its type is not re-entrant and another policy of this type is already executing.” on page 26

The *policy_name* could not be enforced because it contains invalid keys

Source: ZENworks Linux Management; Policy Handlers

Severity: Critical

Possible Cause: Some other application might have locked the settings that are defined in the policy they cannot be written to GConf.

Action: Ask the user to login again to the managed device.

The *policy_name* could not be enforced because few keys defined in the policy could not be cleared appropriately before enforcement

Source: ZENworks Linux Management; Policy Handlers

Severity: Critical

Possible Cause: Some other application might have locked the settings that are defined in the policy. They could not be removed from GConf.

Action: Ask the user to log in again to the managed device.

The *policy_name* could not be enforced because the format of the policy data was invalid

Source: ZENworks Linux Management; Policy Handlers

Severity: Critical

Possible Cause: The policy details were corrupted while retrieving or applying it.

Action: Perform the following:

- 1** To refresh the policy details, run the following command from the command line:
`/opt/novell/zenworks/bin/rug refresh`
- 2** If the policy is not enforced, stop zmd by running the following command from the command line:
`/etc/init.d/novell-zmd stop`
- 3** Remove the policy cache files from `/var/opt/novell/zenworks/cache/zmd/PolicyManager/policies.xml`.
- 4** Start zmd by running the following command from the command line:
`/etc/init.d/novell-zmd start`
- 5** Ask the user to log in again to the managed device.

The *policy_name* could not be enforced because the user specified was invalid

Source: ZENworks Linux Management; Policy Handlers

Severity: Critical

Possible Cause: The user's login entry for device does not exist in the `/etc/passwd` file.

Action: Make sure that the user's entry exists in the `/etc/passwd` file.

Possible Cause: An internal error occurred while applying the policy.

Action: Perform the following:

- 1 Restart zmd by running the following command from the command line:
`/etc/init.d/novell-zmd restart`
- 2 Ask the user to log in again to the managed device.

The *policy_name* could not be enforced because the username has not been specified in the policy

Source: ZENworks Linux Management; Policy Handlers

Severity: Critical

Possible Cause: An internal error occurred while applying the policy.

Action: Perform the following:

- 1 Restart zmd by running the following command from the command line:
`/etc/init.d/novell-zmd restart`
- 2 Ask the user to log in again to the managed device.

The GConfEnforcer could not find any settings to read from the device

Source: ZENworks Linux Management; Policy Handlers

Severity: Critical

Possible Cause: The default schema files of GConf are corrupted or not valid.

Action: Ensure that the default schema files of GConf are valid.

Possible Cause: You might not have configured any specific GConf values for the user.

Action: Configure some values for the user.

For more information about configuring GConf values, refer “[Understanding Policies](#)” in the *Novell ZENworks 7.2 Linux Management Administration Guide*.

The GConfEnforcer could not read the requested settings from the device for the specified user

Source: ZENworks Linux Management; Policy Handlers

Severity: Critical

Possible Cause: The user's entry does not exist in the `/etc/passwd` file.

Action: Make sure that the user's entry exists in the `/etc/passwd` file.

The settings made by the *policy_name* enforcers could not be cleared completely. Settings made by policies of this type might still be in effect on the device

Source: ZENworks Linux Management; Policy Handlers

Severity: Critical

Possible Cause: Some other application might have locked the settings that are defined in the policy, so cannot be removed from GConf.

Action: Perform the following:

- 1 Ask the user to log in again to the managed device.
- 2 Clear the policy enforcement again on the managed device.

The *policy_name* could not be enforced because there was an error in setting or unsetting the values into the configuration source

Source: ZENworks Linux Management; Policy Handlers

Severity: Critical

Possible Cause: The home directory of a user who has logged in to the managed device does not exist in the `/etc/passwd` file.

Action: Ensure that a valid home directory is specified for a user on the managed device in the `/etc/passwd`.

Possible Cause: Root has insufficient rights to access the home directory of a user on the managed device.

Action: Ensure that root has sufficient rights to access the home directory.

Possible Cause: Some other application might have locked the settings that are defined in the policy, so they cannot be written to GConf.

Action: Ask the user to log in again to the managed device.

The read settings operation could not be performed by the enforcer GConf Enforcer because there was an error in reading from the configuration source

Source: ZENworks Linux Management; Policy Handlers

Severity: Critical

Possible Cause: The home directory of a user whose settings are being retrieved from the managed device does not exist in the `/etc/passwd` file.

Action: Ensure that a valid home directory is specified for a user on the managed device in `/etc/passwd` file.

Possible Cause: The user does not have sufficient rights to access the directory from the ZENworks Management Daemon.

Action: Ensure that the user has sufficient rights to access the ZENworks Management Daemon.

Possible Cause: Some other application might have locked the settings that are defined in the policy, so they cannot be written to GConf.

Action: Retry importing the settings.

The enforcement of *policy_name* was unsuccessful and the application is not installed/compatible. The version of *name of the application* should be \geq *minimum required version*

Source: ZENworks Linux Management; Policy Handlers

Severity: Critical

Possible Cause: The application (Firefox*, Epiphany*, or EvolutionTM) is not installed or the specified version is earlier than the minimum supported version.

Action: Upgrade the application to the minimum required version and try enforcing the policy again.

The enforcement of *name of the policy* was unsuccessful and the operating system distribution is not compatible. The distribution should be \geq *distribution required version*. Only some keys might be enforced

Source: ZENworks Linux Management; Policy Handlers

Severity: Critical

Possible Cause: The distribution or version of the operating system is not compatible with the policy you are trying to enforce.

Action: Associate the policy to a device with the required distribution and version of the operating system.

The *policy_name* will not be enforced because the *name of the application* is not installed

Source: ZENworks Linux Management; Policy Handlers

Severity: Critical

Possible Cause: The policy might be associated to a device that does not have the application installed.

Action: Install the required application.

The *policy_name* will not be enforced because the operating system is not *required distribution version* or higher

Source: ZENworks Linux Management; Policy Handlers

Severity: Critical

Possible Cause: The Novell Linux Desktop policy or the SUSE Linux Enterprise Desktop policy is associated to a device that does not have Novell Linux Desktop or SUSE Linux Enterprise Desktop operating system respectively.

Action: Associate the Novell Linux Desktop policy only to devices having Novell Linux Desktop operating system installed, and the SUSE Linux Enterprise Desktop policy only to the devices having the SUS Linux Enterprise Desktop operating system installed.

The *policy_name* was requested to be enforced, however, it is already executing, therefore, we will not start it again.

Source: ZENworks Linux Management; Policy Handlers

Severity: Important

Explanation: If two or more users are logging into the device at the same time, the policy enforcement might not have finished for the first user before it started for the other user. The specified policy is not enforced for users other than the first user.

Possible Cause: Two or more users have logged in to the device at the same time.

Action: The users after the first user should login again for the policies to take effect.

Possible Cause: One of the policies is taking a long time.

Action: For Text File and Remote Execute policies, review any scripts/programs specified in the policy to see if they could take excessive time. Correct those situations to reduce the amount of time and try enforcing the policy again. For GConf-based policies, do not include any settings in the policy that are not relevant to you. If the policy data is correct, then restart ZMD and enforce the policy again.

Possible Cause: The time interval for enforcing the policy is too small compared to the amount of time it takes to enforce the policy.

Action: Increase the time interval.

- 1 In the ZENworks Control Center, click *Policies*.
- 2 Click any Remote Execute or Text File policy for which you want to increase the time interval.
- 3 On the *Summary* page, click *Relative to Refresh* in *Assignments* section.
- 4 In the *Edit Schedule* dialog box, increase the time interval you have specified in *After Executing, Repeat Every* option.

Rescheduling the enforcement of *name of the policy* for 2 minutes later, because its type is not re-entrant and another policy of this type is already executing.

Source: ZENworks Linux Management; Policy Handlers

Severity: Important

Possible Cause: A read settings request was made to the managed device while a user was trying to login.

Action: Ask the user to login again to the managed device.

Possible Cause: There is an internal error.

Action: Restart ZMD and ask the user to login again to the managed device.

The enforcer executable, *enforcer_name*, could not be located

Source: ZENworks Linux Management; Policy Handlers

Explanation: The Policy Manger logs the error message in the ZENworks Control Center when you log into a managed device that does not have the GConf binaries installed.

Possible Cause: The ZENworks Agent is installed with the -x option on the managed device that does not have GConf binaries installed.

Possible Cause: The ZENworks Agent installation is corrupted.

Action: If the error message is displayed when a GConf based policy is assigned, do one of the following:

- ◆ To apply the GConf based policy, reinstall the ZENworks Agent without -x option.

- ◆ Remove the assignment between the policy and the device that does not have the Gconf binaries installed.

Action: If the error message is displayed when a GConf based policy is not assigned, ignore the message and acknowledge it in ZENworks Control Center.

3.2 Remote Execute Policy Error Messages

- ◆ “The policy_name was enforced and the program launched did not complete the execution” on page 27

The *policy_name* was enforced and the program launched did not complete the execution

Explanation: This message indicates that the launched script or binary or Java* program didn't complete the execution when the enforcer returned, so the exit code returned by the launched program could not be reported in the message. This message does not mean that the launched program was terminated abnormally.

Possible Cause: While creating the policy, the *Maximum Time to Wait* setting was specified as *Do Not Wait* or *Wait For number of seconds Secs*.

Action: In the *Maximum Time to Wait* setting, select *Wait Till the Program Completes the Execution*.

Policy Handlers Troubleshooting Strategies

4

This section provides solutions to problems you might encounter when using Novell® ZENworks® Linux Management Policy Handler component.

- ♦ [Section 4.1, “General Troubleshooting Strategies,” on page 29](#)
- ♦ [Section 4.2, “Troubleshooting the Epiphany Policy,” on page 32](#)
- ♦ [Section 4.3, “Troubleshooting the Generic GNOME Policy,” on page 32](#)
- ♦ [Section 4.4, “Troubleshooting the Remote Execute Policy,” on page 33](#)
- ♦ [Section 4.5, “Troubleshooting the Text File Policy,” on page 34](#)

4.1 General Troubleshooting Strategies

- ♦ [“The new policy is not enforced on the device after multiple refreshes” on page 29](#)
- ♦ [“The updated policy is not being enforced on the device after multiple refreshes” on page 31](#)
- ♦ [“A new policy is not enforced following an immediate manual refresh after policy assignment” on page 31](#)
- ♦ [“The assigned policies are enforced but applications do not reflect the specified behavior” on page 31](#)
- ♦ [“The policy is not displayed in the Effective Policies list” on page 31](#)

The new policy is not enforced on the device after multiple refreshes

Source: ZENworks Linux Management; Policy Handlers

Possible Cause: The policy does not display in the effective policies list of the device.

Action: In the policy Summary page, assign the policy to the device by using Assignment section.

Possible Cause: The minimum system requirements for the policy to be enforced on the device are not met.

Action: Ensure that the minimum system requirement for the policy to be enforced on the managed device are met.

Possible Cause: The policy enforcement schedule is not set.

Action: For the Text File and Remote Execute policies, verify that the schedule to enforce a policy has been set.

Action: For GNOME-based policies, verify that the User Login event has occurred by viewing the `/var/opt/novell/log/zenworks/zmd-messages.log` file.

Possible Cause: For policies other than Remote Execute and Text File, there might be more than one policy of the same type associated with the device.

Action: Define all your settings only in one policy and associate it to the device.

Possible Cause: The policy was not refreshed on the device.

Action: Perform the following:

- 1 If you have recently assigned the policy to the managed device, wait for a few minutes to see if the policy is simply slow in being enforced.
- 2 If it is not enforced within a few minutes, on the ZENworks Control Center, go to the Devices page and select the device where you have assigned a policy.
- 3 In the Action menu, select Refresh Device.
- 4 On the managed device, open the file `/var/opt/novell/zenworks/cache/zmd/PolicyManager/Policies.xml`.
- 5 Search for the policy you have defined by using its name as the search string.
- 6 Refresh the device multiple times.

Possible Cause: You have not logged in through the user interface login on the device.

Explanation: If the policy is set to run on User Login, a user for whom the policy has not applied should log in by using the user interface on the device.

Action: Make sure that you log in through the user interface and verify the policy status again.

Possible Cause: The window manager is not GDM and KDM.

Action: By default, GConf-based policies support GDM, KDM, or XDM display managers. If you want your existing Display Manager to change to GDM, KDM, or XDM:

If you are using the Novell Linux Desktop or SUSE® Linux and you want to change to GDM, KDM, or XDM:

- 1 Edit the `/etc/sysconfig/displaymanager` file as follows:

```
DISPLAYMANAGER=<<GDM, KDM, or XDM>>
```

For more details, refer to the [GNOME Documentation \(http://www.gnome.org/projects/gdm/docs.html\)](http://www.gnome.org/projects/gdm/docs.html)

- 2 Edit the `/usr/X11R6/bin/gnome` file and add the following to the beginning of the file:

```
/opt/novell/zenworks/bin/checkEnforcement
```

If you are using Red Hat* and you want to change to GDM, KDM, or XDM:

- 1 Edit the `/etc/sysconfig/desktop` file as follows:

```
DISPLAYMANAGER=<<GDM, KDM, or XDM>>
```

- 2 Edit the `/etc/X11/xdm/Xsession` file and add the following to the beginning of the file:

```
/opt/novell/zenworks/bin/checkEnforcement
```

NOTE: If you do not want to use the GDM, KDM, or XDM Display Manager, you must manually make changes in the configuration file. This delays the

start of the desktop session and allows the enforcement of Gconf-based policies to be completed. To do this, you must create a file similar to `/usr/X11R6/bin/gnome` (on SuSE/NLD) or `/etc/X11/xdm/Xsession` (on Red Hat). These files must satisfy the following conditions:

- ♦ A user without the administrator privilege should not be able to edit the file.
- ♦ The file should be invoked every time a user logs in using the GUI

Add the following to the beginning of the file:

```
/opt/novell/zenworks/bin/checkEnforcement
```

The updated policy is not being enforced on the device after multiple refreshes

Source: ZENworks Linux Management; Policy Handlers

Possible Cause: The Revision number of the policy was not incremented.

Action: To increment the revision number:

- 1 In ZENworks Control Center, click *Policies*.
- 2 Click the policy for which you want to increment the revision number.
- 3 On the *Summary* page, increment the revision number and refresh the device.

To check the version of the policy available in the Cache:

- 1 Open the `/var/opt/novell/zenworks/cache/zmd/PolicyManager/Policies.xml` file.
- 2 Search for the policy name. The version should be listed in between `<Version>` `</Version>`.

A new policy is not enforced following an immediate manual refresh after policy assignment

Source: ZENworks Linux Management; Policy Handlers

Possible Cause: The synchronization between a policy and the managed device might have been delayed.

Action: Wait for 5 minutes before manually refreshing after you update or assign a policy to the managed device.

The assigned policies are enforced but applications do not reflect the specified behavior

Source: ZENworks Linux Management; Policy Handlers

Possible Cause: The desktop session has started before enforcement was complete.

Action: Log out and log in from the managed device where the policy has been enforced.

The policy is not displayed in the Effective Policies list

Source: ZENworks Linux Management; Policy Handlers

Possible Cause: A schedule is not specified on the Policy Schedule page.

Action: Define a schedule:

- 1 In the ZENworks Control Center, click *Policies*.
- 2 Click the policy for which you want to define a schedule.
- 3 On the *Summary* page, click *Advanced* in the *Assignments* section.
- 4 In the *Edit Schedule* dialog box, specify an appropriate schedule, then click *OK*.

The schedule is defined for the policy you have selected.

4.2 Troubleshooting the Epiphany Policy

- ♦ “Unable to find the downloaded file even after enforcing the Epiphany policy” on page 32

Unable to find the downloaded file even after enforcing the Epiphany policy

Source: ZENworks Linux Management; Policy Handlers

Possible Cause: You might have provided an incorrect path or you might not have the necessary rights to write to the directory.

Action: Perform the following:

- 1 Ensure that users have Read, Write, and Execute rights to the download directory.
- 2 If the absolute path is not specified in the download folder, specify only the directory name.

A directory with this name is created in user's home directory and all downloaded files are saved in that directory.

4.3 Troubleshooting the Generic GNOME Policy

- ♦ “The Generic GNOME policy is not being enforced for some applications” on page 32
- ♦ “The warning is logged even if the distribution system requirements are met” on page 33
- ♦ “GNOME-based policies might not be enforced” on page 33

The Generic GNOME policy is not being enforced for some applications

Source: ZENworks Linux Management; Policy Handlers; Generic GNOME Policy

Explanation: The Generic GNOME policy defines setting for many applications. Not all the applications reflect the settings that are defined in the policy.

Possible Cause: The applications that do not reflect the policy settings might not be working properly with GConf.

Action: To check if the problem is with the application and not with the ZENworks Linux Management, perform the following:

- 1 Open the GConf Editor.
- 2 Navigate to the settings that you have configured.

3 Select the setting you have defined.

If the GConf Editor displays that this value cannot be changed, the policy is enforced appropriately. The problem might be with the application. Refer to the application documentation to resolve the issue.

If the GConf Editor displays that this value can be changed, see [“The new policy is not enforced on the device after multiple refreshes” on page 29](#)

Possible Cause: The application is started before the policy settings are enforced.

Action: Restart the application.

The warning is logged even if the distribution system requirements are met

Source: ZENworks Linux Management; Policy Handlers; Generic GNOME Policy

Possible Cause: After the settings are imported from the managed device, the system requirements might have changed or removed before the policy was applied on the managed device.

Action: If the settings in the policy are not distribution dependent, ignore the warning.

If the policy is distribution dependent, add or modify system requirements on the Details page of the policy.

GNOME-based policies might not be enforced

Source: ZENworks Linux Management; Policy Handlers; Generic GNOME Policy

Explanation: GNOME-based policies such as Epiphany*, Evolution*, Firefox*, Generic GNOME*, Novell Linux Desktop, and SUSE® Linux Enterprise Desktop might not be enforced.

Action: Log in as an administrator and remove all the hidden files (file names starts with '.') with .status.completed extension from the HOME directory of the user, for whom the policy enforcement is not working. The policy is enforced for the same user on subsequent logins.

4.4 Troubleshooting the Remote Execute Policy

- ♦ [“An error occurs while executing a given script, binary, or Java program” on page 33](#)
- ♦ [“Policy enforcement does not give the status of the launched program” on page 34](#)

An error occurs while executing a given script, binary, or Java program

Source: ZENworks Linux Management; Policy Handlers; Remote Execute Policy

Possible Cause: The input parameters given in the policy are incorrect.

Action: If you have not defined your own script:

1 Combine the inputs for the following fields as one line in the policy:

```
InterpreterName InterpreterParameters ProgramName  
ProgramParameters
```

2 On the managed device, execute the above statement from the command line.

- 3 If there is an error, give the correct parameters for InterpreterName, InterpreterParameters, ProgramName, and ProgramParameters.

If you have defined your Own Script, perform the following:

- 1 On the managed device, create a file containing the script you have specified in the policy.
- 2 Execute the script file from the command line.
- 3 If there is an error, give the correct parameters for InterpreterName, InterpreterParameters, ProgramName, and ProgramParameters.
- 4 Copy the correct script to the policy.

Possible Cause: In the Binary or Java executable type, shell or redirection operators are specified in the parameters.

Action: If you want to use shell or redirection operators with a Binary or Java executable, perform the following:

- 1 On the Remote Execute policy page, select Script as the Executable type.
- 2 In Script to Run field, select Define Your Own Script.
- 3 Combine the inputs for the following fields as one line in the policy:
InterpreterName InterpreterParameters ProgramName
ProgramParameters

Policy enforcement does not give the status of the launched program

Source: ZENworks Linux Management; Policy Handlers; Remote Execute Policy

Possible Cause: The Maximum Waiting Time setting might not have the right value.

Action: On the Remote Execute policy page, in the Maximum Time to Wait field, select Wait Till the Program Completes the Execution.

4.5 Troubleshooting the Text File Policy

- ♦ [“The Text File policy is not enforced” on page 34](#)
- ♦ [“Unable to find the backup file after the Text File policy has modified the file” on page 35](#)
- ♦ [“Text File policy enforcement failed because of an error, but the file still appears modified or some unknown files appear in the same directory as the file” on page 35](#)
- ♦ [“How to ensure that the post-change action has been successful when the Text File policy was enforced” on page 36](#)

The Text File policy is not enforced

Source: ZENworks Linux Management; Policy Handlers; Text File Policy

Possible Cause: Policy Enforcement might have failed.

Action: Ensure that the policy has been enforced correctly by checking the Event Log of the policy or of the managed device.

Possible Cause: The search string was not found in the file.

Action: Verify that the Additional Info field in a log message contains a list of changes that were not performed. Ensure that the search string specified in the changes which were not done is found in the file.

Possible Cause: The pre-change action that is specified in the policy failed and the Action When the Execution Fails field was set to Do Not Modify the Text File.

Action: Ensure that the pre-change action does not fail.

Unable to find the backup file after the Text File policy has modified the file

Source: ZENworks Linux Management; Policy Handlers; Text File Policy

Possible Cause: There was an error while creating the backup of the modified file.

Action: Perform the following:

- 1 Verify the value of the backup exit code in the message that is logged after policy was enforced.
- 2 If the exit code is 1, it indicates that there was an error while taking the backup. Check the Additional Information field of the message to get more information on the error that is occurred.

Possible Cause: You might not be looking at the correct location of the backup.

Action: Perform the following:

- 1 Verify the value of the backup exit code in the message that is logged after policy was enforced.
- 2 If the exit code is 0, it indicates that the backup was taken successfully. Check to see if the backup file is in the same directory as the modified file.

Text File policy enforcement failed because of an error, but the file still appears modified or some unknown files appear in the same directory as the file

Source: ZENworks Linux Management; Policy Handlers; Text File Policy

Possible Cause: When the text file enforcement failed, there was also an error while rolling back the changes in the files being modified.

Action: Perform the following:

- 1 Verify the value of the rollback exit code in the logged error message.
- 2 If the exit code is 1, it indicates that there was an error while rolling back the changes. Check the Additional Information field of the message to get more information the error that occurred during rollback.

Possible Cause: There might be another Text File policy that modifies the same file.

Action: Perform the following:

- 1 Verify the value of rollback exit code in the logged error message.
- 2 If the exit code is 0, it indicates that the rollback was done successfully. Check to see if there is another Text File policy that modifies the same file.

- 3 If the exit code is -1, it indicates that the rollback operation was not done because the file was not modified. Check to see if there is another Text File policy that modifies the same file.

How to ensure that the post-change action has been successful when the Text File policy was enforced

Source: ZENworks Linux Management; Policy Handlers; Text File Policy

Action: Verify the value of the post-change action exit code in the message that was logged after policy was enforced. This value is the exit code, which was returned by the program or script launched in the post-change action.

Event Monitoring



If the Event Monitoring component of Novell® ZENworks® Linux Management displays an error message or if specific instructions for an error message are not available, you can try the more general troubleshooting strategies to resolve the problem.

This section contains the following topic:

- ◆ [Chapter 5, “Event Monitoring Troubleshooting Strategies,” on page 39](#)

Event Monitoring Troubleshooting Strategies

5

This section provides solutions to problems you might encounter when using Novell® ZENworks® Linux Management Event Monitoring component.

5.1 Troubleshooting Event Monitoring

- ♦ “Changing the severity level for a local log from the Centralized Message Logging setting in Novell Control Center is not taking effect” on page 39
- ♦ “SMTP mail is not working for the GMail server” on page 39
- ♦ “Unable to send e-mail to the specified e-mail address” on page 39
- ♦ “I am receiving unknown traps on the trap console” on page 40
- ♦ “Unable to send the traps to the trap console” on page 40

Changing the severity level for a local log from the Centralized Message Logging setting in Novell Control Center is not taking effect

Severity: ZENworks Linux Management; Event Monitoring

Possible Cause: The Debug and Above message severity set using the command line interface takes precedence over the severity defined using the Centralized Message Logging user interface.

Action: Turn off the Debug and Above severity from command line interface using the following command:

```
set debug-level off
```

SMTP mail is not working for the GMail server

Severity: ZENworks Linux Management; Event Monitoring

Possible Cause: The Event Monitoring component of ZENworks 7.2 Linux Management does not support SMTP on a Transport Layer Security (TLS) server.

Action: For the GMail server, use only SMTP and Secure SMTP servers.

Unable to send e-mail to the specified e-mail address

Severity: ZENworks Linux Management; Event Monitoring

Possible Cause: You might have defined filters or relays on the SMTP server.

Action: Clear the filters or relay that you have defined that block the SMTP packets from the ZENworks 7.2 Linux Management server.

Possible Cause: The authentication information you have provided in the E-mail Notification section of the Centralized Message Logging page is not correct.

Action: Ensure that the username and password you have specified are correct.

I am receiving unknown traps on the trap console

Severity: ZENworks Linux Management; Event Monitoring

Possible Cause: The `messagelogger.mib` file is not compiled on the server.

Action: Compile the `messagelogger.mib` file located at `/opt/novell/zenworks/share/messagelogger`.

For example, if you want to compile `messagelogger.mib` on the Management and Monitoring Services console of ZENworks 7 Server Management, do the following:

- 1 Right-click the ConsoleOne® Site Serve object, then click *Properties*.
- 2 In Properties of *name of the Site Server* dialog box, select the *MIB Pool* page.
- 3 Click *Modify Pool*.
- 4 In the *Add/Remove MIBs* dialog box, click *Add*, then select the MIB that needs to be compiled.
- 5 Click *Compile*.

Unable to send the traps to the trap console

Severity: ZENworks Linux Management; Event Monitoring

Possible Cause: You might have defined filters on the trap console.

Action: Clear the filters you have defined that block the traps generated from ZENworks 7.2 Linux Management server.

Possible Cause: The port number you have specified is not correct.

Action: To specify the correct port number:

- 1 In the ZENworks Control Center, click *Configuration*.
- 2 In *Management Zone Settings*, click *Centralized Message Logging*.
- 3 Specify the correct SNMP port number of the trap console in the *SNMP Trap* section.

Inventory

IV

If the Inventory component of Novell® ZENworks® Linux Management displays an error message, you can look it up in the Error Messages section. If a problem is not accompanied by an error message or if specific instructions for an error message are not available, you can try more general troubleshooting strategies to resolve the problem.

This section contains the following topics:

- ◆ [Chapter 6, “Inventory Roll-Up Error Messages,” on page 43](#)
- ◆ [Chapter 7, “Inventory Troubleshooting Strategies,” on page 47](#)

Inventory Roll-Up Error Messages

6

This section contains detailed explanations of the error messages you might encounter using the Inventory Roll-Up component of Novell® ZENworks® Linux Management.

- ◆ “Incorrect input for the time interval between roll-ups” on page 43
- ◆ “DNS name not found. Will exit now.” on page 43
- ◆ “The IP address of destination Inventory server has not been configured in the Inventory Roll-Up Configuration page” on page 44
- ◆ “The time interval between inventory roll-ups has not been set. By default, the time interval is set for 7 days.” on page 44
- ◆ “filename is deleted as it is older than RollupInitTime” on page 44
- ◆ “Unable to get zeninvRollupTime from the destination inventory server” on page 44
- ◆ “Unable to initiate the file transfer” on page 44
- ◆ “Unable to rename the filename.str file” on page 45
- ◆ “Error while creating inner zip file” on page 45
- ◆ “Sanity check for prp file filename failed. The file may be corrupt” on page 45
- ◆ “The name format of the filename str file is incorrect” on page 45
- ◆ “Could not get service DN from the prp file” on page 46
- ◆ “Unable to retrieve the server name from prp file” on page 46
- ◆ “Unable to procure/retrieve the schedule time from prp file” on page 46
- ◆ “Irrecoverable internal error: error_message. State machine crashed” on page 46
- ◆ “Compression error while compressing and deleting str files” on page 46
- ◆ “The conversion of Deviceinfo to STR format has failed” on page 46
- ◆ “Datamodel Exception occurred while extracting devices from the Inventory database” on page 46
- ◆ “An exception occurred while writing to an STR file” on page 46

Incorrect input for the time interval between roll-ups

Source: ZENworks 7.2 Linux Management; Inventory Roll-Up

Severity: Informational

Action: Specify a valid value in hours. If you do not specify a value, the Inventory Roll-up component takes the default time interval (168 hrs).

DNS name not found. Will exit now.

Source: ZENworks 7.2 Linux Management; Inventory Roll-Up

Severity: Critical

Possible Cause: Unable to get the DNS name of the local machine.

Action: Ensure that the local machine has a valid DNS name.

The IP address of destination Inventory server has not been configured in the Inventory Roll-Up Configuration page

Source: ZENworks 7.2 Linux Management; Inventory Roll-Up

Severity: Informational

Action: To enable the roll-up:

- 1 In the ZENworks Control Center, click *Configuration*.
- 2 In the *Management Zone Settings* pane, click the *Device Inventory* category.
- 3 In the *Inventory Roll-Up Settings* pane, specify the IP address of the destination server.
- 4 Click *Apply*, then click *OK*.

The time interval between inventory roll-ups has not been set. By default, the time interval is set for 7 days.

Source: ZENworks 7.2 Linux Management; Inventory Roll-Up

Severity: Informational

***filename* is deleted as it is older than RollupInitTime**

Source: ZENworks 7.2 Linux Management; Inventory Roll-Up

Severity: Informational

Explanation: Based on the Discard Scan Data Time in the Inventory Service object properties of the Receiver, the Sender deletes the compressed .zip files in the entpushdir directory that have been created earlier than the specified discard scan data time.

Unable to get zeninvRollupTime from the destination inventory server

Source: ZENworks 7.2 Linux Management; Inventory Roll-Up

Severity: Critical

Action: Ensure that the ZENworks Web Server is running on the ZENworks Server Management or the ZENworks Desktop Management destination Inventory server.

Action: On the destination Inventory server, start the Receiver from the Service Manager.

Action: If the Sender fails to connect to the Receiver even after the retries, contact [Novell Support \(http://support.novell.com\)](http://support.novell.com).

Action: Ensure that the network connection between the ZENworks Linux Management server and the ZENworks Desktop Management or ZENworks Server Management server is working.

Unable to initiate the file transfer

Source: ZENworks 7.2 Linux Management; Inventory Roll-Up

Severity: Critical

Action: Ensure that the ZENworks Web Server is running on the ZENworks Server Management or the ZENworks Desktop Management destination Inventory server.

Action: On the destination Inventory server, start the Receiver from the Service Manager.

Action: If the Sender fails to connect to the Receiver even after the retries, contact [Novell Support \(http://support.novell.com\)](http://support.novell.com).

Action: Ensure that the network connection between the ZENworks Linux Management server and the ZENworks Desktop Management or ZENworks Server Management server is working.

Unable to rename the *filename.str* file

Source: ZENworks 7.2 Linux Management; Inventory Roll-Up

Severity: Critical

Explanation: The str files in the entmerge directory cannot be transferred to entpushdir.

Action: Ensure that the entmerge directory exists.

Action: Ensure that you have rights to transfer the str files to the entpushdir directory.

Error while creating inner zip file

Source: ZENworks 7.2 Linux Management; Inventory Roll-Up

Severity: Critical

Possible Cause: The disk on the Inventory server is full.

Action: Ensure that there is free disk space on the server.

Possible Cause: The directory containing the .str files does not exist.

Action: Ensure that the directory exists on the Inventory server.

Possible Cause: There is no Read and Write access to the files in the directory.

Action: Ensure that the directory has Read and Write access for the files in the directory.

Sanity check for prp file *filename* failed. The file may be corrupt

Source: ZENworks 7.2 Linux Management; Inventory Roll-Up

Severity: Critical

Action: Contact [Novell Support \(http://support.novell.com\)](http://support.novell.com).

The name format of the *filename* str file is incorrect

Source: ZENworks 7.2 Linux Management; Inventory Roll-Up

Severity: Critical

Action: Contact [Novell Support \(http://support.novell.com\)](http://support.novell.com).

Could not get service DN from the prp file

Source: ZENworks 7.2 Linux Management; Inventory Roll-Up
Severity: Critical
Action: Contact [Novell Support \(http://support.novell.com\)](http://support.novell.com).

Unable to retrieve the server name from prp file

Source: ZENworks 7.2 Linux Management; Inventory Roll-Up
Severity: Critical
Action: Contact [Novell Support \(http://support.novell.com\)](http://support.novell.com).

Unable to procure/retrieve the schedule time from prp file

Source: ZENworks 7.2 Linux Management; Inventory Roll-Up
Severity: Informational
Action: Contact [Novell Support \(http://support.novell.com\)](http://support.novell.com).

Irrecoverable internal error: *error_message*. State machine crashed

Source: ZENworks 7.2 Linux Management; Inventory Roll-Up
Severity: Critical
Action: Contact [Novell Support \(http://support.novell.com\)](http://support.novell.com).

Compression error while compressing and deleting str files

Source: ZENworks 7.2 Linux Management; Inventory Roll-Up
Severity: Critical
Action: Contact [Novell Support \(http://support.novell.com\)](http://support.novell.com).

The conversion of Deviceinfo to STR format has failed

Source: ZENworks 7.2 Linux Management; Inventory Roll-Up
Severity: Critical
Action: Contact [Novell Support \(http://support.novell.com\)](http://support.novell.com).

Datamodel Exception occurred while extracting devices from the Inventory database

Source: ZENworks 7.2 Linux Management; Inventory Roll-Up
Severity: Critical
Action: Contact [Novell Support \(http://support.novell.com\)](http://support.novell.com).

An exception occurred while writing to an STR file

Source: ZENworks 7.2 Linux Management; Inventory Roll-Up
Severity: Critical
Action: Contact [Novell Support \(http://support.novell.com\)](http://support.novell.com).

Inventory Troubleshooting Strategies

7

This section provides solutions to problems you might encounter when using the Inventory Roll-Up component of Novell® ZENworks® 7 Linux Management.

- ♦ [Section 7.1, “Troubleshooting Inventory Roll-Up,” on page 47](#)
- ♦ [Section 7.2, “Troubleshooting Hardware Inventory,” on page 48](#)

7.1 Troubleshooting Inventory Roll-Up

- ♦ [“Inventory Roll-up fails to roll up the inventory data” on page 47](#)

Inventory Roll-up fails to roll up the inventory data

Source: ZENworks 7.2 Linux Management; Inventory Roll-Up

Possible Cause: The IP address or the DNS name of the destination server is incorrect.

Action: Ensure that the correct IP address or the DNS name of the destination server has been configured in the Inventory Roll-Up settings pane of the ZENworks Control Center.

Possible Cause: The Receiver might not be running on the destination Inventory server of ZENworks Server Management or ZENworks Desktop Management.

Action: On the destination Inventory server, start the Receiver from the Service Manager.

Action: If the Sender fails to connect to the Receiver even after the retries, contact [Novell Support \(http://support.novell.com\)](http://support.novell.com).

Possible Cause: The ZENworks Web Server is not running on the ZENworks Server Management or the ZENworks Desktop Management destination Inventory server.

Action: Ensure that the ZENworks Web Server is running on the ZENworks Server Management or the ZENworks Desktop Management destination Inventory server.

Possible Cause: The network connection between the ZENworks Linux Management server and the ZENworks Desktop Management or ZENworks Server Management server is not working.

Action: Ensure that the network connection between the ZENworks Linux Management server and the ZENworks Desktop Management or ZENworks Server Management server is working.

Possible Cause: The ZENworks 7.2 Linux Management database is not running.

Action: Ensure that the ZENworks 7.2 Linux Management database is up and running.

7.2 Troubleshooting Hardware Inventory

- ♦ “inventory-scanner-option can be set to an invalid value on the managed device” on page 48
- ♦ “Hardware Inventory of the registered devices is not updated successfully to the server” on page 48
- ♦ “How do I control the interval of hardware inventory update to the server?” on page 49
- ♦ “How do I control the probing of hardware information of specific component on managed device?” on page 49
- ♦ “How to control delayed schedules for updating inventory on the ZENworks Linux Management server?” on page 49

inventory-scanner-option can be set to an invalid value on the managed device

Source: ZENworks Linux Management; Inventory

Explanation: The `inventory-scanner-option` is passed to the hardware scanner 'hwinfo' to control the probing of certain hardware component. typically used for problematic or unsupported hardware. The default value is `-braille`.

This option does not uniformly controls probing of all hardware components under hwinfo. The `inventory-scanner-option` can be set to an invalid value.

Hardware Inventory of the registered devices is not updated successfully to the server

Source: ZENworks Linux Management; Inventory

Action: Do the following:

- ♦ Ensure that the Inventory module is loaded by executing the `rug ping` command. If the module is loaded, the `zmd-messages.log` file contains the following message:

```
INFO ModuleLoader Loaded 'Inventory' - 'Software and Hardware inventory module for Linux'
```
- ♦ Execute the `hwinfo --all > hwinventory.log` command, and check the log file to ensure that the Inventory Scanner runs successfully on the managed device.
- ♦ Ensure that the `hardware-inventory-enabled zmd` setting is set to `true`.
- ♦ Execute the `rug sch` command to verify the current Hardware Inventory refresh schedule.

The Hardware inventory on the device is collected and updated based on this schedule. If a new refresh schedule is not added, do the following:

- a. Use `rug sl` to check if the managed device is successfully registered to the server, and is active.
- b. Stop and start the ZENworks agent service, `/etc/init.d/novell-zmd`, and verify that the new schedule is now added.

- ◆ Ensure that the hardware inventory is collected and sent successfully from the managed device.
 - ◆ Set the following zmd options: `log-soap-xml` to `true` and `log-level` to `debug` to procure the logged SOAP messages when hardware inventory module service runs.
 - ◆ Examine the debug log messages, `zmd-messages.log`, and search for "HardwareInventoryCapability" as per timestamp. The following messages are logged when delay schedule for hardware inventory is triggered:


```
DEBUG HardwareInventoryCapability Starting to
send hardware inventory
(SOAP packets here)
DEBUG HardwareInventoryCapability Done sending
hardware inventory
```

 This indicate that the hardware inventory of the managed device is now updated to the ZENworks server.

How do I control the interval of hardware inventory update to the server?

Source: ZENworks Linux Management; Inventory

Action: Do the following:

- ◆ Change the `refresh-interval-hardware` zmd setting to the desired value in seconds.

A new hardware inventory refresh schedule is created for the registered device.

- ◆ (Optional) Reset the `delay` zmd setting to send hardware inventory within new 'delay' interval.

The random delayed schedule "Hardware Inventory delay" is added when the refresh schedule triggers to update the Hardware Inventory. The default 'delay' value is 900. All inventory delayed schedules are affected by changing the zmd setting 'delay'.

How do I control the probing of hardware information of specific component on managed device?

Source: ZENworks Linux Management; Inventory

Action: Change the `inventory-scanner-options` zmd setting to a particular hardware component. This option is passed to the hardware scanner, 'hwinfo -all', to control the probing of specific hardware components.

For example, `hwprobe=inventory-scanner-options hwinfo --all`.

For more information, see the hwinfo readme located in `/usr/share/doc/packages/hwinfo`.

How to control delayed schedules for updating inventory on the ZENworks Linux Management server?

Source: ZENworks Linux Management; Inventory

Action: The inventory delayed schedules for a registered device is affected when you change the zmd setting, delay. The default value is 900. The random delayed schedules to update inventory at the server are created using the delay setting. The new delay settings affect the next random delayed schedule only after the next refresh schedule.

All delayed schedules for inventory are added during the device registration and subsequently, when refresh schedules are triggered. The “Software Inventory delay” schedule is added to update inventory when packages are installed or removed on a client.

Disaster Recovery



If the Disaster Recovery component of Novell® ZENworks® Linux Management displays an error message, you can look it up in the Error Messages section. If a problem is not accompanied by an error message or if specific instructions for an error message are not available, you can try more general troubleshooting strategies to resolve the problem.

This section contains the following topics:

- ♦ [Chapter 8, “Disaster Recovery,” on page 53](#)
- ♦ [Chapter 9, “Disaster Recovery Error Messages,” on page 59](#)

This section explains how to restore a Novell® ZENworks® Linux Management system after the failure of a ZENworks Primary Server.

Restoration consists of the following:

1. Converting a ZENworks Secondary Server with an eDirectory read/write replica to a ZENworks Primary Server.
2. Moving all the devices that were managed by the old ZENworks Primary Server to the new ZENworks Primary Server. For more information, see “[Registering Devices](#)” in the *Novell ZENworks 7.2 Linux Management Administration Guide*.

The following sections provide additional information:

- ◆ [Section 8.1, “Safeguarding Your System through Backups,”](#) on page 53
- ◆ [Section 8.2, “Safeguarding Your System through Server Configuration,”](#) on page 54
- ◆ [Section 8.3, “Restoring Your System after a Primary Server Failure,”](#) on page 55
- ◆ [Section 8.4, “Moving Devices to the New Primary Server,”](#) on page 57

8.1 Safeguarding Your System through Backups

To restore your ZENworks Linux Management environment if the ZENworks Primary Server fails, you need backups of the Data Store, the Object Store, the package repository, and the zlmmirror configuration files.

8.1.1 The Data Store

ZENworks Linux Management supports both PostgreSQL and Oracle* databases as the ZENworks Data Store; both engines provide backup mechanisms that should be implemented. For information on backing up and restoring the Data Store, see “[ZENworks Database Maintenance](#)” in the *Novell ZENworks 7.2 Linux Management Administration Guide*.

8.1.2 The Object Store

The ZENworks Object Store is Novell eDirectory 8.7.3. For information on backing up and restoring the ZENworks Object Store, see “[ZENworks Database Maintenance](#)” in the *Novell ZENworks 7.2 Linux Management Administration Guide*.

8.1.3 The Package Repository

The package repository is the `/var/opt/novell/zenworks/pkg-repo` directory on the ZENworks Primary Server. You need to make a periodic backup of this directory. For more information on package management, see “[Package and Content Management](#)” in the *Novell ZENworks 7.2 Linux Management Administration Guide*.

8.1.4 The zlmirror Configuration Files

If zlmirror has been configured, you should back up the zlmirror configuration files that the administrator has created. Because the names of the configuration files for zlmirror and their locations are determined by the administrator, it is the administrator's responsibility to keep them backed up. For more information on zlmirror, see “[Mirroring Software](#)” in the *Novell ZENworks 7.2 Linux Management Administration Guide*.

8.2 Safeguarding Your System through Server Configuration

When ZENworks Linux Management is installed, a Management Zone is created. The Zone is managed by a group of ZENworks servers; the first server is the ZENworks Primary Server and the others are ZENworks Secondary Servers. The Management Zone is highly dependent on the availability of the Data Store and the Object Store to function properly. Thus, it becomes important to understand how to configure your environment to provide fault tolerance and higher availability.

8.2.1 Data Store

The ZENworks Linux Management software provides an option to install the Data Store locally onto the ZENworks Primary Server. This option is generally sufficient in an environment where fault tolerance is not required. However, if the ZENworks Primary Server is lost, all of the data is lost unless there is a backup of the Data Store prior to the disaster. When the primary server fails, ZENworks Secondary Servers lose connectivity to the Data Store, which causes much of the data in the ZENworks Control Center to become unreadable. The ZENworks Linux Management system continues to function, but no data is recorded.

To provide fault tolerance, we recommend locating the Data Store on a machine that is remote from the ZENworks Primary and Secondary Servers. The ZENworks Linux Management software provides an option to install to a remote PostgreSQL or Oracle database. In this case, when the ZENworks Primary Server is lost, the secondary servers continue to have access to the Data Store.

8.2.2 Object Store

The ZENworks Object Store is Novell eDirectory 8.7.3. The ZENworks Primary Server holds a master replica of the Object Store and the next two consecutive ZENworks Secondary Servers installed in the Management Zone hold a read/write replica of the Object Store. The rest of the secondary servers do not hold a replica of the Object Store.

When the ZENworks Primary Server is disconnected, removed for maintenance, or otherwise lost, the ZENworks Secondary Servers with the read/write replicas act as a live backup of the ZENworks Object Store to the other ZENworks Secondary Servers that have no replica. By default, secondary servers with no replica go through the primary server to obtain Object Store information; as a temporary solution, eDirectory on those secondary servers might need to be restarted to provide functionality while the primary server is out. zlmirror and content replication are functions of the primary server, so those services remain interrupted until the primary server is brought back up.

If the primary server is lost, the master replica of the Object Store is also lost. This situation is remedied by converting one of the two secondary servers with a read/write replica of the Object Store to a primary server, then by creating another read/write replica on another secondary server.

8.2.3 Package Repository

Creation of bundles or packages either manually or through `zlmirror` or content replication are all functions that are performed through the ZENworks Primary Server.

When the ZENworks Primary Server is disconnected, removed for maintenance, or otherwise lost, bundles and packages cannot be created on the ZENworks Primary Server or replicated to ZENworks Secondary Servers. Existing assignment of replicated bundles and packages remains available to devices registered to ZENworks Secondary Servers. New assignments of replicated bundles and packages can also be made to those devices. However, new assignments of non-replicated bundles and packages, although they can be made, fail to distribute until the bundles and packages have been replicated to the ZENworks Secondary Server to which the device is registered.

If `zlmirror` has been configured in the environment and content replication has taken place, the package repository on the ZENworks Primary Server is replicated onto all ZENworks Secondary Servers. Information about the new bundles and packages is also written to the Data Store. Therefore, when the ZENworks Primary Server is lost and a ZENworks Secondary Server is converted into a new ZENworks Primary Server, the bundles and packages from the `zlmirror` operation would already be local to the new ZENworks Primary Server; all that is necessary is to re-create or restore the `zlmirror` configuration files onto the new ZENworks Primary Server.

If `zlmirror` has been configured in the environment but no content replication has taken place when the ZENworks Primary Server is lost, the `zlmirror` operation causes new bundles and packages to be downloaded locally onto the ZENworks Primary Server and their information to be written into the Data Store. When a ZENworks Secondary Server is converted into a new ZENworks Primary Server, the package repository on the new primary server is out of sync with the Data Store. Because the package repository is out of sync with the Data Store, content replication and `zlmirror` will fail. Unless you have a backup of these bundles and packages, their information must be removed from the database. This operation also causes any user-created packages to be lost.

8.2.4 Message Logger

The Message Logger continues to function normally regardless of which servers are down. But if the Data Store is local to the primary server and the primary server is down, no database logging occurs until a new Data Store is restored to the environment. Additionally, if the Data Store is down, the conversion does not function properly. For more information on the Message Logger, see “[Message Logger](#)” in the *Novell ZENworks 7.2 Linux Management Administration Guide*.

8.3 Restoring Your System after a Primary Server Failure

Before starting the process of converting a secondary server to a primary server, all the secondary servers that don't have a read/write replica of the ZENworks Object Store need to have eDirectory restarted. When it is restarted, eDirectory recognizes that the primary server is lost and no longer tries to communicate with it. To restart eDirectory:

- 1 Type `etc/init.d/nds restart` on each secondary server that doesn't have a read/write replica of eDirectory.

8.3.1 Converting a Secondary Server to a Primary Server

To convert a ZENworks Secondary Server to a ZENworks Primary Server:

- 1** Choose a secondary server with a read/write replica to be the new primary server and change the ZENworks Object Store replica on that server to be the master replica by typing `ndsrepair -P -Ad`.
- 2** On all the secondary servers, copy `var/opt/novell/zenworks/zfs/pds/security/csr/*.csr` to `var/opt/novell/zenworks/zfs/pds/security/*.cer`.
- 3** From within the `/opt/novell/convertserver` directory, type `./convertserver` on the server that is being promoted to the primary server, then follow the prompts. You'll need the administrator password.
- 4** If required, restore the ZENworks Data Store (for instructions, see “ZENworks Database Maintenance” in the *Novell ZENworks 7.2 Linux Management Administration Guide*).
- 5** If you want to have all the devices that were using the old primary server, change the address of the old primary server name on the DNS server to that of the new primary server.
- 6** Restore or re-create any `zlmirror` configuration files that existed previously.
- 7** Restore the package and bundle directories if they have been backed up.
- 8** If you haven't done so already, install ConsoleOne® for Linux.
 - 8a** Download the Linux version of ConsoleOne from www.novell.com/download. You are prompted to enter your Novell account username and password. If you don't have a Novell account, use the “create new account” link.
 - 8b** Save the ConsoleOne compressed file to disk and uncompress it.
 - 8c** Run the `cl-install` installation script. Install all the snap-ins.
- 9** Use ConsoleOne to remove the old primary server object from the ZENworks Object Store.
 - 9a** Start ConsoleOne by running the ConsoleOne executable located under `/usr/ConsoleOne/bin`.
 - 9b** Authenticate to eDirectory by clicking the tree icon. You are prompted with a login credential dialog box. Log in to your server with the following information:
 - ◆ Login name: admin
 - ◆ Password: Password from the ZLM install
 - ◆ Tree: IP address of a secondary server that holds a read/write replica of the ZENworks Object Store
 - ◆ Context: system
 - 9b1** Under My World/NDS/.ZONENAME-TREE/system, select your old primary server object. Right-click and select Delete NDS object. Answer Yes.
- 10** After a secondary server has been promoted to be the primary server, a read/write replica of the ZENworks Data Store needs to be created on one of the other secondary servers. Use ConsoleOne to create a new read/write eDirectory partition on one of the secondary servers that has no replica.
 - 10a** In the left pane of ConsoleOne, expand NDS. The new zone name is appended with -TREE.

- 10b** Click the new zone name. Click *View* from the menu, then click *Partition and Replica View*. The servers and their replica types are listed.
- 10c** Select any server. Right-click it and select *Add Replica*.
- 10d** Select a server using the browse button. Navigate to the system container, then click the server object that will be your new read/write replica. Click *OK*.
- 10e** Click *OK* twice.

8.4 Moving Devices to the New Primary Server

After you have set up a new primary server, the devices managed by the old primary server need to be moved to the new primary server. For instructions on how to do that, see “[Registering Devices](#)” in the *Novell ZENworks 7.2 Linux Management Administration Guide*.

Disaster Recovery Error Messages

9

This section contains detailed explanations of the error messages you might encounter using the Novell® ZENworks® Linux Management's Disaster Recovery component:

- ♦ “Error Encountered, Cannot Proceed.” on page 59
- ♦ “Could not authenticate to the eDirectory server. Please check your password.” on page 59

Error Encountered, Cannot Proceed.

Source: ZENworks Linux Management; Disaster Recovery

Severity: Critical

Possible Cause: The `zlm.conf` file that is required to obtain the LDAP connection information does not exist in `/etc/opt/novell/zenworks`.

Action: Ensure that the `zlm.conf` file exists in `/etc/opt/novell/zenworks`.

Possible Cause: The `hibernate.cfg.xml` file that is required to obtain database connection and configuration information does not exist in `/etc/opt/novell/zenworks`.

Action: Ensure that the `hibernate.cfg.xml` file exists in `/etc/opt/novell/zenworks`.

Possible Cause: While copying the password from the `hibernate.cfg.xml` file, you entered an incorrect password to authenticate to the database.

Action: Refer the password that is specified in the `hibernate.cfg.xml` file and ensure that you specify a correct password.

Could not authenticate to the eDirectory server. Please check your password.

Source: ZENworks Linux Management; Disaster Recovery

Severity: Informational

Possible Cause: When you attempted to authenticate to eDirectory™, you might have entered an incorrect password at the shell prompt.

Action: Ensure that you have entered a correct password.

Remote Management

VI

If the Remote Management component of Novell® ZENworks® Linux Management displays an error message, you can look it up in the Error Messages section. If a problem is not accompanied by an error message or if specific instructions for an error message are not available, you can try more general troubleshooting strategies to resolve the problem.

This section contains the following topics:

- ◆ [Chapter 10, “Remote Management Error Messages,” on page 63](#)
- ◆ [Chapter 11, “Remote Management Troubleshooting Strategies,” on page 67](#)
- ◆ [Chapter 12, “Frequently Asked Questions,” on page 71](#)

Remote Management Error Messages

10

This section contains detailed explanations of the error messages you might encounter using the Novell® ZENworks® Linux Management Remote Management component:

- ♦ “Network error:could not connect to server:port number of the Remote Management service” on page 63
- ♦ “Unable to initiate a remote session because the Remote Management settings cannot be read on the Managed device. Contact your ZENworks administrator.” on page 64
- ♦ “Unable to initiate a remote session because the authentication to the X server, which is running on the managed device, could not succeed. Contact your ZENworks administrator.” on page 64
- ♦ “host post is not an RFB Server” on page 64
- ♦ “Unable to initiate a remote session because the Remote Management settings cannot be read on the Managed Device” on page 65

Network error:could not connect to server:port number of the Remote Management service

Source: ZENworks Linux Management; Remote Management

Severity: Informational

Possible Cause: The network firewall of the managed device blocks the required port.

Action: Configure the firewall on the managed device to allow incoming connections for the required port.

For example, to configure the firewall on Novell Linux Desktop:

- 1 In the *System* menu, click *Administrator Settings* to launch YaST.
- 2 In the YaST Control Center, click *Security and Users*.
- 3 In the right pane, click *Firewall*.
- 4 In *Firewall Configuration: Basic Settings*, select the *Internal Interface* according to your preference.
- 5 In *Firewall Configuration: Services*, click *Expert*.
- 6 In the *Edit Additional Services* dialog box, specify the Remote Management port numbers in *Additional TCP Services*, then click *OK*.
- 7 Click *Next*.
- 8 In *Firewall Configuration: Features*, click *Next*.
- 9 In *Firewall Configuration: Logging Options*, click *Next*.
- 10 In the *Save Settings and Activate Firewall* dialog box, click *Continue*.

Possible Cause: The Remote Control service (or Remote Login service) might not be running on the specified port.

Action: Start the Remote Control service (or Remote Login service) on the managed device using the following command:

```
/etc/init.d/xinetd start
```

NOTE: This may start other services enabled under xinetd. Refer xinetd man pages for more details.

Possible Cause: The port number you have specified in the Remote Management dialog box is not correct.

Action: Specify the correct port number in the Remote Management dialog box.

Unable to initiate a remote session because the Remote Management settings cannot be read on the Managed device. Contact your ZENworks administrator.

Source: ZENworks Linux Management; Remote Management

Severity: Important

Possible Cause: Remote Management settings are not available on the managed device.

Action: Do the following:

- 1 In ZENworks Control Center, click *Devices*.
- 2 Click *Servers* or *Workstations*.
- 3 Select the device you want to refresh.
- 4 In *Action* menu, click *Refresh Device*.

Unable to initiate a remote session because the authentication to the X server, which is running on the managed device, could not succeed. Contact your ZENworks administrator.

Source: ZENworks Linux Management; Remote Management

Severity: Informational

Possible Cause: You might have changed the X Server configuration.

Action: Restart the Display Manager.

For example, you can restart the Display Manager as follows:

- 1 Switch to any one of the text consoles by pressing Ctrl + Alt + F1 in your graphical session.
- 2 Change the runlevel of the managed device to 3 by entering the following command at the shell prompt:

```
init 3
```
- 3 Change the runlevel back to 5 by entering the following command at the shell prompt:

```
init 5
```

***host post* is not an RFB Server**

Source: ZENworks Linux Management; Remote Management

Severity: Important

Possible Cause: The Remote Control Service has failed to authenticate to the X server.

Action: Restart the Display Manager.

- 1** Switch to any one of the text consoles by pressing Ctrl + Alt + F1 in your graphical session.
- 2** Change the runlevel of the managed device to 3 by entering the following command at the shell prompt:
`init 3`
- 3** Change the runlevel back to 5 by entering the following command at the shell prompt:
`init 5`

Unable to initiate a remote session because the Remote Management settings cannot be read on the Managed Device

Source: ZENworks Linux Management; Remote Management

Possible Cause: On Linux, the http and https IP addresses are different in the system-wide proxy setting.

Action: Use the same proxy for both http and https.

Remote Management Troubleshooting Strategies

11

This section provides solutions to problems you might encounter when using the Novell® ZENworks® Linux Management Remote Management component:

- ♦ “Multiple Remote Login sessions to the same managed device fail” on page 67
- ♦ “The Remote Management session does not proceed if the managed device is displaying the GNOME logout dialog box” on page 67
- ♦ “The Remote Management Viewer window fails to refresh after multiple Remote Management sessions from the same browser session” on page 68
- ♦ “The Password dialog box loses focus during a Remote Management session” on page 68
- ♦ “Unable to continue with the Remote Control operation because the Remote Management Viewer freezes” on page 68
- ♦ “Authentication to the X Server fails” on page 68
- ♦ “Only a grey screen is displayed while performing a Remote Login session” on page 69

Multiple Remote Login sessions to the same managed device fail

Severity: ZENworks Linux Management; Remote Management

Possible Cause: The limitation on the maximum number of Remote Sessions configured for XDMCP causes this.

Action: Configure the XDMCP settings on the managed device to allow more multiple Remote Sessions to the agent.

For example, if you want to configure XDMCP on GDM display manager:

- 1 Run `gdmsetup` at the shell prompt.
- 2 In Login Screen Setup window, Click *XDMCP*.
- 3 Select the *Maximum Remote Sessions* option.
- 4 Configure XDMCP for the number of remote sessions you want to use simultaneously.

The Remote Management session does not proceed if the managed device is displaying the GNOME logout dialog box

Severity: ZENworks Linux Management; Remote Management

Possible Cause: The GNOME session manager freezes all other processes on the logout dialog box by controlling the X Server.

Action: Start the Remote Management session after the user performs an operation in the dialog box on the managed device.

The Remote Management Viewer window fails to refresh after multiple Remote Management sessions from the same browser session

Severity: ZENworks Linux Management; Remote Management

Action: Clear the browser cache.

To clear the browser cache in the Firefox Web browser:

- 1 In *Tools* menu of the Firefox browser, select *Options*.
- 2 In the right pane, click *Privacy*.
- 3 For Cache, click *Clear*.
- 4 Restart the browser.

To clear the browser cache in the Internet Explorer Web browser:

- 1 In the *Tools* menu of the Internet Explorer browser, select *Internet Options*.
- 2 In the *General* page, click *Delete Files* in the *Temporary Internet Files* section.
- 3 Restart the browser.

The Password dialog box loses focus during a Remote Management session

Severity: ZENworks Linux Management; Remote Management

Explanation: If you launch the ZENworks Control Center using Firefox and establish a Remote Management session, sometimes the focus is not on the password dialog box.

Possible Cause: Incompatibilities between the Java 1.4.x Focus Management and Remote Management Viewer causes the loss of focus of password dialog box.

Action: Click the title bar of the Remote Management Viewer window.

Unable to continue with the Remote Control operation because the Remote Management Viewer freezes

Severity: ZENworks Linux Management; Remote Management

Possible Cause: The current encoding that you have selected might not be able to handle numerous screen updates.

Action: In Remote Management Viewer window, select Hextile encoding in the Options tab and retry.

Authentication to the X Server fails

Severity: ZENworks Linux Management; Remote Management

Explanation: A Remote Control session to a Managed Device fails with an error message “*host port* is not an RFB Server”.

Possible Cause: The Remote Control Service has failed to authenticate to the X Server.

Action: Restart the Display Manager.

- 1 Switch to any one of the text console.

- 2 Change the runlevel of the managed device to 3 by entering the following command at the shell prompt:

```
init 3
```

- 3 Change the runlevel back to 5 by entering the following command at the shell prompt:

```
init 5
```

Only a grey screen is displayed while performing a Remote Login session

Severity: ZENworks Linux Management; Remote Management

Explanation: If you select the Remote Login operation in the Remote Management dialog box, the launched session shows only a grey screen with an X cursor.

Possible Cause: XDMCP was not enabled on the managed device.

Action: Manually enable XDMCP by running `/opt/novell/zenworks/bin/novell-rm-fixrl.sh` with the required options.

If you use the `-restartdm` option, make sure that all applications are closed, then run the script from the text console.

For example, if you use the GDM display manager with the configuration file that is located at `/etc/opt/gnome/gdm/gdm.conf`, you can enable XDMCP using the following command:

```
#/opt/novell/zenworks/bin/novell-rm-fixrl.sh -dm gdm -  
cf /etc/opt/gnome/gdm/gdm.conf enable
```


Frequently Asked Questions

12

This section provides answers to the questions you might have when using the Novell® ZENworks® Linux Management Remote Management component:

- ◆ Section 12.1, “How do I secure my Remote Management session?,” on page 71
- ◆ Section 12.2, “How can I improve Remote Management performance on a slow link?,” on page 72
- ◆ Section 12.3, “Why do I get a black screen when I perform the Remote Control operation?,” on page 72
- ◆ Section 12.4, “Why does the Remote Management Viewer show only a toolbar at the center of the applet window?,” on page 73
- ◆ Section 12.5, “Why is the Novell Remote Management Viewer Applet signed?,” on page 73
- ◆ Section 12.6, “Why do I get a warning indicating that an unsecure download is in progress on Internet Explorer?,” on page 73
- ◆ Section 12.7, “I rejected the Novell Remote Management certificate and now I am unable to perform Remote Management operations.,” on page 73
- ◆ Section 12.8, “Can I use any other third-party VNC viewer to connect to the ZENworks 7 Linux managed device?,” on page 73
- ◆ Section 12.9, “Can I use the Novell ZENworks Remote Management Viewer window to Remote Control any third-party VNC server?,” on page 74
- ◆ Section 12.10, “Why is the certificate is not displayed while trying to start the Remote Management session for a managed device?,” on page 74

12.1 How do I secure my Remote Management session?

When connecting to remote machines, you should use SSH or VPN. You can also tunnel the VNC protocol through the encrypted SSH channel.

The VNC protocol and data are unencrypted between the Remote Management Viewer and the managed device. If you perform Remote Management operations over an insecure network like the Internet, you should tunnel the VNC protocol using SSH for secure communication.

- 1 Establish SSH tunneling to use VNC between the Remote Management Viewer and the managed device.

For more information on establishing VNC through SSH tunnelling between the Remote Management Viewer and the managed device, refer “[Establishing SSH Tunneling](#)” in the *Novell ZENworks 7.2 Linux Management Administration Guide*.

- 2 In the ZENworks Control Center, click the *Devices* page.
- 3 Launch the Remote Control session from Device Tasks in the top left pane.
- 4 Specify the IP address and the port number of the configured SSH tunnel.
- 5 Select the desired operation from the drop-down list.

6 Click *OK*.

12.2 How can I improve Remote Management performance on a slow link?

The performance during a Remote Management session over a slow link or a fast link varies depending on the network traffic. For better response time, try one or more of the following strategies:

On the Management Console

On the Remote Management viewer window at the console, click *Options* and do the following:

- ◆ Set the Encoding type to Tight
- ◆ Adjust the Compression level and JPEG image quality depending on the quality of the image required.
- ◆ Set Cursor Shape Updates to No.
- ◆ Set the CopyRect option to Yes.
- ◆ Use 8 bit color mode by setting Restricted Colors to Yes.

On the Managed Device

- ◆ The speed of the Remote Management session depends upon the processing power of the managed device. We recommend that you use a Pentium* III, 500MHz (or more) with 64 MB RAM or higher.
- ◆ Disable the wallpaper.
- ◆ Configure the following settings at the managed device:
 - ◆ Reduce the screen resolution.
 - ◆ Reduce the depth of color pixels.

More Performance Tuning Tips

For additional information on performance tuning tips, refer to the following Web sites for specific components:

- ◆ [The Tight VNC Web site \(http://www.tightvnc.com\)](http://www.tightvnc.com)
- ◆ [The Real VNC Web site \(http://www.realvnc.com\)](http://www.realvnc.com)
- ◆ [FAQs on x11VNC \(http://www.karlrunde.com/x11vnc\)](http://www.karlrunde.com/x11vnc)

12.3 Why do I get a black screen when I perform the Remote Control operation?

The ZENworks 7 Linux Management provides VNC-based Remote Management, which does not support Remote Control over the Text consoles.

12.4 Why does the Remote Management Viewer show only a toolbar at the center of the applet window?

If the Ask for Permission from User setting is enabled for the managed device, the “Ask For Permission From User On The Managed Device” dialog box appears on the managed device when a remote control session is initiated. The viewer displays the toolbar until the user at the managed device accepts or declines the connection or a timeout occurs.

12.5 Why is the Novell Remote Management Viewer Applet signed?

Any unsigned applet can only connect back to the same device from which it is downloaded. However, the Novell Remote Management Viewer Applet is downloaded from the management server with each remote session request and then connects to different managed device. So, it has to be signed.

12.6 Why do I get a warning indicating that an unsecure download is in progress on Internet Explorer?

All connections to the management server use HTTPS. But, to download the Novell Remote Management Applet from the management server, a HTTP connection is used which causes the warning.

12.7 I rejected the Novell Remote Management certificate and now I am unable to perform Remote Management operations.

Do the following:

- 1 Restart the browser by closing all the browser window and opening a new browser window.
- 2 Launch the Novell Remote Management session through the ZENworks Control Center.
- 3 When the Java security dialog box appears again, choose Yes or Always to perform Remote Management operations.

12.8 Can I use any other third-party VNC viewer to connect to the ZENworks 7 Linux managed device?

Yes. You can use any VNC viewer to connect to a ZENworks 7 Linux Managed Device. However, you need to connect to the port of the corresponding service. By default, the Remote Control Service listens on port 5950 and the Remote Login Service listens on port 5951.

12.9 Can I use the Novell ZENworks Remote Management Viewer window to Remote Control any third-party VNC server?

Yes. You can use Novell Remote Management viewer to Remote Control any third party VNC server.

12.10 Why is the certificate is not displayed while trying to start the Remote Management session for a managed device?

The Remote Management viewer requires the Java 1.4.x plug-in to be installed on the browser machine.

If you are using Firefox web browser, you can verify the plug-in version by entering the following command in the URL bar:

`about:plugins`

If you are using the Internet Explorer Web browser, you can verify the plug-in version by clicking *Tools > Internet Options > Advanced*.

If the Dell OpenManage Deployment Toolkit (DTK) component of Novell® ZENworks® Linux Management displays an error message, or if specific instructions for an error message are not available, you can try the more general troubleshooting strategies to resolve the problem.

- ◆ [Chapter 13, “Dell Configuration Bundle Troubleshooting Strategies,” on page 77](#)

Dell Configuration Bundle Troubleshooting Strategies

13

The following procedure provides a scenario for troubleshooting a Dell Configuration Preboot bundle:

- 1 Create or modify a Dell Configuration bundle.

For steps to do this, see “[Creating Dell Configuration Bundles](#)” in the *Novell ZENworks 7.2 Linux Management Administration Guide*.

- 2 Do one of the following:

- ♦ Assign the bundle to a managed device (see “[Creating Dell Configuration Bundles](#)” in the *Novell ZENworks 7.2 Linux Management Administration Guide*).
- ♦ Create a Preboot Work Assignment rule for an unmanaged device (see “[Creating Dell Configuration Bundles](#)” in the *Novell ZENworks 7.2 Linux Management Administration Guide*).

- 3 In the TFTP directory, locate the `.../dell-dtk/dell-dtk.s` file and open it in an editor.

- 4 Modify this file by adding a `#` character at the beginning of each of the last two lines to comment them out:

```
./dtask  
reboot
```

- 5 Save the edited file.

- 6 Allow the device to boot through PXE.

The device should be assigned work and boot into the DTK environment, but the assigned work will not be executed, because the `./dtask` and `reboot` lines in the `dell-dtk.s` file were disabled.

- 7 After the device has booted to the Dell DTK in maintenance mode, press Alt-F2 to obtain a usable console.

- 8 Check the following items to determine if the Dell Configuration bundle worked correctly:

- ♦ A directory named `/tmp/dell-dtk` should have been created.
A script named `dell-dtk-maint.s` that is downloaded from `/srv/tftp/dell-dtk` creates the `/tmp/dell-dtk` directory.
- ♦ A utility named `dtktask` should have been placed in the `/tmp/dell-dtk` directory.
- ♦ To determine whether various environment variables have been set appropriately, enter the following commands to see if the TFTP_IP and PROXYADDR variables display the IP address of your ZENworks® Imaging server:

```
echo $TFTP_IP  
echo $PROXYADDR
```

- 9 If all of these items show no problems, change to the `/tmp/dell-dtk` directory.

- 10 Run the `dtktask` utility:

```
./dtktask -v
```

The verbose option (-v) is optional. It causes the information being sent to the `dtktask.log` file to be displayed on screen.

- 11** To further determine any problems, examine the following log file:

`/var/log/dtktask.log`

If the log file doesn't resolve the problem, determine what action to take from the information in the log file.

To troubleshoot, you could manually download the files, run the utilities, and look for error messages on screen.

- 12** After each trial run, reboot the device or reassign the Preboot work so that your troubleshooting starts at a known state, then repeat these steps to troubleshoot a different Dell Configuration bundle.

Package and Content Management

VIII

If the Package and Content Management features of Novell® ZENworks® Linux Management displays an error message, you can look it up in the Error Messages section. If a problem is not accompanied by an error message, or if specific instructions for an error message are not available, you can try more general troubleshooting strategies to resolve the problem.

This section contains the following topics:

- ◆ [Chapter 14, “Package and Content Management Error Messages,” on page 81](#)
- ◆ [Chapter 15, “Package and Content Management Troubleshooting Strategies,” on page 83](#)

Package and Content Management Error Messages

14

This section contains detailed explanations of the error messages you might encounter using the Novell® ZENworks® Linux Management Package and Content Management features:

- ♦ “Error receiving message: Unknown response message from server, status: CancelSignal” on page 81
- ♦ “Error receiving message: Read failure” on page 81
- ♦ “Cannot deploy this version because one or more packages have been deleted” on page 81

Error receiving message: Unknown response message from server, status: CancelSignal

Source: ZENworks Linux Management; Package and Content Management

Action: Do the following:.

- 1 Increase the `memory-threshold` value in the `zmd.conf` file. The `zmd.conf` file is located in `/etc/zmd/` on SLES 10 and SLED 10 devices, and in `/etc/opt/novell/zenworks/zmd/` on other devices.
- 2 Restart the `zmd`.

Error receiving message: Read failure

Source: ZENworks Linux Management; Package and Content Management

Action: Do the following:.

- 1 Increase the `memory-threshold` value in the `zmd.conf` file. The `zmd.conf` file is located in `/etc/zmd/` on SLES 10 and SLED 10 devices, and in `/etc/opt/novell/zenworks/zmd/` on other devices.
- 2 Restart the `zmd`.

Cannot deploy this version because one or more packages have been deleted

Source: ZENworks Linux Management, Package and Content Management

Explanation: The error message is displayed on the Secondary server for all packages after content replication. But you can assign this bundle to all the managed devices that are registered to the Secondary server.

Action: Ignore the message.

Package and Content Management Troubleshooting Strategies

15

This section provides solutions to problems you might encounter when using Novell® ZENworks® Linux Management Package and Content Management features:

- ♦ “Installing updates that were mirrored from the Update sites, such as <http://updates.novell.com> (<http://updates.novell.com/>), using the `rug up` command fails with dependency errors” on page 83
- ♦ “Rug refresh hangs” on page 83
- ♦ “Bundle or package installation might fail with the error message, “Resolvable ID (number) does not exist”” on page 83
- ♦ “The command to set the password on the managed device is truncated in the error message” on page 84
- ♦ “Adding a custom repository fails with an error” on page 84
- ♦ “Installing the YOU patches without any particular order using the `rug` command fails” on page 84

Installing updates that were mirrored from the Update sites, such as <http://updates.novell.com> (<http://updates.novell.com/>), using the `rug up` command fails with dependency errors

Source: ZENworks Linux Management; Package and Content Management

Possible Cause: The dependent packages are not available on the ZENworks Linux Management server.

Action: To distribute and install RPMs to managed devices, you need to ensure that all packages the RPMs depend on, and all packages dependent on the RPM are also imported to the ZLM server. For example, to distribute updates to the SLES 10 devices mirrored from updates.novell.com, you need to ensure that all the packages from the SLES 10 media are imported to the ZLM server. You need not assign the bundles or catalogs containing the dependent RPMs to the managed devices.

Rug refresh hangs

Source: ZENworks Linux Management; Package and Content Management

Explanation: The `rug refresh` command sometimes hangs.

Action: Execute the `rug restart` command.

Bundle or package installation might fail with the error message, “Resolvable ID (number) does not exist”

Source: ZENworks Linux Management; Package and Content Management

Possible Cause: The `zmd.db` file is corrupt.

Action: Regenerate `zmd.db`.

- ◆ On SLE 10, enter the following at the command line:

```
#!/etc/init.d/novell-zmd stop  
  
#rm /var/lib/zmd/zmd.db  
  
#!/etc/init.d/novell-zmd start
```

- ◆ On other platforms, enter the following at the command line:

```
#!/etc/init.d/novell-zmd stop  
  
#rm /var/opt/novell/zenworks/lib/zmd/zmd.db  
  
#!/etc/init.d/novell-zmd start
```

The command to set the password on the managed device is truncated in the error message

Source: ZENworks Linux Management; Package and Content Management

Explanation: When you try to initiate a remote session, the following message is displayed if the password is not set on the managed device:

```
Unable to initiate a remote session because a password  
has not been set on the managed device. To set the  
password, run "zrmservice --pas"
```

The command displayed by the message is truncated.

Action: The complete message is as follows.

```
Unable to initiate a remote session because a password  
has not been set on the managed device. To set the  
password, run "zrmservice --passwd".
```

Adding a custom repository fails with an error

Source: ZENworks Linux Management; Package and Content Management

Explanation: The following error message might be displayed when you add a custom repository:

```
ERROR: Could not add 'http://foobar.com/sled-10-i586':  
Failed to parse XML metadata: Unsigned file '/repdata/  
repomd.xml (file:/var/cache/zmd/web/files/foobar.com/  
sled-10-i586/)'
```

Action: Log in as root, and execute the following command: `rug set security-level checksum`.

Installing the YOU patches without any particular order using the rug command fails

Source: ZENworks Linux Management; Package and Content Management

Explanation: If you try to install the YOU patches from a catalog by using wildcard characters in the patch name (For example, `rug bin catalog_name patch*`), then you might encounter issues because of the order in which the patches get installed.

Possible Cause: The usage of wildcard characters change the installation order of the YOU patches. The patched numbered higher could depend on the lower numbered patches.

Action: Do not use wildcard characters for installing a set of patches that are dependent on each other.

Documentation Updates

A

This section contains information on documentation content changes that were made in this *Troubleshooting Guide* after the initial release of Novell® ZENworks® 7.2 Linux Management. The information can help you to keep current on updates to the documentation.

All changes that are noted in this section are also made in the documentation. The documentation is provided on the Web in two formats: HTML and PDF. The HTML and PDF documentation are both kept up-to-date with the documentation changes listed in this section.

The documentation update information is grouped according to the date the changes are published. Within a dated section, the changes are alphabetically listed by the names of the main table of contents sections in the guide.

If you need to know whether a copy of the PDF documentation you are using is the most recent, the PDF document contains its publish date on the front title page.

The documentation was updated on the following dates:

- [Section A.1, “August 23, 2007,” on page 87](#)
- [Section A.2, “May 21, 2007,” on page 87](#)

A.1 August 23, 2007

Updates were made to the following section:

A.1.1 Inventory

The following changes were made in this section:

Location	Change
Section 1.1, “Troubleshooting the Installation,” on page 13	Added the following scenario: “Executing the rug ref command on the PPC, IPF, and zSeries devices results in exceptions related to Inventory” on page 14

A.2 May 21, 2007

Updates were made to the following section:

A.2.1 Inventory

The following changes were made in this section:

Location	Change
Section 7.2, "Troubleshooting Hardware Inventory," on page 48	Added the following scenario: "How to control delayed schedules for updating inventory on the ZENworks Linux Management server?" on page 49
